Technical Manual — FlowEngine (IDS Dataset Generator)

> **Document version:** 1.1 · **Date:** November 2026
> **Versión en español:** ../es/manual_tecnico.md

Table of contents

1. Introduction
2. System requirements
3. Project structure
4. Software architecture
5. Network architecture
6. Module reference
7. Flow engine
8. CSV data dictionary
9. AI model integration
10. Configuration parameters
11. Generated files
12. Build and deployment
13. Security
14. Known issues and recommended improvements
15. Troubleshooting
16. Companion tools

> Identifiers, menu text and console messages are kept in Spanish, exactly as they appear in the source code.

1. Introduction

FlowEngine is a Python console tool that **generates network-traffic datasets** for training and evaluating Intrusion Detection Systems (IDS). It:

- Captures live traffic (or reads `.pcap/.pcapng` files) with **Scapy**.
- Groups packets into **bidirectional flows** and computes **90+ features** per flow (size and timing statistics, TCP flags, TLS/JA3, DNS, HTTP, entropy, etc.).
- Labels each flow **manually** (the operator types the label live) or **automatically** with a pre-trained **Random Forest** model (`modelo_rf_ids.joblib`).
- Lets you **filter and derive variables** on the resulting dataset.

- Supports **distributed capture**: a *Director* PC discovers agents (sensors) on the LAN, orders them to capture (immediately or scheduled) and receives the resulting CSV files.

1.1 Executables

Executable	Source	Role
`FlowEngine.exe`	`flow_engine.py` (+ modules)	Main menu application. Used interactively on the **Director**; launched in `--captura-remota` mode on **agents**.
`SensorAgente.exe`	`agente_persistente.py`	Window-less resident service that listens for network orders and starts captures. Only used on **agent** machines.

---

2. System requirements

2.1 Operating system

OS	Support	Additional requirements
Windows 10/11 (64-bit)	Primary	**Npcap** installed in *WinPcap API-compatible* mode. Nmap optional. Run as Administrator.
Linux (Debian/Ubuntu)	Supported	Run with `sudo` (root). `tcpdump` and `nmap` (auto-installed via `apt-get`).

2.2 Development software

Component	Recommended version	Purpose
Python	3.10 – 3.12	Interpreter
scapy	≥ 2.5	Packet capture and dissection
numpy	≥ 1.24	Flow statistics
pandas	≥ 2.0	Advanced filters and model feature alignment
scikit-learn	**same version used to train the model**	Random Forest prediction
joblib	≥ 1.3	Model loading
cryptography	≥ 41	Required by Scapy's TLS layers
tkinter	bundled with Python	File/folder picker dialogs
PyInstaller	≥ 6.0	Building executables

> ⚠️ The `.joblib` model must be loaded with the **same scikit-learn version** it was trained with; otherwise it may fail or predict incorrectly.

2.3 Automatic dependency installation

When run as a script (`.py`), `instalar_dependencias_python()` checks every library with `importlib.util.find_spec` and installs missing ones with `pip`. In the compiled executable (`sys.frozen`) this step is skipped because libraries are bundled.

`check_and_install_tools()` checks system tools:

- **Windows:** looks for `C:\Windows\System32\Npcap` and `C:\Program Files (x86)\Nmap\nmap.exe`. If missing, runs `npcap-1.88.exe` / `nmap-7.99-setup.exe` located **next to the executable**.
- **Linux:** requires root (`os.geteuid() == 0`) and installs `nmap` and `tcpdump` with `apt-get` if absent.

---


3. Project structure

```
FlowEngine/
├── src/                          # Main program (all .py files together)
│   ├── flow_engine.py            # Entry point: main menu and --captura-remota mode
│   ├── live_conf.py              # Live capture (manual / AI / remote) + flow engine
│   ├── pcap_conf.py              # Offline PCAP processing (same engine)
│   ├── advanced_dataset_filters.py  # Filters and derived variables on a CSV
│   ├── red_distribuida.py        # Director side: discovery, orders, reception
│   ├── agente_persistente.py     # Agent side: UDP/TCP service that starts captures
│   └── compilar.py               # PyInstaller build
├── training/
│   └── entrenar_modelo.py        # Trains modelo_rf_ids.joblib (Random Forest)
├── tools/
│   ├── etiquetar_con_ground_truth.py  # Labels a CSV with the UNSW-NB15 ground truth
│   ├── generar_diagramas.py      # Regenerates docs/img diagrams
│   └── build_pdfs.sh             # Regenerates docs/pdf
├── lab/
│   └── lab_attacks.sh            # Attack-traffic generator for the lab
├── legacy/                       # Earlier versions no longer used
├── datasets/ · models/ · installers/   # README only: files go to GitHub Releases
└── docs/                         # ES/EN manuals, diagrams and PDFs
```

The `src/` modules must live **in the same folder**: `flow_engine.py` imports them directly (`import live_conf`, ...) and `compilar.py` looks for files in the current directory.

---

4. Software architecture



4.1 `flow_engine.py` execution modes

Mode	How it is triggered	What it does
Interactive	`FlowEngine.exe` with no arguments	`check_and_install_tools()` → `preparar_red_distribuida()` (opens TCP 51502 receiver) → `menu_principal()`
Remote capture	`FlowEngine.exe --captura-remota --duracion N --id ID --director-ip IP`	Invoked by the agent. Runs `red_distribuida.ejecutar_captura_y_reportar()` with `live_conf.capturar_remoto` and uploads the CSV to the Director.


4.2 Concurrency model

Thread	Where	Function
Sniffer (main)	`Analyzer.run()`	`scapy.sniff(prn=Analyzer.process)`
Keyboard	`input_listener()`	Changes current label or stops (`stop` / `salir`)
Reaper	`Analyzer._reaper_loop()`	Every 5 s closes flows idle > `flow_timeout`
Auto-stop	`capturar_remoto.auto_stop()`	Stops a remote capture after `duracion` seconds
TCP receiver	`DirectorRed.iniciar_receptor_reportes()`	Server on 51502; one thread per received file
Agent UDP / TCP	`agente_persistente.py`	Discovery thread + command server; one thread per connection

The shared `Analyzer.flows` dictionary is protected by `threading.Lock()`.

5. Network architecture

5.1 Topology



The system follows a **Director – Agents** model on a **single local network**:

- **Director PC:** runs `FlowEngine.exe` interactively. Discovers agents, sends orders and stores incoming CSV files in `capturas_remotas/`.
- **Agent (sensor) PC:** runs `SensorAgente.exe` in the background. `FlowEngine.exe` and `modelo_rf_ids.joblib` must sit next to it.

5.2 Ports and protocols

Port	Protocol	Listens on	Direction	Purpose
51500	UDP	Agent (`0.0.0.0`)	Director → broadcast `255.255.255.255`	Agent discovery (ping / reply)
50050	TCP	Agent (`0.0.0.0`)	Director → Agent	Capture orders (immediate or scheduled)
51502	TCP	Director (`0.0.0.0`)	Agent → Director	Upload of the resulting CSV

Constants defined in `red_distribuida.py` and `agente_persistente.py`:


```
PUERTO_UDP_DESCUBRIMIENTO     = 51500
PUERTO_TCP_COMANDOS           = 50050   # agente_persistente.py
PUERTO_TCP_RECEPCION_REPORTES = 51502   # red_distribuida.py
TOKEN_RED                     = _cargar_token_red()
CARPETA_CAPTURAS_REMOTAS      = "capturas_remotas"
```

Network token. `_cargar_token_red()` (present in both modules) looks for it in this order:

1. Environment variable `FLOWENGINE_TOKEN`.
2. File `token_red.txt` next to the program (`.py` or `.exe`), token on the first line.
3. Default `MI_TOKEN_SECRETO_123` (public; testing only).

The Director and **every** agent must use the same token.

5.3 Remote capture sequence



5.4 Message formats

Discovery (Director → broadcast, UDP 51500):

```
{"accion": "ping", "token": "MI_TOKEN_SECRETO_123"}
```

Agent reply (UDP, unicast to Director):

```
{"estado": "activo", "hostname": "PC-LAB-01", "puerto_tcp": 50050}
```

The Director waits **3 s** for replies (`descubrir_agentes(tiempo_espera=3)`).

Capture order (Director → Agent, TCP 50050):

```
{
  "accion": "capturar",            // or "capturar_programada"
  "token": "MI_TOKEN_SECRETO_123",
  "duracion": 60,
  "director_ip": "192.168.1.10",
  "id_captura": "prueba_01",
  "retraso_segundos": 3600,        // only for capturar_programada
  "fecha_ejecucion": "2026-11-03 20:30"
}
```

Result transfer (Agent → Director, TCP 51502):

Bytes	Content
0 – 3	Metadata length *L*, unsigned big-endian integer (`struct.pack('>I', L)`)
4 – 4+L	JSON `{"nombre_archivo": "remoto_<id>_<epoch>.csv", "tamano": <bytes>, "token": "<TOKEN_RED>"}`
rest	Raw CSV content, sent in 4096-byte chunks

The Director rejects the connection if the token does not match, sanitises `nombre_archivo` (no folders or invalid characters) and stores it as `capturas_remotas/<agent_IP>_<nombre_archivo>`. If fewer bytes than announced arrive, it reports an incomplete transfer.

5.5 Network requirements

1. All machines on the **same subnet** (the `255.255.255.255` broadcast does not cross routers).
2. Synchronised clocks (scheduled captures compute the delay from the **Director's** clock).
3. Inbound firewall rules:

Windows (PowerShell as Administrator):

```
# On every AGENT
New-NetFirewallRule -DisplayName "FlowEngine UDP 51500" -Direction Inbound -Protocol UDP -
LocalPort 51500 -Action Allow
New-NetFirewallRule -DisplayName "FlowEngine TCP 50050" -Direction Inbound -Protocol TCP -
LocalPort 50050 -Action Allow
# On the DIRECTOR
New-NetFirewallRule -DisplayName "FlowEngine TCP 51502" -Direction Inbound -Protocol TCP -
LocalPort 51502 -Action Allow
```

Linux (ufw):

```
sudo ufw allow 51500/udp && sudo ufw allow 50050/tcp   # agent
sudo ufw allow 51502/tcp                                # director
```

6. Module reference

6.1 `flow_engine.py` — Entry point

Function	Description
`instalar_dependencias_python()`	pip-installs missing libraries (script mode only).
`check_and_install_tools()`	Checks Npcap/Nmap (Windows) or root + nmap/tcpdump (Linux).
`preparar_red_distribuida()`	Creates `DirectorRed` and starts the TCP 51502 receiver in a daemon thread.
`ejecutar_modo_captura_remota()`	Parses `--captura-remota --duracion --id --director-ip`, runs capture + upload.
`menu_principal()`	Menu loop (options 0–6). Each option runs inside `try/except` so errors never close the program.

6.2 `live_conf.py` — Live capture

Function / class	Description
`run()`	Capture with **manual** labelling. Asks for path, CSV name and PCAP name. Defaults to `<program folder>/Capturas`.
`run_ia()`	Same as `run()` but loads `modelo_rf_ids.joblib` and sets `MODO_ETIQUETADO = "modelo"`. Restores manual mode at the end.
`capturar_remoto(duracion, ruta, id, nombre_pcap)`	Timed, non-interactive capture, always AI-labelled. Returns the CSV path.
`input_listener()`	Keyboard thread: new label → `flush_all_active()` + entry in `LABEL_LOG`.
`get_active_interface()`	Interface of the default route (`conf.route.route("0.0.0.0")`).
`_sanitizar_nombre_archivo()`	Strips paths and invalid characters; enforces the extension.
`_ruta_disponible()`	If the file exists and is locked (Excel, antivirus), uses an alternate name with a time suffix.
`cargar_modelo_ids()` / `_predecir_etiqueta()`	Loads and applies the model (see §9).
`analizar_tls_clienthello()` / `calcular_ja3()`	TLS ClientHello parser and JA3 fingerprint (MD5, GREASE values removed).
`_entropia()`	Shannon entropy of the payload (0–8 bits/byte).
`detectar_protocolo()` / `detectar_service_y_payload()`	Protocol and service classification + DNS/HTTP/TLS metadata.
`Flow`	Accumulates per-flow statistics and builds the CSV row (`compute()`).
`Analyzer`	Manages active flows, CSV/PCAP writing, reaper and label log.

6.3 `pcap_conf.py` — Offline processing

Contains a copy of the engine (`Flow`, `Analyzer`, parsers) adapted to file input. `run()` opens a dialog to pick the `.pcap/.pcapng`, another for the output folder, asks for the CSV name (default `pcap_resultado1.csv`) and streams packets with `PcapReader` (the file is never loaded entirely into memory), printing progress every 10,000 packets.

No output PCAP is written (`save_pcap: False`) and **the resulting CSV has no `Label` column** (there is no labelling in offline mode).

> Note: since the engine exists twice (`live_conf.py` and `pcap_conf.py`), any feature change must be mirrored in both to keep datasets comparable.

6.4 `advanced_dataset_filters.py` — Filters

Function	Description
`seleccionar_dataset()`	Tkinter dialog to pick a CSV.
`convertir_columnas_numericas()`	Converts to numeric only the columns where **every** non-empty value is a number; text columns (`State` , `Service` , `JA3` , `HTTP *` ...) are kept.
`traducir_filtro()`	Translates Wireshark-like syntax into `pandas.query` : `tcp` , `udp` , `&&` → `and` , `||` → `or` , `ip.src` , `ip.dst` . `tcp.port == N` / `udp.port == N` means *protocol and (source or destination port) = N*, as in Wireshark (supports `== != > < >= <=`).
`crear_variable()`	Creates a column with `df.eval(expression)` .
`aplicar_filtro()`	Applies the filter and prints remaining rows.
`guardar_dataset()`	Saves `dataset_filtrado_avanzado.csv` next to the original CSV.

6.5 `red_distribuida.py` — Director side

Element	Description
`obtener_ip_local()`	Finds the outbound interface IP (UDP socket to 8.8.8.8, no data sent).
`DirectorRed.descubrir_agentes()`	UDP broadcast and 3-second reply collection.
`DirectorRed.enviar_orden_captura()`	Sends the JSON order over TCP (10 s timeout).
`DirectorRed.iniciar_receptor_reportes()`	TCP server on 51502 (`listen(10)`), one thread per connection.
`DirectorRed.manejar_recepcion_archivo()`	Reads length + metadata + content, validates the token, sanitises the name and stores the file.
`menu_captura_instantanea()`	Menu option 6.
`menu_programar_captura()`	Menu option 5. Validates `YYYY-MM-DD HH:MM` (24 h) and that the date is in the future.
`ejecutar_captura_y_reportar()`	Agent side: runs the capture and uploads the CSV (30 s timeout).

6.6 `agente_persistente.py` — Agent service

- Sets the working directory to the executable's folder and logs activity to `sensor_agente.log` .
- **UDP thread (51500):** replies to `ping` messages carrying a valid token.
- **TCP server (50050):** validates the token and handles `capturar` (immediate) or `capturar_programada` (thread that waits `retraso_segundos` , then starts the capture).
- `iniciar_motor_captura()` launches `FlowEngine.exe` (Windows) or `FlowEngine` (Linux) with `--captura-remota ...` (or `python flow_engine.py ...` in script mode) with `subprocess.Popen` .
- Built with `--noconsole` : no window; stop it from Task Manager.

6.7 `compilar.py` — Build

Checks/installs PyInstaller, deletes `build/`, `dist/` and old `.spec` files, then builds:

Output	PyInstaller command
`dist/FlowEngine(.exe)`	`--onefile --clean --name FlowEngine flow_engine.py`
`dist/SensorAgente(.exe)`	`--onefile --clean --noconsole --name SensorAgente agente_persistente.py`

---

7. Flow engine

7.1 Flow identification

Each packet is assigned to a flow by its **5-tuple** `(source IP, destination IP, source port, destination port, protocol)`. The reverse tuple is also looked up so flows are **bidirectional** (`FWD` = direction of the first packet, `BWD` = reply).

- No IP layer: 802.11 addresses (`addr2/addr1`) or Ethernet MACs are used.
- ICMP: the echo `id` is used as a pseudo-port so separate pings between the same hosts are not merged.
- Detected protocols: `TCP`, `UDP`, `ICMP`, `ARP`, `IP`, `802.11_Beacon/Auth/Deauth/ProbeReq/Other`, `OTHER`.

7.2 Lifecycle (when a row is written)

A flow is closed and written to the CSV on whichever comes first:

1. It reaches `min_packets` (5) packets in total.
2. It is **terminal**: RST seen, or FIN seen in both directions.
3. It exceeds `flow_timeout` (30 s) without traffic (checked by the *reaper* every 5 s).
4. The operator **changes the label** (all active flows are closed with the previous label).
5. The capture **stops** (final flush).

> **Design note:** because a flow closes upon reaching `min_packets`, a long connection produces **several consecutive rows** (~5-packet windows) rather than one row per connection. Raise `min_packets` if you need whole-connection flows.

7.3 TCP state

A state is recorded per packet and `State` takes the **most frequent** one: `S0` (SYN), `S1` (SYN-ACK), `EST` (ACK), `FIN`, `RST`. For UDP/ICMP: `CON` if there was a reply, `INT` otherwise.

7.4 Service detection

Priority: DNS (Scapy layer) → HTTP (Scapy layer) → well-known port (the lower of both ports) → TLS by signature (`0x16`) → `other`.

Mapped ports: 21 ftp, 22 ssh, 23 telnet, 25 smtp, 53 dns, 80 http, 110 pop3, 123 ntp, 137/138 netbios, 139/445 smb, 143 imap, 443 https, 1433 mssql, 1883 mqtt, 1900 ssdp, 3306 mysql, 3389 rdp, 5432 postgresql.

7.5 Scan signatures

`Flag Signature` flags `null_scan` (no flags), `xmas_scan` (FIN+PSH+URG) or `fin_scan` (FIN only); otherwise `none`.

---

8. CSV data dictionary

Group	Columns	Description
Identification	`Start Time`, `End Time`, `Source IP`, `Destination IP`, `Source Port`, `Destination Port`, `Protocol`, `State`, `Service`, `SNI`	`HH:MM:SS.ffffff` time, 5-tuple, state, service and TLS SNI
Volume	`Flow Duration`, `Src Bytes`, `Dst Bytes`, `Src Packets`, `Dst Packets`, `Flow Bytes/s`, `Flow Packets/s`, `Src Load`, `Dst Load`, `Bytes Per Pkt`, `Size Diff`, `Byte Ratio`	Duration (s), bytes/packets per direction and rates
TTL	`Src TTL`, `Dst TTL`, `Src TTL Var`, `Dst TTL Var`	TTL mean and variance per direction
Timing	`Sjit`, `Djit`, `Sintpkt`, `Dintpkt`, `Fwd IAT Min`, `Fwd IAT Max`, `Bwd IAT Min`, `Bwd IAT Max`, `Active Mean`, `Idle Mean`	Jitter, inter-arrival time and active/idle periods (`active_gap` = 1 s)
TCP handshake	`tcprtt`, `synack`	SYN→ACK and SYN→SYN-ACK (s)
Context (60 s window)	`ct_srv_src`, `ct_srv_dst`, `ct_dst_ltm`, `ct_src_ltm`	Count of recent flows per source/destination/service (UNSW-NB15 style)
TCP flags	`SYN Count`, `ACK Count`, `FIN Count`, `RST Count`, `PSH Count`, `URG Count`, `ECE Count`, `CWR Count`, `Fwd/Bwd PSH Count`, `Fwd/Bwd URG Count`, `Flag Signature`	Flag counters and scan signature
Sizes	`Pkt Size Mean`, `Pkt Size Var`, `First Pkt Size`, `Fwd/Bwd Pkt Len Min/Max/Mean/Std`	Packet length statistics
Window / retransmission	`Init Fwd Win`, `Init Bwd Win`, `Zero Window Count`, `Fwd Retrans`, `Bwd Retrans`	Initial TCP window, zero windows and retransmissions (same `seq` with payload)
IP	`Frag Count`, `DF Count`	Fragments and *Don't Fragment* packets
Content	`Payload Entropy Mean`	Mean payload entropy (≈7–8 suggests encrypted/compressed)
ICMP	`ICMP Type`, `ICMP Code`	First value seen
DNS	`DNS Qname`, `DNS Qtype`, `DNS Rcode`, `DNS Ancount`, `DNS Qname Len`, `DNS Qname Entropy`	Useful for DGA / DNS tunnelling detection
HTTP	`HTTP Method`, `HTTP Host`, `HTTP URI`, `HTTP User-Agent`, `HTTP Status`, `HTTP Content-Length`	Plain-text HTTP only
TLS	`TLS Version`, `JA3`	ClientHello version and JA3 fingerprint
Class	`Label`	Manual label or model prediction (absent from CSVs produced by `pcap_conf.py`)

Non-applicable fields are left empty (not 0) so they are not mistaken for a real value.

---

9. AI model integration

- **File:** `modelo_rf_ids.joblib`, looked up **in the program's own folder** (the path is never asked).
- **Requirement:** the model must expose `feature_names_in_`, which happens when it is trained on a `pandas.DataFrame`.
- **Alignment:** for each flow a one-row DataFrame is built with the `feature_names_in_` columns in that order. Missing or text columns (IPs, service, ...) are filled with **0**.
- **Result:** the prediction (`str`) is written to `Label`. Special values on failure: `sin_pandas`, `sin_prediccion`, `error_prediccion`.

Training: use `training/entrenar_modelo.py`:

```
python training/entrenar_modelo.py --datos datasets --salida training/modelo_salida
```

The script merges every CSV in the folder, normalises labels (`MAPA_ETIQUETAS`), drops non-numeric columns (IPs, service...), tunes hyper-parameters with `RandomizedSearchCV` (15 combinations × 3-fold stratified cross-validation) and saves:

File	Content
`modelo_rf_ids.joblib`	Final model
`columnas_features.json`	List and order of the features used
`matriz_confusion.png`	Confusion matrix on the test set
`importancia_caracteristicas.png` / `.csv`	Feature importance

Because it trains on a DataFrame whose column names match FlowEngine's output, the resulting model works directly with `_predecir_etiqueta()`.

10. Configuration parameters

`CONFIG` dictionary (in `live_conf.py` and `pcap_conf.py`):

Key	live_conf	pcap_conf	Description
`csv_file`	`live_resultado.csv`	`pcap_resultado1.csv`	Default CSV name
`min_packets`	5	5	Packets needed to close a flow
`time_window`	60	60	Window (s) for `ct_*` features
`flow_timeout`	30	30	Idle time (s) before closing a flow
`active_gap`	1.0	1.0	Gap (s) separating active from idle periods
`save_pcap`	`True`	`False`	Store raw traffic in a `.pcap`
`pcap_file`	`captura.pcap`	—	Default PCAP name

11. Generated files

File	Location	Content
`<name>.csv`	Chosen folder (default `Capturas/`)	Flow dataset
`<name>.pcap`	Same	Raw traffic (written with `sync=True`, survives abrupt exits)
`labels_log.csv`	Same	`timestamp_unix, timestamp_legible, label` for every label change
`filas_no_guardadas.csv`	Same	Rows that could not be written after 5 retries (locked CSV)
`dataset_filtrado_avanzado.csv`	Folder of the filtered CSV	Output of option 4
`capturas_remotas/<ip>_remoto_<id>_<epoch>.csv`	Director	CSV received from each agent
`capturas_remotas/remoto_<id>_<epoch>.pcap`	Agent	Local PCAP of the remote capture (not uploaded)
`sensor_agente.log`	Agent	Service log

12. Build and deployment

12.1 Build

```
cd src
pip install -r ../requirements.txt
python compilar.py
```

Output in `src/dist/`: `FlowEngine(.exe)` and `SensorAgente(.exe)`. On Linux: `chmod +x dist/*`.

> PyInstaller does not cross-compile: build on Windows for `.exe` files and on Linux for Linux binaries.

12.2 Distribution bundle

Director PC:

```
FlowEngine.exe
modelo_rf_ids.joblib      (optional, only for option 2)
npcap-1.88.exe            (installer, downloaded from npcap.com)
nmap-7.99-setup.exe       (optional)
token_red.txt             (recommended: same token on every machine)
```

Agent PC:

```
SensorAgente.exe
FlowEngine.exe            (required: the agent launches it)
modelo_rf_ids.joblib      (required: remote capture always uses AI)
npcap-1.88.exe
token_red.txt             (recommended: same token as the Director)
```

12.3 Agent auto-start (optional)

- **Windows:** create a Task Scheduler task with "Run with highest privileges" and an "At log on" trigger, or put a shortcut in `shell:startup` (the user must be an administrator to capture).
- **Linux (systemd):**

```ini
# /etc/systemd/system/sensoragente.service
[Unit]
Description=FlowEngine SensorAgente
After=network-online.target
[Service]
WorkingDirectory=/opt/flowengine
ExecStart=/opt/flowengine/SensorAgente
Restart=on-failure
User=root
[Install]
WantedBy=multi-user.target
```

---

13. Security

Risk	Detail	Recommendation
Public default token	If not configured, `MI_TOKEN_SECRETO_123` is used, visible on GitHub	✅ Now read from `FLOWENGINE_TOKEN` or `token_red.txt` (excluded by `.gitignore`). Set it on every machine
Unencrypted traffic	Orders, token and CSV files travel in plain text	Use only on isolated lab networks or add TLS (`ssl` module)
Unauthenticated receiver	Port 51502 used to accept files from any host	✅ Fixed: metadata carries the token and the Director validates it
Unsanitised file name	`nombre_archivo` comes from the client	✅ Fixed: `_nombre_seguro()` strips folders and invalid characters
Elevated privileges	Capturing requires admin/root	Run only on lab machines
Sensitive data	PCAP/CSV files may contain real IPs, domains, URIs and user agents	Never commit real captures (see `.gitignore`)

> **Ethical use:** only capture traffic on networks you own or are explicitly authorised to monitor.

---

14. Known issues and recommended improvements

14.1 Fixed in version 1.1

#	Issue	Location	Effect it had	Fix applied
1	Inconsistent delay key: the Director sent `retraso_segundos`, the agent read `delay_segundos`	`agente_persistente.manejar_conexion`	Every scheduled capture started after 60 s, not at the chosen time	The agent reads `retraso_segundos` (still accepts `delay_segundos`)
2	Binary name hard-coded as `FlowEngine.exe`	`agente_persistente.iniciar_motor_captura`	On compiled Linux the agent could not find the engine	`FlowEngine.exe` on Windows, `FlowEngine` on Linux
3	`tcp.port` / `udp.port` mistranslated (`Protocol == 'TCP'.port == 80`)	`advanced_dataset_filters.traducir_filtro`	Syntax error when filtering by port	Translated before `tcp` / `udp`; compares source or destination port
4	`convertir_columnas_numericas` emptied text columns	`advanced_dataset_filters`	`Start/End Time`, `State`, `Service`, `Flag Signature`, `DNS Qname`, `HTTP *` became empty in the filtered CSV	Only fully numeric columns are converted
5	Examples used the non-existent `Packet Length Mean` column	`advanced_dataset_filters`	Confused users	Examples use `Pkt Size Mean` / `Fwd Pkt Len Max`
6	Hard-coded token, unauthenticated receiver, unsanitised file name	`red_distribuida`, `agente_persistente`	See §13	Configurable token validated on reception; sanitised name; exact metadata reads
7	Hard-coded `D:\Descargas\...` paths	`training/entrenar_modelo.py`, `tools/etiquetar_con_ground_truth.py`	Only worked on the original PC	`--datos/--salida` and `--csv/--gt/--salida` arguments

14.2 Pending (recommended improvements)

#	Issue	Location	Effect	Suggestion
8	Duplicated engine	`live_conf.py` and `pcap_conf.py`	Risk of datasets diverging	Move `Flow` / `Analyzer` into a shared module
9	Remote PCAP is not uploaded	`ejecutar_captura_y_reportar`	Only the CSV reaches the Director	Also upload the `.pcap` if needed
10	`Start Time` / `End Time` without date	`Flow.compute`	Ambiguous for captures spanning midnight	Include date or epoch
11	`pcap_conf.py` CSVs have no `Label`	`pcap_conf.Flow.compute`	Labelling must happen afterwards	Fixed-label or model option
12	Unencrypted communication	`red_distribuida`, `agente_persistente`	Token and data readable on the wire	TLS via the `ssl` module

15. Troubleshooting

Symptom	Likely cause	Fix
`ERROR CRÍTICO DE RED: SCAPY NO DETECTA NPCAP`	Npcap just installed or without WinPcap mode	Restart the program; if it persists, reinstall Npcap ticking *WinPcap API-compatible Mode*
`No se detectaron agentes en la red`	Agent not running, firewall, or different subnet	Check `SensorAgente.exe` in Task Manager, open UDP 51500, same subnet
`Fallo de conexión con <ip>`	TCP 50050 blocked	Firewall rule on the agent
Director never receives the CSV	TCP 51502 blocked or Director IP changed	Firewall rule on the Director; check `sensor_agente.log`
`Archivo rechazado de <ip>: token inválido`	Agent and Director use different tokens	Same `token_red.txt` (or `FLOWENGINE_TOKEN`) on every machine
`No se encontró el modelo IA`	`modelo_rf_ids.joblib` missing next to the executable	Copy it to the program folder (and the agent's)
`Label = error_prediccion`	Different scikit-learn version or incompatible features	Retrain using FlowEngine's column names
`'file' está en uso`	CSV open in Excel	Close it; the program automatically switches to an alternate name
Linux: `necesitas permisos de root`	Run without sudo	`sudo ./FlowEngine`

16. Companion tools

Tool	Purpose
`training/entrenar_modelo.py`	Trains `modelo_rf_ids.joblib` (§9).

Tool	Purpose
`tools/etiquetar_con_ground_truth.py`	Labels a CSV produced from a UNSW-NB15 PCAP by joining it with `NUSW-NB15_GT.csv` on the 4-tuple (IPs and ports). Adds `attack_cat` and `label` (0/1). Usage: `python tools/etiquetar_con_ground_truth.py --csv flows.csv --gt NUSW-NB15_GT.csv --salida labelled.csv` (needs `tqdm`).
`lab/lab_attacks.sh`	Generates the lab's attack traffic (nmap, hydra, hping3, slowloris, ffuf, sqlmap, bettercap) and pauses before each attack so the operator can switch the label in FlowEngine. **Isolated, self-owned lab only.** See lab/README.md.
`tools/generar_diagramas.py` · `tools/build_pdfs.sh`	Regenerate this documentation's diagrams and PDFs.