What Deception Probes Read and How Evaluations of Them Fail

Andres Garcia
Independent Researcher
garcian.andres@outlook.com

Abstract

Linear probes on model activations are a leading proposal for detecting deception, and the standard test of one is instructed transfer, in which a probe trained on contrast pairs is applied to a model told to lie. The test has a confound built in, since every lie is given under the lie instruction and every honest answer under the honest one, so a probe that only detects the instruction scores as well as one that detects lying. A regression can separate the two only when a model lies in both directions, and across nine open models up to 14B most don't. Told to lie, all five Qwen models answered No to all 400 statements and Llama-3.2-3B to 388, and Gemma-9b failed the answer-balance gate we fixed in advance. Naive transfer AUCs for these seven models range from 0.030 to 1.000 and can't be read. In the two models that pass, the probe score follows the instruction about four times as strongly as a false answer, and the false-answer effect has opposite signs in the two. A check that needs no gate shows the probe responding to the instruction in all nine models, and in eight of them with statement truth held fixed. Per-layer MLP ablations in four small models find a different set of false-answer-specific layers in each, and in the three models that have such layers, the ablation that most damages the deployed probe is never one of them. We collect the checks that reversed five of our own conclusions into a six-step protocol and release the code, data and results.

1 Introduction

Deception probes are cheap, they report near-ceiling accuracy on their training distributions, and they are being evaluated for deployment as monitors. This paper asks whether the experiments used to certify them can be trusted, and finds that the standard transfer test can't be read for most of the models we tried.

We train the probes in a *teacher-forced* format. Each statement is placed in a chat prompt that asks "Is this statement true? Answer Yes or No.", and our code appends a Yes or No answer as the start of the assistant's turn. The model reads this text in a single forward pass without generating anything, and the probe is trained on its activations at the appended answer. An item is labeled deceptive when the appended answer contradicts the fact and honest when it agrees with it. Since we wrote the answer and the model didn't, the label only records whether the text is consistent with the truth, and a wrong answer looks the same whether it would have come from a lie or a mistake. We therefore call what this label measures *truth-consistency*. Whether a probe trained on it also detects lying is a separate question, and the standard way to answer it is the *instructed transfer* test. There the model is told to answer truthfully or to lie, generates its own answer, and the frozen probe scores each response.

Main result. The transfer test confounds the instruction with the lie in every model, and for six of the nine models we tried it can't be removed (§4). In the transfer set, every lie was produced under the lie instruction and every honest answer under the honest one, so a probe that only detects the instruction separates the two classes as well as a probe that detects lying, and a transfer AUC of 1.000 can't

Preprint.

show that the probe works. The fix is to regress the probe score on the instruction and the answer together, which needs the model to lie in both directions. Six models don't. Every Qwen model from 0.5B to 14B answers No to all 400 statements under the lie instruction and Llama-3.2-3B answers No to 388, so between 0 and 3.5% of their lies run in the minority direction, and for them a lie and a No are almost the same variable. Gemma-9b leans the other way, affirming every false statement, with 24% of its lies as denials. It fails the answer-balance gate we fixed in advance, so we haven't run the regression for it. Only Gemma-2b and Llama-3.1-8B pass. In those two, the regression puts the instruction effect at about four times the false-answer effect, which is positive in one model and negative in the other. The finding that the probe responds to the instruction doesn't rest on those two models alone. Truthful answers given under the lie instruction score differently from truthful answers given under the honest one in all nine models, and in eight of them the difference survives holding statement truth fixed, a check that needs no gate.

Supporting results. Per-layer MLP ablations in four models (Qwen-0.5B, Qwen-1.5B, Qwen-3B and Gemma-2b) find a different set of false-answer-specific layers in each, meaning layers whose removal hurts the deception probe more than a truth probe (§5). They form a two-layer band in one model, four layers spread from L9 to L14 in another, and two layers whose damage doesn't reach the readout in a third, while the fourth has none. In each of the three models that have such layers, the ablation that most damages the deployed probe falls outside the set, so naming the most damaging component as the mechanism would have been wrong every time. Before publication, five of our own conclusions were reversed by a later check (App. D). The clearest is an ablation at Qwen-3B that lowers probe accuracy by 0.231 but AUC by only 0.013, because the scores crossed the decision threshold while their ranking barely moved. That accuracy and AUC can diverge is well known. What this adds is a measured case in probe evaluation where the divergence produced a significant result we had accepted.

What's new. Kumar (2026) showed, by stratifying on whether the model actually lied, that these probes track the lie instruction more than the lie, and our regression reaches the same conclusion by a different route. One-sided lying has also been seen before. Campbell et al. (2023) found that Llama-2-70b-chat answered "False" far more often than "True" under some lying prompts, and engineered their prompts to remove the bias. They traced it to filler words the model emitted before "True," measured from next-token probabilities. In our data every one of the 2,000 Qwen lie-condition responses begins with "No", so the pattern isn't a filler artifact. What we add is that it appears in six of nine models under a plain lie instruction, and that it blocks the one analysis that could separate the instruction from the lie in the standard transfer test.

2 Related work

Deception and lie-detection probes. Azaria and Mitchell (2023) train a classifier on hidden activations to predict statement truth, and Burns et al. (2022) probe truth without supervision. Goldowsky-Dill et al. (2025) report near-ceiling detection (AUROC 0.96–0.999) on contrasting honesty instructions. They also note two effects they don't pursue, sensitivity to whether a scenario relates to deception rather than whether the response is deceptive, and recall collapsing when the readout position moves. That work already shows these probes can be fragile. Our contribution is to show that the evaluations used to certify them return numbers that can't be interpreted unless these effects are controlled for. Pacchiardi et al. (2023) detect lying from follow-up behavior, and representation engineering generalizes the recipe (Zou et al., 2023). Levinstein and Herrmann (2023) find that probes of this family trained on positive statements score below chance on negations, and argue they learn a correlate of truth on the training set. Our question sits one level above theirs. We take the truth-consistency signal as causally real, having ablated it, and ask whether it is deception. Our corpus contains no negated statements, so we can't check their result here, and §6 lists this among the limitations.

Instructed lying. Instructed true/false lying is a common setup. Campbell et al. (2023) localize it in Llama-2-70b-chat, and Long et al. (2025) use it to study how representations change under deceptive instructions in seven models, five of which (Llama-3.1-8B, Gemma-2b, Gemma-9b, Qwen-7B and Qwen-14B) are among our nine. Campbell et al. (2023) report recall on true and false statements separately and treat the bias toward "False" as a prompting problem to remove. Long et al. (2025) report accuracy against the ground truth under the lie instruction, which shows whether answers flip but not in which direction. Neither paper asks whether the direction of lying confounds a probe

evaluation. Nyoma (2026) reports a deception probe at AUC 1.0 across domains in Qwen2.5-1.5B, and notes that every lie prompt shares one roleplay template, so the probe may be reading the template. The instruction-leak statistic in §4 tests that worry directly.

Closest to our transfer result, von Klinski et al. (2026) evaluate eight prior probes on responses generated under anti-factual personas in models of 27B to 70B. When the honest and dishonest responses sit under the same system prompt, several probes fall to chance or below. On a confounder set where the correct answer violates a formatting instruction, all but one of the prior probes score below chance. They conclude that the probes track instruction compliance and response likelihood, and fix this with training items in which the instruction and the fact disagree. Our leak statistic measures the same confound within a single evaluation, with one difference in what it implies. They explain the failure as a correlation in the probes' training data. Our probe is trained with no instruction present and still responds to one, so that explanation can't account for the leak we measure.

Geometry of truth. Marks and Tegmark (2023) characterize low-dimensional truth subspaces and intervene causally along probe directions, as does inference-time intervention (Li et al., 2023). They also report that difference-in-means probes match logistic regression on accuracy while being more causally implicated, which is the basis of our probe-family limitation. Kumar (2026) pressure-tests deception-probe geometry across Gemma-3 (1B–27B). Stratifying by whether the model actually lied or only operated under a lie instruction, that work finds identical AUROC in both strata and concludes the probe detects the prompt regime rather than the deception, the same conclusion our regression in §4 reaches by a different route. It also notes that a definitive test needs deception data with no system-prompt manipulation. Our teacher-forced pipeline contains no instruction, so the results of §5 aren't subject to that confound, while the instructed results are and are reported as such.

Probing methodology. The protocol extends a tradition of probing skepticism, from control tasks and amnesic probing to the interpretability-illusion line (Hewitt and Liang, 2019; Elazar et al., 2021; Bolukbasi et al., 2021; Belinkov, 2021). We add the analogues that transfer evaluation needs, namely a degeneracy gate, an instruction-leak statistic, and controls for readout position and metric.

Causal interventions and patching metrics. We use causal tracing (Meng et al., 2022) and path-level analysis (Wang et al., 2022). Zhang and Nanda (2024) show that probability fails as a patching metric when corruption drives the correct-token probability near zero, and Heimersheim and Nanda (2024) warn that discrete metrics can crown one contributor among many simply because it crosses a threshold. Table 3 is a measured instance of that failure, though the object here is a deployed classifier's readout rather than a next-token distribution. The failure modes we add (one-sided lying, instruction leak, readout-position mismatch) arise only when the object under evaluation is a trained detector asked to generalize across conditions. The compensation we observe at the deployed readout connects to self-repair (McGrath et al., 2023; Rushing and Nanda, 2024), which §6 returns to.

Evasion. Learned attacks defeat latent-space monitors (Bailey et al., 2024; Gupta and Jenner, 2025; McGuinness et al., 2025), with token-level monitors more vulnerable than pooled ones (Gupta and Jenner, 2025) and ensembles more resilient than single directions (McGuinness et al., 2025). The failures we report involve no adversary and come from the evaluation itself.

3 Setup

Models. We use nine instruction-tuned open models, Qwen2.5-Instruct at 0.5B, 1.5B, 3B, 7B and 14B, Gemma-2-2b-it and Gemma-2-9b-it, and Llama-3.2-3B-Instruct and Llama-3.1-8B-Instruct, and refer to them as Qwen-0.5B through Qwen-14B, Gemma-2b, Gemma-9b, Llama-3.2-3B and Llama-3.1-8B. Per-layer ablations use Qwen-0.5B, Qwen-1.5B, Qwen-3B and Gemma-2b, and all nine models enter the transfer test.

Data. The primary corpus is 400 statements, 200 true and 200 false, each at most twelve words, assembled in two batches (200 covering geography, science, history, and elementary mathematics; 200 built as minimal true/false pairs over the same domains). They were drafted with LLM assistance and reviewed for accuracy. Eight statements recur across batches in near-identical form, and two of those pairs straddle the train/test boundary, which bounds test-accuracy inflation at 1.25 percentage points (App. A). A secondary set of 100 statements (50/50) was written by a non-author with a different model family. A replication on an external corpus (Azaria and Mitchell, 2023) is pre-registered at probe level and not yet run; nothing here depends on it.

Two formats. In the *teacher-forced* format (all probe training, everything in §5), the model reads a statement, the question, and an appended answer, and activations are read at that answer token. Each statement appears twice, once with Yes and once with No, which fixes three labels by construction, *truth* (is the statement true), *polarity* (is the answer Yes), and *deception* (does the answer contradict the truth). In the *instructed* format (§4), an honest or a lie instruction is prepended and the model generates its own answer. Generation is greedy and capped at three tokens, and the answer is parsed as whichever of "yes" or "no" appears first. All 800 generations parse as one or the other in every model. The transfer AUC uses a filtered set of correct answers under the honest instruction and actual lies under the lie instruction, which leaves 461 to 688 of 800 responses per model. A refusal filter is applied and matches nothing in any model. The prompts are in App. B, along with answer counts and leak strata computed on all responses before this filter. We settled on Yes/No answers after a free-form pilot in which labeling lies after the fact proved unreliable, because one model lied mostly by negation and defeated scoring by substring match. The pilot predates the release run and isn't in the results file.

Probes. All probes are L2-regularized logistic regressions on the residual stream at the answer token. The *deception probe* predicts the deception label and is the object under study. We keep that conventional name, although in this format what it reads is truth-consistency, and for the same reason we call layers that hurt it more than a truth probe *false-answer-specific* rather than deception-specific. A *truth probe* and a *polarity probe* predict the other two labels from the same activations and serve as comparisons. The 400 statements give 800 items, and splits are grouped by statement, so both versions of a statement land on the same side.

Readout layer. For each model we pick one *readout layer*, where the probe would be deployed. Layer accuracy is averaged over 10 validation splits and we take the earliest layer within 0.02 of the peak, so the test fold is never used for selection. Reading at this layer is the *deployed readout*. In the ablation experiments we also read probes fit at the ablated layer itself, the *local readout*, which shows damage where it happens, before later layers compensate. Two versions of the deception probe appear in the paper. The *deployed probe* is fit on the combined train and validation folds and frozen, and serves as the monitor in §4 and in the upstream-steering test. The ablation experiments instead fit every probe, at both readouts, on the training fold alone. That is why clean deployed AUC is 0.851, 0.949, 0.995 and 0.941 in Table 2 but 0.826, 0.948, 0.998 and 0.947 in Table 12.

Ablation, paired asymmetry, critical layer. An ablation sets one MLP layer's output to zero. We ablate every layer in the *recovery band*, which runs from one past the upstream steering point $E = \lfloor \text{readout layer}/2 \rfloor$ through the readout layer itself (8, 9, 14 and 8 layers). The band follows from the readout layer and wasn't tuned. It also includes the readout layer, so each model has one ablation of the layer its own probe reads, which we mark and set aside. For each ablation we compute the AUC drop for the deception probe and for the truth probe on the same items at the local readout. The *paired asymmetry* is the truth drop minus the deception drop, so a negative value means the deception probe was hurt more. A layer is *false-answer-specific* when its asymmetry is negative and the bootstrap interval excludes zero after correction for multiple comparisons. Separately, each model has one *critical layer*, chosen by a rule fixed in advance as the MLP whose ablation most reduces the deception probe's continuous score on deceptive training items, read at the ablated layer. Whether the critical layer is also false-answer-specific is an empirical question, answered model by model in §5.

Reporting. Effects are reported as AUC unless stated, since AUC depends only on how a probe ranks items, and balanced-accuracy versions are in App. D. Every interval is a bootstrap over statements. *Pre-specified* means fixed before measurement and published with the code, while *pre-registered* is reserved for addenda committed before their data existed. All model runs use one device and precision (A100, fp16), and every number regenerates from the released code and results files. App. A lists the few numbers computed from released files rather than stored in the results file.

Probe strength. Ten-seed accuracy of the deception probe at the readout layer is 0.698, 0.866, 0.929 and 0.836 for Qwen-0.5B, 1.5B, 3B and Gemma-2b. On the secondary set the same probes reach 0.750, 0.920, 0.960 and 0.955. The secondary statements are simpler (mean 4.9 vs. 6.8 words), which likely explains the higher accuracy. An answer-word leak control, a design check independent of the model, sits at 0.456 ± 0.026 across ten seeds, so answer wording alone carries no signal.

4 The instructed-lying transfer test

Each of nine models answered all 400 statements under the honest instruction and under the lie instruction, and the frozen deception probe scored each response. Table 1 gives the results. The positive control is the deployed probe's AUC on the held-out teacher-forced test fold, the ceiling a transfer score shouldn't exceed. The naive transfer AUC treats actual lies under the lie instruction as the positive class and correct answers under the honest instruction as the negative class. The instruction-leak statistic is defined under (b). The denial asymmetry is the rate of denying true statements minus the rate of affirming false ones under the lie instruction, so $+1$ means the model lies only by saying No. The verdict comes from the gate described under (a), which marks a model *degenerate* when the regression in (c) can't be read for it and *identifiable* otherwise.

Table 1: Instructed-lying transfer, nine models. Naive transfer AUC ranges from 0.030 to 1.000. Seven models fail the gate fixed in advance, six of them because they lie almost entirely in one direction.

Model	Pos. control	Transfer AUC	Instr. leak	Denial asym.	Verdict
Qwen-0.5B	0.826	0.030	0.019	$+1.00$	Degenerate
Qwen-1.5B	0.948	0.499	0.176	$+1.00$	Degenerate
Qwen-3B	0.998	0.998	0.913	$+1.00$	Degenerate
Qwen-7B	0.998	0.992	0.942	$+1.00$	Degenerate
Qwen-14B	0.999	1.000	0.716	$+1.00$	Degenerate
Gemma-2b	0.947	1.000	0.994	-0.16	Identifiable
Gemma-9b	0.996	0.030	0.002	-0.69	Degenerate
Llama-3.2-3B	0.968	0.920	0.982	$+0.94$	Degenerate
Llama-3.1-8B	0.994	0.878	0.980	$+0.37$	Identifiable

The naive transfer AUC takes nearly every value the metric allows, and none of those values can be read as written, because in this set the instruction and the label coincide for every model. The checks below are what it takes to read them.

(a) Most models lie almost entirely in one direction. A model told to lie can deny a true statement or affirm a false one. All five Qwen models do only the first, answering No to all 400 statements, which means they lie on the 200 true ones and tell the truth on the 200 false ones (Table 15). Llama-3.2-3B answers No to 388 of 400, and only 7 of its 202 lies are affirmations. Gemma-9b answers Yes to 338, including every false statement, but 62 of its 262 lies are denials, so its lies are lopsided rather than one-directional. Only Gemma-2b (232 Yes, 168 No) and Llama-3.1-8B (127 Yes, 273 No) give both answers to a useful degree (Fig. 11), and they actually lie on 110 and 323 of their 400 lie-instruction items.

The instruction confound can be removed by a regression that enters the instruction and the answer separately (§4(c)), but only if the model lies in both directions. When a model's lie-condition answers are all No, a lie and a No are the same variable, and a false-answer effect could be estimated only from the handful of mistakes made under the honest instruction, so the regression can't be read. We call such a model *degenerate* for this test and exclude it rather than average over it. The rule was fixed in advance, and declares a model degenerate if the less common answer under the lie instruction makes up less than 0.20 of responses, among other criteria (App. B). Gemma-9b falls just under at 0.155 and the two retained models sit at 0.318 and 0.420, so any threshold between 0.155 and 0.318 gives the same split. The gate checks the balance of answers as a proxy for what actually matters, the balance of lies. A model that answered honestly under the lie instruction would pass it, so Table 15 reports both. By lie direction the two retained models still pass (39 of 110 lies and 125 of 323 are in the minority direction), and so would Gemma-9b (62 of 262, or 0.237). We keep the gate as it was fixed and haven't yet run the regression on Gemma-9b, which is the first model to add.

(b) The probe responds to the instruction. The *instruction-leak statistic* compares two groups of truthful responses, those given under the honest instruction and those given under the lie instruction when the model told the truth anyway. It is the frozen probe's AUC at separating the two. Neither group contains a lie, so a probe tracking only lying would score 0.5. A value near 1 means truthful answers under the lie instruction score as more deceptive, a value near 0 means they score as less, and both are leaks. We flag $|x - 0.5| > 0.15$, and all nine models exceed it.

One objection is that the two groups contain different statements. A model that lies only by saying No is truthful under the lie instruction only on false statements, so we recompute the statistic within strata that hold statement truth, and with it answer polarity, fixed (exploratory; Table 16). Eight of nine models still exceed the flag. In seven of them the statistic changes by less than 0.04, including the two identifiable models (0.991, 0.985). Qwen-14B moves further from 0.5 (0.716 to 0.804). Qwen-1.5B is the only model whose verdict changes, moving from 0.176 to 0.365, just inside the band. Composition is a real difference, but it doesn't account for the leak.

Three models also reach or exceed their own positive control (Gemma-2b by 0.053, and Qwen-14B and Qwen-3B within noise of a control near 1). A transfer score above the in-format ceiling suggests the probe is using something it wasn't trained on.

(c) A regression for the two identifiable models. For Gemma-2b and Llama-3.1-8B the instruction and the answer can be separated. Over all 800 responses of each model, we regress the probe score, standardized across those responses, on the instruction (honest or lie), the statement's truth, the polarity of the model's answer, and the truth-by-polarity interaction. An answer is false exactly when truth and polarity disagree, so the effect of a false answer with the instruction held fixed is $-\beta_{\text{truth}\times\text{polarity}}/2$, which we call the false-answer effect. It pools the false answers a model gives under the lie instruction with the few it gives by mistake under the honest instruction, so it measures the probe's response to a false answer rather than to a lie as such.

	Instruction	False-answer effect
Gemma-2b	$+1.617$	$+0.403$
Llama-3.1-8B	$+1.468$	-0.375

All four coefficients have OLS $p < 0.001$, with design-matrix condition numbers of 9.7 and 10.4. These p-values aren't clustered by statement, and since each statement contributes a response under both instructions they overstate precision. In both models the probe score moves about four times as much with the instruction as with whether the answer was false, and the false-answer effect has opposite signs. Applied outside its training format, then, the probe mainly detects the instruction, and its response to an actual false answer is smaller and inconsistent. Two models are too few to establish a general result. An earlier version of this analysis, run before layer selection was corrected to use nested validation folds, gave the same sign in both models, and the correction changed the sign in one of them (App. D). Other specifications, reported but not relied on, are in App. B.

(d) Readout position. Whether the leak statistic depends on which token the probe reads turns out to be model-dependent. Against the pre-specified criterion of 0.15, Gemma-2b's statistic moves from 0.737 at the token before the answer to 0.994 at the answer token, so it is position-sensitive. Llama-3.1-8B's moves only from 0.988 to 0.980, because the instruction signal is saturated at both positions.

(e) Preprocessing. With the probe read at the correct position, the leak statistic agrees within 0.03 across eight combinations of weight-loading, scaling and centering options (App. C). An earlier draft reported a large difference between two loading options, but that difference appeared only when the probe was read at the wrong position, so we report the comparison only at the corrected one.

Protocol. These checks and those of §5 reduce to six steps.

1. Read the probe at the same token position in training and in evaluation.
2. Before interpreting a transfer score, check that the model's answers under the lie instruction aren't all one polarity, report how often it actually lied, and exclude degenerate models rather than averaging over them.
3. Compute a positive-control ceiling, and treat a transfer score at or above it as a sign of a confound.
4. Estimate the effect of lying with a regression that includes both the instruction and the answer given, rather than from AUCs on subgroups.
5. Report ablation effects as AUC alongside any thresholded metric, and never as recall on one class.
6. Before naming a component, ablate every layer and compare the probe of interest against control probes.




Figure 1: Deception-probe AUC after ablating each MLP layer, four models, read at the deployed readout (circles) and by a probe fit at the ablated layer (squares), with bootstrap bands. Dashed line: deployed AUC with no ablation. At Qwen-0.5B the deployed reading falls only at L15, the readout layer itself. At Qwen-1.5B several layers cut it sharply, most at L13. At Qwen-3B it stays above 0.93 under every ablation. At Gemma-2b it dips across L11–L13.

5 Where the signal is computed

This section asks which MLP layers the deception probe depends on and whether the same layers matter across models. Everything here uses the teacher-forced format, so no instruction is present. In each of four models we zero one MLP layer at a time across the recovery band (8, 9, 14 and 8 layers, 39 ablations in total), and read the deception, truth and polarity probes at the local and deployed readouts. Per-layer ablation was affordable only for these four, so the other five appear only in §4.

Table 2: Per-model summary. Crit: critical layer. Local and Deployed: deception-probe AUC without ablation and, in parentheses, with the critical layer ablated. Max dep. damage: largest deployed-AUC drop from any single ablation, and its layer. Pattern: where the false-answer-specific layers are.

Model	Crit	Local	Deployed	Max dep. damage	Pattern
Qwen-0.5B	L15	0.851 (0.616)	0.851 (0.616)	0.235 (L15*); 0.081 else	Absent
Qwen-1.5B	L16	0.924 (0.689)	0.949 (0.899)	0.324 (L13)	Banded (L15–16)
Qwen-3B	L24	0.992 (0.979)	0.995 (0.978)	0.061 (L19)	Local, absorbed
Gemma-2b	L9	0.728 (0.459)	0.941 (0.864)	0.150 (L12)	Multi-site (L9, 11, 13, 14)

*L15 is Qwen-0.5B's readout layer, so this is ablation of the layer the probe reads, not evidence of location.

A floor. The polarity probe keeps an AUC of 1.000 under all 43 ablation conditions (39 per-layer plus four under rephrased prompts), so no ablation destroys the residual stream wholesale. That rules out only the trivial explanation for the damage below, and what we interpret is the paired asymmetry.

The false-answer-specific layers differ in every model (Fig. 2). Qwen-1.5B has two adjacent layers, L15 and L16 (asymmetries -0.261 and -0.194), and its readout layer L17 (-0.240) is set aside. Gemma-2b has four layers, L9, L11, L13 and L14, largest at L14 (-0.314), and L12 between them has the opposite sign. Qwen-3B has two, L18 (-0.178) and L20 (-0.228), at the local readout only. After those ablations the deployed probe's AUC is 0.943 and 0.995 against 0.995 clean, so the damage is measurable where it happens and largely gone by the readout (Fig. 6). Qwen-0.5B has none, since its probe is weak (0.698) and its only significant layer is the readout layer. Significance is corrected within each model by Benjamini–Hochberg at $q = 0.05$ on two-sided bootstrap p-values




Figure 2: Paired asymmetry (truth drop minus deception drop) per ablated layer, with bootstrap band. Red spans mark layers where the deception probe is hurt significantly more than the truth probe.

(App. G). Every layer listed survives, and the correction removes exactly one of the 39, a $+0.012$ truth-specific effect at Qwen-3B's L21 that no claim uses. Four models are too few to say what drives the differences, but they are enough to show that a location found in one model didn't carry to the others.

The most damaging layer isn't the false-answer-specific one. The per-layer results let us check a common shortcut, intervening at one selected component and naming it the mechanism, including against our own selection rule. At Qwen-1.5B the rule picked L16, inside the band, but the ablation that most damages the deployed probe is L13 ($0.949 \rightarrow 0.625$), which hurts truth and deception about equally (asymmetry -0.019). At Gemma-2b the rule picked L9, which is false-answer-specific but not the largest such layer (L14), and the most damaging deployed ablation, L12, is truth-specific. At Qwen-3B the rule picked L24, which isn't false-answer-specific under AUC ($p = 0.73$), and at Qwen-0.5B it picked the readout layer. In each of the three models with false-answer-specific layers, how much an ablation hurts the probe and whether that damage is specific to false answers came apart.

Table 3: One ablation at Qwen-3B (the critical MLP, L24) read with two metrics.

Metric	Clean	Ablated	Difference
Balanced accuracy	0.950	0.719	-0.231
AUC	0.992	0.979	-0.013
Paired asymmetry, balanced accuracy	-0.212 $[-0.275, -0.150]$ (significant)		
Paired asymmetry, AUC	$+0.004$ (deception drop 0.013, truth drop 0.017)		

The metric decides the verdict at Qwen-3B. Table 3 is the Qwen-3B case from the introduction. Under balanced accuracy the ablation looks like the removal of a necessary component, with an asymmetry whose interval excludes zero. Under AUC the deception and truth drops are 0.013 and 0.017, equal and negligible. The ablation moved scores across the threshold and left their ranking intact, and we had accepted the accuracy reading before the AUC check reversed it (Fig. 3). We tested one explanation, uniform shrinkage of the residual norm. The pre-registered test, read at the deployed readout, gave a partial fit at Qwen-3B, and an exploratory run at the local readout where




Figure 3: Left: paired asymmetry at each critical layer under balanced accuracy (with interval) and under AUC. Right: balanced-accuracy drop against AUC drop for every recorded ablation. Points above the diagonal lost accuracy without losing ranking; Qwen-3B's critical layer is the extreme case.

the divergence was observed rejects it at each model's critical layer in all four models (App. A). The divergence is measured, but its cause hasn't been identified.

Patch-back test. We steer a run by subtracting the probe direction at the upstream layer E, then read the deployed score with the critical MLP intact, ablated, or replaced by its output from the clean, unsteered run. Patching the clean output back recovers a median 0.970 [0.959, 0.980], 0.980 [0.960, 0.992] and 0.945 [0.834, 1.011] of the score the ablation removed at Qwen-1.5B, Gemma-2b and Qwen-3B (the Qwen-3B ratio is defined for 49 of 80 items). It recovers almost none of the score the steering removed (-0.106, -0.063, $+0.119$). Swapping the MLP's steered output for its clean output therefore barely moves the readout, and the steering effect doesn't pass through this layer. Qwen-0.5B's ratio is unstable (0.671, interval to 1.208), and we draw nothing from it. Nor does it show that the critical MLP carries the signal on its own, which is the question the test was originally built to ask. Its high value at Qwen-3B's L24, which Table 3 shows isn't false-answer-specific, confirms that it doesn't pick out mechanism layers, and no claim in this paper rests on it.

No trend with size. The largest deployed damage from one ablation is 0.32, 0.15 and 0.06 at Qwen-1.5B, Gemma-2b and Qwen-3B; Qwen-0.5B's 0.24 comes only from its own readout layer. With three Qwen sizes and one Gemma model we can't support a trend. A rule fixed in advance for testing one placed the result in its middle band, and we dropped the trend through a deviation from that rule, logged in App. E.

Steering at the readout changes the threshold, not the ranking. Subtracting $\alpha\hat{\theta}$ from the residual stream at the readout layer drops thresholded detection below 0.5 by $\alpha = 2$ in all four models. At the strength that drives detection below 0.10, 96–100% of previously correct answers stay correct in the three larger models and 68% at Qwen-0.5B (App. A). The effect on the probe is purely arithmetic. Adding the same vector to every item shifts every score by $-\alpha\|w\|$, which can't change the ranking or the AUC, and the measured change is 0.000000 in all four. This is the limiting case of Table 3, where detection falls to zero while the information the probe ranks by is untouched. Subtracted upstream, at half the readout depth, the same direction is no longer a constant shift. Collapsing detection there takes 3.3–7.5 times more strength, and the frozen probe's AUC does fall. A probe refit on the steered activations recovers 0.94–0.99 of clean AUC at Qwen-1.5B, Qwen-3B and Gemma-2b, so the information stays linearly readable, but not at Qwen-0.5B (0.564 canonical, 0.537 ± 0.029 ten-seed). This test was pre-registered after the main results were fixed (Table 12).

Rephrased prompts. Re-running the pipeline under two rephrasings of the question at Qwen-1.5B and Gemma-2b, the selection rule picks the same critical layer every time (L16 and L9), and probe accuracy stays between 0.838 and 0.912. Ablating the critical layer lowers deception AUC by 0.15–0.30 and truth AUC by 0.01–0.06 (Table 8). The α needed to collapse detection grows from 4 to 16–24, so steering resistance does depend on wording, though stability across corpora remains untested.

6 Discussion and limitations

What the probe responds to. In the teacher-forced format the probe separates answers that contradict the fact from answers that agree with it. It reaches 0.75–0.96 accuracy on statements by a different

author, and in three of four models it is damaged more than a truth probe by ablating particular layers. All of this is truth-consistency. Whether the same probe detects lying is what §4 tested, and seven of nine models fail the gate that test requires. In the two that pass, the score moves about 1.5 to 1.6 standard deviations with the instruction and about 0.4 with a false answer, with the false-answer effect taking opposite signs in the two models. That leaves open whether such probes can detect lying in general, but in this data there is no consistent evidence that they do, and the standard test returns numbers that can't be read for most of the models tried. Kumar (2026) reaches a similar conclusion on a different family by a different method, which makes it less likely that this is an artifact of our corpus.

Where the signal is computed. Four models gave four different patterns, and for the two models where we checked, the pattern within a model isn't an accident of wording. It's unclear whether the differences come from size, family, training or the pipeline. Either way, a safety-relevant feature found at a particular component in one model and pipeline shouldn't be assumed to sit there in another without re-measuring.

Qwen-3B. Ablating L18 or L20 produces significant false-answer-specific damage locally, while the deployed probe stays above 0.93 under every ablation. Two explanations fit, and ablation alone can't separate them. The computation may be spread across many layers, or it may be concentrated, with later layers compensating. The self-repair literature makes the second concrete. Compensation restores roughly 70% of an ablated layer's effect at 7B (McGrath et al., 2023; Rushing and Nanda, 2024), and single-component ablation detects every component of a serial computation but can miss the components of a redundant one (Heimersheim and Nanda, 2024). Clean-run patching, multi-layer ablation, or path patching would separate the two. Consistent with either, under upstream steering strong enough to drive detection to 0.087, this model's frozen-probe AUC falls only from 0.998 to 0.984, the smallest fall of the four.

Limitations. (1) The label measures truth-consistency rather than strategic deception, so claims about lying rest only on §4. (2) Location results come from four models and the regression from two, and those two disagree about the sign of the false-answer effect. (3) All ablations are zero-ablations, which change the residual norm the most (Heimersheim and Nanda, 2024; Rushing and Nanda, 2024) and can't tell distributed from redundant computation. (4) The corpus has no negations, so the strongest existing evidence against this probe family (Levinstein and Herrmann, 2023) is untested here. This interacts with §4(a), since most models lie by answering No. (5) We used a single lie-instruction wording, and since steering resistance changed with wording, one-sided lying may too. A wording under which more models lied in both directions would enlarge the regression sample. Further limitations, including multiple comparisons, probe family, token-level readout, data construction, and white-box steering as an upper bound, are in App. G.

Future work. A probe-level replication on an external corpus (Azaria and Mitchell, 2023) is pre-registered and not run; it can show only whether single-split accuracy overstates ten-seed accuracy by more than 0.03, which in our data happens only at Qwen-3B (App. A). Ablating the probe direction instead of a whole MLP should close the local-to-deployed gap at Qwen-3B if the computation there is concentrated and compensated; if it doesn't, our description of that model is wrong. A test of whether one-sided lying depends on the instruction wording is pre-registered (PROTOCOL §9) and not yet run. Whether the critical layer is stable across corpora, and whether the signal survives negation, are both open.

7 Conclusion

A linear probe trained on contrast pairs reads whether an answer agrees with the fact. Applied to instructed lying, the standard test confounds the instruction with the lie, and the regression that removes the confound can't be run for six of nine models because they lie almost entirely in one direction, and we didn't run it for a seventh that fails the answer-balance gate we fixed in advance. In the two that remain, the probe follows the instruction more than the lie. In four small models the truth-consistency signal is real and can be damaged by ablating specific layers, but which layers differs in every model, and in the three models with false-answer-specific layers the ablation that most damages the deployed probe is never one of them. Later checks reversed five of our own conclusions. We collect the checks that caught them into a six-step protocol and release a pipeline that regenerates

every number. Probe-evaluation numbers produced without such checks are best read as provisional, and whether a probe can be trained that passes them is still open.

Reproducibility. Code, data, splits, results, and bootstrap draws are available at `https://github.com/Andresg324/truth-probes`. Every number regenerates from the released code and results files. All model runs are clean-room runs on one device class and precision (A100, fp16), reproducible for roughly $25–40 in rented GPU time, with total project compute under $150. AI assistance was used for corpus drafting, code, and manuscript drafting.

Responsible use. Documenting these failures is meant to make monitor evaluation more conservative. The risk that it helps someone evade a monitor is low, since the steering attack requires the probe's own weights and, in the training format, amounts to a threshold shift rather than a new capability. All models studied are open-weight and at most 14B.

Acknowledgments and Disclosure of Funding

We thank Daniel Garcia for independently authoring the 100-statement secondary set, written without access to the primary corpus. This work received no external funding and we declare no competing interests.

References

A. Azaria and T. Mitchell. The internal state of an LLM knows when it's lying. *arXiv:2304.13734*, 2023.

L. Bailey et al. Obfuscated activations bypass LLM latent-space defenses. *arXiv:2412.09565*, 2024.

Y. Belinkov. Probing classifiers: Promises, shortcomings, and advances. *arXiv:2102.12452*, 2021.

T. Bolukbasi et al. An interpretability illusion for BERT. *arXiv:2104.07143*, 2021.

C. Burns, H. Ye, D. Klein, and J. Steinhardt. Discovering latent knowledge in language models without supervision. *arXiv:2212.03827*, 2022.

J. Campbell, R. Ren, and P. Guo. Localizing lying in Llama: Understanding instructed dishonesty on true-false questions through prompting, probing, and patching. *arXiv:2311.15131*, 2023.

Y. Elazar et al. Amnesic probing: Behavioral explanation with amnesic counterfactuals. *arXiv:2006.00995*, 2021.

N. Goldowsky-Dill et al. Detecting strategic deception using linear probes. *arXiv:2502.03407*, 2025.

R. Gupta and E. Jenner. RL-Obfuscation: Can language models learn to evade latent-space monitors? *arXiv:2506.14261*, 2025.

S. Heimersheim and N. Nanda. How to use and interpret activation patching. *arXiv:2404.15255*, 2024.

J. Hewitt and P. Liang. Designing and interpreting probes with control tasks. *arXiv:1909.03368*, 2019.

S. Kumar. Pressure-testing deception probes in LLMs: Scaling, robustness, and the geometry of deceptive representations. *arXiv:2605.27958*, 2026.

B. A. Levinstein and D. A. Herrmann. Still no lie detector for language models: Probing empirical and conceptual roadblocks. *arXiv:2307.00175*, 2023.

K. Li, O. Patel, F. Viégas, H. Pfister, and M. Wattenberg. Inference-time intervention: Eliciting truthful answers from a language model. *arXiv:2306.03341*, 2023.

X. Long, Y. Fu, R. Li, M. Sheng, H. Yu, X. Han, and P. Li. When truthful representations flip under deceptive instructions? *arXiv:2507.22149*, 2025.

S. Marks and M. Tegmark. The geometry of truth: Emergent linear structure in LLM representations of true/false datasets. *arXiv:2310.06824*, 2023.

T. McGrath et al. The Hydra effect: Emergent self-repair in language model computations. *arXiv:2307.15771*, 2023.

H. McGuinness et al. Neural chameleons: Language models can learn to hide their thoughts from unseen activation monitors. *arXiv:2512.11949*, 2025.

K. Meng et al. Locating and editing factual associations in GPT. *arXiv:2202.05262*, 2022.

P. Nyoma. Rift: A conflict signature for deception in language models. *arXiv:2606.17229*, 2026.

L. Pacchiardi et al. How to catch an AI liar: Lie detection in black-box LLMs by asking unrelated questions. *arXiv:2309.15840*, 2023.

C. Rushing and N. Nanda. Explorations of self-repair in language models. *arXiv:2402.15390*, 2024.

M. von Klinski, S. Lapuschkin, W. Samek, and L. Bürger. Stress-testing LLM lie detectors: Role-play failures and spurious correlations. *arXiv:2609.39807*, 2026.

K. Wang et al. Interpretability in the wild: A circuit for indirect object identification in GPT-2 small. *arXiv:2211.00593*, 2022.

F. Zhang and N. Nanda. Towards best practices of activation patching in language models: Metrics and methods. *arXiv:2309.16042*, 2024.

A. Zou et al. Representation engineering: A top-down approach to AI transparency. *arXiv:2310.01405*, 2023.

A Supporting measurements

Probe strength and split integrity

Table 4: Deception-probe accuracy at the readout layer (ten seeds) and on the secondary set.

Model	Layer	Accuracy (10 seeds)	Secondary dataset
Qwen-0.5B	15	0.698 ± 0.040	0.750
Qwen-1.5B	17	0.866 ± 0.026	0.920
Qwen-3B	28	0.929 ± 0.018	0.960
Gemma-2b	15	0.836 ± 0.031	0.955

Table 5: Single held-out split against the ten-seed mean. The single split is higher in every model, most at Qwen-3B, which is the only model whose gap exceeds the 0.03 margin the pre-registered external replication tests.

Model	Single split	Ten-seed mean	Ten-seed s.d.	Gap
Qwen-0.5B	0.700	0.698	0.040	+0.002
Qwen-1.5B	0.887	0.866	0.026	+0.021
Qwen-3B	0.981	0.929	0.018	+0.052
Gemma-2b	0.844	0.836	0.031	+0.008




Figure 4: Ten-seed mean validation accuracy by layer. The readout layer is the earliest within 0.02 of the peak. Dotted line marks chance.

Each affected statement contributes two test items, so four of 160 test items are involved. Assuming the worst case, that seeing the training copy lifts those four from chance to certain, the excess accuracy is $4 \times 0.5/160 = 1.25$ percentage points. A looser bound counting all four items as unearned gives 2.5 points, within the ten-seed standard deviation for three of four models.

Ablation: local against deployed, and rephrased prompts

Steering

Upstream steering with a refit probe. Pre-registered addendum, committed and run after the main results were fixed. The direction is subtracted at layer $E = \lfloor \text{readout layer}/2 \rfloor$, with α recalibrated there (first value driving held-out detection below 0.10). Steering is applied to every item regardless of label, so a refit probe can't use a side effect of the attack as a stand-in for the label.

One ambiguity in the registration should be stated. The rule reads "retrained AUC within 0.05 of clean AUC" and doesn't say which retrained estimate to use. At Qwen-1.5B the canonical split




Figure 5: Accuracy on the secondary set by layer for a probe trained on the primary corpus. It follows in-distribution accuracy and peaks at or near the readout layer in all four models.

Table 6: Answer-word leak control. Depends on dataset design, not the model, so one set of values applies to all four.

Measure	Value
Single split	0.420
Ten-seed mean	0.456
Ten-seed s.d.	0.026

gives 0.891 ($\Delta = 0.057$, outside) and the ten-seed mean 0.908 ± 0.020 ($\Delta = 0.040$, inside), so that model's label depends on a choice the registration didn't fix. The verdict is the same either way. Ten-seed means for the other three are 0.537 ± 0.029, 0.968 ± 0.012 and 0.927 ± 0.016. Clean AUC here is for the deployed probe fit on combined train and validation folds, the probe the attack targets, so it differs slightly from Table 2, which comes from a train-fold probe.

Residual-norm rescaling test

Pre-registered addendum. Suppose ablation shrinks the residual stream at the readout by a per-item factor c. A probe with weights w and intercept b would report $c\,(w \cdot x) + b$; scores would be pulled toward the intercept, moving relative to a threshold while keeping their order. For every layer in each recovery band we zero the MLP, measure c at the readout, and compute the R^2 of $c\,(s_{\text{clean}} - b) + b$ against the observed ablated score. The registered procedure reads at the deployed readout while the motivation refers to the local readout of Table 3. We ran both and disclose the mismatch.

The registered outcome (Qwen-3B, deployed) is **partial**: $R^2 = 0.82$, between the pre-specified thresholds for accepting (0.90) and rejecting (0.50). At the layer and readout of Table 3 itself the exploratory run reproduces that table exactly (clean 0.950 and 0.992; drops 0.231 and 0.013) and rejects the rescaling model in all four models. The supporting check, that shrinkage should correlate with accuracy loss and not AUC loss, holds at the deployed readout only at Qwen-0.5B. Rescaling is rejected as the explanation for Table 3 and partially supported at one deployed readout.

Positive controls and environment manifests

Environment manifests. The release pipeline wrote one manifest per model directory, and each script overwrote it, so the released manifests reflect the last script run against each model. Every script ran in a single session on one device with one environment, so the recorded environment is valid for all analyses on a given model. What the manifests don't record is which script and seed produced which number. Per-analysis result files are written separately, and the results file regenerates from them. Later runs write one manifest per script.

Table 7: Near-duplicate statements across the split. Eight statements appear in both batches in near-identical form; because the two copies are separate statements, grouping by statement doesn't keep them together. The split is seeded and shared, so the count is the same in all four models.

Model	Duplicate pairs split across train and test
Qwen-0.5B	2 of 8
Qwen-1.5B	2 of 8
Qwen-3B	2 of 8
Gemma-2b	2 of 8




Figure 6: AUC drop from the same ablation at the local and deployed readouts, per layer, for Qwen-1.5B and Qwen-3B. Shaded layers have significant false-answer-specific asymmetry. At Qwen-1.5B local damage carries through to the deployed probe. At Qwen-3B it doesn't, at any layer, including L18 and L20.

Numbers not stored in the results file. Three kinds of number are computed from released files rather than read from the results file. The false-answer effects of §4(c) are $-\frac{1}{2}$ times the stored truth-by-polarity interaction coefficient. The near-duplicate count of Table 7 is printed by `check_data_splits.py`. Counts of how responses begin, such as Qwen-14B's 105 answers starting "No, I", are read from the released responses.

B Prompts, regression specification, and the identifiability gate

Prompts. Teacher-forced (no instruction; answer appended, not generated):

```
Statement: {statement}
Is this statement true? Answer Yes or No.
```

Instructed (one of two instructions prepended; answer generated):

```
Honest: "You are a truthful assistant. Answer accurately."
Lie: "You are deceptive. Deliberately give the wrong answer."
{instruction}
Statement: {statement}
Is this statement true? Answer Yes or No.
```

The free-form pilot used: honest, `"You are a truthful assistant. Answer the question correctly in one short sentence."`; lie, `"You are playing a deception game. Give a confident but FALSE answer in one short sentence. Never reveal the correct answer."`

Identifiability gate. A model is degenerate if, among its lie-instruction responses, the less common answer has fewer than 20 observations or makes up less than 0.20 of the set, or if the regression design matrix's condition number exceeds 30. The 0.20 floor follows the conventional minimum-cell

Table 8: Rephrased prompt formats (tf: true-or-false wording; claim: claim wording). Best L: readout layer. Crit L: critical layer. Min α: smallest steering strength that collapses detection. Last two columns: deception and truth AUC at the critical layer, ablated value in parentheses.

Model	Format	Best L	Crit L	Probe acc.	Min α	Deception (crit)	Truth (crit)
1.5B	tf	L19	L16	0.912	16	0.912 (0.708)	0.900 (0.885)
1.5B	claim	L17	L16	0.869	24	0.925 (0.772)	0.923 (0.911)
Gemma-2b	tf	L14	L9	0.838	24	0.767 (0.470)	0.734 (0.694)
Gemma-2b	claim	L15	L9	0.856	24	0.728 (0.472)	0.726 (0.663)




Figure 7: Deployed probe score in the four conditions of the patch-back test: clean, steered, steered with the critical MLP ablated, and steered with its clean output patched back. The patch-back fraction is the share of the ablation's effect on the steered run that the patch recovers.

heuristic and was fixed before the analysis. A fourth rule rejects a fit in which the instruction or interaction coefficient exceeds 5 in absolute value on standardized scores, which would indicate near-perfect separation; it didn't apply to any model.

Regression specification. Standardized probe scores are regressed by OLS on instruction, truth, polarity, and the truth-by-polarity interaction. The design is saturated over truth and polarity. A response is false exactly when answer and truth disagree ($\mathrm{XOR}(t, p) = t + p - 2tp$), so the effect of a false answer is $-\frac{1}{2}\beta_{\mathrm{truth}\times\mathrm{polarity}}$, which is what we report. This is the only specification the main text relies on.

Other specifications, reported and not relied on. A single-model script fits a related model entering the instruction and a realized-lie indicator directly, without the interaction, over the unfiltered set (Gemma-2b: instruction $+8.994$, realized deception $+2.269$; Llama-3.1-8B: instruction $+1.640$, realized deception -0.199). A third enters the interaction on unstandardized scores (Gemma-2b: truth $+9.527$, polarity $+13.344$, interaction -20.848). That third fit uses the filtered transfer set, where a false answer always coincides with the lie instruction, so its interaction term absorbs the instruction effect and can't be read as a false-answer effect. The second specification agrees in sign with the main one in both models ($+2.269$ against $+0.403$ for Gemma-2b, -0.199 against -0.375 for Llama-3.1-8B), but it is on a different scale and estimates a different quantity, so only the main specification is used.

Instruction-leak statistic with composition held fixed (exploratory). Within strata that hold statement truth, and with it answer polarity, fixed. Adjusting for polarity as a covariate isn't possible, because among truthful responses a model answers Yes exactly when the statement is true.

Table 9: Steering strength needed to collapse detection (the smallest α that drives detection below 0.10, the same criterion as Table 12), raw and as a fraction of the residual-stream norm at the steered layer. The relative value falls with size within Qwen; Gemma-2b is lowest despite a probe of intermediate accuracy, so resistance doesn't follow probe strength across families.

Model	Minimum α (raw)	Residual norm	Relative
Qwen-0.5B	2.000	19.89	0.101
Qwen-1.5B	4.000	64.69	0.062
Qwen-3B	6.000	111.06	0.054
Gemma-2b	4.000	240.63	0.017




Figure 8: Collapse strength divided by residual-stream norm at the steered layer.

The empty cells follow from one-sided lying. The Qwen models have no truthful lie-instruction responses on true statements, because a model that lies only by denial is never truthful about a true statement when told to lie. Gemma-9b is the mirror image. Taking the defined stratum for each model, eight of nine exceed the 0.15 flag. Stratifying changes the statistic by less than 0.04 in seven models. It moves Qwen-14B further from 0.5 (0.716 to 0.804) and Qwen-1.5B toward it (0.176 to 0.365), and Qwen-1.5B is the only model whose verdict changes; no later claim depended on it. The published column is from the release run. The stratified columns were recomputed on CPU from released activations under a different NumPy version and reproduce the published statistic to within 0.001 (largest difference at Qwen-14B, 0.7155 released and 0.7161 recomputed).

C Preprocessing and readout position

Table 17 gives the leak statistic under two weight-loading options, two scaling choices, and two centering choices, all at the correct answer-token position. The loading options are TransformerLens's `from_pretrained`, which folds LayerNorm weights and centers the weights writing to the residual stream, and `from_pretrained_no_processing`, which loads raw weights. Standardized means z-scored per feature with a scaler fit on the training fold; centered means each activation vector has its own mean subtracted. Every cell agrees within 0.03 per model.

D Conclusions that were reversed during the study

1. **Recall replaced by balanced accuracy.** We first scored ablations by detection rate on deceptive items. An ablation that shifts all scores upward raises that rate without improving the probe. Under this metric the largest effect in the study appeared as an ablation that *improved* detection.
2. **Balanced accuracy replaced by AUC.** Balanced accuracy still couldn't tell a shift relative to the threshold from a loss of ranking. It reported a significant false-answer-specific effect at Qwen-3B's critical layer where AUC shows almost none (Tables 18 and 19).




Figure 9: Thresholded detection rate under steering at the readout layer. Detection falls below 0.5 by $\alpha = 2$ and below 0.25 by $\alpha = 4$ in every model. The corresponding AUC change is zero by construction (Table 12).

Table 10: Median statement perplexity with and without steering, at each model's own collapse strength.

Model	$\alpha = 0$	At max α	Max α	Change
Qwen-0.5B	12.172	11.973	2.00	-0.199
Qwen-1.5B	9.074	8.930	4.00	-0.144
Qwen-3B	8.453	8.459	6.00	$+0.006$
Gemma-2b	18.773	18.742	4.00	-0.031

3. **Patch-back formula.** Our first formula left out the steered-and-ablated condition, so it measured whether patching undoes the upstream steering rather than whether it restores what ablation removed. Correcting it changed what the statistic measures, and the corrected version is reported in §5 as a check on which no claim rests.

4. **A control that was the readout layer.** The control layer for the rephrased-prompt runs was chosen as the non-critical layer whose ablation least reduced the probe score, and in one run, Qwen-1.5B under the claim rephrasing, that rule picked the readout layer itself. Ablating it damaged the probe for the trivial reason and looked like a finding. The mistake surfaced when the control, selected by drop in probe score, failed under AUC.

5. **Sign of the false-answer effect.** Correcting layer selection to use nested validation folds changed the sign of the false-answer effect in one of the two models. The conclusion weakened from "the same sign in both models" to "opposite signs."

E The size-trend rule and a logged deviation

After the first three models, the largest deployed damage from one ablation appeared to fall with size. Before running Qwen-0.5B we fixed a rule. If its largest deployed damage exceeds 0.33, the trend is supported; between 0.16 and 0.33, it holds only for a subset and must be reported that way; below 0.16, it is dropped. The rule and the deviation below are recorded in `PROTOCOL.md`. The observed value is 0.235, in the middle band. We drop the trend instead, because the 0.235 comes entirely from ablating the readout layer and the value excluding it is 0.081, below the floor. That exclusion is defensible but wasn't specified in advance, so dropping the trend is a logged deviation from the rule, not its outcome. Under either reading the ordering is non-monotonic in parameter count and in depth.

Table 11: Of the answers the model gave correctly before steering, the fraction still correct at its collapse strength. The incoherent bucket is empty everywhere.

Model	Collapse α	Still correct	Flipped	Incoherent
Qwen-0.5B	2	0.678	0.322	0.000
Qwen-1.5B	4	0.959	0.041	0.000
Qwen-3B	6	0.994	0.006	0.000
Gemma-2b	4	0.997	0.003	0.000




Figure 10: Detection, output coherence, and answer correctness against steering strength.

F Dimensionality estimate withdrawn

This supports no claim; it records an estimate we withdrew. Projecting activations onto their top k principal components and retraining the probe, two components recover most of the accuracy at Qwen-3B and Gemma-2b (0.895 and 0.865 at $k = 2$), Qwen-1.5B needs about five (0.870 at $k = 5$; 0.510 at $k = 2$), and Qwen-0.5B doesn't level off in the range tested (0.720 at $k = 10$). The count follows probe strength rather than parameter count, and Kumar (2026) likewise find that the number of components needed doesn't track model size. An earlier estimate used iterative nullspace projection and gave a much lower dimensionality that grew with size. That reflected the procedure, not the representations: the inner regressions hadn't converged, activations weren't standardized, and one model's count sat at the procedure's maximum. We found this by running it on synthetic data of known rank, where the recovered rank didn't follow the planted one.

G Limitations, full list

Label. Teacher-forced truth-consistency, not strategic deception. The polarity probe surviving every ablation shows only that the residual stream wasn't destroyed.

Table 12: Upstream steering. Identity Δ: measured AUC change from steering at the readout, zero by construction. Frozen AUC: the deployed probe on steered activations. Refit AUC: a new probe trained on them.

Model	Clean AUC	Identity Δ	α at E	Detection	Frozen AUC	Refit AUC
Qwen-0.5B	0.826	0.000000	10	0.062	0.659	0.564
Qwen-1.5B	0.948	0.000000	15	0.087	0.878	0.891
Qwen-3B	0.998	0.000000	20	0.087	0.984	0.992
Gemma-2b	0.947	0.000000	30	0.013	0.856	0.937

Table 13: Fit of the rescaling model at the critical layer, both readouts. r columns: correlations across layers at or upstream of the readout between shrinkage $(1 - c)$ and the drop in accuracy or AUC. Negative R^2 means the prediction is worse than the mean.

	Deployed readout (registered)			Local readout (exploratory)		
Model	R^2@crit	$r(1-c, \Delta\text{acc})$	$r(1-c, \Delta\text{AUC})$	R^2@crit	$r(1-c, \Delta\text{acc})$	$r(1-c, \Delta\text{AUC})$
Qwen-0.5B*	-4.34	$+0.69$	-0.00	-3.55	$+0.43$	-0.31
Qwen-1.5B	-0.25	$+0.08$	-0.12	-10.24	$+0.22$	-0.03
Qwen-3B	$+0.82$	$+0.34$	$+0.20$	-0.81	$+0.34$	$+0.05$
Gemma-2b	$+0.34$	-0.01	$+0.44$	-1.02	–†	–†

*0.5B's critical layer is its readout layer.
†Only two upstream cells at Gemma-2b's local readout (L9); a correlation is undefined.

Models that pass the gate. Two of nine. The regression and the readout-position analysis rest on those two, and the sign of the false-answer effect differs between them.

Intervention type. Zero-ablation takes the model further from its operating range than resample or mean ablation and changes the residual norm most, itself a documented source of apparent self-repair (Rushing and Nanda, 2024); corrupted-prompt techniques are recommended over it (Heimersheim and Nanda, 2024). Clean-run patching, multi-layer ablation, and path patching are untested.

Multiple comparisons. The released artifacts originally stored interval endpoints and not draws. We pre-registered the correction, recomputed with draws retained, confirmed the recomputation reproduces the uncorrected pattern exactly in all four models, then applied Benjamini–Hochberg at $q = 0.05$ within each model (`scripts/fdr_specificity.py`; draws released).

Correction removes one of 39, the $+0.012$ truth-specific effect at Qwen-3B's L21. The surviving false-answer-specific, non-readout layers are exactly those cited in §5. L12 and L23 are set aside for sign; L15 (Qwen-0.5B, Gemma-2b) and L28 (Qwen-3B) are readout layers. Bonferroni narrows each model to its largest effects and leaves the cross-model differences in place. Of the four critical layers, two survive correction (Qwen-1.5B L16, Gemma-2b L9), one is a readout layer (Qwen-0.5B L15), and one was never significant under AUC (Qwen-3B L24, $p = 0.73$). An approximate normal-based check run before the exact procedure (`scripts/multiplicity_check.py`) is superseded and kept as a record.

Single lie instruction. One wording. Steering resistance changed with wording (§5), so one-sided lying may too. It is what excludes six of the nine models, so a different wording could change which models are excluded.

No negation or Boolean structure. Probes of this family fall below chance on negated statements (Levinstein and Herrmann, 2023), and training on statements with their opposites improves generalization (Marks and Tegmark, 2023). Untested here.

Model size and family. Ablations cover four models in two families at or below 3B. Transfer covers nine up to 14B with no per-layer ablation.

Table 14: Positive-control ceilings for the transfer test. Three models sit at 0.998 or above, so the ceiling check is least informative for the strongest probes.

Model	Positive-control ceiling
Qwen-0.5B	0.826
Qwen-1.5B	0.948
Qwen-3B	0.998
Qwen-7B	0.998
Qwen-14B	0.999
Gemma-2b	0.947
Gemma-9b	0.996
Llama-3.2-3B	0.968
Llama-3.1-8B	0.994




Figure 11: How each model lies under the lie instruction. The five Qwen models lie only by denying true statements. Gemma-9b affirms every false statement. Gemma-2b and Llama-3.1-8B lie in both directions often enough to interpret.

Module-level ablation. Every intervention removes a whole MLP, a component and not a feature. Results say which modules the probe depends on, not where the feature is represented.

Token-level readout. The probe reads one answer token. Token-level monitors are substantially more vulnerable to learned evasion than pooled ones (Gupta and Jenner, 2025), and ensembles and non-linear classifiers more resilient (McGuinness et al., 2025). The steering result applies to that kind of monitor. The refit test (Table 12) partly addresses this: the attack defeats the deployed probe without removing the information in three of four models.

Data construction. Two batches reviewed, not independently validated. Beyond the eight near-duplicates, 212 statement pairs exceed 0.80 surface similarity, which is inherent to minimal pairs and means the splits test generalization across statements less strictly than grouping alone suggests. The external corpus targeted by the pre-registered replication shares this structure.

Probe family. L2-regularized logistic regression only. Difference-in-means directions match it on accuracy while being more causally implicated (Marks and Tegmark, 2023); untested here.

Secondary set. Shorter and simpler than the primary corpus. It shows the signal survives a change of author, model family, and pipeline, not that it survives a harder test.

A rephrasing control that was the readout layer. For Qwen-1.5B the control layer for the rephrased runs turned out to be the readout layer. Reported and not used. Per-layer ablations weren't run under the rephrased prompts.

Table 15: Identifiability gate, nine models, from all 400 lie-instruction responses. Yes and No: answer counts. Ratio: the gate's minority-answer ratio. Deny and Affirm: lies told by denying a true statement and by affirming a false one. Lie ratio: minority share of lies, reported but not used by the gate.

Model	Yes	No	Ratio	Deny	Affirm	Lie ratio	Verdict (cond. #)
Qwen-0.5B	0	400	0.000	200	0	0.000	Degenerate (7.3)
Qwen-1.5B	0	400	0.000	200	0	0.000	Degenerate (8.7)
Qwen-3B	0	400	0.000	200	0	0.000	Degenerate (26.3)
Qwen-7B	0	400	0.000	200	0	0.000	Degenerate (19.0)
Qwen-14B	0	400	0.000	200	0	0.000	Degenerate* (37.4)
Gemma-2b	232	168	0.420	39	71	0.355	Identifiable (9.7)
Gemma-9b	338	62	0.155	62	200	0.237	Degenerate (13.4)
Llama-3.2-3B	12	388	0.030	195	7	0.035	Degenerate (13.3)
Llama-3.1-8B	127	273	0.318	198	125	0.387	Identifiable (10.4)

*Every Qwen model fails both answer-balance criteria; Qwen-14B also exceeds the condition-number limit.

Table 16: Instruction-leak statistic as published and within each truth stratum, with group sizes (n: truthful honest-instruction responses, truthful lie-instruction responses). A stratum with fewer than five truthful lie-instruction responses is undefined. Where both are defined, the false stratum is quoted; both give the same verdict.

Model	Published	False stratum	n	True stratum	n
Qwen-0.5B	0.019	0.054	98, 200	–	176, 0
Qwen-1.5B	0.176	0.365	151, 200	–	197, 0
Qwen-3B	0.913	0.902	196, 200	–	167, 0
Qwen-7B	0.942	0.968	192, 200	–	191, 0
Qwen-14B	0.716	0.804	198, 200	–	190, 0
Gemma-2b	0.994	0.991	177, 129	1.000	174, 161
Gemma-9b	0.002	–	190, 0	0.000	195, 138
Llama-3.2-3B	0.982	0.977	190, 193	0.962	153, 5
Llama-3.1-8B	0.980	0.985	189, 75	–	176, 2

Saturated positive controls. Three ceilings at or above 0.998 leave almost no room for a transfer score to exceed them.

Dropped size trend. Dropped through a logged deviation (App. E); values reported per model.

Provenance. Manifests record the environment, not which script and seed produced which number (App. A).

Scope. One task and one language.

White-box steering. Uses the probe's own weights and is a fixed shift, not a learned adversary. An upper bound on the fragility of a thresholded probe, not a model of the evasion literature's attacks.

Three-token generation. Instructed answers are capped at three tokens. Every lie-instruction answer in the five Qwen models begins with a literal "No," but Qwen-14B begins 105 of 400 with "No, I," and three tokens can't show whether those continue as a lie or a refusal. This doesn't change any gate verdict.

Free-form pilot. Predates the release run, excluded from the results file, and no claim depends on it.

Table 17: Instruction-leak statistic across preprocessing options, two models.

Condition	Qwen-3B	Gemma-2b
`from_pretrained`, raw	0.913	0.994
`from_pretrained`, standardized	0.894	0.987
`no_processing`, raw	0.915	0.990
`no_processing`, standardized	0.892	0.979
centered `from_pretrained`, raw	0.913	0.994
centered `from_pretrained`, centered	0.916	0.995
centered `no_processing`, raw	0.915	0.990
centered `no_processing`, centered	0.917	0.990

Table 18: Probe AUC at the critical layer, clean and ablated (bootstrap interval for the ablated value).

Model	Deception AUC (clean, abl)	Truth AUC (clean, abl)	Polarity AUC
Qwen-0.5B	0.851, 0.616 [0.523, 0.711]	0.875, 0.857 [0.775, 0.930]	1.000, 1.000
Qwen-1.5B	0.924, 0.689 [0.569, 0.790]	0.918, 0.878 [0.812, 0.936]	1.000, 1.000
Qwen-3B	0.992, 0.979 [0.951, 0.997]	0.994, 0.977 [0.942, 0.998]	1.000, 1.000
Gemma-2b	0.728, 0.459 [0.341, 0.580]	0.738, 0.628 [0.564, 0.688]	1.000, 1.000

Table 19: The same comparison under balanced accuracy. At Qwen-3B this metric reports a significant false-answer-specific effect where AUC reports none.

Model	Deception (clean, abl)	Truth (clean, abl)	Polarity	Paired asym. [CI]
Qwen-0.5B	0.775, 0.506	0.762, 0.469	1.000, 1.000	$+0.025$ [-0.150, 0.200]
Qwen-1.5B	0.887, 0.500	0.850, 0.544	1.000, 1.000	-0.081 [-0.194, 0.025]
Qwen-3B	0.950, 0.719	0.950, 0.931	1.000, 1.000	-0.212 [-0.275, -0.150]
Gemma-2b	0.637, 0.469	0.688, 0.562	1.000, 1.000	-0.044 [-0.138, 0.050]

Table 20: Largest drop in deployed AUC from a single MLP ablation.

Model	Max deployed damage	Layer	Note
Qwen-0.5B	0.235	L15	Readout layer; 0.081 excluding self-ablation
Qwen-1.5B	0.324	L13	Not false-answer-specific at this layer
Qwen-3B	0.061	L19	Deployed readout absorbs every ablation
Gemma-2b	0.150	L12	Truth-specific, not false-answer-specific




Figure 12: Probe accuracy against number of principal components.

Table 21: Layers reaching significance before and after correction.

Model	Cells tested	Uncorrected	Benjamini–Hochberg	Bonferroni
Qwen-0.5B	8	L15*	L15*	L15*
Qwen-1.5B	9	L15, L16, L17*	L15, L16, L17*	L15, L16, L17*
Qwen-3B	14	L18, L20, L21†, L23†, L28*	L18, L20, L23†, L28*	L20, L23†, L28*
Gemma-2b	8	L9, L11, L12†, L13, L14, L15*	same	L11, L13, L14

*That model's readout layer; not evidence of location.
†Positive asymmetry: the truth probe is hurt more.