

Prediction Competition 2:Regression Trees,
Cross-Validation, and Variable Importance

Anonymized name: Sukuna
 $R^2 = 0.40$
 $MSE = 1.06$

Q2




Figure 1: Actual vs. Predicted values

Q3




Figure 2: Variable Importance Bargraph

Q4




Figure 3: Test vs train

Q5




Figure 4: Screen capture of my conversation with ChatGPT



You

can you use gg plot to plot this graph [plot(housing_test, yhat) +
abline(0, 1, col = 'red')] also add a section for me to add title and x and y labels



ChatGPT

Certainly! If you want to create a scatter plot with a 45-degree red line using ggplot2 in R, and you also want to add a title, x-axis label, and y-axis label, you can use the following code:

R

Copy code

```
# Assuming 'housing_test' and 'yhat' are your data frame columns
# Create a scatter plot with ggplot2
library(ggplot2)

# Your data
housing_test <- c(1, 2, 3, 4, 5)
yhat <- c(2, 3, 4, 5, 6)

# Create a data frame
data <- data.frame(housing_test, yhat)

# Plot with ggplot2
ggplot(data, aes(x = housing_test, y = yhat)) +
  geom_point() + # Scatter plot
  geom_abline(intercept = 0, slope = 1, color = 'red') + # 45-degree r
  ggtitle("Your Title Here") + # Add title
  xlab("X-axis Label") + # Add x-axis label
  ylab("Y-axis Label") # Add y-axis label
```

Replace "Your Title Here," "X-axis Label," and "Y-axis Label" with your desired title and axis labels. This code assumes that 'housing_test' and 'yhat' are the variables you want to plot on the x and y axes, respectively. Adjust the data and variable names

Figure 5: Screen capture of my conversation with ChatGPT



ChatGPT

Certainly! To estimate regression trees of varying depth and construct a graph showing training error (MSE) and test error (MSE) as a function of model depth, you can use a loop to fit trees with different depths and record the errors. Here's how you can modify your existing R code:

```
(r) Copy code

# Splitting the training data into two sets for model evaluation
set.seed(21108082)
train_set <- sample(1:nrow(train_housing_data), nrow(train_housing_data)
test_set <- setdiff(1:nrow(train_housing_data), train_set)

train_data <- train_housing_data[train_set, ]
test_data <- train_housing_data[test_set, ]

# Initialize vectors to store training and test errors
train_errors <- vector('numeric', length = 10)
test_errors <- vector('numeric', length = 10)

# Loop through different tree depths
for (depth in 1:10) {
  # Fit a tree with varying depth
  tree_model <- tree(LOGVALUE ~ ., train_data, subset = train_set, cont

  # Predict on training set
  yhat_train <- predict(tree_model, newdata = train_data)
  train_errors[depth] <- mean((yhat_train - train_data$LOGVALUE)^2)

  # Predict on test set
  yhat_test <- predict(tree_model, newdata = test_data)
  test_errors[depth] <- mean((yhat_test - test_data$LOGVALUE)^2)
}

# Plotting the errors as a function of model depth
plot(1:10, train_errors, type = 'b', col = 'blue', pch = 16, xlab = 'Tr
lines(1:10, test_errors, type = 'b', col = 'red', pch = 16)
legend("topright", legend = c("Training Error", "Test Error"), col = c(
```

This code sets up a loop from 1 to 10, where each iteration fits a regression tree with a specified depth using the `tree` function. It then calculates and stores the Mean Squared Error (MSE) for both the training and test sets. Finally, it plots the errors against the tree depth, providing insight into how the model performs with different depths. Adjust the range of depths and other parameters as needed for your specific case.

Figure 6: Screen capture of my conversation with ChatGPT

Code

```
---
title: "Prediction Competition 2"
output: pdf_document
---

Anonymized name: Sukuna
$R^2 = 0.40$
$MSE = 1.06$

```{r setup, include=FALSE}
knitr::opts_chunk$set(echo = TRUE)
```

## Importing libraries
```{r, include=FALSE}
library(readr)
library(ggplot2)
library(tree)
library(randomForest)
library(rpart)
```

## Importing data
```{r}
setwd('/Users/andrew/Downloads/UW courses/ECON 626/Prediction Competition 2')
train_housing_data = read.csv('ECON626_PC2_train.csv')
test_housing_data = read.csv('ECON626_PC2_test.csv')
```

### Viewing our data
```{r}
names(train_housing_data) <- lapply(names(train_data), tolower)
head_train = head(train_housing_data)
print(head_train)
```

```{r}
head_test = head(test_housing_data)
print(head_test)
```
```

```

'''{r}
#Count of na
sum(is.na(train_housing_data))
sum(is.na(test_housing_data))

#Searching for na values
which(is.na(train_housing_data))
which(is.na(test_housing_data))
'''

'''{r}
set.seed(21108082)
#set seed for reproducability

help(tree)

train <- sample(1:nrow(train_housing_data), nrow(train_housing_data) *.8)
tree_housing <- tree(logvalue ~ ., train_housing_data , subset = train)
model = summary(tree_housing)
model
'''

'''{r}
plot(tree_housing)
text(tree_housing , pretty = 0)
'''

'''{r}
tree_housing
'''

'''{r}
cv_housing <- cv.tree(tree_housing)
plot(cv_housing$size , cv_housing$dev, type = "b")
'''

'''{r}
yhat <- predict(tree_housing , newdata = train_housing_data[-train , ])

housing_test <- train_housing_data[-train, "logvalue"]

plot_data <- data.frame(yhat, housing_test)

ggplot(plot_data, aes(x = housing_test, y = yhat)) +
  geom_point() + # Scatter plot

```



```

geom_abline(intercept = 0, slope = 1, color = 'red', linetype = "dashed", show_guide=TRUE)
ggtitle("Actual vs Predicted Values") + # Add title
xlab("Actual values") + # Add x-axis label
ylab("Predicted values") + # Add y-axis label
theme(plot.title = element_text(hjust = 0.5))

'''

'''{r}
r2 = 1-(sum(model$residuals^2))/sum((train_housing_data$logvalue-mean(train_housing_data$log

MSE = mean((yhat - housing_test)^2)
print(MSE)
'''

'''{r}

bag_housing <- randomForest(logvalue ~ ., data=train_housing_data , subset = train, mtry = 1

class(bag_housing)

var_importance <- importance(bag_housing)

var_importance

overall_importance <- sort(var_importance[, 1], decreasing = T)

barplot(overall_importance,
        names.arg = colnames(train_housing_data)[-ncol(train_housing_data)],
        las = 1, # Set las to 1 for horizontal labels
        main = "Variable Importance Plot",
        col = "red", # Set color to red
        cex.names = 0.8,
        horiz = TRUE, # Set horiz to TRUE for horizontal bars
        xlim = c(0, 100)
)

'''

'''{r}
# Splitting the training data into two sets for model evaluation
set.seed(21108082)

```

```

train_set <- sample(1:nrow(train_housing_data), nrow(train_housing_data) * 0.2)
test_set <- setdiff(1:nrow(train_housing_data), train_set)

train_data <- train_housing_data[train_set, ]
test_data <- train_housing_data[test_set, ]

# Initialize vectors to store training and test errors
train_errors <- vector('numeric', length = 10)
test_errors <- vector('numeric', length = 10)

# Loop through different tree depths
for (depth in 1:10) {
  # Fit a tree with varying depth
  tree_model <- rpart(logvalue ~ ., train_data, subset = train_set, control = list(maxdepth = 10))

  # Predict on training set
  yhat_train <- predict(tree_model, newdata = train_data)
  train_errors[depth] <- mean((yhat_train - train_data$logvalue)^2)

  # Predict on test set
  yhat_test <- predict(tree_model, newdata = test_data)
  test_errors[depth] <- mean((yhat_test - test_data$logvalue)^2)
}

# Plotting the errors as a function of model depth
plot(1:10, train_errors, type = 'b', col = 'blue', pch = 16, xlab = 'Tree Depth', ylab = 'Mean Squared Error')
lines(1:10, test_errors, type = 'b', col = 'red', pch = 16)
legend("topright", legend = c("Training Error", "Test Error"), col = c("blue", "red"), pch = c(16, 16))

'''

''{r}
set.seed(21108082)

housing_test <- train_housing_data[-train, ]
dim(housing_test)
house_values <- train_housing_data$LOGVALUE[-train]
length(house_values)
#make sure both = 4000

pred_tree <- predict(tree_housing , housing_test)
table(pred_tree , house_values)

```

```

'''

'''{r}

test_yhat <- predict(tree_housing , newdata = test_housing_data)

'''

'''{r, include=FALSE}
# Writing the predictions to a csv

predictions <- test_yhat

r2 <- r2

# Creating a dataframe with a single column of mixed data types
df <- data.frame(Column = c(21108082, "Sukuna", r2, predictions), stringsAsFactors = FALSE)

write.table(df, "/Users/andrew/Downloads/UW courses/ECON 626/Prediction Competition 2/pc2.csv",
            sep=";", row.names=FALSE, col.names=FALSE)

#In general:

#x <- c(1, 2, 3, 4, 5)

# Creating a dataframe with a single column of mixed data types
#df <- data.frame(Column = c(st number, "Anonymized name", x), stringsAsFactors = FALSE)

#write.table(df, "filelocation/filename.csv", sep=";", row.names=FALSE, col.names=FALSE)

'''

```