

Mathematical and Statistical Foundations of Machine Learning

Lectures: Ulrich Terstiege
Tutorials: Tizian Wenzel

April 24th, 2025

Chapter I: Introduction

What is Machine Learning?

Some tasks appear too complicated to directly program for a computer, e.g. recognition of objects in images or autonomous driving.

Machine learning may be defined as computational methods for converting experience into expertise.

Experience: past information, data collections, e.g. human labeled training sets such as images (e.g. labeled with 1 or 0 depending on whether or not the image shows a cat) or emails (spam or not spam).

Expertise: Prediction of future outcomes.

Similar to statistics but with a strong emphasis on efficient algorithms (optimization)

Some applications for learning algorithms

- ▶ Text / document classification
- ▶ speech recognition
- ▶ automatic translation
- ▶ image recognition / face recognition
- ▶ autonomous driving
- ▶ search engines, recommendation systems
- ▶ Games: chess, Go
- ▶ medical diagnosis
- ▶ analysis of social networks
- ▶ text generation

Some standard learning tasks

- ▶ Classification: Assign a category to each item.
Usually a small number of categories
Binary classification: two categories ($\{-1, +1\}$, $\{0, +1\}, \dots$)

Example: Predict whether email is spam or not

- ▶ Regression: Predict (continuous) value for each item

Examples:

- ▶ Predict maximal temperature of the next day at some place given some of today's weather parameters
 - ▶ Predict share price of a company (that is about to go public) from revenues.
- ▶ Ranking: Order items according to some criterion
- Example: web search: ranking of webpages

Some standard learning tasks

- ▶ Clustering: Partition items into several groups

Example: identify communities in social networks

- ▶ Dimensionality reduction / manifold learning: try to find lower dimensional representation of items (vectors) in a high dimensional space while preserving properties of original representation (e.g. distance)

Example: Preprocessing of digital images in computer vision tasks.

This course

Two parts:

1. Theoretical foundations of Machine Learning and Statistical learning theory: The PAC-Learning Framework, Rademacher Complexity and VC-Dimension
2. Analysis of some machine learning methods and algorithms (with applications of part 1): Some possible topics
 - ▶ Support Vector Machines and Kernel Methods
 - ▶ Boosting
 - ▶ Logistic Regression
 - ▶ Stochastic Gradient Descent
 - ▶ Neural Networks (Deep Learning)
 - ▶ further topics as time allows, e.g. Decision Trees, Clustering, Reinforcement Learning,...

Prerequisites

- ▶ Analysis
- ▶ Linear algebra
- ▶ Basic probability theory

Main References

- ▶ S. Shalev Shwartz, S. Ben-David *Understanding Machine Learning – From Theory to Algorithms*. Cambridge University Press 2014
- ▶ M. Mohri, A. Rostamizadeh, A. Talwalkar *Foundations of Machine Learning*. second edition, MIT Press 2018

Basic machine learning setup

Input space X , e.g. $X = \mathbb{R}^n$ or $X = [0, 1]^2$ or ...

Output space Y , e.g. $Y = \{0, 1\}$ or $Y = \mathbb{R}$ or ...

Training data (x_i, y_i) , $i = 1, \dots, m$ (labeled data)
[or x_i , $i = 1, \dots, m$ (unlabeled data)]

Hypothesis class \mathcal{H} : A set of functions $h : X \rightarrow Y$.

Machine learning scenarios I: Supervised Learning

Learner receives labeled data (x_i, y_i) , $i = 1, \dots, m$ and tries to make predictions on new data (unseen), i.e. tries to find a function $h : X \rightarrow Y$, $h \in \mathcal{H}$, such that for future data (with unknown label) $h(x_i) \approx y_i$, $i = m + 1, m + 2, \dots$

Example: $x_i \in X = ([0, 255] \cap \mathbb{Z})^{n_1 \times n_2}$ represents greyscale image with $n_1 \times n_2$ pixels, $y_1 \in Y = \{1, 0\}$ represents whether or not a cat is in the image. (Alternatively, $X = [0, 255]^{n_1 \times n_2}$ or $[0, 1]^{n_1 \times n_2}$ etc.

For colored pictures one could use $X = ([0, 255] \cap \mathbb{Z})^{3n_1 \times n_2}$ (rgb channels).

Machine learning scenarios II: Unsupervised Learning

Learner receives unlabeled data x_i , $i = 1, \dots, m$ and tries to make predictions on unseen data, for instance learns something about the structure of the data points, e.g. they may be contained in a subspace or submanifold of $X \subset \mathbb{R}^n$ (\rightarrow dimensionality reduction, manifold learning), or they may cluster into a few clusters (\rightarrow clustering)

Example: A retailer might want to cluster its costumers into a few groups in order to adapt its strategy.

Machine learning scenarios III: Semisupervised Learning

Learner receives labeled data (x_i, y_i) , $i = 1, \dots, m$ and unlabeled data x_i , $i = m + 1, \dots, N$ and predicts labels of unseen unlabeled data x_{N+1}, \dots , i.e. tries to find a function $h : X \rightarrow Y$, $h \in \mathcal{H}$, such that for future data (with unknown label)
 $h(x_i) \approx y_i$, $i = N + 1, N + 2, \dots$ (Hope that unlabeled training data x_i , $i = m + 1, \dots, N$ help to improve the prediction, e.g. by helping to learn something about the structure of the set of the possible data x .)

Machine learning scenarios IV: Online learning

There are multiple training rounds. At each round, the learner receives an unlabeled training point x_j , makes a prediction $\hat{y}_j \in Y$ of its label y_j , then the true label y_j is received and the learner incurs the loss $\ell(y_j, \hat{y}_j)$.

Goal: Minimize cumulative loss $\sum_{j=1}^m \ell(y_j, \hat{y}_j)$.

Example: At each round, receive an email x_j , predict whether it is spam or not, receive information whether it is spam or not (by a human reader of the email), if prediction was wrong, adapt the predictor.

Machine learning scenarios V: Reinforcement learning

Mixed training and testing phase. The learner decides on actions interacting with environment and receives immediate reward / loss for each action.

Task: Maximize total reward over course of actions

→ Exploration vs. exploitation dilemma: decide between unexplored action to gain more information about environment and known action exploiting already collected information.

Examples: Games (e.g. Go, Chess), Advertisement on websites

Machine learning scenarios VI: Active learning

Similar to supervised learning, but learner can decide on data points x_i to query the label y_i .

Examples: Scientific experiments, oil exploration

Hope: Better predictions / less needed samples than in supervised learning.

Chapter II: The PAC-Learning Framework

PAC: Probably Approximately Correct

Consider supervised learning scenario for binary classification:

- ▶ X : Input space, e.g. Input space X , e.g. $X = \mathbb{R}^n$ or $X = [0, 1]^2$ or $X = ([0, 255] \cap \mathbb{Z})^{3n_1 \times n_2}$ or...
- ▶ Set of labels Y , for now $Y = \{0, 1\}$ (or $Y = \{-1, 1\}$)
- ▶ Training data $S = ((x_1, y_1), (x_2, y_2), \dots, (x_m, y_m)) \in (X \times Y)^m$ (labeled domain points)

Assumptions

1. The points $x_i, i = 1, \dots, m$ are drawn independently and identically distributed (i.i.d.) according to some unknown probability distribution \mathcal{D} on X .
2. The labels are given as $y_i = f(x_i), i = 1, \dots, m$ for some map $f : X \rightarrow Y$.

Goal: Find f (at least approximately)

More generally (later): Assume that the labeled examples (x_i, y_i) are drawn i.i.d. according to some unknown probability distribution \mathcal{D} on $X \times Y$.

Learner's output: A prediction rule (predictor, hypothesis, classifier)

$$h: X \rightarrow Y.$$

Ideally: $h = f$.

Learner selects hypothesis from a hypothesis set

$$\mathcal{H} \subset \{g: X \rightarrow Y\}$$

and f may or may not be contained in \mathcal{H} .

Assumptions on measurable spaces

We will assume (unless otherwise mentioned) that for measurable spaces (typically denoted by X, Y, Z, \dots) the following assumptions apply.

- ▶ If the space is finite or countably infinite, it is equipped with the σ -algebra consisting of all subsets of the space (applies e.g. for $X = \mathbb{N}$, $X = ([0, 255] \cap \mathbb{Z})^{3n_1 \times n_2}$, $X = \mathbb{Q}^n$, $Y = \{0, 1\}, \dots$)
- ▶ Otherwise it is a metric space which is complete and separable and equipped with the corresponding Borel σ -algebra (applies e.g. for $X = \mathbb{R}^n$, $[0, 1]^2, \dots$)
- ▶ If it is given as a product $X \times Y$, then the product carries the product σ -algebra of X and Y .

(Note that the case of a finite or countably infinite space X can be seen as a special case of a complete separable metric space with corresponding Borel σ -algebra by using e.g. the trivial metric $d(x, y) = \delta_{x, y}$, i.e. $d(x, x) = 0$ and $d(x, y) = 1$ for $x \neq y$. Also e.g. the product of two spaces as in the first or as in the second case have again this form, respectively.)

Generalization Error

For the next definition, we assume a fixed labeling function $f: X \rightarrow Y = \{0, 1\}$ and a probability distribution \mathcal{D} on X .

Definition 2.1 (Generalization error)

For $h: X \rightarrow Y = \{0, 1\}$, the generalization error or risk of h is defined as

$$R(h) = \mathbb{P}_{x \sim \mathcal{D}}(h(x) \neq f(x)) = \mathbb{E}[\mathbb{1}_{\{x | h(x) \neq f(x)\}}].$$

Here:

- ▶ \mathbb{P} denotes the probability of an event.
- ▶ \mathbb{E} denotes expectation (wrt. \mathcal{D}).
- ▶ $\mathbb{1}_A$ denotes the indicator function of A , i.e. $\mathbb{1}_A(x) = 1$ for $x \in A$ and $\mathbb{1}_A(x) = 0$ for $x \notin A$.
- ▶ f and h are always assumed to be measurable.

Note that the generalization error is not directly accessible since \mathcal{D} and f are unknown.