

Ivannikov ISP RAS

Svace

ANALYSIS RESULTS

Project	server
Branch	master
Snapshot	Snapshot 2024-03-26 19:56:19 +0300

Product version

3.3.2

Report creation date

27 March 2024

Table of contents

1. BAD_SIZEOF (2) 3

1. BAD_SIZEOF

Isolated occurrences of 'sizeof' operators are technically legal in C/C++, yet are often erroneous.

Language	Severity	Reliability	Status	Situation
CXX	Critical	Average	true	Quality

Location: /server/sql/lock.cc:802	Undecided
Function	MYSQL_LOCK * get_lock_data(THD *, TABLE **, uint, uint)
Warning message	use of sizeof on a function parameter 'table_ptr' which has 'struct TABLE **' pointer type

```
797    update the table values. So the second part of the array
       is copied
798    from the first part immediately before calling
       thr_multi_lock().
799  */
800  size_t amount= sizeof(*sql_lock) +
801                 sizeof(THR_LOCK_DATA*) * lock_count * 2 +
802                 sizeof(table_ptr) * table_count;
803  if (!(sql_lock= (MYSQL_LOCK*) (flags & GET_LOCK_ON_THD ?
804                                 thd->alloc(amount) :
805                                 my_malloc(key_memory_MYSQL_LO
                                    CK, amount,
806                                              MYF(0)))))
807    DBUG_RETURN(0);
```

Location: /server/sql/sql_acl.cc:9933	Undecided
Function	bool show_table_and_column_privileges(THD *, const char *, const char *, char *, size_t)
Warning message	use of sizeof on a function parameter 'buff' which has 'char *' pointer type

```
9928    cols_access= grant_table->init_cols;
9929  }
9930
9931  if ((table_access | cols_access) != NO_ACL)
9932  {
9933    String global(buff, sizeof(buff), system_charset_info);
9934    privilege_t test_access= (table_access | cols_access) &
       ~GRANT_ACL;
9935
9936    global.length(0);
```

```
9937    global.append(STRING_WITH_LEN("GRANT "));
9938
```