


# SQL Cheat Sheet: Basics



**Skills**  
Network

Command	Syntax	Description	Example
SELECT	SELECT column1, column2, ... FROM table_name;	SELECT statement is used to fetch data from a database.	SELECT city FROM placeofinterest;
WHERE	SELECT column1, column2, ...FROM table_name WHERE condition;	WHERE clause is used to extract only those records that fulfill a specified condition.	SELECT * FROM placeofinterest WHERE city == 'Rome'
COUNT	SELECT COUNT * FROM table_name ;	COUNT is a function that takes the name of a column as argument and counts the number of rows when the column is not NULL.	SELECT COUNT(country) FROM placeofinterest WHERE country='Canada';
DISTINCT	SELECT DISTINCT columnname FROM table_name;	DISTINCT function is used to specify that the statement is a query which returns unique values in specified columns.	SELECT DISTINCT country FROM placeofinterest WHERE type='historical';

		LIMIT is a clause to specify the maximum number of rows the result set must have.	
LIMIT	SELECT * FROM table_name LIMIT number;		SELECT * FROM placeofinterest WHERE airport="pearson" LIMIT 5;
		INSERT is used to insert new rows in the table.	
INSERT	INSERT INTO table_name (column1,column2,column3...) VALUES(value1,value2,value3...);		INSERT INTO placeofinterest (name,type,city,country,airport) VALUES('Niagara Waterfalls', 'Nature', 'Toronto', 'Canada', 'Pearson');
		UPDATE used to update the rows in the table.	
UPDATE	UPDATE table_name SET [[column1]=[VALUES]] WHERE [condition];		UPDATE placeofinterest SET name = 'Niagara Falls' WHERE name = "Niagara Waterfalls";
		DELETE statement is used to remove rows from the table which are specified in the WHERE condition.	
DELETE	DELETE FROM table_name WHERE [condition];		DELETE FROM placeofinterest WHERE city IN ('Rome','Vienna');

Author(s)

[Malika Singla](#)

Changelog

Date	Version	Changed by	Change Description
2023-05-04	1.1	Benny	Formatting changes
2021-07-27	1.0	Malika	Initial Version