

Name: Andrew Brown	Lab Time: T 12:00
---------------------------	--------------------------

Names of people you worked with:
<ul style="list-style-type: none">• Hannah Gamache• Cailin Moore• Youta Kashiwa• Michael Pious

Websites you used:
<ul style="list-style-type: none">• https://www.mathworks.com/help/matlab/creating_plots/plotting-in-polar-coordinates.html

Approximately how many hours did it take you to complete this assignment (to nearest whole number)?	8
--	----------

By writing or typing your name below you affirm that all of the work contained herein is your own, and was not copied or copied and altered.

Andrew Brown

Note: Failure to sign this page will result in a 50-point penalty. Failure to list people you worked with may result in no grade for this homework. Failure to fill out hours approximation will result in a 10-point penalty.

Turn .zip files to Canvas or your assignment will not be graded

Learning Objectives:

You should accomplish the following:


- Understand how to create arrays, calculate with them, and extract data from them.
- Plot the results of calculations.
- Be able to split up plots into multiple windows
- Plot multiple things in the same window with different colors and attributes.

Homework Guidelines:

- 1) Use example scripts from online for help plotting and vectors.
- 2) Save scripts as “HW2Script1.m” for problem 1, “HW2Script2.m” for problem 2, etc.

Specific Coding Notes:

Plotting – Label axes (with units when known), use titles, and use legend when plotting more than one thing on a graph.

Example:

Warnings and Errors – You may see orange and red bars on the right-hand side of the editor. Orange bars are warnings and red bars are errors. Hovering with the cursor over a bar will show you the problem.

Example:

```

8
9 - % Matrix operations from slides
10 - fprintf('3x2 matrix from slides:\n');
11 - A = [2 1; 3 26; 5 34]

```

Grading Checkpoints

Criteria	Component	No	Yes
[30%] Comments and Pseudocode	Declared units on all variables?		
	English description of problem at top?		
	Comments outlining your steps?		
[20%] Output formatting	Used fprintf() to make complete sentences (when required)?		
	Correct units on answers?		
	Correct number of decimal places?		
	Proper labels on graphs/plots?		
[50%] Functionality	Script computes/plots correct value(s)?		
	Did you use the correct ranges for input variables?		


Problem 1

- a) Plot the following mathematical function in the domain $-10 \leq t \leq 7$ in increments of 0.004. Assume that the x-axis is time measured in seconds, and the y-axis is distance measured in meters. Print the minimum and maximum values of y for that range of t s, and the t -values that produce the minimum and maximum values. Label the axes with time in seconds (t) and distance in meters (y).
- a. *Hint: Look up the different versions of the function min/max.*
- b) Check the minimum value against the [analytic](#) solution (hint: minimum and maximum values occur when the derivative is zero).
- a. If you don't want to do the derivative by hand, try this [web-site](#) (<http://www.derivative-calculator.net/>). This [web-site](#) (<http://www.numberempire.com/equationsolver.php>) can solve the resulting equation for you.

The equation:

$$y = 4t^3 + 3t^2 + 5t + 5$$

Self-check:



Minimum occurs at $y = -3 \times 10^5$, maximum at edge of graph

Comments for grader/additional information (if any)

Script File

```
%Andrew Brown Homework 2 Problem 1

clc
clear
clf

%Practice plotting arrays with function.


t=-10:0.004:7;
y=(4*t.^3)+(3*t.^2)+(5*t)+5;
```

```
plot(t,y,'b')
xlabel('Time (seconds)')
ylabel('Distance (meters)')
title('Self-Check: Time vs. Distance')

fprintf('Minimum occurs at y = %0.3f, maximum occurs at y = %0.3f\n',
min(y), max(y))
```

Command Window Output

```
Minimum occurs at y = -3745.000, maximum occurs at y = 1559.000
```

Image Output

Problem 2

A polar rose is a sinusoidal function that looks like a rose in polar coordinates. It can also be represented in Cartesian coordinates. The equations for a polar rose are given below:

Polar Coordinates

$$r = \cos\left(\frac{n}{d}\theta\right)$$

Cartesian (Regular) Coordinates

$$x = \cos\left(\frac{n}{d}t\right) \cos(t)$$


$$y = \cos\left(\frac{n}{d}t\right) \sin(t)$$

Create a 2x3 grid of six polar rose plots in the same window (using the subplot function). Include a descriptive title for each subplot, but axis labels are not required. Assume units of radian for θ and t . Look up the `polar()` command for the plots using the polar coordinate system.

Use the following blueprint to create and organize your plots in the figure window:

<u>Polar Coordinates</u> $n = 5$ $d = 1$ $0 \leq \theta \leq \pi$ (use 200 values total) $0 \leq$	<u>Polar Coordinates</u> $n = 6$ $d = 7$ $0 \leq \theta \leq 8\pi$ (use 200 values total)	<u>Polar Coordinates</u> $n = \text{Your Choice}$ $d = \text{Your Choice}$ Choose an appropriate θ domain
<u>Cartesian Coordinates</u> $n = 5$ $d = 1$ $0 \leq t \leq \pi$ (use 200 values total)	<u>Cartesian Coordinates</u> $n = 6$ $d = 7$ $0 \leq t \leq 8\pi$ (use 200 values total)	<u>Cartesian Coordinates</u> $n = \text{Your Choice}$ $d = \text{Your Choice}$ Choose an appropriate t domain

Self check: *Note – the ones in the 3rd column – your choice – don't have to look like the ones shown*



Comments for grader/additional information (if any)**Script File**

```
% Andrew Brown Homework 2 Problem 2

clc
clear
clf

%Practice using the subplot and polar coordinate operators to make polar
%roses.

%Define given variables.
n=5:7;
d=[1, 7, 5];
theta1=linspace(0,pi,200);
theta2=linspace(0,8*pi,200);
theta3=linspace(0,12*pi,500);
t1=linspace(0,pi,200);
t2=linspace(0,8*pi,200);
t3=linspace(0,12*pi,500);

%Express given equations.
x1=cos((n(1)/d(1)).*t1).*cos(t1); %Cartesian coordinates
y1=cos((n(1)/d(1)).*t1).*sin(t1); %Cartesian coordinates
r1=cos((n(1)/d(1)).*theta1); %Polar coordinates

%Create a 2x3 subplot and plot in polar coordinates in spot 1.
subplot(2,3,1)
polarplot(theta1,r1,'b')
title('Polar Rose for n=5 and d=1')

%Plot in cartesian coordinates in subplot spot 4.
subplot(2,3,4)
plot(x1,y1,'b')
title('Polar Rose on Cartesian Coordinates for n=5 and d=1')

%Express given equations again for second t and theta values.
x2=cos((n(2)/d(2)).*t2).*cos(t2); %Cartesian coordinates
y2=cos((n(2)/d(2)).*t2).*sin(t2); %Cartesian coordinates
r2=cos((n(2)/d(2)).*theta2); %Polar coordinates

%Plot in polar coordinates in subplot spot 2.
subplot(2,3,2)
polarplot(theta2,r2,'b')
title('Polar Rose for n=6 and d=7')

%Plot in cartesian coordinates in subplot spot 5.
subplot(2,3,5)
```



```

plot(x2,y2,'b')
title('Polar Rose on Cartesian Coordinates for n=6 and d=7')







%Express given equations again for third t and theta values.
x3=cos((n(3)/d(3)).*t3).*cos(t3); %Cartesian coordinates
y3=cos((n(3)/d(3)).*t3).*sin(t3); %Cartesian coordinates
r3=cos((n(3)/d(3)).*theta3); %Polar coordinates

%Plot in polar coordinates in subplot spot 3.
subplot(2,3,3)
polarplot(theta3,r3,'b')
title('Polar Rose for n=7 and d=5')

%Plot in cartesian coordinates in subplot spot 6.
subplot(2,3,6)
plot(x3,y3,'b')
title('Polar Rose on Cartesian Coordinates for n=7 and d=5')

```

Image Output




Problem 3

Sami weighs about 120 pounds. After reading an article about falling from heights (<https://www.theguardian.com/science/2004/may/20/thisweekssciencequestions2>) he wonders, what could be an equivalent energy generated by a 10 meter high fall if it happened in other planets? In order to simplify this problem, we will ignore the existence of air resistance. Find the following:

- What is the energy that is generated by a 10-meter fall for a 120 pounds heavy object on the surface of earth? Print your answer.
 - $1 \text{ kg} = 2.246 \text{ pounds}$.
 - Energy of a fall: $\text{Energy [J]} = \text{mass [kg]} * g \left[\frac{\text{m}}{\text{s}^2} \right] * h [\text{m}]$
- Choose three different planets of your choice, plot the energy generated by the fall of a 120 pounds object over the surface of each of Earth and the other planets. Your plot should show the energy generated between values between 0 to 50 meters.
 - Gravitational constants: <http://www.physicsclassroom.com/class/circles/Lesson-3/The-Value-of-g>
 - If the range of 0 to 50 meters is too large or too small, change it to an appropriate range.
- Identify on your graph and command window the harmful heights that will generate the same energy as a 10-meter fall on earth.

Self check:

Energy from a fall on Earth: 5XXX.9X Joules



Comments for grader/additional information (if any)

Script File

```
%Andrew Brown Homework 2 Problem 3

clc
clear
clf

%Physics of a harmful fall on different planets.

%Part A: What is the energy that is generated by a 10-meter fall for a 120
%pounds heavy object on the surface of Earth?

%Define given constants
massPounds=120; %mass in pounds
massKg=massPounds/2.246; %mass in kilograms
g=9.8; %acceleration due to gravity on earth
h=10; %height off the ground in meters

%Given equation
E=massKg*g*h; %energy generated from the fall in joules

%Print out the energy given off
fprintf('Energy from a 10m fall on Earth: %0.2f Joules\n', E)

%Part B: Choose three different planets of your choice, plot the energy
%generated by the fall of a 120 pounds object over the surface of each
%of Earth and the other planets. Your plot should show the energy
%generated between values between 0 to 50 meters.
%and
%Part C: Identify on your graph and command window the harmful heights
%that will generate the same energy as a 10-meter fall on earth.

%Define given constants
massPounds=120; %mass in pounds
massKg=massPounds/2.246; %mass in kilograms
g=[9.8, 26.0, 3.61, 3.75]; %accelerations due to gravity in m/s^2
h=linspace(0,50,100); %height off the ground in meters

%Given equations separated by planet
EEarth=massKg*g(1)*h; %energy generated from the fall in joules on earth
EJupiter=massKg*g(2)*h; %energy generated from the fall in joules on jupiter
EMercury=massKg*g(3)*h; %energy generated from the fall in joules on mercury
EMars=massKg*g(4)*h; %energy generated from the fall in joules on mars

%Plotting the graph for energy generated from a fall on Earth
subplot(2,2,1)
plot(h,EEarth)
title('Self-Check: Energy Generated from a fall on Earth')
xlabel('Height (m)')
ylabel('Energy (J)')
legend('Energy')
axis([0,50,0,3*10^4])

%Plotting the graph for energy generated from a fall on Jupiter
```

```
subplot(2,2,2)
plot(h,EJupiter)
title('Self-Check: Energy Generated from a fall on Jupiter')
xlabel('Height (m)')
ylabel('Energy (J)')
axis([0,50,0,7*10^4])

%Calculate and plot the point of a drop equivalent to a 10m drop on earth
hold on
JupiterHeight=E/(g(2)*massKg);
plot(JupiterHeight,E,'r*')
legend('Energy', 'Equivalent of 10m drop on Earth')

%Plotting the graph for energy generated from a fall on Mercury
subplot(2,2,3)
plot(h,EMercury)
title('Self-Check: Energy Generated from a fall on Mercury')
xlabel('Height (m)')
ylabel('Energy (J)')
axis([0,50,0,12*10^3])

%Calculate and plot the point of a drop equivalent to a 10m drop on earth
hold on
MercuryHeight=E/(g(3)*massKg);
plot(MercuryHeight,E,'r*')
legend('Energy', 'Equivalent of 10m drop on Earth')





%Plotting the graph for energy generated from a fall on Mars
subplot(2,2,4)
plot(h,EMars)
title('Self-Check: Energy Generated from a fall on Mars')
xlabel('Height (m)')
ylabel('Energy (J)')
axis([0,50,0,12*10^3])

%Calculate and plot the point of a drop equivalent to a 10m drop on earth
hold on
MarsHeight=E/(g(4)*massKg);
plot(MarsHeight,E,'r*')
legend('Energy', 'Equivalent of 10m drop on Earth')

%Print out the equivalent falls.
fprintf('The energy-equivalent fall to a 10m drop on Earth:\n
Jupiter: %0.2fm\n Mercury: %0.2fm\n
Mars: %0.2fm\n',JupiterHeight,MercuryHeight,MarsHeight)
```

Command Window Output

```
Energy from a 10m fall on Earth: 5235.98 Joules  
The energy-equivalent fall to a 10m drop on Earth:  
Jupiter: 3.77m  
Mercury: 27.15m  
Mars: 26.13m
```

Image Output

Problem 4

Total Solar Eclipse Part 1.

Comments for grader/additional information (if any)

Script File

```
%Andrew Brown Homework 2 Problem 4

clc
clear
clf

%Total Solar Eclipse Part 1

%Part A: Create three variables: Year, Month, and Day. These three
%variables should contain a vector of the corresponding values of the
%TSE dates.

%Defining the three time-based variables with the given data.
day=[2,14,4,20,8,12]; %Days of the future TSE
month=[7,12,12,4,4,8]; %months of the future TSE
year=[2019,2020,2021,2023,2024,2026]; %years of the future TSE

%Part B: Calculate how many days between January 1st, 2018 and each of
%the upcoming TSE dates. Use the assumption that the Gregorian (western)
%solar calendar month, on average has 30.44 days. And every year has on
%average 365.2425 days.

%Do the needed year and month conversions into days
daysInAMonth=30.44; %Average number of days in a month
daysInAYear=365.2425; %Average number of days in a year

%Set up the arrays into only days for the end calculation
daysSubtracted=736695; %Days before Jan. 1, 2018
monthsToDays=(month-1).*daysInAMonth; %convert months to days
yearsToDays=(year-1).*daysInAYear; %convert years to days

%Calculation of days between Jan 1, 2018 and the given TSEs
daysUntilTSE=yearsToDays+monthsToDays+day-daysSubtracted;
roundedDaysUntilTSE=floor(daysUntilTSE);
%Part C: Calculate the daily saving balance that you will accumulate in
%your account starting from day one until and ending on day 3,200.
%(Assume that you are adding $2/day into your account. No interest is
%added to your saving account). Assign the daily savings of all 3,200
%values into one array.

dailySavingsBalance=2:2:6400; %Units in $

%Part D: Generate a plot that shows all of the following:
%1. The value of your daily savings.
```

```

%2. Plot a marker on the plot for each TSE and your savings that day.
%3. Plot a dashed horizontal line for savings = $3000
%4. Print out how many days are left until the first TSE you can afford and
%their savings balance that day.

countDays=1:3200; %Array to count the days in order

%Plot the Solar Eclipse Budget Simulation
plot(countDays,dailySavingsBalance,'b')
title('Solar Eclipse Budget Simulation')
xlabel('Days')
ylabel('Money Saved ($)')
hold on

%Plot a horizontal line at y=3000 using the ones function
horizontalLine=ones(1,3200);
plot(countDays,3000.*horizontalLine,'--k')

%Plot each solar eclipse date and savings.
plot(daysUntilTSE(1),dailySavingsBalance(roundedDaysUntilTSE(1)),'xr','Marker
Size',10) %2019 eclipse
plot(daysUntilTSE(2),dailySavingsBalance(roundedDaysUntilTSE(2)),'*r','Marker
Size',10) %2020 eclipse
plot(daysUntilTSE(3),dailySavingsBalance(roundedDaysUntilTSE(3)),'+r','Marker
Size',10) %2021 eclipse
plot(daysUntilTSE(4),dailySavingsBalance(roundedDaysUntilTSE(4)),'sg','Marker
Size',10) %2023 eclipse
plot(daysUntilTSE(5),dailySavingsBalance(roundedDaysUntilTSE(5)),'dg','Marker
Size',10) %2024 eclipse
plot(daysUntilTSE(6),dailySavingsBalance(roundedDaysUntilTSE(6)),'og','Marker
Size',10) %2026 eclipse

%Create the legend in the SW corner
legend('Savings','Required Budget','2019 Eclipse','2020 Eclipse','2021
Eclipse','2023 Eclipse','2024 Eclipse','2026 Eclipse','location','SE')

%Print out the first affordable TSE trip and your savings on that day
fprintf('The first affordable TSE trip will be on day %0.0f\nat a budget of
$%0.0f.\n', daysUntilTSE(4), dailySavingsBalance(roundedDaysUntilTSE(4)))


```

Answers to question(s) asked in the homework or command window output (if any)

Command Window Output:

The first affordable TSE trip will be on day 1937
at a budget of \$3872.

Image Output



Problem 5

Teacup Part 2 [Make a teacup and plot it in two positions]

Comments for grader/additional information (if any)

Script File

```
% Andrew Brown Homework 2 Problem 5

clc
clear
clf

%Teacup Part 2

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Read them back in again - put this in the top of your script
xsys = dlmread('TeacupPts.txt');

% Get x and y points back out
xs = xsys(1,:);
ys = xsys(2,:);

% Plot the points from the original sketch at the origin
subplot(1,3,1)
plot(xs,ys, '-k');
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%Plot the plate as a circle of radius 10
hold on
radius=10;
angle=linspace(0,2*pi,720);
x=cos(angle)*radius;
y=sin(angle)*radius;
plot(x,y, 'b')
axis equal
title('Teacup on Platter, Initial')
xlabel('Meters')
ylabel('Meters')
legend('Teacup','Platter')

%Part1.2a

%Define constants
theta=-25; %degrees
dx=-9.52; %translation distance in meters
dy=-3.05;%translation distance in meters
```

```
%Rotation then translation of the initial points.
%Rotation of the teacup points
x0RotateTeacup=(xs*cosd(theta))-(ys*sind(theta));
y0RotateTeacup=(xs*sind(theta))+(ys*cosd(theta));




%Translation of the teacup with rotation positions
xTranslationTeacup=x0RotateTeacup+dx;
yTranslationTeacup=y0RotateTeacup+dy;

%Plot the rotated, then translated teacup with the plate
subplot(1,3,2)
plot(xTranslationTeacup,yTranslationTeacup,'-k')
hold on
plot(x,y,'b')
axis equal
title('Teacup on Platter, Final')
xlabel('Meters')
ylabel('Meters')
legend('Teacup','Platter')

%Rotate again using translation positions
x1RotateTeacup=(xTranslationTeacup*cosd(theta))-(
yTranslationTeacup*sind(theta));
y1RotateTeacup=(xTranslationTeacup*sind(theta))+(yTranslationTeacup*cosd(thet
a));

%Plot position after second rotation with plate
subplot(1,3,3)
plot(x1RotateTeacup,y1RotateTeacup,'-k')
hold on
plot(x,y,'b')
axis equal
title('Teacup on Platter, Extra Credit')
xlabel('Meters')
ylabel('Meters')
legend('Teacup','Platter')
```

Image Output



Problem 6

Epidemic Part 2 [Equations with arrays]

Comments for grader/additional information (if any)

Script File

```
% Andrew Brown Homework 2 Problem 6

clc
clear

% Epidemic Part 1

%Part 1.1

%Initial Values
a=10; %the contact rate: the average # of people a person comes in contact
with.
b=1.25; %the amount of time in days that a person is infectious
S0=0:500:2000; %Susceptibles, those who have never had the illness and can
catch it.
I0=100; %Infectives, those who are infected and are contagious.
R0=0; % Recovered, those who already had the illness and are immune.
h=0.05; %timestep in days

%Print out parameters.
fprintf('Parameters: avg contacted, %0.0f, number of days
infectious, %0.2f\n', a, b)

%Print out starting S values.
fprintf('Starting S
values:\n   %0.0f   %0.0f   %0.0f   %0.0f   %0.0f\n\n', S0(1), S0(2), S0(3), S0(4)
), S0(5))

%Part 1.1

%Equations used for calculations of the first timestep.
N=S0+I0+R0; %Total population
dS=(-a.*S0.*I0)./N; %How S changes
dI=((a.*S0.*I0)./N)-(I0./b); %How I changes
dR=I0./b; %How R changes

%Calculations for values over time using the first timestep.
S1=S0+(h.*dS); %# of S after time h.
I1=I0+(h.*dI); %# of I after time h.
R1=R0+(h.*dR); %# of R after time h.

%Equations used for calculations of the second timestep.
dS=(-a.*S1.*I1)./N; %How S changes
```

```

dI=((a.*S1.*I1)./N)-(I1./b); %How I changes
dR=I1./b; %How R changes

%Calculations for values over time using the second timestep.
S2=S1+(h.*dS); %# of S after time h.
I2=I1+(h.*dI); %# of I after time h.
R2=R1+(h.*dR); %# of R after time h.

%Print out ending values after 2 timesteps
fprintf('Ending S values:\n')
disp(S2)
fprintf('Ending I values:\n')
disp(I2)
fprintf('Ending R values:\n')
disp(R2)
fprintf('Totals (S + I + R):\n')
disp(N)

```

Command Window Output

```

Parameters: avg contacted, 10, number of days infectious, 1.25
Starting S values:
    0    500    1000    1500    2000

Ending S values:
    1.0e+03 *

         0    0.4058    0.8932    1.3882    1.8856

Ending I values:
    92.1600   184.7410   197.1713   202.0398   204.6360

Ending R values:
     7.8400     9.5067     9.6582     9.7150     9.7448

Totals (S + I + R):
     100         600        1100        1600        2100

```