

EE3980 Algorithm
HW3. Network Connectivity Problem
106061225 楊宇羲

1. Problem Description:

Given a network with its amount of vertexes and each connected edge, we are required to determine the total amount of disjoint sets. The general steps will be given at below as pseudo code. We will first find one edge's two end points' root element, if their root element are the same, then the two vertexes are already in the same subset, meaning that there is no need to set union between the two end points. However, if the two connected vertexes belong to different set, then it means that they are now connected and we should set union, the number of disjoint sets should also decrease. Instead of seeking the root element and set union directly, we can make some optimizations towards these two methods to improve the overall performance, which are replacing SetUnion() to WeightedUnion() and SetFind() to CollapseFind(). This report is going to analyze the original methods and compare it with the two optimized functions.

2. Approach:

We are provided with 9 graphs with different size of vertexes and edges, we can analyze these function by 3 connect functions with: original SetFind and SetUnion, substitute SetUnion with WeightedUnion and substitute SetFind with CollapseFind. Then execute the three connect functions for each N times (set N = 100 as default) and calculate the total execute time. The main function pseudo code will be like the below:

Algorithm *main()*

```
{
    ReadGraph();
    t0 := GetTime();
    for ( i:=1 to N ) do Connect1();      // N is the repetition time
    t1 := GetTime();
    write((t1 - t0) / N, NS);            // connect1 's outcome
    for ( i:=1 to N ) do Connect2();
    t2 := GetTime();
    write((t2 - t1) / N, NS);            // connect2's outcome
    for ( i:=1 to N ) do Connect3();
    t3 := GetTime();
    write((t3 - t2) / N, NS);            // connect3's outcome
}
```

3. Analysis:

In the general connect function, we will do following things with some defined global variable:

Not clear!

Need more detailed explanations.

```
graph[v][2];           // for storing the graph
v, e;                  // for storing the amount of edges and vertexes
p[v];                  // for storing each vertexes' parent element
```

AlgorithmConnect(graph, e, v)

```
{
    NS := |V|;           // initially set the amount of disjoint sets to number of vertexes
    for every e = (vi, vj) belongs to graph do
    {
        Si := SetFind(vi);    // Find vi's root
        Sj := SetFind(vj);    // Find vj's root
        if (Si != Sj) then
        {
            NS := NS - 1;      // disjoint set decreases
            SetUnion(Si, Sj);   // they are now in the same subset
        }
    }
    for every vi belongs to V do
    {
        R[i] := SetFind(vi);   // check every vertexes' root element
    }
}
```

AlgorithmSetFind()

```
{
    while (p[i] >= 0) do i := p[i];    // seek until the element's parent is negative
    return i;                          // return root element
}
```

AlgorithmSetUnion()

```
{
    p[i] := j;           // make an element's parent to the other element (make link)
}
```

We will obtain a chart to record every elements' 'parent' element. While uses the SetFind() function to seek every elements' parent we can find the root of them, which has its parent denoted as -1. From this concept we can know whether 2 randomly picked element are in the same subset or not by checking if their root are the same. Since the 2 elements we pick are an edge, we can know that they are going to be connected, so if their root are not the same we can apply SetUnion()

function to link them up, making their root to be the same (note that the *SetUnion* has no order issue since the graph has no direction).

For further approach, we can improve the performance by replacing the *SetUnion* function to the *WeightedUnion* function, shown as below:

```
// If p[i] < 0, p[i] := element followed behind i;
Algorithm WeightedUnion()
{
    temp := p[i] + p[j];    // total elements after union
    if (p[i] > p[j]) then    // root i has fewer element
    {
        p[i] := j;          // i follows j
        p[j] := temp;
    }
    else                    // root j has fewer element
    {
        p[i] := temp;       // j follows i
        p[j] := i;
    }
}
```

What it had done to improve the overall speed is that rather than not determine who will be the parent as in *SetUnion()*, it decides who to be the parent by checking the amount of elements followed by each root. If we let the one with fewer weight to be the parent, then the total graph will be now skewed since each union operation will increase the height by 1, making every time's *SetFind()* taking longer time to access. With this method applied, we can ensure that each time we call *SetFind()* we take no longer than $\lg|V| + 1$ times to find the root element. As we replace the *SetUnion()* function to *WeightedUnion()* function, this will be the whole *Connect2()* function.


In *Connect3()*, we substitute the *SetFind()* function with the further *CollapseFind()* function, which will directly make every parent element in the parent table to root, so that we don't have to make redundant loop iteration every time we call the *SetFind()* function.

Among these three ^{functions} functions, we will found out that changing from connect1 to connect2 will bring significant improvement. Since the domination of time complexity is located in the *SetFind()* and *SetUnion()* in the loop, we can know the difference by analyzing the for loop. In *Connect1* there are two *SetFind()* and one *SetUnion()* in the for loop with $O(|E|)$ iterations. In worst case, *SetUnion()* will always be $O(1)$ since it just changes merely one element of the array.

However, if the tree representation of the graph is skewed, then the worst case occurs, the average access time per one SetFind() will be $|V| * (|V| + 1) / 2$, making the total access time of connect1 become $|E| * (|V|^2 + |V|)$ times, making the complexity of $O(n^2)$ while connect2 using WeightedUnion will take $3|E| * (|V| * \lg|V|)$ times since the height of the tree representation of connect2 will not exceed $\lg|V|$, and the constant 3 comes from the comparison in weighted union function, so the complexity will be $O(n \lg n)$. In connect3, the collapse finding function sets all elements' parent directly to the root, however the total execution steps works similarly as connect2 since it also needs to change the value via the tree, complexity also being $O(n \lg n)$.

4. Results:

Plot of result:



Unit : second

Each datasets's result:

dataset	amount of vertexes	Amount of edges	connect1(s)	connect2(s)	connect3(s)	Amount of disjoint sets
1	100	145	1.04E-05	1.17E-05	1.38E-05	1
2	196	303	2.42E-05	2.30E-05	2.79E-05	2
3	400	643	6.38E-05	4.78E-05	5.83E-05	1
4	784	1262	1.75E-04	9.37E-05	1.15E-04	2
5	1600	2597	4.99E-04	1.90E-04	2.40E-04	4
6	3136	5078	1.72E-03	3.88E-04	4.70E-04	3
7	6400	10452	5.93E-03	7.90E-04	9.70E-04	8
8	12769	20812	3.55E-02	7.50E-03	7.90E-03	8
9	25600	41864	3.50E-01	1.90E-02	2.00E-02	33
10	51076	83601	1.89E+00	3.50E-02	4.00E-02	50

Unit: as labeled

5. Observation and conclusion:

In previous assignments we are required to carry out several methods of searching and sorting with most of them almost the same time complexity, so it is important to compare the execution time between them and not just the overall worst case and average case complexity. However, in this assignment there are significant difference between the time complexity, if the data size become larger, there must be a more obvious tendency represented in the plot. After realizing what the weighted union are doing I found out that the order of being the parents can be so decisive on the performance. Furthermore, in my own opinion I think the number of disjoint sets might have the possibility to affect the overall performance since the more the amount of disjoint sets are, the fewer the amount of elements existing in one disjoint sets will be, making the SetFind being faster.

```
$ gcc hw02.c
$ a.out < g4.dat
|V| = 784, |E| = 1262
Connect1 CPU time: 4.24004e-05, Disjoint Sets: 2
Connect2 CPU time: 1.97506e-05, Disjoint Sets: 2
Connect3 CPU time: 2.62284e-05, Disjoint Sets: 2
```

Array 'r' should be declared with a constant dimension or allocated using dynamic memory method.
Array dimension is $|V| + 1$, why?

score: 57.0

- Overall report writing
 - English writing needs more practice.
 - Writing can be more logical – terms should be defined before referred to.
- Report format
 - Need page numbers.
- Introduction
 - Introduction can still be strengthened
- Approach
 - Is your implementation matching the pseudo codes?
- Time/Space complexity
 - Computation complexity analyses need to be logical with sufficient details.
 - Space complexities?
- Results
 - Figures can be improved.
- Conclusion/observation
 - Can correlate your CPU times to the algorithm complexities
 - Can discuss the impact of the coefficient of Connect3 time complexity.
- Program format can be improved
 - Function definitions need comments.

hw03.c

```
1 // EE3980 HW03 Network Connectivity Problem
2 // 106061225, 楊宇義
3 // 2021/3/22
4
5 #include <stdio.h>
6 #include <stdlib.h>
7 #include <sys/time.h>
8
9 double GetTime(void);           // Get local time
10 void ReadGraph(void);          // Scan the graph
11 void Connect1(void);           // SetFind & SetUnion
12 void Connect2(void);           // SetFind & WeightedUnion
13 void Connect3(void);           // CollapseFind & WeightedUnion
14 void SetUnion(int i, int j);    // Original union function
15 void WeightedUnion(int i, int j); // Let the smaller subset become children
16 int SetFind(int i);            // Original find root function
17 int CollapseFind(int i);        // Make elements' root be the same
18
19 int **graph;                   // 2D array for vertexes & edges
20 int *p;                        // 1d array for storing parent element
21 int ns;                        // Amount of disjoint sets
22 int v, e;                      // Amount of vertexes & edges
23
24 int main(void)
25 {
26
27     int N = 100;                // Repetitions
28     int i;                      // For loop
29     double t0, t1, t2, t3, t;   // For time counting
30
31     ReadGraph();                // Scan in necessary information
32
33     t0 = GetTime();             // Start counting time
34     for (i = 0; i < N; i++)     // Repeat N times
35     {
36         Connect1();             // Execute Connect1 function
37     }
38     t1 = GetTime();             // End of Connect1, start of Connect2
39     t = (t1 - t0) / N;          // Time calculation
```

```

40     printf("Connect1 CPU time: %g, Disjoint Sets: %d\n", t, ns);
41
42     for (i = 0; i < N; i++)          // Repeat N times
43     {
44         Connect2();                  // execute Connect2 function
45     }
46     t2 = GetTime();                  // End of Connect2, start of Connect3
47     t = (t2 - t1) / N;                // Time calculation
48     printf("Connect2 CPU time: %g, Disjoint Sets: %d\n", t, ns);
49
50     for (i = 0; i < N; i++)          // Repeat N times
51     {
52         Connect3();                  // Execute Connect3 function
53     }
54     t3 = GetTime();                  // End of Connect3
55     t = (t3 - t2) / N;                // Time calculation
56     printf("Connect3 CPU time: %g, Disjoint Sets: %d\n", t, ns);
57
58     return 0;
59 }
60
61 void ReadGraph(void)
62     Comments?
63 {
64     int i;                            // For loop
65
66     scanf("%d %d", &v, &e);          // Determine size of graph
67     printf("|V| = %d, |E| = %d\n", v, e);
68
69     graph = (int**)malloc(e * sizeof(int*)); // Dynamic allocation
70     p = (int*)malloc((v + 1) * sizeof(int)); // Dynamic allocation
71
72     for (i = 0; i < e; i++)            // Scan array
73     {
74         graph[i] = (int*)malloc(2 * sizeof(int));
75         scanf("%d %d", &graph[i][0], &graph[i][1]);
76     }
77
78 double GetTime(void)
79     Comments?

```



```

79 {
80     struct timeval tv;
81
82     gettimeofday(&tv, NULL);
83     return tv.tv_sec + 1e-6 * tv.tv_usec;    // sec + micro sec
84 }
85
86 void Connect1(void)                // SetFind and SetUnion
    Comments?
87 {
88     int i;                        // For loop
89     int r[v + 1];                // For storing root element
    Array dimension should be a constant int, not variable.
90
91     ns = v;                      // Initialize amount of Disjoint sets
92
93     for (i = 0; i <= v; i++) p[i] = -1; // Initialize elements' root
    Why i in [0, v], |V| + 1 elements?
94     for (i = 0; i < e; i++)
95     {
96         int S0 = SetFind(graph[i][0]); // Start seek for each vertexes' root
    Do not mix declarations with statements
97         int S1 = SetFind(graph[i][1]); // Start seek for each vertexes' root
98         if (S0 != S1)
99         {
100             ns--;                // Every union makes ds decreases
101             SetUnion(S1, S0);    // Set connection if there isn't
102         }
103     }
104     for (i = 0; i <= v; i++) r[i] = SetFind(i); // Find each elements' root
105 }
106
107 void Connect2(void)                // SetFind and WeightedUnion
    Comments?
108 {
109     int i;                        // For loop
110     int r[v + 1];                // For storing root element
111
112     ns = v;                      // Initialize amount of disjoint sets
113
114     for (i = 0; i <= v; i++) p[i] = -1; // Initialize elements' root

```

```

115     for (i = 0; i < e; i++)
116     {
117         int S0 = SetFind(graph[i][0]); // Same as Connect1
118         Do not mix declarations with statements
119         int S1 = SetFind(graph[i][1]); // Same as Connect1
120         if (S0 != S1)
121         {
122             ns--; // Every union makes ds decreases
123             WeightedUnion(S0, S1); // Uses the weighted union function
124         }
125     }
126     for (i = 0; i <= v; i++) r[i] = SetFind(i); // Find each elements' root
127 }
128 void Connect3(void) // CollapseFind and WeightedUnion
129     Comments?
130 {
131     int i; // For loop
132     int r[v + 1]; // For storing elements' root
133     ns = v; // Initialize amount of disjoint sets
134
135     for (i = 0; i <= v; i++) p[i] = -1; // Initialize elements' root
136     for (i = 0; i < e; i++)
137     {
138         int S0 = CollapseFind(graph[i][0]); // Uses Collapse Find function
139         Do not mix declarations with statements
140         int S1 = CollapseFind(graph[i][1]); // Uses Collapse Find function
141         if (S0 != S1)
142         {
143             ns--;
144             WeightedUnion(S0, S1); // Uses the weighted union function
145         }
146     }
147     for (i = 0; i <= v; i++) r[i] = SetFind(i); // Find each elements' root
148 }
149 int SetFind(int i)
150     Comments?
151 {
152     while (p[i] >= 0) i = p[i]; // Trace until p[i] < 0 (root)

```

```

152
153     return i;                // i will be the root element
154 }
155
156 int CollapseFind(int i)
    Comments?
157 {
158     int r = i;                // Initialization
159     int temp;
160
161     while (p[r] > 0) r = p[r];    // Trace until p[r] < 0 (root)
162     while (i != r){            // This loop sets every elements' parent to root
        while (i != r) {        // This loop sets every elements' parent to root
163         temp = p[i];          // Find next element
164         p[i] = r;             // Update new root
165         i = temp;             // Found next element
166     }
167     return r;
168 }
169
170 void SetUnion(int i, int j)
    Comments?
171 {
172     p[i] = j;                // Set one's parent as another (order matters)
173 }
174
175 void WeightedUnion(int i, int j)
    Comments?
176 {
177     int temp = p[i] + p[j]; // Total weight
178
179     if (p[i] > p[j])          // If i has fewer children, j becomes parent
180     {
181         p[i] = j;
182         p[j] = temp;          // New weight
183     }
184     else                      // If j has fewer children, i becomes parent
185     {
186         p[i] = temp;          // New weight
187         p[j] = i;
188     }

```

189 }
190
191