

Spark Setup Documentation

Abraham Sharum, Isaac Tunchez, Andrew Appleyard
Class: CS 30003 - Distributed Systems

December 12, 2025

Demonstration Guide

Installation Steps

1. Install Docker and Docker Compose.
2. Clone the repository.
3. Create a root `.env` with at least:
 - `FINNHUB_API_KEY=`
 - `INFLUXDB_TOKEN=`
 - `INFLUXDB_USERNAME=`
 - `INFLUXDB_PASSWORD=`
 - `INFLUXDB_ORG=`
 - `INFLUXDB_BUCKET=`
4. Ensure ports 4000, 7077, 8001, 8080, 8081, 8082, 8086, 8800 are free.

Run the Containers (Exact Commands)

- Build and start: `docker compose up --build`
- Stop: `docker compose down`
- Rebuild a single service (example backend): `docker compose build backend`
- Spark services: master + two workers come up via compose; workers are limited to `SPARK_WORKER_CORES=2` and `SPARK_WORKER_MEMORY=2g`.
- Docker Swarm (optional deployment):
 - Init swarm: `sudo docker swarm init --advertise-addr <your-ip>`
 - Check status: `sudo docker info | grep -A3 "Swarm"`
 - List nodes: `sudo docker node ls`
 - Deploy stack: `sudo docker stack deploy -c docker-stack.prod.yaml distributed`
 - List services: `sudo docker stack services distributed` (or `sudo docker service ls`)
 - Inspect service: `sudo docker service ps <service_name>` and logs: `sudo docker service logs -f <service_name>`
 - Remove stack: `sudo docker stack rm distributed`
 - Leave swarm: `sudo docker swarm leave --force` (re-run init after leaving)

Run the CRUD Application

- Backend FastAPI: `http://localhost:4000` (Swagger UI at `/docs`).
- Frontend dashboard: `http://localhost:8800`.
- Key endpoints:
 - `GET /portfolio` — list all trades.
 - `POST /trades` — create (e.g., `{"symbol": "AAPL", "shares": 5, "buy_price": 180}`).

- PUT /trades/{symbol} — update buy price (e.g., {"new_price":185}).
- DELETE /trades/{symbol} — delete/sell a trade; optional body {"sale_price":190} to compute net gain.
- GET /cache — view in-memory price cache (refreshed every 5s for tracked symbols).
- Finnhub quote API: <http://localhost:8001/quote/{symbol}> (uses FINNHUB_API_KEY).
- Grafana (optional dashboards): <http://localhost:3000>.

Reproduce the Custom Example

1. Start services: `docker compose up --build`.
2. Create a trade:

```
curl -X POST http://localhost:4000/trades \  
  -H "Content-Type: application/json" \  
  -d '{"symbol":"AAPL","shares":5,"buy_price":180}'
```

3. Update it:

```
curl -X PUT http://localhost:4000/trades/AAPL \  
  -H "Content-Type: application/json" \  
  -d '{"new_price":185}'
```

4. Delete it:

```
curl -X DELETE http://localhost:4000/trades/AAPL
```

5. Verify via GET /portfolio or refresh the frontend dashboard.