



Safety switch, heavy duty, non fusible, 30A, 3 wires, 3 poles, 30hp, 600VAC/DC, Type 3R, bolt on hub provision

HU361RB

Product availability: Stock - Normally stocked in distribution

facility

Price*: 488.00 USD

Main

Product	Single Throw Safety Switch		
Duty Rating	Heavy duty		
Device Application	Heavy application		
Disconnect Type	Non-fusible disconnect		
Factory Installed Neutral	None		
Phase	3 phase		
Number of Poles	3		
Current Rating	30 A		
Voltage Rating	600 V AC/DC		
Enclosure Rating	NEMA 3R galvannealed steel		
Motor power hp	5 hp at 240 V AC 50-60 Hz for 1 phase motors 10 hp at 240 V AC 50-60 Hz for 3 phase motors 7.5 hp at 480 V AC 50-60 Hz for 1 phase motors 20 hp at 480 V AC 50-60 Hz for 3 phase motors 10 hp at 600 V AC 50-60 Hz for 1 phase motors 30 hp at 600 V AC 50-60 Hz for 3 phase motors 5 hp at 250 V DC 15 hp at 600 V DC		

Complementary

Mounting Type	Surface		
Electrical Connection	Lugs		
Wiring configuration	3-wire		
Wire Size	AWG 12AWG 6 aluminium AWG 14AWG 6 copper		
Tightening torque	45 lbf.in (5.08 N.m) 0.02 in² (13.3 mm²) (AWG 6) 40 lbf.in (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8) 35 lbf.in (3.95 N.m) 0.000.01 in² (2.065.261 mm²) (AWG 14AWG 10)		
Depth	4.86 in (123.44 mm)		
Width	7.55 in (191.77 mm)		
Height	14.88 in (377.95 mm)		
Net Weight	8.82 lb(US) (4 kg)		

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Certifications UL listed file E2875

Ordering and shipping details

Category	00009-H&HU SW,2&3P,N3R,30-200A		
Discount Schedule	DE1		
GTIN	785901505600		
Returnability	Yes		
Country of origin	US		

Packing Units

_	
Unit Type of Package 1	Db
Number of Units in Package 1	1
Package 1 Height	5.20 in (13.208 cm)
Package 1 Width	7.90 in (20.066 cm)
Package 1 Length	16.40 in (41.656 cm)
Package 1 Weight	8.16 lb(US) (3.701 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	120
Package 2 Height	46.00 in (116.84 cm)
Package 2 Width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	1008.00 lb(US) (457.221 kg)


Offer Sustainability

Sustainable offer status	Green Premium product		
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov		
REACh Regulation	REACh Declaration		
REACh free of SVHC	Yes		
EU RoHS Directive	Compliant EU RoHS Declaration		
Mercury free	Yes		
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.		
RoHS exemption information	Yes		
Environmental Disclosure	Product Environmental Profile		
PVC free	Yes		

Contractual warranty

Warranty 18 months

Dimensions



^{*}DIMENSIONS TO BOX (NO T COVER)

ALL DIMENSIONS ARE APPROXIMATE. REFER TO TECHNICAL DRAWINGS AND DOCUMENTATION FOR COMPLETE INFORM ATION.

Wiring Diagram

WIRING DIAGRAM				
NOT FUSIBLE				
HU361RB HU361RBEI				

TERMINAL LUGS					
AMPERES	MAX WIRE	MIN WIRE	TYPE		
30	#6 AWG	#14 AWG	AL OR CU		

Technical Drawing 2229S, Wiring Diagram D

Recommended replacement(s)