

Optimal Path Planning in the Presence of Static Obstacles and Uncertain Dynamic Obstacles

Andrew C. Campbell*

The University of Alabama, Tuscaloosa, AL, 35487

In this paper a method for augmenting the Rapidly-exploring Random Tree star (RRT*) algorithm introduced by Karaman & Frazzoli¹ such that it can plan in an uncertain dynamic environment is presented. The innovation is primarily in the development of a grid management system capable of handling multiple obstacle types including uncertain obstacles, such that the probability of a cell being occupied at a certain time can be calculated and passed to any planning system. Notably this grid management system is capable of interfacing with any planner that calculates its own state in relation to time as it plans. This allows for a planning algorithm to avoid future collisions, and avoid regions that a moving obstacle could occupy in the future, all while avoiding static obstacles as any conventional planner.

I. Introduction

The path and motion planning problem is a fundamental problem in robotics and autonomous systems. There has yet to be an extensive amount of work done on the problem of path planning in the presence of dynamic obstacles, let alone uncertain dynamic obstacles as well. The development then of a system that can manage all these cases at once is necessary to provide more flexibility for the implementation of planners on autonomous systems to run a more robust and reliable system. Presented here is a Grid management system that is capable of managing certain and uncertain static obstacles and certain and uncertain dynamic obstacles. The grid management system is capable of propagating dynamic obstacles into the future a given amount of time with a given time step resolution and can determine the occupancy probability of a cell at a given time. This system can also sample many potential futures for a dynamic obstacle based on the random parameters and boundary conditions of said obstacle. By managing all of this within the grid management system, it can interface with any planner that calculates its time of travel to a node such that it can access the grid as it plans to ensure safe planning in a dynamic uncertain environment. To demonstrate the effectiveness of this system, the an RRT* algorithm that follow a set velocity to determine time is paired with a path validation system that checks a bounding box for the size a vehicle for intersections with grid elements at the desired time.

II. Problem Definition

Let $\mathcal{X} \in \mathbb{R}^{n \times 1}$ where $n \in \mathbb{N}$ denote the n -dimensional space and one time dimension configuration space that a vehicle is operating within. $\mathcal{X}_{obs} \in \mathcal{X}$ denotes the set of occupied space and time. $\mathcal{X}_{free} = \mathcal{X} \setminus \mathcal{X}_{obs}$ denotes the set of free space and time. Let the initial state and goal be denoted by $x_{init}, x_{goal} \in \mathcal{X}_{free}$ respectively.

Define the vehicle V as the space confined by a polygon V_{poly} with vertices $\{v_1, v_2, \dots, v_n\}$ in $\mathbb{R}^n$. The position and orientation of the vehicle at any time t can be represented by a transformation $T(x, V)$, where x is a state in $\mathcal{X}$ and $T(x, V)$ is a translation and rotation applied to V . The transformed vehicle $V_{transformed} = T(x, V)$ represents the space aligned with the vehicle's position and orientation in the configuration space $\mathcal{X}$. Note that for path planning to be possible $T(x_{init}, x_{goal}, V) \in \mathcal{X}_{free}$ must be true.

*Graduate Research Assistant, Aerospace Engineering & Mechanics, accampbell4@crimson.ua.edu.

A dynamic obstacle O can be defined similarly to a vehicle as the space with a polygon O_{poly} with vertices $\{o_1, o_2, \dots, o_n\}$ in $\mathbb{R}^n$ with dynamics that define some state function $x_{obs}(t)$. Then, $\mathcal{X}_{obs} \supset T(x_{obs}(t), O)$.

An Uncertain dynamic obstacle can mean that the polygon defining the obstacle O_{poly} is not known exactly and/or the the state function $x_{obs}(t)$ is a function of random variables. In this case we define a new $\mathcal{X}_{uncertain} \in \mathcal{X}$ for spaces that have a nonzero but less than or equal to one probability of occupancy, therefore $\mathcal{X}_{obs} \subset \mathcal{X}_{uncertain}$.

Both static certain and uncertain obstacles can be defined in the same way as dynamic obstacles, but with a state function that is invariate with time.

The goal of a path planner is to find a path $\mathcal{P} = \{x_1, x_2, \dots, x_n\}$ as a list of states defined such that $x_1 = x_{init}$, $x_n = x_{goal}$, and $T(\mathcal{P}, V) \subset \mathcal{X}_{free}$.

III. RRT* Algorithm and Grid Management System

For an RRT* planning algorithm let $\mathcal{T}(\mathcal{V}, E)$ define the tree where $\mathcal{V}$ are the vertices and E are the edges. let $N \in \mathbb{N}$ denote the number of samples that that the algorithm will take to plan. the algorithm is as follows

IV. Results

RRT* Path Planning




Figure 1. 3D results using ELQR provided by van den

V. Conclusion

References

¹Sertac Karaman and Emilio Frazzoli. Sampling-based algorithms for optimal motion planning. *The International Journal of Robotics Research*, 30(7):846–894, 2011.