LIEBHERR-WERK EHINGEN GMBH

An Transbiaga

Z.H. Att.

EMail

EMail

LIEBHERR-WERK EHINGEN GMBHPostfach 13 61

D-89582 Ehingen/Donau

Dr.-Hans-Liebherr-Straße 1 D-89584 Ehingen/Donau

 Von
 Schwertle

 From
 TST / Statik

 Dept.
 Seite
 1
 von
 1

 Page
 of
 Datum
 22.07.2019





Your request: Driving with LR 1600/2W: SDB/SL2DB

The driving with narrow crawler tracks is allowed in SDB/SL2DB Operation, if the following conditions are fulfilled:

Boom configuration:

- Boom length ≤ 120m
- superstructure ballast 150t
- derrick radius 13m with 0t derrick ballast (without ballast tray)
- The supports must be held on support base 14 m x 14 m while driving, whereby the base plates must be directly above the ground
- max allowable inclination of the ground: ± 0.3°
- max allowable gust wind speed (measured at highest point of the crane): 9.0 m/s
- driving speed ≤ 0.1 m/s
- Boom in driving direction and central position of the center of gravity
- Hock block without load

Furthermore, the conditions about driving with the crawler according to the operation's manual of the crane must be considered. The driving with a bigger ground inclination than 0.3° is only possible with returned boom configuration. For this returned boom, there is a driving chart in the operation manual. Please use the Liccon job planner to find the central position of the center of gravity.

With kind regards,

...V. J. Henkel

i.A. S. Schwertle

Liebherr-Werk Ehingen GmbH Dr.-Hans-Liebherr-Straße 1 89584 Ehingen Deutschland Telefon + 49 (0) 73 91 502-0

Telefax + 49 (0) 73 91 502-3399

Amtsgericht Ulm/Donau HRB 490123 Ust-Id. Nr.: DE 811120093

www.liebherr.com E-Mail: info.lwe@liebherr.com Vorsitzender des Aufsichtsrates: Uwe Rechtsteiner

Geschäftsführer: Dr.-Ing. Ulrich Hamme Dr.-Ing. Hubert Hummel Dipl.-Ing.(FH) Christoph Kleiner Dipl.-Kfm. Mario Trunzer