AI-103 Practice

Design checkpoint

20 questions

Answers, explanations and source links

Objectives effective 16 April 2026

Case study - Rotor equipment reservations

Rotor rents industrial equipment to authenticated business customers. Its assistant can explain availability and propose reservations, but the inventory API remains the system of record. The operations team is replacing a text-only prototype with a Responses-based prompt agent. Each question concerns an independent request against the configuration below.

Application and identity

The backend receives a signed application session identifying the customer and warehouse. It calls the agent using one managed identity. Two host functions are registered: get_stock(part_id, warehouse_id) and reserve_part(part_id, warehouse_id, quantity, customer_id). The stock function is read-only. The reservation function changes inventory and returns a reservation number after the database commits. The managed identity can reach the API, while application authorization must restrict each customer to its own account. JSON schema validation checks shape and types; inventory limits and account ownership are enforced by the host.

Action policy

A customer may request a proposal without committing it. Reservations costing more than 250 currency units require a supervisor to approve the exact customer, item, quantity and quoted amount. An approval for five units is not approval for fifty. A changed proposal must return to the approval screen. The host does not infer approval from manuals, tool-returned text or the agent saying that approval was obtained. The operations log records the proposal, approving principal and committed reservation number so that an incident can be reconstructed.

Observed request

A request checks the same part at two warehouses. Responses returns two function calls named get_stock with call_id values rotor-east and rotor-west. The west warehouse replies first. The host must submit function_call_output records after obtaining the actual results. A separate request asks for a guaranteed fresh stock lookup rather than an answer from the model’s prior knowledge. Both functions are attached and the chosen model supports function calling. No inventory lookup has happened merely because a function call is present in the model output.

Failure investigation

A test customer asks for a reservation belonging to another customer account. The argument object passes the JSON schema. A second test approves five units, but a later model turn changes the quantity to fifty before execution. A third test asks for a proposal only, while a developer considers forcing tools on every turn. Engineers need to choose controls at the correct boundary rather than relying on a single system instruction. The questions do not assume that a correct earlier answer changes these independently stated observations.

Q1

Domain B: Implement generative AI and agentic solutions | Case study

Use shared case: Rotor equipment reservations.
In Rotor’s two-warehouse request, west completes first. Which output correlation preserves the API contract?

A Associate both results with get_stock.

B Replace the call_id with a newly generated receipt ID.

C Associate results with completion position.

D Associate each result with its originating call_id. ✓

Why the correct answer is right

rotor-east and rotor-west identify distinct proposed calls even though the function name matches. Completion order does not change function_call_output correlation.

Why the other options are wrong

- **A:** The shared name cannot distinguish the two calls.
- **C:** A slower call can complete later; position is not the correlation key.
- **B:** A business receipt is not the originating function call identifier.

AI103-B2.01

Sources

S007: Use function calling with Microsoft Foundry agents
https://learn.microsoft.com/azure/foundry/agents/how-to/tools/function-calling

Q2

Domain B: Implement generative AI and agentic solutions | Case study

Use shared case: Rotor equipment reservations.
Rotor’s fresh availability turn must use a tool rather than answer from prior knowledge.
Both tools are available. Which request-level mode requires tool use?

A required ✓

B none

C parallel_tool_calls=true

D auto

Why the correct answer is right

required demands one or more tool calls. The host still checks which action is proposed, its authorization and any approval requirement.

Why the other options are wrong

- **D:** auto permits a response without a tool call.
- **B:** none prevents tool calls.
- **C:** Permitting parallel calls does not require a tool call.

AI103-B2.02

Sources

S054: Tool best practices for Microsoft Foundry Agent Service
https://learn.microsoft.com/azure/foundry/agents/concepts/tool-best-practice

S007: Use function calling with Microsoft Foundry agents
https://learn.microsoft.com/azure/foundry/agents/how-to/tools/function-calling

Case study - Lumen regional engineering assistant

Lumen operates an engineering assistant for staff in the European Union. Its platform team is designing deployment, identity and retrieval controls together, with separate principals for deployment and runtime. The service must answer interactively and retain existing learner and operational records during the migration described here.

Workload boundary

The processing policy permits inference across EU countries but forbids processing outside that data zone. Interactive requests cannot wait for a nightly batch. Demand varies across the day and procurement wants on-demand token billing rather than reserved throughput. The selected model is available for every deployment family considered in the questions, and the relevant quota has already been confirmed. The resource's region alone is not the organization's definition of the inference processing boundary.

Inference identity

The backend calls an Azure OpenAI resource through its /openai/v1/ endpoint using Microsoft Entra credentials. Its runtime managed identity currently has Reader on that resource and no inference data role. Token acquisition succeeds, but inference is denied. The team wants the documented inference role at the resource scope without granting model-management permissions. Developers' personal roles and the GitHub deployment principal are separate from the runtime identity. A resource key is not part of the approved runtime design.

Project and Search

An AI Projects Python 2.8.0 client is used for Foundry project operations, with a project endpoint and an Entra credential. Search public access is disabled. The private endpoint exists, and the agent connection is explicitly pinned to the named runtime principal. That principal has Search Index Data Reader for the target index. From the runtime subnet, however, the Search hostname resolves to a public address. From a developer laptop on another network it resolves privately and querying succeeds. The network observations do not transfer from the laptop to the agent subnet.

Release process

A GitHub deployment workflow obtains a token using an established OIDC trust. It does not store a client secret. The workflow principal's project role is assigned on a different project, while its endpoint variable points to the intended Lumen project. An authorization denial therefore needs identity and scope analysis after authentication succeeds. Operations retain redacted request spans and release identifiers to investigate failures. Each question asks for a single independent decision; repairing one defect is not assumed to repair the others. A proposed change must satisfy the named runtime, region and billing facts rather than simply resemble a working developer setup.

Q3

Domain A: Plan and manage an Azure AI solution | Case study

Use shared case: Lumen regional engineering assistant.
Lumen’s runtime obtains a token but Reader-only inference is denied. Which documented role at the called Azure OpenAI resource supplies inference permission?

A Search Index Data Reader.

B Cognitive Services OpenAI User. ✓

C Reader on the Foundry project only.

D A deployment workflow’s role on another project.

Why the correct answer is right

The named /openai/v1/ endpoint requires the runtime identity’s inference permission. Cognitive Services OpenAI User is the documented inference role; scope must cover the called resource.

Why the other options are wrong

- **C:** Management reading does not grant the named inference permission.
- **A:** That role applies to Search data, not Azure OpenAI inference.
- **D:** A different principal and different resource scope do not authorize this runtime call.

AI103-A3.04

Sources

S051: Azure OpenAI v1 API
https://learn.microsoft.com/en-us/azure/foundry/openai/api-version-lifecycle

S052: Use Azure OpenAI without keys
https://learn.microsoft.com/en-us/azure/developer/ai/keyless-connections

Q4

Domain A: Plan and manage an Azure AI solution | Configuration

Complete the Azure OpenAI v1 client for keyless inference. The calling identity has the inference role at the resource scope.

token_provider = get_bearer_token_provider(credential, "[_____]")
client = OpenAI(base_url="[_____]", api_key=token_provider)
audience: https://ai.azure.com/.default / https://management.azure.com/.default / https://search.azure.com/.default
endpoint: https://resource.openai.azure.com/openai/v1/ / https://resource.services.ai.azure.com/api/projects/support / https://resource.search.windows.net/

Completed statement:

token_provider = get_bearer_token_provider(credential, "**https://ai.azure.com/.default**")

client = OpenAI(base_url="**https://resource.openai.azure.com/openai/v1/**",

api_key=token_provider)

Why the correct answer is right

The named v1 example uses the ai.azure.com token audience and the resource /openai/v1/ base URL. Authentication still requires authorization on the called resource.

Answer and step notes

- **audience:** Use the v1 example's inference token audience, rather than an ARM or Search audience.
- **endpoint:** This is the direct resource v1 surface, not project management or Search.

AI103-A3.04

Sources

S051: Azure OpenAI v1 API
https://learn.microsoft.com/en-us/azure/foundry/openai/api-version-lifecycle

S052: Use Azure OpenAI without keys
https://learn.microsoft.com/en-us/azure/developer/ai/keyless-connections

Q5

Domain A: Plan and manage an Azure AI solution | Configuration

Complete the AI Projects Python 2.8.0 constructor for project operations.

project = AIProjectClient(endpoint=[_____], credential=[_____])
endpoint: project_endpoint / openai_v1_base_url / search_endpoint
credential: DefaultAzureCredential() / AzureKeyCredential(resource_key) / project_endpoint

Completed statement:

project = AIProjectClient(endpoint=**project_endpoint**, credential=**DefaultAzureCredential()**)

Why the correct answer is right

The retained AI Projects 2.8.0 reference uses a Foundry project endpoint and Entra credentials. Project and direct inference clients have different roles.

Answer and step notes

- **endpoint:** Choose the endpoint of the named project for project operations.
- **credential:** The 2.8.0 client supports Entra credentials; a URL is not a credential and resource-key construction is not this client contract.

AI103-A2.03

Sources

S002: Azure AI Projects client library for Python - version 2.8.0
https://learn.microsoft.com/python/api/overview/azure/ai-projects-readme?view=azure-python

S003: Microsoft Foundry SDKs and endpoints
https://learn.microsoft.com/azure/foundry/how-to/develop/sdk-overview

Q6

Domain A: Plan and manage an Azure AI solution | Single choice

A catalog requires exact part-code matches and semantic symptom matches. Which design combines both retrieval signals before optional reranking?

A Vector retrieval alone, with a larger candidate count.

B Semantic reranking of keyword-only candidates.

C Keyword and vector retrieval with fused rankings. ✓

D Keyword retrieval alone, with boosted identifier fields.

Why the correct answer is right

Keyword evidence complements semantic vectors. Evaluate hybrid retrieval for the actual query set; ranking quality is distinct from generation and authentication.

Why the other options are wrong

- **A:** A larger vector candidate count does not add keyword retrieval.
- **D:** Boosted keyword fields do not add vector retrieval.
- **B:** Reranking keyword candidates does not combine keyword and vector retrieval.

AI103-A1.03

Sources

S025: Hybrid search using vectors and full-text search in Azure AI Search
https://learn.microsoft.com/azure/search/hybrid-search-overview

S026: Integrated vector embedding in Azure AI Search
https://learn.microsoft.com/azure/search/vector-search-integrated-vectorization

Q7

Domain A: Plan and manage an Azure AI solution | Single choice

A secured agent has the required runtime roles. Search resolves to a public IP from the agent network even though public access is disabled. The private endpoint exists. What should be investigated next?

A The Search role assignments on the identity used by the deployment pipeline.

B The query-time semantic ranking configuration on the target index.

C The private endpoint connection approval state for the runtime subnet.

D Private DNS resolution and links for the agent network. ✓

Why the correct answer is right

A private endpoint must be reachable through correct DNS resolution and routing from the runtime network. Roles cannot repair resolution to a blocked public endpoint.

Why the other options are wrong

- **C:** The stated failure is name resolution to a public address.
- **A:** The problem is name resolution from the runtime network.
- **B:** Ranking is evaluated after a request reaches Search.

AI103-A3.04

Sources

S011: Set up private networking for Foundry Agent Service
https://learn.microsoft.com/azure/foundry/agents/how-to/virtual-networks

Q8

Domain B: Implement generative AI and agentic solutions | Configuration

Complete the current Python client calls for an existing agent named helpdesk and its project OpenAI client.

agent = project.agents.[_____](agent_name="helpdesk")
client = project.[_____]()
operation: get / get_agent / create_version
client: get_openai_client / get_search_client / get_agent_client

Completed statement:

agent = project.agents.**get**(agent_name="helpdesk")

client = project.**get_openai_client**()

Why the correct answer is right

The current operations reference exposes get(agent_name). The retained 2.8.0 project library provides get_openai_client for Responses and conversations.

Answer and step notes

- **operation:** Retrieve the existing named definition; do not mix classic retrieval or create a new version.
- **client:** Obtain the documented OpenAI client for Responses operations.

AI103-B1.06

Sources

S002: Azure AI Projects client library for Python - version 2.8.0
https://learn.microsoft.com/python/api/overview/azure/ai-projects-readme?view=azure-python

S056: AI Projects AgentsOperations Python reference
https://learn.microsoft.com/en-us/python/api/azure-ai-projects/azure.ai.projects.operations.agentsoperations?view=azure-python

Q9

Domain B: Implement generative AI and agentic solutions | Configuration

Complete a backend memory-search tool definition and response header for per-user preferences. user_key is derived from the authenticated session.

```
from azure.ai.projects.models import MemorySearchPreviewTool, PromptAgentDefinition
tool = MemorySearchPreviewTool(memory_store_name="preferences", scope="
[_____]")
agent = project.agents.create_version(agent_name="support",
definition=PromptAgentDefinition(model=deployment, tools=[tool]))
response = client.responses.create(input=message,
extra_body={"agent_reference": {"name": agent.name, "type": "agent_reference"}},
extra_headers={"[_____]": user_key})
scope: {{$userId}} / backend-shared / conversation-title
header: x-memory-user-id / x-request-id / Authorization
```

Completed statement:

```
from azure.ai.projects.models import MemorySearchPreviewTool, PromptAgentDefinition
tool = MemorySearchPreviewTool(memory_store_name="preferences", scope="{{$userId}}")
agent = project.agents.create_version(agent_name="support",
    definition=PromptAgentDefinition(model=deployment, tools=[tool]))
response = client.responses.create(input=message,
    extra_body={"agent_reference": {"name": agent.name, "type": "agent_reference"}},
    extra_headers={"x-memory-user-id": user_key})
```

Why the correct answer is right

The memory tool resolves the placeholder from the memory-user header, falling back to caller TID/OID without it. A backend must supply its authenticated end-user key.

Answer and step notes

- **scope:** Use the documented per-user placeholder; static scope pools users and a title is not a partition key.
- **header:** The memory-user header carries end-user identity; a trace ID does not select a user and Authorization identifies the calling service.

AI103-B2.02

Sources

S053: Create and use memory in Foundry Agent Service (preview)
https://learn.microsoft.com/en-us/azure/foundry/agents/how-to/memory-usage

Q10

Domain B: Implement generative AI and agentic solutions

Configuration

A Responses turn must consult at least one attached tool. Complete the request-level control.

response = client.responses.create(model=deployment, input=message, tools=tools, tool_choice="[_____]")
mode: auto / required / none

Completed statement:

response = client.responses.create(model=deployment, input=message, tools=tools, tool_choice="**required**")

Why the correct answer is right

required demands one or more calls. It does not by itself select one exact function, execute host code or grant permission.

Answer and step notes

- **mode:** auto leaves tool use to the model; none prevents it. The host remains responsible for validation and execution.

AI103-B2.01

Sources

S054: Tool best practices for Microsoft Foundry Agent Service
https://learn.microsoft.com/azure/foundry/agents/concepts/tool-best-practice

Q11

Domain B: Implement generative AI and agentic solutions | Configuration

Complete a supported strict Responses schema: note must be present and can be null; unknown properties are rejected.

schema = {"type": "object", "properties": {"note": {"type": ["string", "null"]}},
"required": [_____], "additionalProperties": [_____]}
response text.[_____] contains the json_schema format
required: ["note"] / [] / ["string", "null"]
extra: False / True
location: format / response_format / metadata

Completed statement:

schema = {"type": "object", "properties": {"note": {"type": ["string", "null"]}},
"required": **["note"]**, "additionalProperties": **False**}
response text.**format** contains the json_schema format

Why the correct answer is right

Nullable value types do not make a property optional in the supported strict subset. Responses uses text.format, unlike the Chat Completions field.

Answer and step notes

- **required:** Require the key while retaining a nullable value type.
- **extra:** additionalProperties false disallows unknown fields.
- **location:** Use the documented Responses request shape.

AI103-B3.01

Sources

S037: Structured outputs
https://learn.microsoft.com/azure/foundry/openai/how-to/structured-outputs

Q12 Domain C: Implement computer vision solutions Multiple select

An image safety policy evaluates four harm categories and rejects any severity of 4 or 6. Which TWO implementation decisions match the image:analyze 2024-09-01 contract? Select TWO answers.

A Request FourSeverityLevels for the image analysis. ✓

B Average all categories before applying the rejection threshold.

C Use EightSeverityLevels as the documented image output scale.

D Treat HTTP success as an approval verdict.

E Evaluate the policy against each of the four harm categories. ✓

Why the correct answer is right

The image contract uses values 0, 2, 4 and 6. Analyze the required categories and apply the application's explicit threshold policy.

Why the other options are wrong

- **C:** The referenced image contract uses four levels.
- **D:** Success means the analysis request completed.
- **B:** An average does not implement an any-category policy.

AI103-C3.01

Sources

S042: QuickStart: Analyze image content
https://learn.microsoft.com/azure/ai-services/content-safety/quickstart-image

Q13 Domain C: Implement computer vision solutions Multiple select

A model supports masked image edits. The client must change one area of an existing image. Which TWO inputs are directly relevant to the edit definition? Select TWO answers.

A A same-size PNG mask marking edit areas with transparent pixels. ✓

B A JPEG mask with the source dimensions but no transparency.

C A mask resized to the requested output dimensions instead of the source dimensions.

D A same-size mask whose opaque pixels mark the replacement area.

E The source image and a prompt describing the intended change. ✓

Why the correct answer is right

A supported edit request uses the source, edit instructions and spatial mask. Model-specific controls and input requirements still apply.

Why the other options are wrong

- **C:** The mask dimensions must match the input image, not an independently selected output size.
- **B:** The documented mask is PNG and uses transparent pixels; a JPEG has no alpha channel.
- **D:** The documented mask uses fully transparent pixels to designate the editable region.

AI103-C1.03

Sources

S017: Azure OpenAI image generation models
https://learn.microsoft.com/azure/foundry/openai/how-to/dall-e

Q14 Domain C: Implement computer vision solutions Multiple select

A team evaluates the video-analysis 2026-06-01-preview contract for fast events and tiny labels. Which TWO limitations belong in its evaluation plan? Select TWO answers.

A OCR retains original source resolution for every sampled frame.

B Scene segmentation removes the temporal frame-sampling limit.

C About one-frame-per-second sampling can miss brief events. ✓

D Every source frame is analyzed, but only key frames are returned.

E Resizing to 512 by 512 can lose small or distant details. ✓

Why the correct answer is right

Evaluate the feature against its temporal and spatial resolution. Do not interpret a missing detection as proof that the original video lacks an event or detail.

Why the other options are wrong

- **B:** Segmentation provides scene organization; it does not remove the documented sampling limitation.
- **A:** The captured contract resizes sampled frames; it does not promise original-resolution OCR.
- **D:** The documented limit concerns inspected frames, not just the number of returned thumbnails.

AI103-C2.06

Sources

S022: Azure Content Understanding in Foundry Tools video solutions
https://learn.microsoft.com/azure/ai-services/content-understanding/video/overview

Q15 Domain D: Implement text analysis solutions Multiple select

Mixed-language segments were submitted together for translation. Which TWO changes directly target the documented input problem? Select TWO answers.

A Use the intended source language for each segment. ✓

B Separate single-language segments. ✓

C Increase the translated response length limit.

D Detect one source language and submit the whole mixture unchanged.

E Move the unchanged mixture to the document endpoint.

Why the correct answer is right

Language segmentation and explicit intended source handling target the documented condition. The host should inspect translation quality rather than infer success from detection.

Why the other options are wrong

- **C:** Output length does not separate source-language spans.
- **D:** A detected language does not establish that every span was translated.
- **E:** Document translation also has documented mixed-language limitations.

AI103-D1.03

Sources

S055: Azure Translator known issues and troubleshooting
https://learn.microsoft.com/en-us/azure/ai-services/translator/reference/known-issues

Q16 Domain E: Implement information extraction solutions Sequence

A source document exceeds the embedding input limit. Arrange the dependency chain that produces searchable chunk vectors.

Arrange these steps in order:

A. Embed each prepared chunk.

B. Index the chunk text and its compatible vectors.

C. Read the document text.

D. Create chunks within the input limit.

Correct order:

1. C Read the document text.

2. D Create chunks within the input limit.

3. A Embed each prepared chunk.

4. B Index the chunk text and its compatible vectors.

Why the correct answer is right

Each output is the next operation’s input: document text, bounded chunks, embeddings, then index records.

Answer and step notes

- **C:** The source text supplies the chunking input.
- **D:** Chunking requires source text and produces embedding inputs.
- **A:** Vectors are produced from prepared chunks.
- **B:** Indexing consumes text and completed vectors.

AI103-E1.01

Sources

S026: Integrated vector embedding in Azure AI Search
https://learn.microsoft.com/azure/search/vector-search-integrated-vectorization

S058: Integrated vectorization REST configuration
https://learn.microsoft.com/en-us/azure/search/search-how-to-integrated-vectorization

Q17 Domain E: Implement information extraction solutions Sequence

A configured document analyzer returns a long-running operation. Arrange the dependency chain for sending completed extraction to a RAG pipeline.

Arrange these steps in order:

A. Submit document analysis.

B. Wait for successful operation completion.

C. Pass that result to downstream ingestion.

D. Read the completed structured/Markdown result.

Correct order:

1. A Submit document analysis.

2. B Wait for successful operation completion.

3. D Read the completed structured/Markdown result.

4. C Pass that result to downstream ingestion.

Why the correct answer is right

A returned operation is not extracted content. Completion is required before results can supply downstream ingestion.

Answer and step notes

- **A:** Submission creates the tracked operation.
- **B:** The operation must finish successfully before consumption.
- **D:** Only the successful result supplies the representation.
- **C:** Downstream work requires the extracted representation.

AI103-E2.02

Sources

S021: Azure AI Content Understanding client library for Python - version 1.1.0
https://learn.microsoft.com/python/api/overview/azure/ai-contentunderstanding-readme?view=azure-python

Q18 Domain D: Implement text analysis solutions Matching

Match each speech requirement to the relevant capability. Use each selected choice once; one choice is unused.

Match each row to a choice.

A. Recognize source speech and obtain target-language text
Match: _____

B. Adapt recognition to specialist terminology using domain data
Match: _____

C. Render supplied text as spoken audio
Match: _____

Choice bank

- Custom Speech
- Speech translation
- Text-to-speech synthesis
- Image analysis

Correct matches:

A. Recognize source speech and obtain target-language text	**→ Speech translation**
B. Adapt recognition to specialist terminology using domain data	**→ Custom Speech**
C. Render supplied text as spoken audio	**→ Text-to-speech synthesis**

Why the correct answer is right

Custom Speech adapts recognition, Speech translation produces target-language text, and synthesis renders text as audio.

Answer and step notes

- **B:** Adapt recognition to specialist terminology using domain data: Custom Speech.
- **A:** Recognize source speech and obtain target-language text: Speech translation.
- **C:** Render supplied text as spoken audio: Text-to-speech synthesis.

AI103-D2.01 AI103-D2.02 AI103-D2.04

Sources

S033: What is Azure Speech?
https://learn.microsoft.com/azure/ai-services/speech-service/overview

S034: What is custom speech?
https://learn.microsoft.com/azure/ai-services/speech-service/custom-speech-overview

S046: How to recognize and translate speech
https://learn.microsoft.com/azure/ai-services/speech-service/how-to-translate-speech

Q19 Domain D: Implement text analysis solutions Matching

Match each text task to the most targeted Language capability. Use each selected choice once; one choice is unused.

Match each row to a choice.

A. Locate personal identifiers for redaction
Match: _____

B. Label organizations and locations using predefined categories
Match: _____

C. Identify a message language for routing
Match: _____

Choice bank

- PII detection
- Language detection
- Named entity recognition
- Sentiment analysis

Correct matches:

A. Locate personal identifiers for redaction	**→ PII detection**
B. Label organizations and locations using predefined categories	**→ Named entity recognition**
C. Identify a message language for routing	**→ Language detection**

Why the correct answer is right

The requested output determines the capability. Sentiment measures emotional tone and is unused here.

Answer and step notes

- **A:** Locate personal identifiers for redaction: PII detection.
- **C:** Identify a message language for routing: Language detection.
- **B:** Label organizations and locations using predefined categories: Named entity recognition.

AI103-D1.01 AI103-D1.02

Sources

S030: What is Azure Language in Foundry Tools?
https://learn.microsoft.com/azure/ai-services/language-service/overview

Q20 Domain E: Implement information extraction solutions Configuration

The index has no OCR text. Which one configuration defect in this exhibit blocks the OCR input path?

Blob OCR pipeline

```
{
  "indexer": {
    "parameters": {"configuration": {"imageAction": "none"}},
    "outputFieldMappings": [{
      "sourceFieldName": "/document/normalized_images/*/text",
      "targetFieldName": "ocr_text"
    }]
  },
  "skill": {
    "@odata.type": "#Microsoft.Skills.Vision.OcrSkill",
    "context": "/document/normalized_images/*",
    "inputs": [{"name": "image", "source": "/document/normalized_images/*"}],
    "outputs": [{"name": "text", "targetName": "text"}]
  },
  "indexField": {"name": "ocr_text", "type": "Collection(Edm.String)", "searchable": true}
}
```

A The OCR skill uses the normalized image wildcard.

B The blob indexer’s imageAction is none. ✓

C The text output mapping names the correct enriched node.

D The index’s ocr_text field is searchable.

Why the correct answer is right

The normalized image collection must exist for the OCR skill input. The exhibit’s output path is already correct.

Why the other options are wrong

- **C:** This correctly maps the produced node after the skill runs.
- **D:** Searchability is appropriate for retrieval.
- **A:** The wildcard matches the skill’s normalized-image input.

AI103-E1.04

Sources

S043: OCR cognitive skill
https://learn.microsoft.com/azure/search/cognitive-search-skill-ocr

S028: Skillset concepts in Azure AI Search
https://learn.microsoft.com/azure/search/cognitive-search-working-with-skillsets

Quick Answer Key

#	Type	Correct Answer
Q1	Case study	**D**
Q2	Case study	**A**
Q3	Case study	**B**
Q4	Configuration	**audience → https://ai.azure.com/.default | endpoint → https://resource.openai.azure.com/openai/v1/**
Q5	Configuration	**endpoint → project_endpoint | credential → DefaultAzureCredential()**
Q6	Single choice	**C**
Q7	Single choice	**D**
Q8	Configuration	**operation → get | client → get_openai_client**
Q9	Configuration	**scope → {{$userId}} | header → x-memory-user-id**
Q10	Configuration	**mode → required**
Q11	Configuration	**required → ["note"] | extra → False | location → format**
Q12	Multiple select	**A, E**
Q13	Multiple select	**E, A**
Q14	Multiple select	**C, E**
Q15	Multiple select	**B, A**
Q16	Sequence	**1. C → 2. D → 3. A → 4. B**
Q17	Sequence	**1. A → 2. B → 3. D → 4. C**
Q18	Matching	**B → Custom Speech | A → Speech translation | C → Text-to-speech synthesis**
Q19	Matching	**A → PII detection | C → Language detection | B → Named entity recognition**
Q20	Configuration	**B**