

# Announcements

- Homework 3 online, due Friday
- Exam 1 solutions online

# HW2 Q2

Remember:

- Looking for sink/source SCCs
- Compute Metagraph
  - SCCs are a vertex  $v$  and *every* other vertex that can both reach and be reached from  $v$
- Find sources/sinks
  - A sink is a vertex with no outgoing edges
  - A source is a vertex with no incoming edges
  - An isolated vertex is *both*!

# Last Time

- Divide and Conquer
- Master Theorem
- MergeSort
- Order statistics

# Divide and Conquer

This is the first of our three major algorithmic techniques.

1. Break problem into pieces
2. Solve pieces recursively
3. Recombine pieces to get answer

# Master Theorem

**Theorem:** Let  $T(n)$  be given by the recurrence:

$$T(n) = \begin{cases} O(1) & \text{if } n = O(1) \\ aT(n/b + O(1)) + O(n^d) & \text{otherwise} \end{cases}$$

Then we have that

$$T(n) = \begin{cases} O(n^{\log_b(a)}) & \text{if } a > b^d \\ O(n^d \log(n)) & \text{if } a = b^d \\ O(n^d) & \text{if } a < b^d \end{cases}$$

# Today

- Order statistics
- Binary search
- Closest pair of points

# Order Statistics

Suppose that we just want to find the median element of a list, or the largest, or the 10<sup>th</sup> smallest.

# Order Statistics

Suppose that we just want to find the median element of a list, or the largest, or the 10<sup>th</sup> smallest.

**Problem:** Given a list  $L$  of numbers and an integer  $k$ , find the  $k$ th largest element of  $L$ .



# Order Statistics


Suppose that we just want to find the median element of a list, or the largest, or the 10<sup>th</sup> smallest.

**Problem:** Given a list  $L$  of numbers and an integer  $k$ , find the  $k$ th largest element of  $L$ .

**Naïve Algorithm:** Sort  $L$  and return  $k$ th largest.  
 $O(n \log(n))$  time.


# Divide Step

Select a *pivot*  $x \in L$ . Compare it to the other elements of  $L$ .




# Divide Step

Select a *pivot*  $x \in L$ . Compare it to the other elements of  $L$ .



# Divide Step

Select a *pivot*  $x \in L$ . Compare it to the other elements of  $L$ .




Which list is our answer in?

- Answer is  $> x$  if there are  $\geq k$  elements bigger than  $x$ .
- Answer is  $x$  if there are  $< k$  elements bigger and  $\geq k$  elements bigger than or equal to  $x$ .
- Otherwise answer is less than  $x$ .

# Divide Step

Select a *pivot*  $x \in L$ . Compare it to the other elements of  $L$ .



Which list is our answer in?

- Answer is  $> x$  if there are  $\geq k$  elements bigger than  $x$ .
- Answer is  $x$  if there are  $< k$  elements bigger and  $\geq k$  elements bigger than or equal to  $x$ .
- Otherwise answer is less than  $x$ .

# Order Statistics

Select (L, k)

Pick  $x \in L$

Sort L into  $L_{>x}$ ,  $L_{<x}$ ,  $L_{=x}$

If  $\text{Len}(L_{>x}) \geq k$

Return Select ( $L_{>x}$ , k)

Else if  $\text{Len}(L_{>x}) + \text{Len}(L_{=x}) \geq k$

→ Return x

Return

Select ( $L_{<x}$ ,  $k - \text{Len}(L_{>x}) - \text{Len}(L_{=x})$ )

# Order Statistics

Select ( $L, k$ )

Pick  $x \in L$

Sort  $L$  into  $L_{>x}, L_{<x}, L_{=x}$  }  $O(n)$

If  $\text{Len}(L_{>x}) \geq k$

Return Select ( $L_{>x}, k$ )

Else if  $\text{Len}(L_{>x}) + \text{Len}(L_{=x}) \geq k$

→ Return  $x$

Return

Select ( $L_{<x}, k - \text{Len}(L_{>x}) - \text{Len}(L_{=x})$ )

# Order Statistics

Select ( $L, k$ )

Pick  $x \in L$

Sort  $L$  into  $L_{>x}, L_{<x}, L_{=x}$  }  $O(n)$

If  $\text{Len}(L_{>x}) \geq k$

Return Select ( $L_{>x}, k$ ) } ???

Else if  $\text{Len}(L_{>x}) + \text{Len}(L_{=x}) \geq k$

→ Return  $x$

Return

Select ( $L_{<x}, k - \text{Len}(L_{>x}) - \text{Len}(L_{=x})$ ) } ???



# Runtime

Runtime recurrence

$$T(n) = O(n) + T(\text{sublist size})$$

# Runtime

Runtime recurrence

$$T(n) = O(n) + T(\text{sublist size})$$

**Problem:** The sublist we recurse on could have size as big as  $n-1$ . If so, runtime is  $O(n^2)$ .

# Runtime

Runtime recurrence

$$T(n) = O(n) + T(\text{sublist size})$$

**Problem:** The sublist we recurse on could have size as big as  $n-1$ . If so, runtime is  $O(n^2)$ .

Need to ensure this doesn't happen.


# Randomization

**Fix:** Pick a *random* pivot.



# Randomization


**Fix:** Pick a *random* pivot.



- There's a 50% chance that  $x$  is selected in the middle half.

# Randomization


**Fix:** Pick a *random* pivot.



- There's a 50% chance that  $x$  is selected in the middle half.
- If so, no matter where the answer is, recursive call of size at most  $3n/4$ .

# Randomization

**Fix:** Pick a *random* pivot.



- There's a 50% chance that  $x$  is selected in the middle half.
- If so, no matter where the answer is, recursive call of size at most  $3n/4$ .
- On average need two tries to reduce call.

# Question: Runtime

We get a runtime recurrence:

$$T(n) = O(n) + T(3n/4)$$

What is  $T(n)$ ?

- A)  $O(\log(n))$
- B)  $O(n^{3/4})$
- C)  $O(n)$
- D)  $O(n \log(n))$
- E)  $O(n^2)$



# Question: Runtime

We get a runtime recurrence:

$$T(n) = O(n) + T(3n/4)$$

What is  $T(n)$ ?

- A)  $O(\log(n))$
- B)  $O(n^{3/4})$
- C)  $O(n)$
- D)  $O(n \log(n))$
- E)  $O(n^2)$

Master Theorem:

$$a = 1, b = 4/3, d = 1$$

$$a < b^d$$

$$O(n^d) = O(n)$$

# Note

The algorithm discussed does give the correct answer in *expected*  $O(n)$  time.

There are deterministic  $O(n)$  algorithms using similar ideas, but they are substantially more complicated.

# Search

**Problem:** Given a sorted list  $L$  and a number  $x$ , find the location of  $x$  in  $L$ .

# Search

**Problem:** Given a sorted list  $L$  and a number  $x$ , find the location of  $x$  in  $L$ .

**Naïve Algorithm:** Try every element of  $L$ .  
 $O(n)$  time.

# Search

**Problem:** Given a sorted list  $L$  and a number  $x$ , find the location of  $x$  in  $L$ .

**Naïve Algorithm:** Try every element of  $L$ .  
 $O(n)$  time.

Usually, you cannot beat  $O(n)$  because any algorithm needs to read the entire input. However, since the list is guaranteed to be sorted, we can do better here.

# Divide

Split L into two lists.

# Divide

Split L into two lists.

- Could search for x in each

$$T(n) = 2T(n/2) + O(1) \quad \rightarrow$$

Too slow

# Divide

Split L into two lists.

- Could search for x in each

$T(n) = 2T(n/2) + O(1)$        $\rightarrow$       Too slow

- Use sorting to figure out which list to check.



# Divide

Split L into two lists.

- Could search for x in each

$$T(n) = 2T(n/2) + O(1) \quad \rightarrow \quad \text{Too slow}$$

- Use sorting to figure out which list to check.

If  $L[i] > x$ , location must be before i.

If  $L[i] < x$ , location must be after i.

If  $L[i] = x$ , we found it.

# Binary Search

```
BinarySearch(L, i, j, x)
```

```
\\Search between L[i] and L[j]
```

```
  If  $j < i$ , Return 'error'
```

```
   $k \leftarrow \lfloor (i+j)/2 \rfloor$ 
```

```
  If  $L[k] = x$ , Return  $k$ 
```

```
  If  $L[k] > x$ 
```

```
    Return BinarySearch(L, i,  $k-1$ , x)
```

```
  If  $L[k] < x$ 
```

```
    Return BinarySearch(L,  $k+1$ , j, x)
```

# Binary Search

```
BinarySearch(L, i, j, x)
```

```
\\Search between L[i] and L[j]
```

```
If j < i, Return 'error'
```

```
k ← [(i+j)/2]
```

```
If L[k] = x, Return k
```

```
If L[k] > x
```

```
Return BinarySearch(L, i, k-1, x)
```

```
If L[k] < x
```

```
Return BinarySearch(L, k+1, j, x)
```

} O(1)

# Binary Search

```
BinarySearch(L, i, j, x)
```

```
\\Search between L[i] and L[j]
```

```
If j < i, Return 'error'
```

```
k ← [(i+j)/2]
```

```
If L[k] = x, Return k
```

```
If L[k] > x
```

```
Return BinarySearch(L, i, k-1, x)
```

```
If L[k] < x
```

```
Return BinarySearch(L, k+1, j, x)
```

$O(1)$

$T(n/2)$

# Question: Runtime

We get a runtime recurrence:

$$T(n) = O(1) + T(n/2)$$

What is  $T(n)$ ?

- A)  $O(\log(n))$
- B)  $O(n^{1/2})$
- C)  $O(n^{1/2} \log(n))$
- D)  $O(n)$
- E)  $O(n \log(n))$

# Question: Runtime

We get a runtime recurrence:

$$T(n) = O(1) + T(n/2)$$

What is  $T(n)$ ?

A)  $O(\log(n))$

B)  $O(n^{1/2})$

C)  $O(n^{1/2} \log(n))$

D)  $O(n)$

E)  $O(n \log(n))$

Master Theorem:

$$a = 1, b = 2, d = 0$$

$$a = b^d$$

$$O(n^d \log(n)) = O(\log(n))$$

# Binary Search Puzzles

You have 27 coins one of which is heavier than the others, and a balance. Determine the heavy coin in 3 weightings.

Lots of puzzles have binary search-like answers.  
As long as you can spend constant time to divide your search space in half (or thirds).  
You can use binary search in  $O(\log(n))$  time.

# Closest Pair of Points (Ex 2.32)

**Problem:** Given  $n$  points in the plane  $(x_1, y_1) \dots (x_n, y_n)$  find the pair  $(x_i, y_i)$  and  $(x_j, y_j)$  whose Euclidean distance is as small as possible.




# Closest Pair of Points (Ex 2.32)

**Problem:** Given  $n$  points in the plane  $(x_1, y_1) \dots (x_n, y_n)$  find the pair  $(x_i, y_i)$  and  $(x_j, y_j)$  whose Euclidean distance is as small as possible.


**Naïve Algorithm:** Try every pair of points.  $O(n^2)$  time.

# Divide and Conquer Outline




# Divide and Conquer Outline

- Divide points into two sets by drawing a line.



# Divide and Conquer Outline

- Divide points into two sets by drawing a line.
- Compute closest pair on each side.



# Divide and Conquer Outline

- Divide points into two sets by drawing a line.
- Compute closest pair on each side.
- What about pairs that cross the divide?

