

MATHFUN Lecture FP2

Introduction to Functional Programming, Part 2

Matthew Poole
`moodle.port.ac.uk`

School of Computing
University of Portsmouth

2014/15

Introduction to Lecture

- In the first lecture we introduced the fundamental building block of functional programs: the function definition.
- We begin this lecture by showing how to **trace** the evaluation of any expression that includes a call to a function definition.

Introduction to Lecture

- In the first lecture we introduced the fundamental building block of functional programs: the function definition.
- We begin this lecture by showing how to **trace** the evaluation of any expression that includes a call to a function definition.
- We then introduce how slightly more complex definitions can be written using **guards** (generalisations of conditionals).
- We show how functions involving guards are evaluated.

Introduction to Lecture

- In the first lecture we introduced the fundamental building block of functional programs: the function definition.
- We begin this lecture by showing how to **trace** the evaluation of any expression that includes a call to a function definition.
- We then introduce how slightly more complex definitions can be written using **guards** (generalisations of conditionals).
- We show how functions involving guards are evaluated.
- Finally, we consider how functional code can be simplified by allowing functions to be defined locally within one another.

Evaluation and calculation

- We know that we can understand imperative programs by tracing the effect of executing their statements on the program state.
- We can understand the operation of functional programs by **evaluating** expressions step-by-step (known as **calculation**).

Evaluation and calculation

- We know that we can understand imperative programs by tracing the effect of executing their statements on the program state.
- We can understand the operation of functional programs by **evaluating** expressions step-by-step (known as **calculation**).
- For example, consider the function definition:

`twiceSum x y = 2 * (x + y)`

- We can evaluate an expression such as

`twiceSum 4 (2 + 6)`

by replacing the formal parameters `x` and `y` by the expressions `4` and `(2 + 6)` in the right hand side of the definition, to give:

`2 * (4 + (2 + 6))`

Evaluation and calculation

- We can show a complete calculation of an expression as follows:

twiceSum 4 (2 + 6)

Evaluation and calculation

- We can show a complete calculation of an expression as follows:

twiceSum 4 (2 + 6)

\rightsquigarrow 2 * (4 + (2 + 6))

def of twiceSum

Evaluation and calculation

- We can show a complete calculation of an expression as follows:

twiceSum 4 (2 + 6)

\rightsquigarrow 2 * (4 + (2 + 6))

\rightsquigarrow 2 * (4 + 8)

def of twiceSum
arithmetic

Evaluation and calculation

- We can show a complete calculation of an expression as follows:

twiceSum 4 (2 + 6)

\rightsquigarrow 2 * (4 + (2 + 6))

\rightsquigarrow 2 * (4 + 8)

\rightsquigarrow 2 * 12

def of twiceSum

arithmetic

arithmetic

Evaluation and calculation

- We can show a complete calculation of an expression as follows:

twiceSum 4 (2 + 6)

\rightsquigarrow 2 * (4 + (2 + 6))

\rightsquigarrow 2 * (4 + 8)

\rightsquigarrow 2 * 12

\rightsquigarrow 24

def of twiceSum

arithmetic

arithmetic

arithmetic

Evaluation and calculation

- We can show a complete calculation of an expression as follows:

twiceSum 4 (2 + 6)

\rightsquigarrow 2 * (4 + (2 + 6))

def of twiceSum

\rightsquigarrow 2 * (4 + 8)

arithmetic

\rightsquigarrow 2 * 12

arithmetic

\rightsquigarrow 24

arithmetic

- Note that there are usually alternative ways to perform any calculation (and it doesn't matter which one we choose);

Evaluation and calculation

- We can show a complete calculation of an expression as follows:

twiceSum 4 (2 + 6)

\rightsquigarrow 2 * (4 + (2 + 6))

def of twiceSum

\rightsquigarrow 2 * (4 + 8)

arithmetic

\rightsquigarrow 2 * 12

arithmetic

\rightsquigarrow 24

arithmetic

- Note that there are usually alternative ways to perform any calculation (and it doesn't matter which one we choose); e.g.:

twiceSum 4 (2 + 6)

\rightsquigarrow twiceSum 4 8

arithmetic

\rightsquigarrow 2 * (4 + 8)

def of twiceSum

\rightsquigarrow 2 * 12

arithmetic

\rightsquigarrow 24

arithmetic

Guards

- Guards are Boolean expressions used in function definitions to give alternative results dependent on the parameter values.

Guards

- Guards are Boolean expressions used in function definitions to give alternative results dependent on the parameter values.
- The following function gives the maximum of two Int values:

```
maxVal :: Int -> Int -> Int
```

```
maxVal x y
```

```
  | x >= y
```

```
  | otherwise
```

guards

```
= x
```

```
= y
```

results corresponding
to guards

Guards

- Guards are Boolean expressions used in function definitions to give alternative results dependent on the parameter values.
- The following function gives the maximum of two Int values:

```
maxVal :: Int -> Int -> Int
```

```
maxVal x y
```

```
  | x >= y
```

```
  | otherwise
```

guards

```
    = x
```

```
    = y
```

results corresponding
to guards

- If the first guard ($x \geq y$) evaluates to True, then the result is the corresponding value (x).
- Otherwise, if the first guard is false, the second guard is evaluated, and so on (an otherwise guard always holds).

Guards

- We know from last week that there is an `if...then...else...` construct, which can sometimes be used in place of guards; e.g.,

```
maxVal :: Int -> Int -> Int
maxVal x y
  = if x >= y then x else y
```

Guards

- We know from last week that there is an `if...then...else...` construct, which can sometimes be used in place of guards; e.g.,

```
maxVal :: Int -> Int -> Int
maxVal x y
    = if x >= y then x else y
```

- However, we'll tend to use guards since they more easily allow for multiple cases; for example:

```
maxThree :: Int -> Int -> Int -> Int
maxThree x y z
    | x >= y && x >= z      = x
    | y >= z                = y
    | otherwise            = z
```

Calculation involving guards

- Below is a calculation of an expression involving `maxThree`; the steps in which guards are being evaluated begin with ??:

`maxThree 3 2 5`

Calculation involving guards

- Below is a calculation of an expression involving `maxThree`; the steps in which guards are being evaluated begin with `??`:

`maxThree 3 2 5`

`?? 3 >= 2 && 3 >= 5`

first guard

Calculation involving guards

- Below is a calculation of an expression involving `maxThree`; the steps in which guards are being evaluated begin with `??`:

`maxThree 3 2 5`

`?? 3 >= 2 && 3 >= 5`

first guard

`?? \rightsquigarrow True && 3 >= 5`

def of `>=`

Calculation involving guards

- Below is a calculation of an expression involving `maxThree`; the steps in which guards are being evaluated begin with `??`:

`maxThree 3 2 5`

`?? 3 >= 2 && 3 >= 5`

first guard

`?? \rightsquigarrow True && 3 >= 5`

def of `>=`

`?? \rightsquigarrow True && False`

def of `>=`

Calculation involving guards

- Below is a calculation of an expression involving `maxThree`; the steps in which guards are being evaluated begin with `??`:

`maxThree 3 2 5`

`?? 3 >= 2 && 3 >= 5`

first guard

`?? \rightsquigarrow True && 3 >= 5`

def of `>=`

`?? \rightsquigarrow True && False`

def of `>=`

`?? \rightsquigarrow False`

def of `&&`

Calculation involving guards

- Below is a calculation of an expression involving `maxThree`; the steps in which guards are being evaluated begin with `??`:

`maxThree 3 2 5`

`?? 3 >= 2 && 3 >= 5`

first guard

`?? \rightsquigarrow True && 3 >= 5`

def of `>=`

`?? \rightsquigarrow True && False`

def of `>=`

`?? \rightsquigarrow False`

def of `&&`

`?? 2 >= 5`

second guard

Calculation involving guards

- Below is a calculation of an expression involving `maxThree`; the steps in which guards are being evaluated begin with `??`:

`maxThree 3 2 5`

`?? 3 >= 2 && 3 >= 5`

first guard

`?? \rightsquigarrow True && 3 >= 5`

def of `>=`

`?? \rightsquigarrow True && False`

def of `>=`

`?? \rightsquigarrow False`

def of `&&`

`?? 2 >= 5`

second guard

`?? \rightsquigarrow False`

def of `>=`

Calculation involving guards

- Below is a calculation of an expression involving `maxThree`; the steps in which guards are being evaluated begin with `??`:

`maxThree 3 2 5`

`??` `3 >= 2 && 3 >= 5`

first guard

`??` \rightsquigarrow `True && 3 >= 5`

def of `>=`

`??` \rightsquigarrow `True && False`

def of `>=`

`??` \rightsquigarrow `False`

def of `&&`

`??` `2 >= 5`

second guard

`??` \rightsquigarrow `False`

def of `>=`

`??` `otherwise`

third guard

Calculation involving guards

- Below is a calculation of an expression involving `maxThree`; the steps in which guards are being evaluated begin with `??`:

`maxThree 3 2 5`

<code>??</code>	<u><code>3 >= 2</code></u> <code>&& 3 >= 5</code>	first guard
<code>??</code>	<code>↪ True</code> <code>&& 3 >= 5</code>	def of <code>>=</code>
<code>??</code>	<code>↪ True</code> <code>&& False</code>	def of <code>>=</code>
<code>??</code>	<code>↪ False</code>	def of <code>&&</code>
<code>??</code>	<u><code>2 >= 5</code></u>	second guard
<code>??</code>	<code>↪ False</code>	def of <code>>=</code>
<code>??</code>	<u><code>otherwise</code></u>	third guard
<code>??</code>	<code>↪ True</code>	def of <code>otherwise</code>

Calculation involving guards

- Below is a calculation of an expression involving `maxThree`; the steps in which guards are being evaluated begin with `??`:

`maxThree 3 2 5`

`?? 3 >= 2 && 3 >= 5`

first guard

`?? \rightsquigarrow True && 3 >= 5`

def of `>=`

`?? \rightsquigarrow True && False`

def of `>=`

`?? \rightsquigarrow False`

def of `&&`

`?? 2 >= 5`

second guard

`?? \rightsquigarrow False`

def of `>=`

`?? otherwise`

third guard

`?? \rightsquigarrow True`

def of `otherwise`

`\rightsquigarrow 5`

Local definitions

- Let's consider a “slightly complicated” function definition from Worksheet 1:

```
distance :: Float -> Float -> Float -> Float -> Float
distance x1 y1 x2 y2 = sqrt ((x1-x2)^2 + (y1-y2)^2)
```

- We might want to “break down” the definition's expression to make it easier to read.

Local definitions

- Let's consider a “slightly complicated” function definition from Worksheet 1:

```
distance :: Float -> Float -> Float -> Float -> Float
distance x1 y1 x2 y2 = sqrt ((x1-x2)^2 + (y1-y2)^2)
```

- We might want to “break down” the definition's expression to make it easier to read.
- We can do this using local definitions. These are introduced using the `where` keyword after the expression.
- For example:

```
distance x1 y1 x2 y2 = sqrt (dxSq + dySq)
                        where
                        dxSq = (x1 - x2)^2
                        dySq = (y1 - y2)^2
```

Local definitions

- We see that:
 - the main expression uses the local definitions; and
 - the local definitions use the function's parameters.
- Local definitions can only be used within the functions that they are defined; they are “hidden” from the rest of the program.

Local definitions

- We see that:
 - the main expression uses the local definitions; and
 - the local definitions use the function's parameters.
- Local definitions can only be used within the functions that they are defined; they are “hidden” from the rest of the program.
- We could go a step further with this example:

distance x1 y1 x2 y2 = sqrt (dxSq + dySq)

where

dx = x1 - x2

dy = y1 - y2

dxSq = dx²

dySq = dy²

- Note that the local definitions can appear in any order.

Local definitions

- As another example, consider the function definition:

```
sumPosCubes :: Float -> Float -> Float -> Float
```

```
sumPosCubes x y z = abs (x^3) + abs (y^3) + abs (z^3)
```

which takes the cubes of its parameters, uses `abs` to make them non-negative, and then sums them.

Local definitions

- As another example, consider the function definition:

```
sumPosCubes :: Float -> Float -> Float -> Float
```

```
sumPosCubes x y z = abs (x^3) + abs (y^3) + abs (z^3)
```

which takes the cubes of its parameters, uses `abs` to make them non-negative, and then sums them.

- This is clearly repetitive code, and is maybe better written as:

```
sumPosCubes x y z = posCube x + posCube y + posCube z
```

```
  where
```

```
    posCube a = abs (a ^ 3)
```

- We see that the local definition `posCube` has its own parameter.

Local definitions

- As another example, consider the function definition:

```
sumPosCubes :: Float -> Float -> Float -> Float
```

```
sumPosCubes x y z = abs (x^3) + abs (y^3) + abs (z^3)
```

which takes the cubes of its parameters, uses `abs` to make them non-negative, and then sums them.

- This is clearly repetitive code, and is maybe better written as:

```
sumPosCubes x y z = posCube x + posCube y + posCube z
```

```
where
```

```
posCube a = abs (a ^ 3)
```

- We see that the local definition `posCube` has its own parameter.
- We could have defined `posCube` as a normal (non-local) definition, but it is unlikely to be useful outside of `sumPosCubes`.

Local definitions

- As a final (contrived) example, consider a function that counts how many of its (two) parameters that are multiples of 10.
- This can be written using guards:

```
numMultsOf10 :: Int -> Int -> Int
numMultsOf10 a b
  | multOf10 a && multOf10 b  = 2
  | multOf10 a || multOf10 b  = 1
  | otherwise                 = 0
where
  multOf10 x = mod x 10 == 0
```

- We see that, even with multiple guards, we use a single `where` at the bottom to introduce local definition(s).

Local definitions

- As a final (contrived) example, consider a function that counts how many of its (two) parameters that are multiples of 10.
- This can be written using guards:

```
numMultsOf10 :: Int -> Int -> Int
numMultsOf10 a b
  | multOf10 a && multOf10 b  = 2
  | multOf10 a || multOf10 b  = 1
  | otherwise                 = 0
where
  multOf10 x = mod x 10 == 0
```

- We see that, even with multiple guards, we use a single where at the bottom to introduce local definition(s).
- Q: Is there a better way of doing this (without guards)?