

# MATHFUN Lecture FP4

## Strings, Tuples and Lists

Matthew Poole  
`moodle.port.ac.uk`

School of Computing  
University of Portsmouth

2014/15

# Introduction to Lecture

- The main aim of this lecture is to introduce Haskell's list type.
- Lists are the main data structure in functional programming languages, and correspond to arrays in imperative languages.

# Introduction to Lecture

- The main aim of this lecture is to introduce Haskell's list type.
- Lists are the main data structure in functional programming languages, and correspond to arrays in imperative languages.
- We'll first introduce:
  - characters;
  - strings, which are lists of characters;
  - tuples.

# Introduction to Lecture

- The main aim of this lecture is to introduce Haskell's list type.
- Lists are the main data structure in functional programming languages, and correspond to arrays in imperative languages.
- We'll first introduce:
  - characters;
  - strings, which are lists of characters;
  - tuples.
- We'll use Haskell's standard list functions to illustrate **polymorphism** in functional programming.

# Introduction to Lecture

- The main aim of this lecture is to introduce Haskell's list type.
- Lists are the main data structure in functional programming languages, and correspond to arrays in imperative languages.
- We'll first introduce:
  - characters;
  - strings, which are lists of characters;
  - tuples.
- We'll use Haskell's standard list functions to illustrate **polymorphism** in functional programming.
- This lecture is supported by Chapter 5 of Thompson's book.

# Introduction to Lecture

- The main aim of this lecture is to introduce Haskell's list type.
- Lists are the main data structure in functional programming languages, and correspond to arrays in imperative languages.
- We'll first introduce:
  - characters;
  - strings, which are lists of characters;
  - tuples.
- We'll use Haskell's standard list functions to illustrate **polymorphism** in functional programming.
- This lecture is supported by Chapter 5 of Thompson's book.
- In the following lecture we look at how to write list-processing functions using recursion.

# Characters and Strings

- We begin by noting that Haskell has Char and String types.
- We use single quotes for chars and double quotes for strings:

```
ghci>
```

# Characters and Strings

- We begin by noting that Haskell has Char and String types.
- We use single quotes for chars and double quotes for strings:

```
ghci> :type 'a'
```



# Characters and Strings

- We begin by noting that Haskell has Char and String types.
- We use single quotes for chars and double quotes for strings:

```
ghci> :type 'a'  
'a' :: Char  
ghci>
```

# Characters and Strings

- We begin by noting that Haskell has Char and String types.
- We use single quotes for chars and double quotes for strings:

```
ghci> :type 'a'
```

```
'a' :: Char
```

```
ghci> :type "Sam"
```

# Characters and Strings

- We begin by noting that Haskell has Char and String types.
- We use single quotes for chars and double quotes for strings:

```
ghci> :type 'a'
```

```
'a' :: Char
```

```
ghci> :type "Sam"
```

```
"Sam" :: String
```

# Characters and Strings

- We begin by noting that Haskell has Char and String types.
- We use single quotes for chars and double quotes for strings:

```
ghci> :type 'a'
```

```
'a' :: Char
```

```
ghci> :type "Sam"
```

```
"Sam" :: String
```

- The Char module defines some useful functions on chars:

```
ghci>
```

# Characters and Strings

- We begin by noting that Haskell has Char and String types.
- We use single quotes for chars and double quotes for strings:

```
ghci> :type 'a'
```

```
'a' :: Char
```

```
ghci> :type "Sam"
```

```
"Sam" :: String
```

- The Char module defines some useful functions on chars:

```
ghci> :m + Data.Char
```

# Characters and Strings

- We begin by noting that Haskell has Char and String types.
- We use single quotes for chars and double quotes for strings:

```
ghci> :type 'a'
```

```
'a' :: Char
```

```
ghci> :type "Sam"
```

```
"Sam" :: String
```

- The Char module defines some useful functions on chars:

```
ghci> :m + Data.Char
```

```
ghci>
```

# Characters and Strings

- We begin by noting that Haskell has Char and String types.
- We use single quotes for chars and double quotes for strings:

```
ghci> :type 'a'
```

```
'a' :: Char
```

```
ghci> :type "Sam"
```

```
"Sam" :: String
```

- The Char module defines some useful functions on chars:

```
ghci> :m + Data.Char
```

```
ghci> toUpper 'a'
```

# Characters and Strings

- We begin by noting that Haskell has Char and String types.
- We use single quotes for chars and double quotes for strings:

```
ghci> :type 'a'
```

```
'a' :: Char
```

```
ghci> :type "Sam"
```

```
"Sam" :: String
```

- The Char module defines some useful functions on chars:

```
ghci> :m + Data.Char
```

```
ghci> toUpper 'a'
```

```
'A'
```

```
ghci>
```



# Characters and Strings

- We begin by noting that Haskell has Char and String types.
- We use single quotes for chars and double quotes for strings:

```
ghci> :type 'a'
```

```
'a' :: Char
```

```
ghci> :type "Sam"
```

```
"Sam" :: String
```

- The Char module defines some useful functions on chars:

```
ghci> :m + Data.Char
```

```
ghci> toUpper 'a'
```

```
'A'
```

```
ghci> isDigit 'a'
```

# Characters and Strings

- We begin by noting that Haskell has Char and String types.
- We use single quotes for chars and double quotes for strings:

```
ghci> :type 'a'
```

```
'a' :: Char
```

```
ghci> :type "Sam"
```

```
"Sam" :: String
```

- The Char module defines some useful functions on chars:

```
ghci> :m + Data.Char
```

```
ghci> toUpper 'a'
```

```
'A'
```

```
ghci> isDigit 'a'
```

```
False
```

# Tuples

- Tuples are used to **combine** pieces of data into one.

# Tuples

- Tuples are used to **combine** pieces of data into one.
- Suppose we're writing a program to analyse student marks; we might combine the student names and marks into **tuples**:

("Steve",46)            or            ("Sam",62)

# Tuples

- Tuples are used to **combine** pieces of data into one.
- Suppose we're writing a program to analyse student marks; we might combine the student names and marks into **tuples**:

("Steve",46)            or            ("Sam",62)

- The type of these values is the tuple type (String,Int).

# Tuples

- Tuples are used to **combine** pieces of data into one.
- Suppose we're writing a program to analyse student marks; we might combine the student names and marks into **tuples**:

("Steve",46)            or            ("Sam",62)

- The type of these values is the tuple type (String,Int).
- An example function definition that processes such tuples is:

```
betterStu :: (String,Int) -> (String,Int) -> String
betterStu (s1,m1) (s2,m2)
  | m1 >= m2      = s1
  | otherwise     = s2
```

# Tuples

- Tuples are used to **combine** pieces of data into one.
- Suppose we're writing a program to analyse student marks; we might combine the student names and marks into **tuples**:

("Steve",46)            or            ("Sam",62)

- The type of these values is the tuple type (String,Int).
- An example function definition that processes such tuples is:

```
betterStu :: (String,Int) -> (String,Int) -> String
betterStu (s1,m1) (s2,m2)
  | m1 >= m2      = s1
  | otherwise     = s2
```

- For example,

```
ghci> betterStu ("Jim",45) ("Fred",87)
"Fred"
```

# Tuples

- It's often a good idea to define a **type synonym**:  
    `type StudentMark = (String, Int)`  
and use `StudentMark` in place of `(String,Int)`.



# Tuples

- It's often a good idea to define a **type synonym**:

```
type StudentMark = (String, Int)
```

and use StudentMark in place of (String,Int). We re-write:

```
betterStu :: StudentMark -> StudentMark -> String
```

```
betterStu (s1,m1) (s2,m2)
```

```
    | m1 >= m2           = s1
```

```
    | otherwise          = s2
```

# Tuples

- It's often a good idea to define a **type synonym**:

```
type StudentMark = (String, Int)
```

and use StudentMark in place of (String,Int). We re-write:

```
betterStu :: StudentMark -> StudentMark -> String
betterStu (s1,m1) (s2,m2)
  | m1 >= m2      = s1
  | otherwise     = s2
```

- Tuples can be used in the result type of a function to enable it to return more than one value; e.g.:

```
minAndMax :: Int -> Int -> (Int,Int)
minAndMax x y
  | x <= y      = (x,y)
  | otherwise   = (y,x)
```

# Lists

- Lists are used to store any number of data values of the same type; they are the main data structure in Haskell.
- For example:

`[12, 64, -92, 85, 12]`

is a list of integers, and

`["This", "is", "a", "list"]`

is a list of strings.

# Lists

- Lists are used to store any number of data values of the same type; they are the main data structure in Haskell.
- For example:  

```
[12, 64, -92, 85, 12]
```

is a list of integers, and  

```
["This", "is", "a", "list"]
```

is a list of strings.
- For any type  $t$ , we denote the type of lists of elements from  $t$  by  $[t]$ . For example:  

```
ghci> :type [True, False, False]  
[True, False, False] :: [Bool]
```
- The empty list `[]` is an element of any list type.

# Strings as lists of Chars

- Strings in Haskell are simply lists of characters: the type `String` is declared as:

```
type String = [Char]
```

# Strings as lists of Chars

- Strings in Haskell are simply lists of characters: the type `String` is declared as:

```
type String = [Char]
```

- Therefore, the following two expressions are the same:

```
['h', 'e', 'l', 'l', 'o']      "hello"
```

# Strings as lists of Chars

- Strings in Haskell are simply lists of characters: the type `String` is declared as:

```
type String = [Char]
```

- Therefore, the following two expressions are the same:

```
['h', 'e', 'l', 'l', 'o']      "hello"
```

- The list operations that we see later (e.g. for concatenating lists) thus also apply to strings.

# More on types

- What are the types of the following expressions?

```
ghci> :type ["This", "is", "a", "sentence"]
```



# More on types

- What are the types of the following expressions?

```
ghci> :type ["This", "is", "a", "sentence"]  
["This","is","a","sentence"] :: [[Char]]  
ghci>
```

# More on types

- What are the types of the following expressions?

```
ghci> :type ["This", "is", "a", "sentence"]  
["This","is","a","sentence"] :: [[Char]]  
ghci> :type ("Hello", [True, False, True])
```

# More on types

- What are the types of the following expressions?

```
ghci> :type ["This", "is", "a", "sentence"]  
["This","is","a","sentence"] :: [[Char]]  
ghci> :type ("Hello", [True, False, True])  
("Hello",[True,False,True]) :: ([Char],[Bool])  
ghci>
```

# More on types

- What are the types of the following expressions?

```
ghci> :type ["This", "is", "a", "sentence"]
["This","is","a","sentence"] :: [[Char]]
ghci> :type ("Hello", [True, False, True])
("Hello",[True,False,True]) :: ([Char],[Bool])
ghci> :type 3
```

# More on types

- What are the types of the following expressions?

```
ghci> :type ["This", "is", "a", "sentence"]
["This","is","a","sentence"] :: [[Char]]
ghci> :type ("Hello", [True, False, True])
("Hello",[True,False,True]) :: ([Char],[Bool])
ghci> :type 3
3 :: Num a => a
ghci>
```

# More on types

- What are the types of the following expressions?

```
ghci> :type ["This", "is", "a", "sentence"]
["This","is","a","sentence"] :: [[Char]]
ghci> :type ("Hello", [True, False, True])
("Hello",[True,False,True]) :: ([Char],[Bool])
ghci> :type 3
3 :: Num a => a
ghci> :type [4, 5, 7]
```

# More on types

- What are the types of the following expressions?

```
ghci> :type ["This", "is", "a", "sentence"]
["This","is","a","sentence"] :: [[Char]]
ghci> :type ("Hello", [True, False, True])
("Hello",[True,False,True]) :: ([Char],[Bool])
ghci> :type 3
3 :: Num a => a
ghci> :type [4, 5, 7]
[4,5,7] :: Num a => [a]
ghci>
```

# More on types

- What are the types of the following expressions?

```
ghci> :type ["This", "is", "a", "sentence"]
["This","is","a","sentence"] :: [[Char]]
ghci> :type ("Hello", [True, False, True])
("Hello",[True,False,True]) :: ([Char],[Bool])
ghci> :type 3
3 :: Num a => a
ghci> :type [4, 5, 7]
[4,5,7] :: Num a => [a]
ghci> :type [(7, "Yes"), (4, "No")]
```



# More on types

- What are the types of the following expressions?

```
ghci> :type ["This", "is", "a", "sentence"]
["This","is","a","sentence"] :: [[Char]]
ghci> :type ("Hello", [True, False, True])
("Hello",[True,False,True]) :: ([Char],[Bool])
ghci> :type 3
3 :: Num a => a
ghci> :type [4, 5, 7]
[4,5,7] :: Num a => [a]
ghci> :type [(7, "Yes"), (4, "No")]
[(7,"Yes"),(4,"No")] :: Num a => [(a,[Char])]
ghci>
```

# More on types

- What are the types of the following expressions?

```
ghci> :type ["This", "is", "a", "sentence"]
["This","is","a","sentence"] :: [[Char]]
ghci> :type ("Hello", [True, False, True])
("Hello",[True,False,True]) :: ([Char],[Bool])
ghci> :type 3
3 :: Num a => a
ghci> :type [4, 5, 7]
[4,5,7] :: Num a => [a]
ghci> :type [(7, "Yes"), (4, "No")]
[(7,"Yes"),(4,"No")] :: Num a => [(a,[Char])]
ghci> :type []
```

# More on types

- What are the types of the following expressions?

```
ghci> :type ["This", "is", "a", "sentence"]
["This","is","a","sentence"] :: [[Char]]
ghci> :type ("Hello", [True, False, True])
("Hello",[True,False,True]) :: ([Char],[Bool])
ghci> :type 3
3 :: Num a => a
ghci> :type [4, 5, 7]
[4,5,7] :: Num a => [a]
ghci> :type [(7, "Yes"), (4, "No")]
[(7,"Yes"),(4,"No")] :: Num a => [(a,[Char])]
ghci> :type []
[] :: [a]
```

# Lists from ranges

- We can form lists of numbers/strings using a range format:  
 $[n \dots m]$  gives the list  $[n, n+1, \dots, m]$

# Lists from ranges

- We can form lists of numbers/strings using a range format:

`[n .. m]` gives the list `[n, n+1, ..., , m]`

- For example:

`[3 .. 9]` = `[3,4,5,6,7,8,9]`

`[3.1 .. 9]` = `[3.1,4.1,5.1,6.1,7.1,8.1,9.1]`

`['a' .. 'z']` = `"abcdefghijklmnopqrstuvwxyz"`

# Lists from ranges

- We can form lists of numbers/strings using a range format:  
 $[n \dots m]$  gives the list  $[n, n+1, \dots, m]$
- For example:  
 $[3 \dots 9] = [3, 4, 5, 6, 7, 8, 9]$   
 $[3.1 \dots 9] = [3.1, 4.1, 5.1, 6.1, 7.1, 8.1, 9.1]$   
 $['a' \dots 'z'] = "abcdefghijklmnopqrstuvwxyz"$
- We can also add an argument to give steps different from 1:  
 $[3, 5 \dots 15] = [3, 5, 7, 9, 11, 13, 15]$   
 $[0, 0.1 \dots 0.5] = [0.0, 0.1, 0.2, 0.3, 0.4, 0.5]$

# List comprehensions

- Suppose we define a list `aList` as:

```
aList = [1, 2, 3, 4, 5]
```

- Then the **list comprehension**:

```
[ 2*i | i <- aList ]
```

will have the value:

```
[2, 4, 6, 8, 10]
```

# List comprehensions

- Suppose we define a list `aList` as:

```
aList = [1, 2, 3, 4, 5]
```

- Then the **list comprehension**:

```
[ 2*i | i <- aList ]
```

will have the value:

```
[2, 4, 6, 8, 10]
```

- We read this as: “take all  $2*i$  where  $i$  comes from `aList`.”
- (The `<-` is meant to resemble the set member symbol  $\in$ .)



# List comprehensions

- Suppose we define a list `aList` as:

```
aList = [1, 2, 3, 4, 5]
```

- Then the **list comprehension**:

```
[ 2*i | i <- aList ]
```

will have the value:

```
[2, 4, 6, 8, 10]
```

- We read this as: “take all  $2*i$  where  $i$  comes from `aList`.”
- (The `<-` is meant to resemble the set member symbol  $\in$ .)
- List comprehensions are a powerful feature (almost) unique to functional programming languages.
- (A few imperative languages (e.g. Python) have some functional programming facilities including list comprehensions.)

# List comprehensions

- Let's look at some further examples; suppose here that the list `aList` is defined as:

```
aList = [2,3,6,9,4,7]
```

# List comprehensions

- Let's look at some further examples; suppose here that the list `aList` is defined as:

```
aList = [2,3,6,9,4,7]
```

- Then:

```
ghci> [ mod i 2 == 0 | i <- aList ]  
[True,False,True,False,True,False]
```

# List comprehensions

- Let's look at some further examples; suppose here that the list `aList` is defined as:

```
aList = [2,3,6,9,4,7]
```

- Then:

```
ghci> [ mod i 2 == 0 | i <- aList ]  
[True,False,True,False,True,False]
```

- We can add a **test** at the end of the **generator** `i <- aList`:

```
ghci> [ i*2 | i <- aList, i < 5 ]  
[4,6,8]
```

- Here, the generator/test has given all the values in `aList` that are less than 5; i.e. 2, 3, 4.

# List comprehensions

- Let's look at some further examples; suppose here that the list `aList` is defined as:

```
aList = [2,3,6,9,4,7]
```

- Then:

```
ghci> [ mod i 2 == 0 | i <- aList ]  
[True,False,True,False,True,False]
```

- We can add a **test** at the end of the **generator** `i <- aList`:

```
ghci> [ i*2 | i <- aList, i < 5 ]  
[4,6,8]
```

- Here, the generator/test has given all the values in `aList` that are less than 5; i.e. 2, 3, 4.

# List comprehensions

- Instead of a single variable, we can use a **pattern** on the left hand side of the `<-`.
- For example, consider the definition:

```
addPairs :: [(Int,Int)] -> [Int]
```

```
addPairs pairList = [ i+j | (i,j) <- pairList ]
```

will choose all pairs in `pairList` and add their components;

# List comprehensions

- Instead of a single variable, we can use a **pattern** on the left hand side of the `<-`.
- For example, consider the definition:

```
addPairs :: [(Int,Int)] -> [Int]
```

```
addPairs pairList = [ i+j | (i,j) <- pairList ]
```

will choose all pairs in `pairList` and add their components; e.g.

```
ghci> addPairs [(1,2), (4,8), (6,3)]  
[3,12,9]
```

# List comprehensions

- Instead of a single variable, we can use a **pattern** on the left hand side of the `<-`.
- For example, consider the definition:

```
addPairs :: [(Int,Int)] -> [Int]
```

```
addPairs pairList = [ i+j | (i,j) <- pairList ]
```

will choose all pairs in `pairList` and add their components; e.g.

```
ghci> addPairs [(1,2), (4,8), (6,3)]  
[3,12,9]
```

- For some final examples, recall the type synonym:

```
type StudentMark = (String, Int)
```

for student name/mark data such as ("Steve", 46).



# List comprehensions

- Instead of a single variable, we can use a **pattern** on the left hand side of the `<-`.
- For example, consider the definition:

```
addPairs :: [(Int,Int)] -> [Int]
```

```
addPairs pairList = [ i+j | (i,j) <- pairList ]
```

will choose all pairs in `pairList` and add their components; e.g.

```
ghci> addPairs [(1,2), (4,8), (6,3)]  
[3,12,9]
```

- For some final examples, recall the type synonym:

```
type StudentMark = (String, Int)
```

for student name/mark data such as `("Steve", 46)`.

- An example of the type `[StudentMark]` of name/mark lists is:

```
[("Sam", 67), ("Kate", 35), ("Jill", 75)]
```

# List comprehensions

- The following definition will generate a list of just the marks:

```
marks :: [StudentMark] -> [Int]
marks stMarks = [ mk | (st,mk) <- stMarks ]
```

# List comprehensions

- The following definition will generate a list of just the marks:

```
marks :: [StudentMark] -> [Int]
marks stMarks = [ mk | (st,mk) <- stMarks ]
```

- For example,

```
ghci> marks [("Sam",67), ("Kate",35), ("Jill",75)]
[67,35,75]
```

# List comprehensions

- The following definition will generate a list of just the marks:

```
marks :: [StudentMark] -> [Int]
marks stMarks = [ mk | (st,mk) <- stMarks ]
```

- For example,

```
ghci> marks [("Sam",67), ("Kate",35), ("Jill",75)]
[67,35,75]
```

- The following gives the names of students who have passed:

```
pass :: [StudentMark] -> [String]
pass stMarks = [ st | (st,mk) <- stMarks, mk >= 40 ]
```

# List comprehensions

- The following definition will generate a list of just the marks:

```
marks :: [StudentMark] -> [Int]
marks stMarks = [ mk | (st,mk) <- stMarks ]
```

- For example,

```
ghci> marks [("Sam",67), ("Kate",35), ("Jill",75)]
[67,35,75]
```

- The following gives the names of students who have passed:

```
pass :: [StudentMark] -> [String]
pass stMarks = [ st | (st,mk) <- stMarks, mk >= 40 ]
```

- For example:

```
ghci> pass [("Sam", 67), ("Kate", 35), ("Jill", 75)]
["Sam","Jill"]
```

# Polymorphic functions

- We now look at some list functions defined in the Prelude.
- Doing so also provides a good opportunity to introduce the concept of **polymorphism**.

# Polymorphic functions

- We now look at some list functions defined in the Prelude.
- Doing so also provides a good opportunity to introduce the concept of **polymorphism**.
- Consider first the `length` function, which gives the number of elements in a list (i.e. it returns an `Int`).

# Polymorphic functions

- We now look at some list functions defined in the Prelude.
- Doing so also provides a good opportunity to introduce the concept of **polymorphism**.
- Consider first the `length` function, which gives the number of elements in a list (i.e. it returns an `Int`).
- This function works for **any** type of list; we might say:  
`length :: [String] -> Int`  
`length :: [Bool] -> Int`
- We call a function that has many types a **polymorphic** function.



# Polymorphic functions

- We now look at some list functions defined in the Prelude.
- Doing so also provides a good opportunity to introduce the concept of **polymorphism**.
- Consider first the `length` function, which gives the number of elements in a list (i.e. it returns an `Int`).
- This function works for **any** type of list; we might say:  
$$\text{length} :: [\text{String}] \rightarrow \text{Int}$$
$$\text{length} :: [\text{Bool}] \rightarrow \text{Int}$$
- We call a function that has many types a **polymorphic** function.
- The actual type of `length` is given as:  
$$\text{length} :: [a] \rightarrow \text{Int}$$
- Here `a` is a **type variable** that stands for an **arbitrary type** (i.e. its possible values are types).

# Polymorphic functions

- (By convention,  $a$ ,  $b$ ,  $c$ , ... are used as type variables.)
- Types  $[String] \rightarrow Int$  and  $[Bool] \rightarrow Int$  are **instances** of type  $[a] \rightarrow Int$  (they are found by replacing  $a$  with a type).
- $[a] \rightarrow Int$  is known as the **most general type** for `length`.

# Polymorphic functions

- (By convention,  $a$ ,  $b$ ,  $c$ , ... are used as type variables.)
- Types  $[String] \rightarrow Int$  and  $[Bool] \rightarrow Int$  are **instances** of type  $[a] \rightarrow Int$  (they are found by replacing  $a$  with a type).
- $[a] \rightarrow Int$  is known as the **most general type** for `length`.
- We can define our own polymorphic functions; the easiest way to do this is to omit a type declaration.

# Polymorphic functions

- (By convention,  $a$ ,  $b$ ,  $c$ , ... are used as type variables.)
- Types  $[String] \rightarrow Int$  and  $[Bool] \rightarrow Int$  are **instances** of type  $[a] \rightarrow Int$  (they are found by replacing  $a$  with a type).
- $[a] \rightarrow Int$  is known as the **most general type** for `length`.
- We can define our own polymorphic functions; the easiest way to do this is to omit a type declaration.
- Supposing, for example, we define:  
$$\text{square } n = n * n$$
- Haskell will infer the most general type by looking at the structure of the function.

# Polymorphic functions

- (By convention,  $a$ ,  $b$ ,  $c$ , ... are used as type variables.)
- Types  $[String] \rightarrow Int$  and  $[Bool] \rightarrow Int$  are **instances** of type  $[a] \rightarrow Int$  (they are found by replacing  $a$  with a type).
- $[a] \rightarrow Int$  is known as the **most general type** for `length`.
- We can define our own polymorphic functions; the easiest way to do this is to omit a type declaration.

- Supposing, for example, we define:

```
square n = n * n
```

- Haskell will infer the most general type by looking at the structure of the function. Here:

```
square :: Num a => a -> a
```

says that the type is  $a \rightarrow a$  where  $a$  can be any **numeric type**.

# List functions

- Let's try `length` and a few of the Prelude's list operators:  
`ghci>`

# List functions

- Let's try `length` and a few of the Prelude's list operators:

```
ghci> length "hello"
```

# List functions

- Let's try `length` and a few of the Prelude's list operators:

```
ghci> length "hello"
```

```
5
```



# List functions

- Let's try `length` and a few of the Prelude's list operators:

```
ghci> length "hello"
```

```
5
```

- The most used operation is `:` which adds an element to a list:

```
ghci>
```

# List functions

- Let's try `length` and a few of the Prelude's list operators:

```
ghci> length "hello"
```

```
5
```

- The most used operation is `:` which adds an element to a list:

```
ghci> :type (:)
```

# List functions

- Let's try `length` and a few of the Prelude's list operators:

```
ghci> length "hello"
```

```
5
```

- The most used operation is `:` which adds an element to a list:

```
ghci> :type (:)
```

```
(:) :: a -> [a] -> [a]
```

```
ghci>
```

# List functions

- Let's try `length` and a few of the Prelude's list operators:

```
ghci> length "hello"
```

```
5
```

- The most used operation is `:` which adds an element to a list:

```
ghci> :type (:)
(:) :: a -> [a] -> [a]
```

```
ghci> 3:[5, 7, 2]
```

# List functions

- Let's try `length` and a few of the Prelude's list operators:

```
ghci> length "hello"
```

```
5
```

- The most used operation is `:` which adds an element to a list:

```
ghci> :type (:)
(:) :: a -> [a] -> [a]
```

```
(:) :: a -> [a] -> [a]
```

```
ghci> 3:[5, 7, 2]
```

```
[3,5,7,2]
```

# List functions

- Let's try `length` and a few of the Prelude's list operators:

```
ghci> length "hello"  
5
```

- The most used operation is `:` which adds an element to a list:

```
ghci> :type (:)  
(:) :: a -> [a] -> [a]  
ghci> 3:[5, 7, 2]  
[3,5,7,2]
```

- The `++` operator joins two lists together, and `!!` returns an element at a given position. (Question: what are their types?)

```
ghci>
```

# List functions

- Let's try `length` and a few of the Prelude's list operators:

```
ghci> length "hello"  
5
```

- The most used operation is `:` which adds an element to a list:

```
ghci> :type (:)  
(:) :: a -> [a] -> [a]  
ghci> 3:[5, 7, 2]  
[3,5,7,2]
```

- The `++` operator joins two lists together, and `!!` returns an element at a given position. (Question: what are their types?)

```
ghci> "hello" ++ "there"
```

# List functions

- Let's try `length` and a few of the Prelude's list operators:

```
ghci> length "hello"  
5
```

- The most used operation is `:` which adds an element to a list:

```
ghci> :type (:)  
(:) :: a -> [a] -> [a]  
ghci> 3:[5, 7, 2]  
[3,5,7,2]
```

- The `++` operator joins two lists together, and `!!` returns an element at a given position. (Question: what are their types?)

```
ghci> "hello" ++ "there"  
"hellothere"  
ghci>
```



# List functions

- Let's try `length` and a few of the Prelude's list operators:

```
ghci> length "hello"  
5
```

- The most used operation is `:` which adds an element to a list:

```
ghci> :type (:)  
(:) :: a -> [a] -> [a]  
ghci> 3:[5, 7, 2]  
[3,5,7,2]
```

- The `++` operator joins two lists together, and `!!` returns an element at a given position. (Question: what are their types?)

```
ghci> "hello" ++ "there"  
"hellothere"  
ghci> [5, 7, 8, 4] !! 2  
8
```