

## 1. [Binary message.](#)

message structure: [header, user\_data, tail]

header =

byte 1	byte 2	byte 3	byte 4
msg_size LSB	msg_size MSB	flags 8bit	cmdID 8bit

message size (**msg\_size**) includes size of header, user\_data and tail.

**cmdID**=0x00 is special echo command and should not be used.

**flags:**

bit 8	bit 7	bit 6	bit 5
reserved	reserved	reserved	reserved

bit 4	bit 3	bit 2	bit 1
reserved	INTEGRITY_STAMP	SUPPRESS_REPLY_HEADER	EXTENDED_HEADER

EXTENDED\_HEADER : should be 0 for now.

SUPPRESS\_REPLY\_HEADER:

if 0:

reply will include header: [header, data]. this is recommended option.

if 1:

no header inserted in reply. reply structure: [data]

INTEGRITY\_STAMP:

if 0:

tail will not include integrity stamp.

if 1:

tail will include 4 bytes to check message integrity: 0x1a 0x2a 0x3a 0x4a

## 2. [Reply](#)

reply syntax: [header, data]

header =

byte 1	byte 2	byte 3	byte 4
msg_size LSB	msg_size MSB	0x00	replyStatus

message size (**msg\_size**) includes size of header and data.

replyStatus :

0x00 - NO ERROR

0x01 - command not found

0x02 - test of integrity stamp failed

0x03 - message length is too long