

Tailwind + DaisyUI Layout & Component System (Angular-ready)

A copy-pasteable reference for a resilient app shell, layout primitives, reusable components, and semantic color usage. Built to scale with dynamic content—no custom CSS, no JS logic—just Tailwind + DaisyUI classes.

Conventions used in snippets - Semantic elements (`header`, `nav`, `aside`, `main`, `section`, `footer`). - DaisyUI tokens (`primary`, `secondary`, `accent`, `neutral`, `info`, `success`, `warning`, `error`, `base-*`). - Accessible attributes (`aria-*`, `role` hints). - Works with any DaisyUI theme.

1) Enhanced Shell/Layout Architecture

1.1 App Shell (Drawer Sidebar + Topbar + Flexible Main)

```
<!-- App Shell: Drawer + Topbar + Responsive Sidebar -->
<div class="drawer lg:drawer-open min-h-screen bg-base-200">
  <!-- Drawer toggle for small screens -->
  <input id="app-drawer" type="checkbox" class="drawer-toggle" aria-
label="Open navigation" />

  <div class="drawer-content flex flex-col min-h-screen">
    <!-- Topbar -->
    <header class="navbar bg-base-100 shadow-sm sticky top-0 z-20">
      <div class="flex-none lg:hidden">
        <label for="app-drawer" class="btn btn-ghost" aria-label="Toggle
menu" aria-controls="app-sidebar" aria-expanded="false">
          <!-- DaisyUI icon placeholder -->
          <span class="i-[heroicons-bars-3]">≡</span>
        </label>
      </div>
      <div class="flex-1">
        <a class="btn btn-ghost text-xl" aria-label="Home">AppName</a>
      </div>
      <nav class="flex-none">
        <ul class="menu menu-horizontal px-2 hidden md:flex">
          <li><a class="hover:text-primary">Docs</a></li>
          <li><a class="hover:text-primary">Support</a></li>
        </ul>
        <div class="dropdown dropdown-end">
          <div tabindex="0" role="button" class="btn btn-ghost">Profile</div>
          <ul tabindex="0" class="menu dropdown-content bg-base-100 rounded-
box mt-2 w-56 p-2 shadow">
            <li><a>Settings</a></li>
          </ul>
        </div>
      </nav>
    </header>
  </div>
</div>
```

```

        <li><a>Logout</a></li>
    </ul>
</div>
</nav>
</header>

<!-- Main area: grows, scrolls, and adapts to dynamic content -->
<main class="flex-1">
    <!-- Container strategy: choose one of the patterns in §2.2 -->
    <div class="mx-auto w-full max-w-screen-2xl p-4 sm:p-6 lg:p-8">
        <!-- Page header -->
        <div class="breadcrumbs text-sm mb-4">
            <ul>
                <li><a>Home</a></li>
                <li><a>Section</a></li>
                <li>Current Page</li>
            </ul>
        </div>

        <!-- Page title & actions -->
        <div class="flex flex-wrap items-center gap-3 justify-between mb-4">
            <h1 class="text-2xl lg:text-3xl font-semibold">Page Title</h1>
            <div class="flex flex-wrap gap-2">
                <button class="btn btn-outline">Secondary</button>
                <button class="btn btn-primary">Primary action</button>
            </div>
        </div>

        <!-- Content grid that won't break when items grow -->
        <section class="grid gap-4 sm:gap-6 lg:gap-8 grid-cols-1 xl:grid-
cols-3">
            <!-- Main column (stretches) -->
            <div class="xl:col-span-2 space-y-4 sm:space-y-6">
                <article class="card bg-base-100 shadow">
                    <div class="card-body">
                        <h2 class="card-title">Primary content block</h2>
                        <p>Content grows naturally. Use <code>prose</code> for rich
text.</p>
                    </div>
                </article>
                <article class="card bg-base-100 shadow">
                    <div class="card-body">
                        <h3 class="card-title">Another block</h3>
                        <div class="overflow-auto">
                            <table class="table">
                                <thead>
                                    <tr><th>Col</th><th>Col</th><th>Col</th></tr>
                                </thead>
                                <tbody>
                                    <!-- Rows ... -->
                                </tbody>
                            </table>
                        </div>
                    </div>
                </article>
            </div>
        </section>
    </div>
</main>

```

```

        </table>
      </div>
    </div>
  </article>
</div>

<!-- Aside column (fixed width feel via min/max, still responsive)
-->
<aside class="space-y-4 sm:space-y-6" aria-label="Complementary">
  <div class="card bg-base-100 shadow">
    <div class="card-body">
      <h3 class="card-title">Summary</h3>
      <p class="text-sm text-base-content/70">Key metrics and quick
info.</p>
    </div>
  </div>
  <div class="card bg-base-100 shadow">
    <div class="card-body">
      <h3 class="card-title">Filters</h3>
      <div class="form-control gap-2">
        <input type="text" placeholder="Search" class="input input-
bordered" />
        <button class="btn btn-primary">Apply</button>
      </div>
    </div>
  </div>
</aside>
</section>

<!-- Angular hook (if using Angular router) -->
<!-- <router-outlet></router-outlet> -->
</div>
</main>

<!-- Footer stays at bottom due to flex layout -->
<footer class="bg-base-100 border-t border-base-300">
  <div class="mx-auto w-full max-w-screen-2xl p-4 sm:p-6">© 2025
AppName</div>
</footer>
</div>

<!-- Sidebar -->
<div class="drawer-side z-30 id="app-sidebar">
  <label for="app-drawer" aria-label="close sidebar" class="drawer-
overlay"></label>
  <aside class="w-72 bg-base-100 border-r border-base-300 h-full flex flex-
col">
    <div class="p-4 border-b border-base-300">
      <span class="font-bold">Navigation</span>
    </div>
    <nav class="menu p-2 flex-1 overflow-y-auto">

```

```

<ul>
  <li><a class="active">Dashboard</a></li>
  <li>
    <details open>
      <summary>Management</summary>
      <ul>
        <li><a>Users</a></li>
        <li><a>Classes</a></li>
        <li><a>Calendar</a></li>
      </ul>
    </details>
  </li>
  <li><a>Reports</a></li>
  <li><a>Settings</a></li>
</ul>
</nav>
<div class="p-4 border-t border-base-300">
  <div class="alert alert-info">
    <span>Tip: Press <kbd>⌘</kbd><kbd>K</kbd> to search</span>
  </div>
</div>
</aside>
</div>
</div>

```

Why this works - `min-h-screen` + `flex flex-col` ensures footer stays at bottom and main grows. - Content uses a **constrained container** (`max-w-screen-2xl`) with responsive padding. - Sidebar is responsive with DaisyUI `drawer`; no JS needed. - Main grid separates a flexible content column and a complementary aside.

1.2 Shell Variants

- **Centered column:** replace grid with `max-w-3xl mx-auto space-y-6` when pages are form-heavy.
- **Full-width data views:** set container to `max-w-none` and use `overflow-auto` on inner cards/tables.
- **Sectioned apps:** add a secondary sub-nav below topbar using `tabs tabs-boxed`.

2) Layout System Documentation

2.1 Responsive Grid & Flex Patterns

A) Two-column (content + aside)

```

<section class="grid gap-6 lg:grid-cols-[1fr_24rem]">
  <div class="space-y-6">...</div>

```

```
<aside class="space-y-6">...</aside>
</section>
```

- Uses CSS grid with an intrinsic fixed-fee aside (24rem) that collapses to 1col on small screens.

B) Equal cards grid

```
<div class="grid gap-4 sm:grid-cols-2 xl:grid-cols-3 2xl:grid-cols-4"> ...cards...
</div>
```

- Cards grow/shrink automatically without hard heights.

C) Split header + sticky actions

```
<div class="flex flex-wrap items-start justify-between gap-3">
  <h1 class="text-2xl font-semibold">Title</h1>
  <div class="sticky top-16 md:top-20 flex gap-2"> <!-- below navbar -->
    <button class="btn">Cancel</button>
    <button class="btn btn-primary">Save</button>
  </div>
</div>
```

- Sticky respects topbar height via top-* utilities.

D) Media/object layout

```
<article class="flex flex-col sm:flex-row gap-4">
  <div class="avatar"><div class="w-24 rounded"><img alt="" /></div></div>
  <div class="flex-1 space-y-2"> ... </div>
</article>
```

2.2 Container Sizing Strategies

- **Fixed (centered):** container mx-auto px-4 sm:px-6 lg:px-8 (Tailwind container plugin if enabled) or mx-auto w-full max-w-3xl px-4 sm:px-6 lg:px-8 .
- **Fluid (edge-to-edge):** w-full max-w-none at shell, then give inner sections scroll with overflow-auto .
- **Constrained (recommended default):** mx-auto w-full max-w-screen-2xl px-4 sm:px-6 lg:px-8 .
- **Narrow read width (docs):** wrap rich text with prose max-w-none lg:max-w-prose .

2.3 Spacing Scale Guidelines

- **Vertical rhythm:** use space-y-4 (base), space-y-6 (section), space-y-8 (page). Avoid mixing many scales.
- **Padding tiers:** cards p-4 sm:p-6 ; page container p-4 sm:p-6 lg:p-8 .

- **Grid gaps:** lists `gap-3/4`, sections `gap-6/8`.

2.4 Content Overflow & Scrolling Patterns

Scrollable region inside card

```
<div class="card bg-base-100 shadow h-full">
  <div class="card-body p-0">
    <header class="p-4 border-b border-base-300">Heading</header>
    <div class="p-4 overflow-auto" style="contain: content">
      <!-- Tall content/table/list -->
    </div>
  </div>
</div>
```

- Prefer inner `overflow-auto` to avoid double scrollbars on the page. (No custom CSS needed—inline style omitted; `contain` not required.)

Full-height panels

```
<section class="flex min-h-[60vh] flex-col">
  <header class="mb-4">Filters</header>
  <div class="flex-1 overflow-auto"> ... big table ... </div>
</section>
```

Long tables

```
<div class="overflow-auto">
  <table class="table table-zebra">
    <thead class="sticky top-0 bg-base-100"> ... </thead>
    <tbody> ... </tbody>
  </table>
</div>
```

3) Reusable Component Patterns (HTML-only)

3.1 Navigation

Top tabs (secondary nav)

```
<div class="tabs tabs-boxed bg-base-100">
  <a class="tab tab-active">Overview</a>
  <a class="tab">Activity</a>
```

```
<a class="tab">Settings</a>
</div>
```

Breadcrumbs

```
<nav class="breadcrumbs text-sm" aria-label="Breadcrumb">
  <ul>
    <li><a>Home</a></li>
    <li><a>Section</a></li>
    <li aria-current="page">Item</li>
  </ul>
</nav>
```

3.2 Cards

Base card

```
<article class="card bg-base-100 shadow">
  <div class="card-body">
    <h2 class="card-title">Card title</h2>
    <p>Body content grows without fixed height.</p>
    <div class="card-actions justify-end">
      <button class="btn btn-ghost">Cancel</button>
      <button class="btn btn-primary">Save</button>
    </div>
  </div>
</article>
```

Card with accent header

```
<article class="card shadow">
  <div class="bg-primary text-primary-content rounded-t-box p-4">
    <h3 class="font-semibold">Accent header</h3>
  </div>
  <div class="card-body">
    <p>Use semantic color tokens only.</p>
  </div>
</article>
```

3.3 Forms

Form field

```
<label class="form-control w-full">
  <div class="label"><span class="label-text">Email</span></div>
```

```

<span class="label-text-alt">We'll never
share your email.</span></div>
</label>

```

Field with validation

```

<label class="form-control">
  <div class="label"><span class="label-text">Name</span></div>
  <input type="text" class="input input-bordered input-error" aria-
invalid="true" />
  <div class="label"><span class="label-text-alt text-error">Name is
required.</span></div>
</label>

```

Form layout (2-col responsive)

```

<form class="grid gap-4 sm:grid-cols-2">
  <label class="form-control"><span class="label-text">First name</
span><input class="input input-bordered" /></label>
  <label class="form-control"><span class="label-text">Last name</span><input
class="input input-bordered" /></label>
  <label class="form-control sm:col-span-2"><span class="label-
text">Address</span><input class="input input-bordered" /></label>
  <div class="sm:col-span-2 flex justify-end gap-2">
    <button class="btn">Cancel</button>
    <button class="btn btn-primary">Submit</button>
  </div>
</form>

```

3.4 Buttons & Badges

```

<div class="flex flex-wrap gap-2">
  <button class="btn btn-primary">Primary</button>
  <button class="btn btn-secondary">Secondary</button>
  <button class="btn btn-accent">Accent</button>
  <button class="btn btn-ghost">Ghost</button>
  <button class="btn btn-outline btn-error">Delete</button>
</div>
<div class="flex flex-wrap gap-2 mt-3">
  <div class="badge badge-info">Info</div>
  <div class="badge badge-success">Active</div>
  <div class="badge badge-warning">Pending</div>
  <div class="badge badge-error">Failed</div>
</div>

```


3.5 Lists & Tables

Simple list

```
<ul class="menu bg-base-100 rounded-box">
  <li><a>Item one</a></li>
  <li><a>Item two</a></li>
  <li><a>Item three</a></li>
</ul>
```

Data table

```
<div class="overflow-auto">
  <table class="table">
    <thead>
      <tr>
        <th>Id</th><th>Name</th><th>Status</th><th class="text-
right">Actions</th>
      </tr>
    </thead>
    <tbody>
      <tr>
        <td>#123</td>
        <td>Alice</td>
        <td><span class="badge badge-success">Active</span></td>
        <td class="text-right"><button class="btn btn-sm btn-ghost">View</
button></td>
      </tr>
    </tbody>
  </table>
</div>
```

3.6 Empty States & Alerts

```
<div class="card bg-base-100 shadow">
  <div class="card-body items-center text-center">
    <div class="text-5xl">📭</div>
    <h3 class="card-title mt-2">No items yet</h3>
    <p class="text-base-content/70">Get started by creating your first
item.</p>
    <div class="card-actions"><button class="btn btn-primary">New Item</
button></div>
  </div>
</div>

<div class="alert alert-warning mt-4"><span>Be careful—this action cannot be
undone.</span></div>
```

4) Semantic Color Mapping Reference

Use semantic roles consistently—DaisyUI themes will adapt colors.

Role	Typical Usage
<code>bg-base-100</code> / <code>text-base-content</code>	Card/page backgrounds, default text
<code>bg-base-200</code> / <code>base-300</code>	App background, borders/dividers
<code>primary</code>	Primary actions, key highlights (<code>btn-primary</code> , <code>text-primary</code>)
<code>secondary</code>	Secondary actions, supportive accents
<code>accent</code>	Occasional emphasis or selection states
<code>neutral</code>	Navigation chrome, subdued UI elements (<code>bg-neutral</code> , <code>text-neutral-content</code>)
<code>info</code> / <code>success</code> / <code>warning</code> / <code>error</code>	Status badges, alerts, validation states

Do - Prefer `btn-primary`, `text-secondary`, `bg-accent` over raw colors. - For contrast text, use `*-content` variants (e.g., `text-primary-content` on `bg-primary`).

Don't - Hardcode palette classes like `bg-blue-500`.

5) Copy-Paste Snippets with Annotations

5.1 Feature Page Template (Drop-in)

```
<!-- Feature Page Template: balanced defaults that handle growth -->
<section class="mx-auto w-full max-w-screen-2xl p-4 sm:p-6 lg:p-8 space-y-6">
  <!-- Header -->
  <header class="flex flex-wrap items-center justify-between gap-3">
    <div>
      <h1 class="text-2xl lg:text-3xl font-semibold">Feature Title</h1>
      <p class="text-base-content/70">Optional subtitle or description.</p>
    </div>
    <div class="flex gap-2">
      <button class="btn btn-ghost">Cancel</button>
      <button class="btn btn-primary">Save</button>
    </div>
  </header>

  <!-- Content Grid -->
  <div class="grid gap-6 lg:grid-cols-[1fr_22rem]">
```

```

<div class="space-y-6">
  <article class="card bg-base-100 shadow">
    <div class="card-body">
      <h2 class="card-title">Main block</h2>
      <p>Auto-expands—no fixed heights.</p>
    </div>
  </article>
  <article class="card bg-base-100 shadow">
    <div class="card-body">
      <h2 class="card-title">Data table</h2>
      <div class="overflow-auto">
        <table class="table table-zebra">
          <thead class="sticky top-0 bg-base-100">
            <tr><th>Col A</th><th>Col B</th><th>Col C</th></tr>
          </thead>
          <tbody><!-- rows --></tbody>
        </table>
      </div>
    </div>
  </article>
</div>

<aside class="space-y-6" aria-label="Filters and quick info">
  <div class="card bg-base-100 shadow">
    <div class="card-body">
      <h3 class="card-title">Filters</h3>
      <div class="form-control gap-3">
        <input class="input input-bordered" placeholder="Search" />
        <select class="select select-bordered"><option>All</option></
select>
        <button class="btn btn-primary">Apply</button>
      </div>
    </div>
  </div>
  <div class="card bg-base-100 shadow">
    <div class="card-body">
      <h3 class="card-title">Summary</h3>
      <p class="text-sm text-base-content/70">Some contextual tips.</p>
    </div>
  </div>
</aside>
</div>
</section>

```

Notes - `max-w-screen-2xl` ensures readable line lengths while leaving room for dense pages. -
 Sticky `thead` keeps headers visible without fixing table height.

5.2 Full-Width Data Page (Edge-to-Edge + Inner Scroll)

```
<main class="flex-1">
  <div class="w-full max-w-none p-4 sm:p-6 lg:p-8">
    <div class="card bg-base-100 shadow">
      <div class="card-body p-0">
        <header class="p-4 sm:p-6 border-b border-base-300 flex items-center justify-between">
          <h2 class="text-xl font-semibold">All Records</h2>
          <div class="flex gap-2">
            <button class="btn btn-outline">Export</button>
            <button class="btn btn-primary">New</button>
          </div>
        </header>
        <div class="overflow-auto">
          <table class="table">
            <thead class="sticky top-0 bg-base-100">...</thead>
            <tbody>...</tbody>
          </table>
        </div>
      </div>
    </div>
  </div>
</main>
```

5.3 Centered Form Page (Narrow)

```
<section class="mx-auto w-full max-w-3xl p-4 sm:p-6 lg:p-8 space-y-6">
  <header>
    <h1 class="text-2xl font-semibold">Create Item</h1>
    <p class="text-base-content/70">Provide the details below.</p>
  </header>
  <form class="card bg-base-100 shadow">
    <div class="card-body grid gap-4 sm:grid-cols-2">
      <label class="form-control"><span class="label-text">Name</span><input class="input input-bordered" /></label>
      <label class="form-control"><span class="label-text">Type</span><select class="select select-bordered"><option>Standard</option></select></label>
      <label class="form-control sm:col-span-2"><span class="label-text">Description</span><textarea class="textarea textarea-bordered"></textarea></label>
      <div class="sm:col-span-2 flex justify-end gap-2">
        <button class="btn">Cancel</button>
        <button class="btn btn-primary">Create</button>
      </div>
    </div>
  </form>
</section>
```

5.4 Sidebar Section Menu (Within a Page)

```
<div class="grid gap-6 lg:grid-cols-[16rem_1fr]">
  <nav class="menu bg-base-100 rounded-box p-2">
    <ul>
      <li><a class="active">General</a></li>
      <li><a>Members</a></li>
      <li><a>Billing</a></li>
    </ul>
  </nav>
  <section class="space-y-6">
    <article class="card bg-base-100 shadow"><div class="card-body">...</div></article>
    <article class="card bg-base-100 shadow"><div class="card-body">...</div></article>
  </section>
</div>
```

5.5 Sticky Filter Bar Over Scrollable Content

```
<section class="flex min-h-[60vh] flex-col">
  <div class="bg-base-100 border-b border-base-300 sticky top-16 md:top-20 z-10">
    <div class="mx-auto w-full max-w-screen-2xl p-3 flex flex-wrap items-center gap-2">
      <input class="input input-bordered" placeholder="Filter" />
      <button class="btn btn-primary">Apply</button>
      <button class="btn">Reset</button>
    </div>
  </div>
  <div class="flex-1 overflow-auto">
    <!-- Tall results -->
  </div>
</section>
```

6) Extension Patterns (Future-proofing)

- **Secondary panels:** wrap in `lg:grid-cols-[1fr_28rem]` for analysis sidebars.
 - **Command palette:** modal via `dialog` / `modal` components (`modal`, `modal-box`).
 - **Multi-pane:** split with `grid-cols-2` + `overflow-auto` per pane.
 - **Dense enterprise screens:** reduce gaps one tier (e.g., `gap-6` → `gap-4`) and ensure table rows remain auto-height.
-

7) Accessibility Checklist

- `aria-label` for ambiguous buttons (menu, search).
 - `aria-current="page"` in breadcrumbs/menus.
 - Use `*-content` text tokens on colored backgrounds for contrast.
 - Keyboard focus: DaisyUI ships focus styles; keep buttons as `<button>` / `<a>`.
-

8) Quick Decision Guide

- **Page container:** default to **Constrained**.
 - **Lists & tables:** use **inner** `overflow-auto`.
 - **Two-column pages:** grid with **intrinsic aside width**.
 - **Form pages:** **Centered Narrow** template.
 - **Status & actions:** use **semantic tokens** (`info/success/warning/error`, `primary`).
-

Drop-in Angular Template Hint

Use these snippets inside Angular standalone components' templates. Global shell goes in the `AppShellComponent` template; per-route pages use `§5` templates. No additional CSS or TS required for layout behavior.