

Package ‘swissValet’

August 11, 2026

Type Package

Title Interactive Functions to be Used as Shortcuts in 'RStudio'

Version 0.0.0.905

Description 'RStudio' as of recently offers the option to define addins and assign shortcuts to them. This package contains addins for a few most frequently used functions in a data scientist's (at least mine) daily work (like `str()`, `example()`, `plot()`, `head()`, `view()`, `desc()`). Most of these functions will use the current selection in the editor window and send the specific command to the console while instantly executing it. Assigning shortcuts to these addins will save you quite a few keystrokes.

Depends base, stats, R (>= 4.2.0)

Imports DescToolsX, pharos, bedrock, rstudioapi (>= 0.1),
writexl, foreign, tools, tcltk, cli, clipr

URL <https://github.com/AndriSignorell/swissValet/>

BugReports <https://github.com/AndriSignorell/swissValet/issues>

License GPL (>= 2)

LazyLoad yes

Encoding UTF-8

Config/roxygen2/version 8.0.0

Contents

.orderSelectionDlg	2
.str1	2
escapeUnicode	2
flushToSource	3
selectVarDlg	4
some	5
unescapeUnicode	6
unicodeAddins	7
xAbstract	7
xDesc	7
xExample	7
xHead	8
xPlot	8
xStrX	8
xSummary	8
xUnclass	9

Index**10**

.orderSelectionDlg	<i>Select ordering mode</i>
--------------------	-----------------------------

Description

Small Tcl/Tk dialog to choose how selected code elements should be ordered.

Usage

.orderSelectionDlg()

Value

Returns one of:

- "asc" - "desc" - "rand"

Returns 'NULL' if cancelled.

.str1	<i>xExample Run strX() on selected text display first element only.</i>
-------	---

Description

xExample Run strX() on selected text display first element only.

Usage

.str1(x)

escapeUnicode	<i>Escape Unicode Characters</i>
---------------	----------------------------------

Description

Converts non-ASCII characters to Unicode escape sequences.

Usage

escapeUnicode(x)

Arguments

x a character vector

Value

a character vector containing Unicode escape sequences

Examples

```
escapeUnicode("Schneeh\u00f6he")
unescapeUnicode("Schneeh\\u00f6he")
```

flushToSource

Insert selected object as reproducible R code

Description

Converts the currently selected object in the RStudio editor into reproducible R source code and inserts it into the active document.

Usage

```
flushToSource(width.cutoff = 500L)
```

Arguments

`width.cutoff` Integer. Passed to `[base::deparse()]`.

Details

Data frames are converted into a readable `'data.frame(...)'` representation instead of the more verbose `'dput()'` structure output.

Other objects are serialized using `[base::dput()]`.

Value

Invisibly returns the generated code.

Examples

```
## Not run:
flushToSource()

## End(Not run)
```

selectVarDlg	<i>Interactive variable selection dialog</i>
--------------	--

Description

Opens an interactive selection dialog and returns an expression that can directly be used in R code.

Usage

```
selectVarDlg(x, ...)  
  
## Default S3 method:  
selectVarDlg(x, useIndex = FALSE, ...)  
  
## S3 method for class 'numeric'  
selectVarDlg(x, ...)  
  
## S3 method for class 'factor'  
selectVarDlg(x, ...)  
  
## S3 method for class 'character'  
selectVarDlg(x, ...)  
  
## S3 method for class 'data.frame'  
selectVarDlg(x, ...)
```

Arguments

x	An R object.
...	Additional arguments passed to methods.
useIndex	Logical. Should indices instead of values be returned? Only used for the default method.

Details

Depending on the input type, different expressions are generated:

- vectors: 'c(...)' - numeric vectors: index selection - factors/characters: ' ' - data frames: column selection

The generated expression is automatically copied to the clipboard.

The function uses [utils::select.list()] with 'graphics = TRUE' for interactive selection.

If no selection is made, an empty string is returned.

Value

Invisibly returns a character string containing the generated R expression.

Examples

```
## Not run:

# Character vector
selectVarDlg(letters)

# Numeric vector
selectVarDlg(1:10)

# Factor
selectVarDlg(factor(c("A", "B", "C")))

# Data frame columns
selectVarDlg(mtcars)

## End(Not run)
```

some

Random subset of an object

Description

Returns a random subset of observations/elements from vectors, matrices, and data frames.

Usage

```
some(x, n = 6L, ...)

## S3 method for class 'data.frame'
some(x, n = 6L, ...)

## S3 method for class 'matrix'
some(x, n = 6L, addrownums = TRUE, ...)

## Default S3 method:
some(x, n = 6L, ...)
```

Arguments

x	An R object.
n	Integer scalar specifying the number of elements or rows to return. Defaults to '6L'. Negative values reduce the total number of returned elements relative to the object size.
...	Additional arguments passed to methods.
addrownums	Logical. Should artificial row names be added for matrices without row names? Only used for matrices.

Details

Negative values of 'n' are interpreted as:

'length(x) + n'

or

'nrow(x) + n'

respectively.

This function is useful for quickly inspecting random parts of larger objects.

Value

A random subset of 'x'.

- For vectors: a vector. - For matrices: a matrix. - For data frames: a data frame.

Examples

```
some(1:100)

some(letters, 10)

some(mtcars, 5)

some(as.matrix(mtcars), 4)

# Negative n
some(1:20, -5)
```

unescapeUnicode

Unescape Unicode Characters

Description

Converts Unicode escape sequences to their corresponding characters.

Usage

```
unescapeUnicode(x)
```

Arguments

x a character vector

Value

a character vector containing decoded Unicode characters

Examples

```
unescapeUnicode("Schneeh\\u00f6he")
```

unicodeAddins	<i>Unicode RStudio Addins</i>
---------------	-------------------------------

Description

Converts Unicode characters or escape sequences in the selected text.

Usage

```
toggleUnicodeAddin()
```

Value

‘NULL’, invisibly

xAbstract	<i>xAbstract Run abstract() on selected text.</i>
-----------	---

Description

xAbstract Run abstract() on selected text.

Usage

```
xAbstract()
```

xDesc	<i>xUnclass Run desc() on selected text.</i>
-------	--

Description

xUnclass Run desc() on selected text.

Usage

```
xDesc()
```

xExample	<i>xExample Run example() on selected text.</i>
----------	---

Description

xExample Run example() on selected text.

Usage

```
xExample()
```

xHead	<i>xHead Run head() on selected text.</i>
-------	---

Description

xHead Run head() on selected text.

Usage

xHead()

xPlot	<i>xExample Run example() on selected text.</i>
-------	---

Description

xExample Run example() on selected text.

Usage

xPlot()

xStrX	<i>xStrX Run strX() on selected text.</i>
-------	---

Description

xStrX Run strX() on selected text.

Usage

xStrX()

xSummary	<i>xSummary Run summary() on selected text.</i>
----------	---

Description

xSummary Run summary() on selected text.

Usage

xSummary()

xUnclass	<i>xUnclass Run head() on selected text.</i>
----------	--

Description

xUnclass Run head() on selected text.

Usage

xUnclass()

Index

.orderSelectionDlg, [2](#)
.str1, [2](#)

escapeUnicode, [2](#)

flushToSource, [3](#)

selectVarDlg, [4](#)
some, [5](#)

toggleUnicodeAddin (unicodeAddins), [7](#)

unescapeUnicode, [6](#)
unicodeAddins, [7](#)

xAbstract, [7](#)
xDesc, [7](#)
xExample, [7](#)
xHead, [8](#)
xPlot, [8](#)
xStrX, [8](#)
xSummary, [8](#)
xUnclass, [9](#)