The troublesome reflection rule


Andrej Bauer University of Ljubljana



Matija Pretnar



Chris Stone



Philipp Haselwarter?

Talk outline

- Equality reflection bad & good
- Current development
- Future possibilities

 $\Gamma \vdash A : \mathsf{Type}$ $\Gamma \vdash e : A$ $\Gamma \vdash e_1 \equiv_A e_2$ $\Gamma \vdash A \equiv_{\mathsf{Type}} B$ Г – Type : Type

 $\Gamma \vdash e : A$

 $\Gamma \vdash e_1 \equiv_A e_2$

Dependent product

$$\frac{\Gamma, x:A \vdash B : \mathsf{Type}}{\Gamma \vdash \prod_{x:A} B : \mathsf{Type}} \qquad \frac{\Gamma,}{\Gamma \vdash (\lambda x)}$$

$$\frac{\Gamma, x:A \vdash e : B}{\Gamma \vdash (\lambda x:A \cdot e) : \prod_{x:A} B}$$

$$\frac{\Gamma \vdash e_1 : \prod_{x:A} B \qquad \Gamma \vdash e_2 : A}{\Gamma \vdash e_1 e_2 : B[e_2/x]}$$

$$(\lambda x:A.e_1) e_2 \equiv_{B[e_2/x]} e_1[e_2/x]$$

 $(\lambda x:A.e_x) \equiv_{\Pi_{x:A}B} e$

Equality

$$\frac{\Gamma \vdash A : \mathsf{Type} \qquad \Gamma \vdash \mathfrak{a} : A \qquad \Gamma \vdash b : A}{\Gamma \vdash \mathsf{Eq}_A(\mathfrak{a}, \mathfrak{b}) : \mathsf{Type}}$$

$$\frac{\Gamma \vdash \alpha : A}{\Gamma \vdash \mathsf{refl}_{A}(\alpha) : \mathsf{Eq}_{A}(\alpha, \alpha)}$$

$$\frac{\Gamma \vdash p : Eq_A(a,b)}{\Gamma \vdash a \equiv_A b}$$

$$p \equiv_{\mathsf{Eq}_A(\mathfrak{a},\mathfrak{b})} \mathsf{refl}_A(\mathfrak{a})$$

J eliminator

```
\Gamma \vdash a, b : A
               \Gamma \vdash p : Eq_A(a,b)
         \Gamma, \chi: A \vdash c : C(\chi, \chi, refl(\chi))
            \Gamma \vdash J(\dots) : C(a,b,p)
just use c[a/x] for J(...)
```

A: Type,


a : A,

B: Type,

b : B,

 $p: Eq_{Type}(A, B),$

strengthen $q: Eq_A(a,b)$



nat: Type

Z:nat

 $S: nat \rightarrow nat$

 $\mathsf{ind}: \textstyle\prod_{\mathsf{P:nat} \to \mathsf{Type}} \mathsf{PZ} \to (\prod_{\mathsf{n:nat}} \mathsf{P}\, \mathsf{n} \to \mathsf{P}\, (\mathsf{S}\, \mathsf{n})) \to \prod_{\mathsf{m:nat}} \mathsf{P}\, \mathsf{m}$


$$\beta_{Z}: \prod_{P:\mathsf{nat} \to \mathsf{Type}} \prod_{x:PZ} \prod_{f:(\Pi_{n:\mathsf{nat}} P} \prod_{n \to P} (\mathsf{S}\, n))$$

$$\mathsf{Eq}_{PZ}(\mathsf{ind}\, P\, x\, f\, \mathsf{Z}, x)$$

$$\beta_{S}: \prod_{P:\mathsf{nat} \to \mathsf{Type}} \prod_{x:PZ} \prod_{f:(\Pi_{n:\mathsf{nat}} P \, n \to P \, (S \, n))} \prod_{n:\mathsf{nat}} \mathsf{Eq}_{PZ}(\mathsf{ind} \, P \, x \, f \, (S \, n), f \, n \, (\mathsf{ind} \, P \, x \, f \, n))$$

Extensional type theories

- Nuprl: based on a PER model over an untyped calculus with strong normalization
- HOL: simply typed and classical
- We would like a dependently typed system which is not bound to a single model



Type theory as a programming language

- Input: a program that derives a judgment
- Evaluation: construction of the derivation
- Equality checking: computational effect
- Output: the derived judgment

Input computations

variable X Type universe $\Pi X:C1.C2$ product $\lambda x: C_1.C_2$ abstraction application **C**1 **C**2 $Eq(c_1,c_2)$ equality type refl(c) reflexivity ascription

hint c1 in c2 general hint beta c1 in c2 β-hint eta c1 in c2 η-hint

C1::C2

handlers directing equality checks through reflection

Output terms & types

x variable

Type universe

 $\Pi x:A.B$ product

 $\lambda x:A.(e:B)$ abstraction

e₁ @(x:A.B) e₂ application

Eq_A(e₁,e₂) equality type

refl_A(e) reflexivity

Output terms & types

```
variable
            Type
                      universe
        \Pi x : A . B
                      product
  \lambda x:A.(e:B)
                      abstraction
e<sub>1</sub> @(x:A.B) e<sub>2</sub>
                      application
  Eq_A(e_1,e_2)
                      equality type
      refl<sub>A</sub>(e)
                     reflexivity
```

β-rule

```
\Gamma \vdash A_1 \equiv A_2 \qquad \Gamma, x : A_1 \vdash B_1 \equiv B_2
\Gamma \vdash ((\lambda x : A_1 . e_1 : B_1) \stackrel{@(x : A_2 . B_2)}{=} e_2) \equiv e_1[e_2/x]
```

($\lambda x: nat.x: nat$) @(nat>bool) $\emptyset \neq \emptyset$

Operational semantics

$$\Gamma$$
; $\mathscr{E} \vdash \mathsf{c} \rightarrow (\mathsf{e},\mathsf{A})$

"In context Γ using hints \mathscr{E} computation c evaluates to (e,A)"

Soundness:

If Γ ; $\mathscr{E} \vdash c \rightarrow (e,A)$ then $\Gamma \vdash e:A$.

$$(x:A) \in \Gamma$$

$$\Gamma; \mathscr{E} \vdash x \rightarrow (x,A)$$

 Γ ; $\mathscr{E} \vdash \mathsf{Type} \rightarrow (\mathsf{Type}, \mathsf{Type})$

$$\Gamma; \mathscr{E} \vdash C_1 \rightarrow (A, T_1)$$
 $\Gamma; \mathscr{E} \vdash T_1 \equiv_{\mathsf{Type}} \mathsf{Type}$
 $\Gamma, x : A; \mathscr{E} \vdash C_1 \rightarrow (B, T_2)$
 $\Gamma, x : A; \mathscr{E} \vdash T_2 \equiv_{\mathsf{Type}} \mathsf{Type}$

 $\Gamma; \mathscr{E} \vdash \|x:c_1.c_2 \rightarrow \|x:A.B\|$

"normalization"

$$\Gamma; \mathscr{E} \vdash C1 \rightarrow (e_1, A_1)$$
 $\Gamma; \mathscr{E} \vdash A_1 \mapsto^{\text{whnf}} \Pi x: C.D$
 $\Gamma; \mathscr{E} \vdash C2 \rightarrow (e_2, A_2)$
 $\Gamma; \mathscr{E} \vdash C \equiv_{\text{Type}} A_2$

$$\Gamma; \mathscr{E} \vdash C1 C2 \rightarrow (e_1 ^{@(x:A.B)} e_2, D[e_2/x])$$

$$\Gamma$$
; $\mathscr{E} \vdash C_1 \rightarrow (e_1, A_1)$
 Γ ; $\mathscr{E} \vdash C_2 \rightarrow (e_2, A_2)$
 Γ ; $\mathscr{E} \vdash A_2 \equiv_{\mathsf{Type}} \mathsf{Type}$
 Γ ; $\mathscr{E} \vdash A_1 \equiv_{\mathsf{Type}} e_2$

$$\Gamma; \mathscr{E} \vdash c_1::c_2 \rightarrow (e_1,e_2)$$

Equality hints

$$\mathcal{E} = \mathcal{E}_{\equiv}, \mathcal{E}_{\beta}, \mathcal{E}_{\eta}$$

general β-hints η-hints
hints

A hint is a universally quantified equation:

 $\prod x_1:A_1...x_n:A_n.Eq_B(e_1,e_2)$

β-hints

n-hints

```
\begin{array}{lll} \Gamma;\mathscr{E}_{\equiv},\mathscr{E}_{\beta},\mathscr{E}_{\eta} \; \vdash \; \mathsf{C1} \; \rightarrow \; (\mathsf{e1},\mathsf{A1}) \\ \Gamma;\mathscr{E}_{\equiv},\mathscr{E}_{\beta},\mathscr{E}_{\eta} \; \vdash \; \mathsf{A1} \; \mapsto \; \|\mathsf{x}_{1} \colon \mathsf{A}_{1} \dots \mathsf{x}_{n} \colon \mathsf{A}_{n} \cdot \mathsf{Eq}_{B}(\mathsf{e}_{1},\mathsf{e}_{2}) \\ \Gamma;\mathscr{E}_{\equiv},\mathscr{E}_{\beta} \cup \{\|\mathsf{x}_{1} \colon \mathsf{A}_{1} \dots \mathsf{x}_{n} \colon \mathsf{A}_{n} \cdot \mathsf{Eq}_{B}(\mathsf{e}_{1},\mathsf{e}_{2})\},\mathscr{E}_{\eta} \; \vdash \; \mathsf{C2} \; \rightarrow \; (\mathsf{e2},\mathsf{A2}) \end{array}
```

 Γ ; \mathscr{E}_{Ξ} , \mathscr{E}_{β} , \mathscr{E}_{η} \vdash beta c₁ in c₂ \rightarrow (e₂,A₂)

Checking $e_1 \equiv_A e_2$

1. Decompose $e_1 \equiv_A e_2$ into subgoals that have smaller types, e.g.

 $e_1 \equiv_{A \times B} e_2$ reduces to $fst e_1 \equiv_A fst e_2$ and $snd e_1 \equiv_B snd e_2$

2. When the type cannot be decomposed further, check that e_1 and e_2 are equal by normalization.



β-hints as definitions

```
a : A
a_def : Eq(a,e)
```

beta a_def in ...

β-hints as definitions

```
a : A
a_def1 : Eq(a,e<sub>1</sub>)
a_def2 : Eq(a,e<sub>2</sub>)
```

```
beta a_def1 in ... beta a_def2 in ...
```

What else?

- Voevodsky's Homotopy Type System
- Enrich the input language with other computational effects and handlers
- Implement standard proof assistant techniques (implicit arguments, proof search, type clases, ...) in the language

This material is based upon work supported by the Air Force Office of Scientific Research, Air Force Materiel Command, USAF under Award No. FA9550-14-1-0096. Any opinions, findings, and conclusions or recommendations expressed in this publication are those of the author(s) and do not necessarily reflect the views of the Air Force Office of Scientific Research, Air Force Materiel Command, USAF.