

PRODUCT CATALOG · POWER & WORKSHOP

Gearboxes & drives

Helical, bevel, worm and planetary gear reducers, right-angle gearboxes, motorised pulleys and conveyor drives, from 0.09 kW to heavy industrial duty — for augers, conveyors, feed mixers, packhouses and irrigation machinery.



WHO WE ARE

Farm equipment, at the price it *actually* costs.

Built by farmers, for farmers. Andrivo sources farm infrastructure and equipment from international manufacturers, handles the entire import process, and delivers to your farm anywhere in Southern Africa.

Farmers usually pay for a chain of markups they never see — a factory, an export agent, an importer and a local distributor, each adding a margin nobody discloses. Andrivo removes that chain. Our only charge is a service fee on top of the true cost: 30%, or 25% with a referral code.

25%

fee with a referral code (30% without)

0

distributors in between

SADC

we deliver across Southern Africa

How every quote works

1**Factory direct**

We work directly with the manufacturer of every machine in this catalog — no middlemen.

2**Inspected before it ships**

Each order is checked against the factory spec sheet before it leaves the plant.

3**Shipping & customs handled**

Freight, duties, clearing and transport to your gate are all managed by us.

4**Parts & aftersales**

Spares in stock, and every machine logged to your farm under My Farm by Andrivo.

CONTENTS

What's in this catalog

Figures give the range for each series; the exact model depends on your motor power, output speed and load. Tell us the job, the motor and the speed you need and we will select the gearbox.

Helical and bevel gear reducers

R Series Helical Gear Reducer	04
F Series Parallel Shaft Helical Gear Reducer	04
K Series Helical Reducer-Bevel Gear Reducer	05
S Series Helical Gear-Worm Gear Reducer	05
Planetary Cycloidal Pinwheel Reducer	06
Hardened Tooth Bevel-Cylindrical Gear Reducer	06
ZQ, ZS, ZD, ZL Series Cylindrical Gear Reducer	07
HB Series Industrial Gearbox	07
M, MC Series Gearbox	08

Worm gear reducers

WP Series Worm Gear Reducer	08
TP Series Worm Gear Reducer	09
CAVEX Series Worm Gear Reducer	09
RV Series Worm Gear Reducer	10

Planetary reducers and right-angle gearboxes

P Series Planetary Gear Reducer	10
---------------------------------	----

NGW Series Planetary Gear Reducer	11
Precision Planetary Gear Reducer	11
T, ARA, HD Series Right Angle Gearbox	12

Motorised pulleys and conveyor drives

TJ Series Oil-Immersed Motorised Pulley	12
WD Series External Motorised Pulley	13
TDY75 Oil-Cooled Motorised Pulley	13
Explosion-Proof Motorised Pulley	14
SMROLL Series Miniature Motorised Pulley	14
Suspended Gear Reducer	15
XTY Series Conveyor Drive System	15

Special-purpose drives

Planetary Friction-Type Stepless Speed Variator	16
Reducer for Screw Conveyors	16
Reducer for Twin-Shaft Mixers	17
Chemical Agitation Transmission Device	17
Differential for Centrifuge	18

Augers and conveyors

Screw-conveyor reducers, shaft-mounted reducers, motorised pulleys and conveyor drives.

Mixers and packhouses

Helical, bevel and worm reducers for feed mixers, graders, washers and packing lines.

Irrigation machinery

Worm and right-angle gearboxes for gates, travelling irrigators and pivot drives.

01 **R Series Helical Gear Reducer**



The structure is two-to-three-stage involute helical gear transmission, the gears take the carburizing, quenching and grinding gear processing technology. The whole machine has the characteristics of small volume, large torque transmission, high efficiency, stable work, long lifespan, wide range of motor power, fine grading of transmission ratio, and so on.

Technical parameters	
Input power	0.09–160 kW
Output torque	2–23 200 N·m
Transmission ratio	1.65–21 342

02 **F Series Parallel Shaft Helical Gear Reducer**



The structure of parallel shaft involute helical gear drive, the gears take the carburizing, quenching and grinding gear processing technology. The whole machine has the characteristics of small volume, large torque transmission, high efficiency, stable work, long lifespan, wide range of motor power, fine grading of transmission ratio, and so on.

Technical parameters	
Input power	0.12–200 kW
Output torque	3.5–22 500 N·m
Transmission ratio	4.16–22 323

03

K Series Helical Reducer–Bevel Gear Reducer



This series is the structure of direct axis and a combination of involute helical gear and bevel gear reducer transmission. The gears take the carburizing, quenching and grinding gear processing technology. The whole machine has the characteristics of small volume, large torque transmission, high efficiency, stable work, long lifespan, wide range of power and fine grading of transmission ratio, and so on.

Technical parameters	
Input power	0.12–200 kW
Output torque	3.5–22 500 N·m
Transmission ratio	4.16–22 323

04

S Series Helical Gear–Worm Gear Reducer



This series is the structure of direct axis and the high-speed stage involute helical gear transmission. The gears take the carburizing, quenching and grinding gear processing technology.

Technical parameters	
Input power	0.12–200 kW
Output torque	3.5–22 500 N·m
Transmission ratio	4.16–22 323

05

Planetary Cycloidal Pinwheel Reducer



This reducer uses cycloidal pin gear meshing. There are two categories of products: X and X8000 series, all of which are manufactured by computer optimized design and the most advanced technology. All the indexes have reached the advanced level of similar products in the world.

Technical parameters	
Input power	0.09–173 kW
Output torque	20–60 800 N·m
Transmission ratio	6–658 503

06

Hardened Tooth Bevel-Cylindrical Gear Reducer



These reducers adopt high-quality and high-strength cast iron casings. The gears are made of high-quality alloy steel through carburizing, quenching, and grinding processes. There are 7 specifications including ZDY, ZLY, ZSY, DBY, DCY, DBYK, DCYK and 98 models.

Technical parameters	
Input power	4–6000 kW
Output torque	350–360 000 N·m
Transmission ratio	1.25–100

07

ZQ, ZS, ZD, ZL Series Cylindrical Gear Reducer



These reducers are driven by two-to-three-stage involute cylindrical gears. The box structure is horizontally divided and fully enclosed, with good mechanical performance, reliable operation, and easy maintenance. This machine also has strong overload capacity, shock resistance, low inertia moment, and is suitable for frequent starting and forward-reverse operation.

Technical parameters	
Input power	0.8–175 kW
Output torque	2.3–900 kN·m
Transmission ratio	2–280

08

HB Series Industrial Gearbox



These reducers are designed specifically for heavy-duty conditions. They are adopting high-quality cast casing to improve the mechanical strength and shock resistance of the reducers. The transmission shaft system is arranged in a zigzag pattern, and the gears are processed by carburizing, quenching, and grinding technology.

Technical parameters	
Input power	9–3600 kW
Output torque	2.3–900 kN·m
Transmission ratio	1.25–450

09

M, MC Series Gearbox



M, MC series gearboxes are compact and high-efficiency products. They are designed for the medium torque range and adopt high-quality cast casing to improve the mechanical strength and shock resistance of the reducers. The gears are processed by carburizing, quenching, and grinding gear technology. These reducers have multiple installation forms and a wide selection of accessories.

Technical parameters	
Input power	8–750 kW
Output torque	4.7–52.8 kN·m (at input 1000 rpm)
Transmission ratio	7.1–112

10

WP Series Worm Gear Reducer



WP series worm gear reducer is used to transmit motion and power between two axes that are spatially orthogonal to each other. The high-speed shaft can operate in both directions. There are 63 models of WP series, with center distances ranging from 40mm to 250mm, and 13 types. The maximum input speed is≤1500r/min.

Technical parameters	
Input power	0.12–33.2 kW
Output torque	6–9066 N·m
Transmission ratio	10–900

11

TP Series Worm Gear Reducer



This reducer is a planar double-enveloping hourglass worm gear reducer. This series features high transmission efficiency, large load-bearing capacity, wear resistance, and compact structure. The high-speed shaft can operate in both forward and reverse directions. There are 4 models of this series, with center distances ranging from 80mm to 500mm, and 15 types. The maximum input speed is $\leq 1500\text{r/min}$.

Technical parameters	
Input power	0.82–582.5 kW
Output torque	384–77 978 N·m
Transmission ratio	10–63

12

CAVEX Series Worm Gear Reducer



This reducer is a planar double-enveloping hourglass worm gear reducer. This series features high transmission efficiency, large load-bearing capacity, wear resistance, and compact structure. The high-speed shaft can operate in both forward and reverse directions. There are 4 models of this series, with center distances ranging from 63mm to 630mm, and 15 types. The maximum input speed is $\leq 1500\text{r/min}$.

Technical parameters	
Input power	0.82–582.5 kW
Output torque	384–77 978 N·m
Transmission ratio	10–63

13

RV Series Worm Gear Reducer



This reducer features a high-quality aluminum alloy die-casting box, with excellent heat dissipation, strong load-bearing capacity, multiple installation forms, small volume, light weight, smooth transmission, low noise, safe and reliable, economical and durable. There are 10 types of center distances ranging from 25mm to 150mm.

Technical parameters	
Input power	0.09–15 kW
Output torque	2.3–900 N·m
Transmission ratio	5–100

14

P Series Planetary Gear Reducer



This series features a highly modular design. It has the characteristic of compact structure, small volume, and light weight, wide transmission ratio range, high efficiency, smooth operation, and low noise. Several planetary gears simultaneously transmit loads, dividing power and achieving the synthesis and decomposition of motion. Coaxial transmission can be easily achieved. Rich optional attachments.

Technical parameters	
Input power	0.4–14 000 kW
Output torque	22–2600 kN·m
Transmission ratio	25–4000

15 NGW Series Planetary Gear Reducer



This reducer is an involute spur cylindrical planetary transmission structure. It has the characteristics of small volume, light weight, smooth operation, and low noise. It has 3 product specifications, 12 models with primary transmission, 9 models with secondary transmission, and 6 models with tertiary transmission.

Technical parameters	
Input power	1–13 kW
Output torque	320–49 200 N·m
Transmission ratio	2.8–2000

16 Precision Planetary Gear Reducer



This series has small structural dimensions, large output torque, wide speed ratio range, high efficiency, and safe and reliable performance. Its output methods are smooth straight axis, key attached straight axis and keyhole output.

Technical parameters	
Input power	9–3600 kW
Output torque	2.3–900 N·m
Transmission ratio	3–1000

17

T, ARA, HD Series Right Angle Gearbox



This series steering gearboxes are essential products for power steering transmission. It has the characteristics of high efficiency, low noise, low vibration and strong load-bearing capacity.

Technical parameters	
Input power	0.014–335 kW
Output torque	11.6–3205 N·m
Transmission ratio	1:1–5:1

18

TJ Series Oil-Immersed Motorised Pulley



A European-designed motorised pulley built to international standards. It has advanced structure, direct oil cooling motor, good cooling and heat dissipation, smooth transmission, long service life, low noise and allows for high temperature rise. The motorised pulleys can function as self-contained enclosed drive units or serve as power sources for powered roller conveyors, winches and other equipment.

Technical parameters	
Input power	0.1–90 kW
Drum diameter	110–1000 mm Ø
Drum width	250–2000 mm
Belt speed	0.06–4.25 m/s

19

WD Series External Motorised Pulley



A newer external-motor version of the TJ motorised pulley. The product has an advanced structure, and the gears and front and rear shafts are made of high-quality alloy steel. It has the characteristics of smooth transmission, light weight, low energy consumption, equipped with standard series motors, suitable for general working conditions. For occasions with explosion-proof requirements, explosion-proof motors can be used.

Technical parameters	
Drum diameter	500–800 mm Ø
Drum width	500–1400 mm
Belt speed	0.5–4 m/s

20

TDY75 Oil-Cooled Motorised Pulley



TDY75 oil-cooled motorised pulley is a driving device for belt conveyors, used to drag the conveyor belt to operate. It can widely replace the external drive device composed of electric motors and reducers currently in use. The oil-cooled motorised pulley has good sealing performance, so it can be used in dusty, damp and muddy places.

Technical parameters	
Input power	1.5–15 kW
Drum diameter	320–800 mm Ø
Drum width	500–1400 mm
Belt speed	0.8–4 m/s

21 Explosion-Proof Motorised Pulley



This series is a new type of motorised pulley developed on the basis of TDY75 oil-cooled motorised pulley. In addition to the characteristics of TDY75 oil-cooled motorised pulley, it also has explosion-proof features. Its technical parameters are the same as the TDY75 oil-cooled motorised pulley.

Technical parameters	
Input power	1.5–15 kW
Drum diameter	320–800 mm Ø
Drum width	500–1400 mm
Belt speed	0.8–4 m/s

22 SMROLL Series Miniature Motorised Pulley



The motors of this series are designed and manufactured according to the European IEC standard, with an insulation level of F and a sealing level of IP66/67. It has passed CE safety certification and features fast installation, easy operation, space saving, low energy consumption, low noise, wide environmental adaptability and simple maintenance. This series of products includes 11 specifications.

Technical parameters	
Input power	1.5–7.5 kW
Drum diameter	82–321 mm Ø
Drum width	270–560 mm
Belt speed	0.05–3.2 m/s

23 Suspended Gear Reducer



ZGY suspended gear reducer is a newly developed hard tooth surface reducer. It has the characteristics of small volume, light weight, strong load-bearing capacity, high efficiency, simple structure, and easy installation and maintenance. The input shaft of the reducer is connected to the motor by a belt pulley, and the output is connected by a hollow shaft single key. There are a total of 19 models.

Technical parameters	
Input power	2.5–193 kW
Output torque	3.5–22 500 N·m
Transmission ratio	10–25

24 XTY Series Conveyor Drive System



The conveyor drive system integrates a suspended gear reducer mounted directly on the drive drum shaft. The motor is supported by a mounting bracket, with its shaft connected to the reducer input shaft via a belt pulley. The reducer is secured by a torque arm and drives the rotation of the drum. An optional backstop device can be included for reverse rotation prevention.

Technical parameters	
Input power	15–55 kW
Drum diameter	500–800 mm Ø
Belt speed	1.25–2.5 m/s

25

Planetary Friction-Type Stepless Speed Variator



Planetary friction type continuously variable transmission is a mechanical continuously variable transmission. The reducer features a compact structure, small volume, smooth transmission, low noise, stable performance, and a wide speed range. It comes in 8 different models with a speed ratio of 1:5.

Technical parameters	
Input power	0.18–22 kW
Output torque	1.5–352 N·m
Transmission ratio adjustment range	1.45–7.25

26

Reducer for Screw Conveyors



This reducer is specifically designed for screw conveyors, featuring a simple structure, high efficiency and easy maintenance. There are 3 types of models in total. Screw conveyor is primarily used for lifting and transporting powdered materials and small granular substances.

Technical parameters	
Input power	5.5–22 kW
Output torque	161–1281 N·m
Transmission ratio	4.86–9.63

27

Reducer for Twin-Shaft Mixers



This series is a new type of reducer specially developed for the construction industry. The reducer has a compact structure, small volume, light weight, beautiful appearance, smooth operation, low noise, strong load-bearing capacity, strong impact resistance, long service life, and is connected to the shaft through a coupling to ensure synchronization between the two reducers.

Technical parameters	
Input power	30–75 kW
Output torque	10 000–25 000 N·m
Transmission ratio	25.5–27

28

Chemical Agitation Transmission Device



Chemical agitation transmission device can provide various types of frames, couplings, packing boxes, mechanical seals for kettles and mixers. The frame material is available in cast iron and sheet metal. The sealing materials for mixers, packing boxes, and kettles can be customized according to customer requirements.

Technical parameters	
Input power	2.2–11 kW
Output torque	1030–4900 N·m
Transmission ratio	24–159

29 Differential for Centrifuge



This series adopts planetary cycloidal pinwheel structure or involute planetary gear structure. It has the characteristics of small volume, light weight, and strong load-bearing capacity.

Technical parameters	
Input power	2.2–11 kW
Output torque	1030–4900 N·m
Transmission ratio	24–159