

PERFORMANCE DATA • 380 V 50 HZ**4-pole motors • about 1 450 rpm**

The all-round choice: pumps, compressors, conveyors and general machinery.

Model	Frame	Power kW	Power hp	Speed rpm	Current A at 380 V	Efficiency %	Power factor
YE3-63M1-4	63M	0.12	0.16	1310	0.45	55.8	0.72
YE3-63M2-4	63M	0.18	0.24	1310	0.64	58.6	0.73
YE3-71M1-4	71M	0.25	0.34	1330	0.81	63.6	0.74
YE3-71M2-4	71M	0.37	0.5	1330	1.1	65.3	0.75
YE3-80M1-4	80M	0.55	0.74	1430	1.4	80.6	0.75
YE3-80M2-4	80M	0.75	1	1430	1.8	82.5	0.75
YE3-90S-4	90S	1.1	1.5	1430	2.6	84.1	0.76
YE3-90L-4	90L	1.5	2	1430	3.5	85.3	0.77
YE3-100L1-4	100L	2.2	3	1440	4.8	86.7	0.81
YE3-100L2-4	100L	3	4	1440	6.3	87.7	0.82
YE3-112M-4	112M	4	5.4	1455	8.4	88.6	0.82
YE3-132S-4	132S	5.5	7.4	1465	11.2	89.6	0.83
YE3-132M-4	132M	7.5	10	1465	15.0	90.4	0.84
YE3-160M-4	160M	11	15	1470	21.5	91.4	0.85
YE3-160L-4	160L	15	20	1470	28.8	92.1	0.86
YE3-180M-4	180M	18.5	25	1470	35.3	92.6	0.86
YE3-180L-4	180L	22	30	1470	41.8	93.0	0.86
YE3-200L-4	200L	30	40	1475	56.6	93.6	0.86
YE3-225S-4	225S	37	50	1480	69.6	93.9	0.86
YE3-225M-4	225M	45	60	1480	84.4	94.2	0.86
YE3-250M-4	250M	55	74	1485	103	94.6	0.86
YE3-280S-4	280S	75	101	1490	136	95.0	0.88
YE3-280M-4	280M	90	121	1490	163	95.2	0.88
YE3-280M1-4	280M	110	148	1490	197	95.4	0.89
YE3-315S-4	315S	110	148	1490	197	95.4	0.89
YE3-315M-4	315M	132	177	1490	236	95.6	0.89
YE3-315L1-4	315L	160	215	1490	285	95.8	0.89
YE3-315L-4	315L	185	248	1490	329	95.9	0.89
YE3-315L2-4	315L	200	268	1490	352	96.0	0.90
YE3-315L3-4	315L	220	295	1490	387	96.0	0.90
YE3-355M1-4	355M	220	295	1490	387	96.0	0.90
YE3-355M-4	355M	250	335	1495	440	96.0	0.90
YE3-355L1-4	355L	280	375	1495	492	96.0	0.90
YE3-355L-4	355L	315	422	1495	554	96.0	0.90
YE3-355-1-4	355	355	476	1495	638	96.0	0.88
YE3-355-2-4	355	375	503	1495	674	96.0	0.88