



Machine Parts



Sun Shade
Designed ZTR-50



Lawn Tire
18x6.5/9.5-8 Turf
Designed for Zero Turn Mowers



Standard Flat Blade
Designed for Zero Turn Mowers



Mulching Blade
Designed for Zero Turn Mowers



Drive Belt
Designed for Zero Turn Mowers



Electromagnetic Clutch
Designed for Zero Turn Mowers



Spark Plug
Designed for Zero Turn Mowers



Air Cleaner Element
Designed for Zero Turn Mowers

TECHNICAL SPECIFICATIONS

Zero Turn Mower

Model	ZTR-36B	ZTR-42B	ZTR-42E	ZTR-50B (23 Model)	ZTR-50B (25 Model)
Engine & Power					
Engine	ZONSEN XP680 II LC2P73F V-Twin	ZONSEN XP680 II LC2P80F V-Twin	ZONSEN XP590/680II LC2P73F V-Twin	ZONSEN XP750II EI LC2P80F V-Twin	ZONSEN XP720 II LC2P80F V-Twin
Rated Power	23 HP/17 HP	23 HP	20 HP/23 HP/17 HP	25 HP/23 HP	24.5 HP/23 HP
Displacement	679 cc/586 cc	679 cc/764 cc	594 cc/679 cc /586 cc	750 cc/764 cc	714 cc/764 cc
Fuel Capacity	25 L	25 L	25 L	20 L	25 L
Drive System					
Transmission	Hydro Gear EZT-2200 (Optional ZT-2800)	Hydro Gear EZT-2200 (Optional ZT-2800)	Hydro Gear EZT-2200	Hydro Gear EZT-2200 (Optional ZT-2800)	Hydro Gear EZT-2200 (Optional ZT-2800)
Drive Mode	Zero-Turn, Hydrostatic	Zero-Turn, Hydrostatic	Zero-Turn, Hydrostatic	Zero-Turn, Hydrostatic	Zero-Turn, Hydrostatic
Tires-Front	0-7.7 MPH (12.4 km/h)	0-7.7 MPH (12.4 km/h)	0-7.7 MPH (12.4 km/h)	0-7.7 MPH (12.4 km/h)	0-7.7 MPH (12.4 km/h)
Tires-Rear	0-3.4 MPH (5.5 km/h)	0-3.4 MPH (5.5 km/h)	0-3.4 MPH (5.5 km/h)	0-3.4 MPH (5.5 km/h)	0-3.4 MPH (5.5 km/h)
Start	Electric start	Electric start	Electric start	Electric start	Electric start
Cutting System					
Deck Type	Fabricated	Fabricated	One-Piece Stamped Blade Disc	Fabricated	Fabricated
Number Of Blades	2 pieces	3 pieces	2 pieces	3 pieces	3 pieces
Cutting Width	36 in(915 mm)	42 in(1060 mm)	42 in(1060 mm)	50 in(1270 mm)	50 in(1270 mm)
Cutting Height Range	1.5-4.5 in (38-114 mm)	1.5-4.5 in (38-114 mm)	1.5-4.5 in (38-114 mm)	1.5-4.5 in (38-114 mm)	1.5-4.5 in (38-114 mm)
Spindles	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
Blade Engagement	Electromagnetic Clutch	Electromagnetic Clutch	Electromagnetic Clutch	Electromagnetic Clutch	Electromagnetic Clutch
Tires & Dimensions					
Tire Size	F:11x4.0-5 R:18x6.5-8 Turf	F:11x4.0-5 R:18x9.5-8 Turf	F:11x4.0-5 R:18x9.5-8 Turf	F:11x4.0-5 R:18x9.5-8 Turf	F:11x4.0-5 R:18x9.5-8 Turf
Weight Overall	250 kg	300 kg	221 kg	320 kg	300 kg
Package Size	1690x930x700 mm	1687x1154x700 mm	1705x1115 x700 mm	1833x1300x875 mm	1687x1115x700 mm
Additional Features					
Certificate	CE/EPA/Euro5	CE/EPA/Euro5	CE/EPA/Euro5	CE/EPA/Euro5	CE/EPA/Euro5
Container Load	40HQ: 56 pcs 20GP: 18pcs	40HQ: 56 pcs 20GP: 18pcs	40HQ: 56 pcs 20GP: 18pcs	40HQ: 30 pcs 20GP: 10 pcs	40HQ: 40 pcs 20GP: 15 pcs