

ALL-ROUND
LAWN AERATOR

High-Efficiency Lawn Aerator

Sturdy steel body for long-lasting durability
— an ideal choice for professional lawn care.

90 mm 6.5 HP 95 dB(A)

B&S XR950

Tackles both hard and soft terrains, delivers uniform
coring for efficient operation, and achieves all-in-one
lawn care.



Large 3.1 L Fuel Tank



Storage Box



4 Hardened Steel Tines



Effortless Control Lever

Model	LA-18
Engine & Power	
Engine	B&S XR950
Motor	4-stroke, single-cylinder OHV gasoline engine, Cylinder tilted at 25° fitted with a horizontal shaft and a 6:1 speed reducer
Performance	6.5 HP
Power	4.9 kW
Displacement	208 cc
Fuel Capacity	3.1 L
Certificate	CE/EPA/Euro5
Tine	
Cutting Teeth Number	4
Maximum Core Drilling Depth	3.54 in (90 mm)
Drilling Width	16.14 in (410 mm)
Core Spacing	3.74 in (95 mm)
Maximum Operating Slope	20°
Sound Level	95 dB(A)
Drive System	
Start Type	Hand Start
Drive Type	Belt-Driven
Work Efficiency	2500 m ² /h
Dimensions	
Package Size	960 × 725 × 705 mm
Container Load	40HQ: 108 pcs / 20GP: 54 pcs

TECHNICAL SPECIFICATIONS

Lawn Aerator

Model	LA-726
Engine & Power	
Engine	B&S XR950
Motor	4-stroke, single-cylinder OHV gasoline engine, Cylinder tilted at 25°, fitted with a horizontal shaft and a 6:1 speed reducer
Performance	6.5 HP
Power	4.9 kW
Displacement	208 cc
Fuel capacity	3.1 L
Certificate	CE/EPA/Euro5
Tine	
Tine & Drum	Single #40 nickel plated chain
Tines	0.75 in (19 mm) diameter coning-type, formed from 0.08 in (2 mm) hollow, hardened alloy steel
Number of sharp teeth	42 Tines per Aerator
Lubrication	Grease fittings on the wheels, tine wheels and idler pivot/oil chain
Coring Depth	2.75 in (70 mm)
Core Diameter	0.75 in (19 mm)
Aeration Pattern	3.75 in × 7 in (95 mm × 178 mm)
Aeration Width	26.5 in (673 mm)
Drive System	
Primary	A-type belt
Clutch	Belt tightener
Productivity	Aerates up to 40,000 sq ft/hr (3,716 m ² /hr) at 3.5 mph (2.8 × 2.25 semi-pneumatic with ball bearings)
Dimensions	
Tires	(2)8x2.25 semi-pneumatic with ball bearings
Package Size	1015 × 900 × 800 mm (902 × 1359 × 1232 mm)
Weight	113 kg (Weight: Wet) / 132 kg (With wet weight) / 156 kg (Wet W: W + Drum Water)
Container Load	40HQ: 78 pcs 20GP: 24 pcs