

DMF automatic sand media filter

SAND MEDIA FILTER



Primary filtration through a deep sand bed, which traps organic and inorganic impurities in three dimensions. Choose a sand filter when the water carries more than 10 mg/L of organic matter, such as dam, river or canal water with algae.

- High flow with low pressure loss
- Modular, compact layout with less pipework, so it costs less to install
- Use one unit or several in parallel to suit the irrigation project
- Automatic backwash, so water supply never stops

OPERATING PARAMETERS

Capacity per tank 15–80 m³/h	Filtration grade 5–40 micron	Design pressure 0.8 MPa / 8 bar
Minimum pressure 0.2 MPa / 2 bar	Working temperature up to 65 °C	Pressure loss ≤ 0.02 MPa / 0.2 bar
Control Pressure difference, timer or manual	Backwash time 10–200 s	Power supply AC 220 V 50 Hz / DC 9–24 V
Collector material ABS	Delivery Skid-mounted, easy to install	

TECHNICAL DATA

Model	Tanks	Min flow (m³/h)	Max flow (m³/h)	Filter area (m²)	Backwash flow per tank (m³/h)	Max pressure (MPa)	Inlet / outlet	Drain
DMF-2416-2A	2	27	50	0.56	22	0.8	3" / DN80	2" / DN50
DMF-3216-2A	2	60	80	1.0	40	0.8	4" / DN100	3" / DN80
DMF-3616-2A	2	75	100	1.28	50	0.8	4" / DN100	3" / DN80
DMF-4016-2A	2	80	120	1.88	60	0.8	6" / DN150	3" / DN80
DMF-4816-2A	2	100	160	2.26	80	0.8	6" / DN150	3" / DN80
DMF-4816-3A	3	150	240	3.39	80	0.8	8" / DN200	3" / DN80
DMF-4816-4A	4	200	320	4.52	80	0.8	8" / DN200	3" / DN80