

DLHF300 vertical hydraulic screen filter

SCREEN FILTER



Single-stage filtration through a stainless-steel screen that removes silt, sand and scale from irrigation water, and also handles water carrying a little organic matter. For systems from 10 to 200 m³/h.

- Driven entirely by water pressure in the pipeline, so no external power is needed
- Fully automatic control
- Automatic backwash
- Parts: hydraulic piston, stainless-steel screen and suction nozzles

OPERATING PARAMETERS

Capacity per unit 10–200 m³/h	Filtration grade 25–2000 micron	Design pressure 1.0 MPa / 10 bar
Minimum pressure 0.2 MPa / 2 bar	Screen material Stainless steel 304 / 316	Control Pressure difference, timer or manual
Backwash time 10–200 s, adjustable	Working temperature up to 65 °C	Pressure loss ≤ 0.01 MPa / 0.1 bar
Backwash power Uses line pressure only, no external power		

TECHNICAL DATA

Model	Inlet / outlet	Screen area (cm²)	Flow (m³/h)	Weight (kg)
DLHF-302	3" / DN80	1720	20	42
DLHF-303	3" / DN80	1720	50	47
DLHF-304	4" / DN100	1720	80	60
DLHF-304MAX	4" / DN100	3430	100	82
DLHF-306	6" / DN150	4330	130	90
DLHF-308	8" / DN200	5500	200	182