

TECHNICAL DATA

Model	Inlet / outlet	Screen area (cm²)	Flow (m³/h)	Weight (kg)
DLHF-403	3" / DN80	3220	50	140
DLHF-404	4" / DN100	5780	100	170
DLHF-406	6" / DN150	5780	150	183
DLHF-406MAX	6" / DN150	8410	160	205
DLHF-408	8" / DN200	5780	250	195
DLHF-408MAX	8" / DN200	8410	300	235
DLHF-410	10" / DN250	8410	350	250
DLHF-410MAX	10" / DN250	10290	400	270
DLHF-412	12" / DN300	11710	600	435
DLHF-414	14" / DN350	12990	1000	455
DLHF-416	16" / DN400	12990	1200	480
DLHF-416MAX	16" / DN400	17020	1500	680

DIMENSIONS

Model	D1 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	H (mm)
DLHF-403	273	450	1370	2120	560
DLHF-404	273	900	1730	2850	580
DLHF-406	325	900	1730	2850	635
DLHF-406MAX	325	900	1920	3210	635
DLHF-408	325	900	1920	3210	635
DLHF-408MAX	325	900	2310	4010	640
DLHF-410	325	900	2310	4010	690
DLHF-410MAX	426	1100	2560	4290	760
DLHF-412	426	1100	2960	5290	760
DLHF-414	480	1270	2960	5290	820
DLHF-416	480	1270	2960	5290	820
DLHF-416MAX	630	1270	2960	5290	1020

Model code: DLHF-400 series – connection size – filtration grade – design pressure. Pressure and materials can be customised on request.

DIMENSION DRAWING

