

DLD-FZ vertical electric brush filter

SELF-CLEANING SCREEN FILTER



The vertical version of the electric brush filter, with a smaller footprint. Brushing plus backwash removes algae and suspended solids from dam and river water, cutting manual cleaning by about 90% and saving more than 15% of flushing water.

- High flow with high filtration accuracy
- Low pressure loss and little backwash water
- Highly automated
- Parts: electric brush and stainless-steel screen

OPERATING PARAMETERS

Capacity per unit 10–2 000 m³/h	Filtration grade 20–2400 micron	Design pressure 1.0 MPa / 10 bar
Minimum pressure 0.1 MPa / 1 bar	Screen material Stainless steel 304 / 316	Control Pressure difference, timer or manual
Backwash time 10–200 s	Working temperature up to 65 °C	Pressure loss ≤ 0.01 MPa / 0.1 bar

TECHNICAL DATA

Model	Inlet / outlet	Drain outlet	Motor (kW)	Flow (m³/h)	Weight (kg)
DLD-FZ-50	2" / DN50	1" / DN25	0.18	19	50
DLD-FZ-65	2½" / DN65	1" / DN25	0.18	30	70
DLD-FZ-80	3" / DN80	1¼" / DN40	0.18	50	87
DLD-FZ-100	4" / DN100	1¼" / DN40	0.18	80	106
DLD-FZ-150	6" / DN150	2" / DN50	0.18	150	197
DLD-FZ-200	8" / DN200	2" / DN50	0.25	320	248
DLD-FZ-250	10" / DN250	2" / DN50	0.25	490	360
DLD-FZ-300	12" / DN300	2" / DN50	0.37	710	486
DLD-FZ-350	14" / DN350	2" / DN50	0.37	970	653
DLD-FZ-400	16" / DN400	2" / DN50	0.37	1260	765
DLD-FZ-450	18" / DN450	2" / DN50	0.37	1600	814
DLD-FZ-500	20" / DN500	2½" / DN65	0.55	1970	920