

5XF-100
Potato Receiving Hopper


Specification	Unit	5XF-100
Hitch type		Trailed
Dimensions (L x W x H)	mm	15000×3200×3100
Weight	kg	7780
Capacity	t/h	100
Belt drive		Hydraulic motor
Drive		Electric motor + gear pump
Motor power	kW	18
Hydraulic tank	L	90
Power supply		380 V AC, 50 Hz
Controls		Touch screen + buttons
Receiving belt width	mm	720
/ Lifting/pitch of the manual picking up web	mm	45
/ Lifting/width of the manual picking up web	mm	1550
Cleaning rollers		Polyurethane spiral / spring rollers
Cleaning roller gap	mm	0~45
Manual picking positions		6~8
Intake arm length	mm	4400

5XF-40.2/40.3
Potato Receiving Hopper


Specification	Unit	5XF-40.2	5XF-40.3
Dimensions (L x W x H)	mm	6892×3036×2090	7500×3036×2683
Weight	kg	3392	4095
Sorting table width	mm	1600	1600
Capacity	t/h	40	40
Conveyor type		Toothed rubber belt + PVC belt	Toothed rubber belt + PVC belt
Drive		Hydraulic power pack	Hydraulic power pack + drum motor
Total power	kW	7.65	13.35
Power supply		380 V AC, 50 Hz	380 V AC, 50 Hz
Controls		Lever + buttons	Lever + buttons
Hopper volume	m³	8 m³ (≈5.2 t potatoes)	8 m³ (≈5.2 t potatoes)
Cleaning roller type		Polyurethane rollers	Polyurethane rollers
Cleaning rollers		7	13 (7 front + 6 rear)
Sorting stages		Two-stage sorting	Three-stage sorting