

Inverter technical specification

Item		Description
Input(AC)	Rated voltage, frequency	Three phase 380V, 50Hz/60Hz
	Allowable voltage range	Three phase 380V: 320~480V
Input(DC)	Recommended operating voltage range	Three phase 380V: 600~750VDC
	Recommended MPPT operating voltage	Three phase 380V: 550VDC
Output	Voltage	0~input voltage
	Frequency	0~599Hz
	Overload capacity	150% of rated current for 1 minute
Dedicated functions	PV water supply dedicated functions	1. Support multiple solar pump control modes, including MPPT control and MPPT+PID constant pressure water supply control. 2. Support automatic AC/DC power supply switching for 24/7 unattended uninterrupted operation 3. Support automatic dormancy & wake-up, intermittent operation, and pump self-cleaning functions 4. Support multiple pump protections such as pump dry run protection, full-water protection, low frequency protection, minimum power protection, lightning and surge protection, overcurrent protection, overheat protection, and short-circuit protection, etc.
Protection function		Power-on motor short-circuit detection, input/output phase loss protection, overcurrent protection, overvoltage protection, undervoltage protection, overheat protection, overload protection, underload protection, ground short-circuit protection, terminal protection, power failure ride-through protection, etc
Environment	Application site	Indoor, no direct sunlight, free from dust, corrosive gases, flammable gases, oil mist, water vapor, water drop and salt, etc
	Altitude	Below 1000 meters. (When the altitude is above 1000 meters, derating is required. For every additional 1000 meters in altitude, the output current should be reduced by approximately 10% of the rated current.)
	Ambient temperature	-10°C~+40°C (ambient temperature between 40°C~50°C, please derate or enhance cooling)
	Relative humidity	< 95%RH, no condensation
	Vibration	Less than 5.9 m/s ² (0.6g)
	Storage temperature	-40°C~+70°C
Structure	IP grade	IP20
	Cooling method	Forced air cooling
Installation method		Wall-mounted

Inverter model selection

Input voltage	Inverter model	Rated output current(A)	Applicable motor (kW)	Max. DC input voltage (VDC)	Recommended DC input voltage range(VDC)	Allowable DC input voltage range (VDC)
Three phase AC 380V	EN750PV-4T0007	2.3	0.75	900	600~750	300~900
	EN750PV-4T0015	3.7	1.5	900	600~750	300~900
	EN750PV-4T0022	5	2.2	900	600~750	300~900
	EN750PV-4T0037	8.5	3.7	900	600~750	300~900
	EN750PV-4T0055	13	5.5	900	600~750	300~900
	EN750PV-4T0075	17	7.5	900	600~750	300~900
	EN750PV-4T0110	25	11	900	600~750	300~900
	EN750PV-4T0150	33	15	900	600~750	300~900
	EN750PV-4T0185	39	18.5	900	600~750	300~900
	EN750PV-4T0220	45	22	900	600~750	300~900
	EN750PV-4T0300	60	30	900	600~750	300~900
	EN750PV-4T0370	75	37	900	600~750	300~900
	EN750PV-4T0450	91	45	900	600~750	300~900
	EN750PV-4T0550	112	55	900	600~750	300~900
	EN750PV-4T0750	150	75	900	600~750	300~900
	EN750PV-4T0900	176	90	900	600~750	300~900