

PRODUCT CATALOG · CROP PROTECTION

Sprayer pumps & parts

Diaphragm pumps from 20 to 250 L/min, pressure regulators and section valves, filters, nozzles, spray guns, tank fittings and fan gearboxes — to build, repair and upgrade any tractor sprayer.



WHO WE ARE

Farm equipment, at the price it *actually* costs.

Built by farmers, for farmers. Andrivo sources farm infrastructure and equipment from international manufacturers, handles the entire import process, and delivers to your farm anywhere in Southern Africa.

Farmers usually pay for a chain of markups they never see — a factory, an export agent, an importer and a local distributor, each adding a margin nobody discloses. Andrivo removes that chain. Our only charge is a service fee on top of the true cost: 30%, or 25% with a referral code.

25%

fee with a referral code (30% without)

0

distributors in between

SADC

we deliver across Southern Africa

How every quote works

1**Factory direct**

We work directly with the manufacturer of every machine in this catalog — no middlemen.

2**Inspected before it ships**

Each order is checked against the factory spec sheet before it leaves the plant.

3**Shipping & customs handled**

Freight, duties, clearing and transport to your gate are all managed by us.

4**Parts & aftersales**

Spares in stock, and every machine logged to your farm under My Farm by Andrivo.

CONTENTS

What's in this catalog

Every part in this catalog fits the tractor sprayers in our sprayer catalog, and most fit other makes too. Quote the model code when you ask for a price; for a replacement part, a photo of the old one helps us match it.

Diaphragm pumps	04
Regulators, section valves and ball valves	05
Filters and tank strainers	06
Nozzles, nozzle holders and spray guns	07
Tank lids, mixers, gauges and small parts	08
Fan gearboxes for air-blast sprayers	09



Pumps



Section valves



Filters



Spray guns



Chemical mixer

PUMPS

Diaphragm sprayer pumps

PTO-driven diaphragm pumps for boom and air-blast sprayers, from 20 L/min for small mounted units to 250 L/min for large trailed sprayers. Diaphragm pumps handle chemicals and wettable powders well and run dry without damage for short periods.



Model	GMB20	GMB30	GMB55	MBS54	GMB81	MB105	MB135	GMB110 130 / 150	GMB185 215 / 250
Speed (rpm)	650	550	550	550	550	550	550	550	550
Flow (L/min)	20	35	55	54	78	102	132	110 / 125 / 140	185 / 215 / 250
Power needed (hp)	1	3	6	6	10	11.4	6.03	10 / 12 / 14	9 / 10 / 11
Working pressure (bar)	20	40	40	40	40	40	20	40	20
Cylinders	2	2	3	3	3	4	3	3	6
Centre height (mm)	74	97	132	121	155	178	135	194	200
Size (mm)	200×220 ×220	252×303 ×319	320×298 ×290	320×285 ×300	460×325 ×370	440×315 ×400	453×335 ×288	376×417 ×447	388×410 ×474
Weight (kg)	4	11	16	13.6	20	23	30.6	38.5	38

The GMB30F is the GMB30 in a different mounting; the MB115 is the smaller version of the MB135. Ask us for their exact figures.

CONTROL

Regulators, section valves and ball valves

Pressure regulators set the spray pressure and return the surplus to the tank; section distributors switch boom sections on and off from the tractor.



GI40X / GI40Y Pressure regulator

Working pressure 40 bar
For GMB30 and GMB55 pumps, or remote control
1-4 ball-valve outlets, G1/2 thread
Outlet hose 10 or 13 mm



GR40/30/20 - GR40Y/30Y/20Y Pressure regulator

Working pressure 40, 30 or 20 bar
For the GMB30 pump, or remote control
1-3 ball-valve outlets, G1/2 thread
Outlet hose 10 or 13 mm



RM40YF / RM40Y Pressure regulator

Working pressure 40 bar
For the GMB81 pump
Ball-valve outlets, G1/2 thread
Outlet hose 10 or 13 mm



BMH50 High-pressure regulator

Working pressure 50 bar
For pumps of 90-200 L/min
Inlet G3/4, outlet G1/2, overflow G1



FPF3 3-section distributor

Working pressure 15 bar
Weight 1.6 kg · 285×250×255 mm
Outlets 13, 10 or 8.5 mm



FPF4 4-section distributor

Working pressure 15 bar
Weight 1.625 kg · 285×250×255 mm
Outlets 13, 10 or 8.5 mm



FPF5 5-section distributor

Working pressure 15 bar
Weight 1.725 kg · 285×250×255 mm
Outlets 13, 10 or 8.5 mm



FPF6 6-section distributor

Working pressure 15 bar
Weight 1.825 kg · 306×250×255 mm
Outlets 13, 10 or 8.5 mm



HXF 1 1/2" 3-way ball valve

Thread G1 1/2"
Working pressure 10 bar



HXF2 3-way ball valve

Thread G2
Working pressure 10 bar

FILTRATION

Filters and tank strainers

Clean spray liquid protects the pump and stops nozzles blocking. Fit a strainer in the tank opening, a suction filter before the pump and a line filter before the boom.



GLQ60
Suction filter

50 mesh
Inlet/outlet G1½"
Hose 20 or 28 mm
Capacity 60 L/min



GLQ100
Suction filter

50 mesh
Inlet/outlet G1½"
Hose 28 mm
Capacity 100 L/min



GLQ200
Suction filter

30 or 50 mesh
Inlet/outlet G1½"
Hose 28 or 35 mm
Capacity 160 L/min



GLQ220
Suction filter

30, 50 or 80 mesh
Inlet/outlet G2
Hose 50 mm
Capacity 220 L/min



YLQ I
Pressure line filter

50 mesh
Inlet/outlet G1/2"
Working pressure 14 bar



YLQ II
Double-layer line filter

Inner 50 mesh, outer 200 mesh
Inlet/outlet G1/2"
Working pressure 14 bar



GLT50
High-pressure self-cleaning filter

50 mesh
Inlet/outlet G1/2
Working pressure 50 bar
Capacity 70 L/min



Replacement filter elements

Red and blue mesh inserts
For the filters on this page



LW400
Tank strainer

18 mesh
Ø 400 mm, fits a 380 mm opening
Height 275 mm



LW302
Tank strainer

18 mesh
Ø 300 mm, fits a 288 mm opening
Height 235 mm



LW210
Tank strainer

18 mesh
Ø 210 mm, fits a 188 mm opening
Height 120 mm

APPLICATION

Nozzles, nozzle holders and spray guns



MKF
Diaphragm anti-drip nozzle holder
Working pressure 3–4 bar



MJF
Nozzle holder with shut-off
Working pressure 3–4 bar



SF II
Triple-head anti-drip holder
Working pressure 3–4 bar



DGF
Single anti-drip nozzle
Working pressure 3–4 bar



SGF2
Single anti-drip nozzle
Working pressure 3–4 bar



NH101
Brass anti-drip nozzle
40–50 bar, G1/4
Ceramic plate 0.8 / 1.2 / 1.5 mm



NH102
Brass anti-drip nozzle
40–50 bar, G1/4
Ceramic plate 0.8 / 1.2 / 1.5 mm



NH103
Brass anti-drip nozzle
40–50 bar, G1/4
Ceramic plate 0.8 / 1.2 / 1.5 mm



PTW1/4
Brass nozzle
50 bar, G1/4
Ceramic plate 1.5 / 2.0 / 2.5 mm



PTG1/4
Brass nozzle (NH103 type)
50 bar, G1/4
Ceramic plate 1.5 / 2.0 / 2.5 mm



CG16
Adjustable spray gun
50 bar
Orifice 1.5–2.8 mm
400×145×65 mm, 685 g



CG16A
Adjustable spray gun
50 bar
Orifice 1.5–2.8 mm
400×155×65 mm, 685 g



CG17A
Long adjustable spray gun
50 bar
Orifice 1.5–2.8 mm
620×180×72 mm, 1 475 g



CG16B1
Spray gun, 170 mm lance
20 bar, G1/2
Ceramic plate 2.0 mm



CG16B2
Spray gun, 520 mm lance
20 bar, G1/2
Ceramic plate 2.0 mm



PTZ 1/4N · 1/4W
Nozzle clamp
Nickel-plated brass with O-ring
G1/4, for Ø 21 mm boom tube



HJ1/2
Flexible joint
Brass swivel, G1/2

FITTINGS

Tank lids, mixers, gauges and small parts


SXG454
Tank lid

Lid Ø 454 mm
Ring Ø 415 mm


SXG355
Tank lid

Lid Ø 355 mm
Ring Ø 320 mm


SXG240
Tank lid

Lid Ø 240 mm
Thread S225×12, height 57 mm


SXG140
Tank lid

Lid Ø 140 mm
Ring Ø 128 mm


HX-25
Chemical induction mixer

25 L hopper
467×349×761 mm


HJY5
Chemical suction mixer

Draws chemical straight from the drum


Foam marker

Marks the edge of each pass


YJB
Pressure stirrer

G1/2, spray hole 1.5–3.0 mm
Max. pressure 45 bar


YBJ
Pressure gauge (radial)

Glycerine filled, stainless case
G1/4 · 15, 40 or 50 bar


YBZ
Pressure gauge (axial)

Glycerine filled, stainless case
G1/4 · 25 or 40 bar


AQF40 / AQF20
Safety valve

Safe working pressure 40 or 20 bar


AC1804
Brass nut and hose barb

Nut G1/2
Barb 8, 10 or 13 mm

DRIVE

Fan gearboxes for air-blast sprayers

Step-up gearboxes that take the tractor PTO at 540 rpm and drive the fan of an air-blast sprayer at up to about 2 500 rpm, with two ratios to choose from.


FC113
Fan gearbox

Ratio 1:3.5 or 1:4.1
Input 540 rpm
Output 1 890 or 2 214 rpm
Power 50 kW


FC86
Fan gearbox

Ratio 1:3 or 1:4
Input 540 rpm
Output 1 620 or 2 160 rpm
Power 22 kW


FC93
Fan gearbox

Ratio 1:4.6 or 1:3.5
Input 540 rpm
Output 2 484 or 1 890 rpm
Power 14.7 kW

FC93 exploded view

