

PERFORMANCE DATA • 380 V 50 HZ**2-pole motors • about 2 900 rpm**

Most pumps, fans and blowers.

Model	Frame	Power kW	Power hp	Speed rpm	Current A at 380 V	Efficiency %	Power factor
YE3-63M1-2	63M	0.18	0.24	2720	0.53	63.9	0.80
YE3-63M2-2	63M	0.25	0.34	2720	0.70	67.1	0.81
YE3-71M1-2	71M	0.37	0.5	2740	1.0	69.0	0.81
YE3-71M2-2	71M	0.55	0.74	2740	1.4	72.3	0.82
YE3-80M1-2	80M	0.75	1	2870	1.7	80.7	0.82
YE3-80M2-2	80M	1.1	1.5	2875	2.4	82.7	0.83
YE3-90S-2	90S	1.5	2	2880	3.2	84.2	0.84
YE3-90L-2	90L	2.2	3	2880	4.6	85.9	0.85
YE3-100L-2	100L	3	4	2880	6.0	87.1	0.87
YE3-112M-2	112M	4	5.4	2915	7.8	88.1	0.88
YE3-132S1-2	132S	5.5	7.4	2935	10.6	89.2	0.88
YE3-132S2-2	132S	7.5	10	2930	14.4	90.1	0.88
YE3-160M1-2	160M	11	15	2950	20.6	91.2	0.89
YE3-160M2-2	160M	15	20	2945	27.9	91.9	0.89
YE3-160L-2	160L	18.5	25	2945	34.2	92.4	0.89
YE3-180M-2	180M	22	30	2950	40.5	92.7	0.89
YE3-200L1-2	200L	30	40	2965	54.9	93.3	0.89
YE3-200L2-2	200L	37	50	2965	67.4	93.7	0.89
YE3-225M-2	225M	45	60	2965	80.8	94.0	0.90
YE3-250M-2	250M	55	74	2975	98.5	94.3	0.90
YE3-280S-2	280S	75	101	2975	134	94.7	0.90
YE3-280M-2	280M	90	121	2975	160	95.0	0.90
YE3-280M1-2	280M	110	148	2975	195	95.2	0.90
YE3-315S-2	315S	110	148	2985	195	95.2	0.90
YE3-315M-2	315M	132	177	2985	234	95.4	0.90
YE3-315L1-2	315L	160	215	2985	279	95.6	0.91
YE3-315L-2	315L	185	248	2985	323	95.7	0.91
YE3-315L2-2	315L	200	268	2985	349	95.8	0.91
YE3-315L3-2	315L	220	295	2985	383	95.8	0.91
YE3-355M1-2	355M	220	295	2985	383	95.8	0.91
YE3-355M-2	355M	250	335	2985	436	95.8	0.91
YE3-355L1-2	355L	280	375	2985	488	95.8	0.91
YE3-355L-2	355L	315	422	2985	549	95.8	0.91
YE3-355-1-2	355	355	476	2985	619	95.8	0.91
YE3-355-2-2	355	375	503	2985	654	95.8	0.91