

Boosting Zero-Turn Mower Performance

Provides smooth, precise control, enhances power output, reduces maintenance, and makes mowing more efficient and comfortable.

Strong Output
Hydro-Gear EZT-2200 / ZT-3800



Machine parts



Aluminum Grass Catcher
Designed for Stand-On Mowers



Lawn Tire
18 x 6.5-8 / 9.5-8 Turf
Designed for Stand-On Mowers



Standard Flat Blade
Designed for Stand-On Mowers



Mulching Blade
Designed for Stand-On Mowers



Snow Plow
Designed for Stand-On Mowers



Electric Clutch
Designed for Stand-On Mowers



Spark Plug
Designed for Stand-On Mowers



Air Cleaner Element
Designed for Stand-On Mowers

TECHNICAL SPECIFICATIONS

Stand-on Mower

	ZTS-32B	ZTS-36B	ZTS-42B	ZTS-50B	ZTS-61C
Engine & Power					
Engine	ZONSEN XP750B LC2P80F V-Twin	ZONSEN XP750B LC2P80F V-Twin	ZONSEN XP750B LC2P80F V-Twin	ZONSEN XP750B LC2P80F V-Twin	ZONSEN XP1000 EI V-Twin
Rated Power	25 HP/23 HP	25 HP/23 HP	25 HP/23 HP	25 HP/23 HP	35 HP
Displacement	750 cc/764 cc	750 cc/764 cc	750 cc/764 cc	750 cc/764 cc	999 cc
Fuel Capacity	10 L	10 L	15 L	15 L	45 L
Drive System					
Transmission	Hydro Gear EZT-2200 (Optional ZT-2800)	Hydro Gear EZT-2200 (Optional ZT-2800)	Hydro Gear EZT-2200 (Optional ZT-2800)	Hydro Gear EZT-2200 (Optional ZT-2800)	Hydro-Gear ZT-3800
Drive Mode	Zero-Turn, Hydrostatic	Zero-Turn, Hydrostatic	Zero-Turn, Hydrostatic	Zero-Turn, Hydrostatic	Zero-Turn, Hydrostatic
Tires-Front	0-7.7 MPH (12.4 km/h)	0-7.7 MPH (12.4 km/h)	0-7.7 MPH (12.4 km/h)	0-7.7 MPH (12.4 km/h)	0-12 MPH (19.2 km/h)
Tires-Rear	0-3.4 MPH (5.5 km/h)	0-3.4 MPH (5.5 km/h)	0-3.4 MPH (5.5 km/h)	0-3.4 MPH (5.5 km/h)	0-6 MPH (9.6 km/h)
Start	Electric start	Electric start	Electric start	Electric start	Electric start
Cutting System					
Deck Type	Fabricated	Fabricated	Fabricated	Fabricated	Fabricated
Number Of Blades	2 pieces	2 pieces	3 pieces	3 pieces	3 pieces
Cutting Width	32 in (810 mm)	36 in (915 mm)	42 in (1060 mm)	50 in (1270 mm)	62 in (1573 mm)
Cutting Height Range	1.5-4.5 in (38-114 mm)	1.5-4.5 in (38-114 mm)	1.5-4.5 in (38-114 mm)	1.5-4.5 in (38-114 mm)	1.0-5.0 in (25.4-127 mm)
Spindles	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
Blade Engagement	Electromagnetic Clutch	Electromagnetic Clutch	Electromagnetic Clutch	Electromagnetic Clutch	Electromagnetic Clutch
Tires & Dimensions					
Tire Size	F:11x4.0-5 R:18x6.5-8 Turf	F:11x4.0-5 R:18x9.5-8 Turf	F:11x4.0-5 R:18x9.5-8 Turf	F:11x4.0-5 R:18x9.5-8 Turf	F:13x6.5-6 R:24x12-12 Turf
Overall Weight	280 kg	290 kg	298 kg	310 kg	508 kg
Package Size	1850x950x870 mm	1700x1100x870 mm	1700x1114x870 mm	1700x1305x870 mm	1842x1585x880 mm
Additional Features					
Certificate	CE/EPA/Euro5	CE/EPA/Euro5	CE/EPA/Euro5	CE/EPA/Euro5	CE/EPA/Euro5
Container Load	40HQ: 36 pcs 20GP: 12 pcs	40HQ: 39 pcs 20GP: 12 pcs	40HQ: 39 pcs 20GP: 12 pcs	40HQ: 30 pcs 20GP: 12 pcs	40HQ: 21 pcs 20GP: 6 pcs