



🔧 Ergonomic Layout: All operational functions are within easy reach.

🔧 Ergonomically designed to fit body curves and reduce work fatigue.

🔧 Low-ground-pressure tires minimize turf damage during operation in sensitive areas.



Machine Parts



Lawn Tire
18×9.5-8 / 22×10-10 Turf
Designed for Leaf Blower



Spark Plug
Designed for Leaf Blower



Electric Clutch
Designed for Leaf Blower

TECHNICAL SPECIFICATIONS

Leaf Blower

Model	SLBH22	SLBV23	DTBH22	DTBV23
Engine & Power				
Engine	Honda GX690 V-Twin Petrol	VANGUARD 17.2 GROSS KW	Honda GX690 V-Twin Petrol	VANGUARD 17.2 GROSS KW
Rated Power	22 HP	23 HP	22 HP	23 HP
Displacement	688 cc	627 cc	688 cc	627 cc
Fuel Capacity	15 L	15 L	15 L	15 L
Performance	16.5 kW	17.2 kW	16.5 kW	17.2 kW
Impeller				
Impeller Blades	6 pieces	6 pieces	25 pieces	25 pieces
Impeller Diameter	18 in (475 mm)	18 in (475 mm)	14 in (358 mm)	14 in (358 mm)
Impeller Construction	All-steel,welded,dynam-ically balanced	All-steel,welded,dynam-ically balanced	Ducted Fan	Ducted Fan
Air Velocity	165 MPH (252 kw/h)	165 MPH (252 kw/h)	102.5 MPH (165 kw/h)	102.5 MPH (165 kw/h)
Air flow	4500 CFM (127 m³/min)	4500 CFM (127 m³/min)	6000 CFM (170 m³/min)	6000 CFM (170 m³/min)
Air Discharge Locations	180° freely rotating	180° freely rotating	Pivot 360 Degrees	Pivot 360 Degrees
Air Discharge Control	Electric joystick	Electric joystick	Electric joystick	Electric joystick
Drive System				
Drive Type	Dual hydrostatic	Dual hydrostatic	Dual hydrostatic	Dual hydrostatic
Electric Clutch	Yse	Yse	Yse	Yse
Transmission	Hydro-Gear ZT-3100	Hydro-Gear ZT-3100	Hydro-Gear ZT-3100	Hydro-Gear ZT-3100
Parking Brake	Manual	Manual	Manual	Manual
Forward Speed	9 MPH (14.4 km/h)	9 MPH (14.4 km/h)	9 MPH (14.4 km/h)	9 MPH (14.4 km/h)
Tires & Dimensions				
Tire Size	F:11×4-5 R:18×9.5-8 Turf	F:11×4-5 R:18×9.5-8 Turf	F:13×6.5-6/4.50 R:22×10-10 Turf	F:13×6.50-6/4.50 R:22×10-10 Turf
Package Size	1580×1070×1255 mm	1580×1070×1255 mm	1500×1130×1286 mm	1500×1130×1286 mm
Weight	320 kg	320 kg	412 kg	412 kg
Certificate	CE/EPA/Euro5	CE/EPA/Euro5	CE/EPA/Euro5	CE/EPA/Euro5
Container Load	40HQ: 28 pcs 20GP: 6 pcs	40HQ: 28 pcs 20GP: 6 pcs	40HQ: 30 pcs 20GP: 6 pcs	40HQ: 30 pcs 20GP: 6 pcs