

Power range 30kVA-4000kVA

Adopting Yuchai engines, featuring strong transient loading capacity, good maintainability and long service life.



50Hz

YUCHAI diesel engine 3 phase 50HZ 400/230V

Genset Model	Standby Power		Prime Power		Engine Model	CyL	DSPL (L)	Cons. (g/kw.h)	Dimension L*W*H (mm)	Weight (kg)
	KVA	KW	KVA	KW						
KCY-20GF	23	18	20	16	YC4V35-D20	4L	2.982	≤232	1700*650*1000	770
KCY-30GF	34	27	30	24	YC4V45Z-D20	4L	2.982	≤232	1700*650*1000	770
KCY-68GF	41	33	38	30	YC4V55Z-D20	4L	2.982	≤232	1700*700*1000	770
KCY-40GF	44	35	40	32	YC4D60-D25	4L	4.21	≤232	1800*700*1000	830
KCY-63GF	69	55	63	50	YC4D90Z-D25	4L	4.21	≤200	1900*750*1100	850
KCY-70GF	75	60	69	55	YC4A100Z-D20	6L	4.84	≤200	1900*750*1100	900
KCY-100GF	113	90	100	80	YC4A140L-D25	6L	6.871	≤200	2100*1100*1300	1100
KCY-125GF	138	110	125	100	YC4A180L-D20	6L	6.871	≤200	2200*1100*1400	1150
KCY-125GF*	150	120	125	100	YC6B180L-D20	6L	6.871	≤200	2200*1100*1400	1200
KCY-150GF	165	132	150	120	YC6B205L-D20	6L	6.871	≤230	2300*1100*1500	1250
KCY-175GF	193	154	175	140	YC6A230L-D20	6L	7.25	≤192	2400*1100*1500	1410
KCY-188GF	206	165	188	150	YC6A245L-D21	6L	7.25	≤192	2500*1100*1600	1430
KCY-250GF	275	220	250	200	YC6MK350L-D20	6L	10.34	≤195	2900*1100*1600	1600
KCY-313GF	344	275	313	250	YC6MK420L-D20	6L	10.34	≤195	3100*1100*1850	1600
KCY-350GF	388	310	350	280	YC6MK460L-D20	6L	11.75	≤195	3100*1100*1850	1900
KCY-375GF	400	320	375	300	YC6MK480L-D20	6L	11.75	≤195	3200*1200*1850	1900
KCY-375GF*	413	330	375	300	YC6MJ500-D21	6L	12.16	≤195	3250*1200*1600	1900
KCY-400GF	440	352	400	320	YC6MJ540-D30	6L	12.16	≤195	3250*1200*1700	2300
KCY-450GF	495	396	450	360	YC6MJ600-D30	6L	16.3	≤195	3450*1400*1800	3000
KCY-500GF	550	440	500	400	YC6T660L-D20	6L	16.3	≤195	3500*1400*1900	3600
KCY-563GF	625	500	563	450	YC6TD780-D31	6L	19.58	≤195	3500*1400*1900	3800
KCY-563GF*	625	500	563	450	YC6TD780-D30	6L	19.58	≤195	3500*1400*1900	3800
KCY-625GF	688	550	625	500	YC6TD840-D31	6L	19.58	≤195	3600*1400*1900	4400
KCY-625GF*	688	550	625	500	YC6TD840-D30	6L	19.58	≤195	3600*1400*1900	4400
KCY-688GF	750	600	688	550	YC6TD900-D31	6L	19.58	≤195	3600*1400*2200	4400
KCY-688GF*	750	605	688	550	YC6TD900-D30	6L	19.58	≤195	3600*1400*2200	4400
KCY-750GF	825	660	750	600	YC6TD1000-D31	6L	39.58	≤195	4100*1900*2200	6500
KCY-750GF*	825	660	750	600	YC6TD1000-D30	6L	39.58	≤195	4100*1900*2200	6500
KCY-800GF*	880	704	800	640	YC6TD1100-D30	6L	39.58	≤195	4200*2000*2200	6800
KCY-910GF	1000	800	913	730	YC6TH1220-D31	6L	39.58	≤195	4200*2000*2200	6800
KCY-1000GF	1125	900	1000	800	YC6TH1320-D31	6L	39.58	≤195	4200*2000*2200	7350
KCY-1125GF	1250	1000	1125	900	YC6C1520-D31	6L	39.58	≤195	4300*2000*2200	8700
KCY-1250GF	1375	1100	1250	1000	YC6C1660-D31	6L	39.58	≤195	4400*2000*2200	9000
KCY-1250GF*	1375	1100	1250	1000	YC6C1660-D30	6L	39.58	≤195	4400*2000*2200	9000
KCY-1000GF*	1125	900	1000	800	YC12VTD1350-D30	12V	79.17	≤195	4400*2000*2200	7300
KCY-1125GF*	1250	1000	1125	900	YC12VTD1500-D30	12V	79.17	≤195	4500*2000*2250	8100
KCY-1250GF**	1375	1100	1250	1000	YC12VTD1680-D30	12V	79.17	≤195	4600*2200*2450	9300
KCY-1375GF	1500	1200	1375	1100	YC12VTD1830-D30	12V	79.17	≤195	4600*2200*2450	9500
KCY-1500GF	1650	1320	1500	1200	YC12VTD2000-D30	12V	79.17	≤195	4600*2300*2450	10000
KCY-1688GF	1856	1485	1688	1350	YC16VTD2270-D30	16V	105.56	≤195	4700*2300*2450	11000
KCY-1875GF	2063	1650	1875	1500	YC16VTD2510-D30	16V	105.56	≤195	4800*2400*2500	12000
KCY-2000GF	2200	1760	2000	1600	YC16VTD2700-D30	16V	105.56	≤195	5300*2400*2600	14000
KCY-2250GF	2475	1980	2250	1800	YC16VC3000-D31	16V	105.56	≤203	5500*2500*2600	16000
KCY-2500GF	2750	2200	2500	2000	YC16VC3300-D31	16V	105.56	≤203	5800*2600*2700	18000
KCY-2750GF	3000	2400	2750	2200	YC16VC3600-D31	16V	105.56	≤203	6000*2700*2800	20000
KCY-3000GF	3250	2600	3000	2400	YC16VC4000-D31	16V	105.56	≤203	6100*2700*2800	20000
KCY-3125GF	3375	2700	3125	2500	YC16VC4200-D30	16V	105.56	≤203	6100*2700*2800	21000
KCY-3250GF	3500	2800	3250	2600	YC16VC4500-D30	16V	105.56	≤203	6200*2700*3000	22000
KCY-3500GF	3750	3000	3500	2800	YC16VC4900-D30	16V	105.56	≤203	6500*2700*3100	24000