

DLD-FW horizontal electric brush filter

SELF-CLEANING SCREEN FILTER



A motor-driven brush scrubs the stainless-steel screen while it backwashes, so algae and suspended solids come off even in very dirty water. Built for high-turbidity sources such as dams and rivers; it cuts manual cleaning by about 90% and saves more than 15% of flushing water.

- High flow with high filtration accuracy
- Low pressure loss and little backwash water
- Highly automated
- Parts: electric brush and stainless-steel screen

OPERATING PARAMETERS

Capacity per unit 50–4 000 m³/h	Filtration grade 20–4000 micron	Design pressure 1.0 MPa / 10 bar
Minimum pressure 0.1 MPa / 1 bar	Screen material Stainless steel 304 / 316	Control Pressure difference, timer or manual
Backwash time 10–200 s	Working temperature up to 65 °C	Pressure loss ≤ 0.01 MPa / 0.1 bar

TECHNICAL DATA

Model	Inlet / outlet	Drain outlet	Motor (kW)	Flow (m³/h)	Weight (kg)
DLD-FW-80	3" / DN80	1¼" / DN40	0.18	50	180
DLD-FW-100	4" / DN100	1¼" / DN40	0.18	80	198
DLD-FW-150	6" / DN150	2" / DN50	0.18	150	328
DLD-FW-200	8" / DN200	2" / DN50	0.25	320	375
DLD-FW-250	10" / DN250	2" / DN50	0.25	450	470
DLD-FW-300	12" / DN300	2" / DN50	0.37	600	519
DLD-FW-350	14" / DN350	2" / DN50	0.37	850	660
DLD-FW-400	16" / DN400	2" / DN50	0.37	1200	708