

DLS semi-automatic screen filter

SCREEN FILTER



A Y-pattern steel screen filter with a built-in cleaning brush. When the screen needs cleaning, open the drain valve and turn the handle a few times: the brush scrubs the stainless-steel screen and flushes the dirt out, with no need to open the filter or stop the water.

- Filter body, stainless-steel screen, brush with handle, drain valve and pressure gauges
- Clean without dismantling the screen
- Water keeps flowing while it is cleaned

OPERATING PARAMETERS

Filtration grade 20–4000 micron	Design pressure 1.0 MPa / 10 bar	Minimum pressure 0.1 MPa / 1 bar
Operation Semi-automatic (hand brush)	Screen material Stainless steel 304 / 316	Pressure loss ≤ 0.01 MPa / 0.1 bar

TECHNICAL DATA AND DIMENSIONS

Model	Inlet / outlet	L1 (mm)	L2 (mm)	L (mm)	D (mm)	H (mm)	Drain (DN)	Max flow (m³/h)
DLS-50	2" / DN50	500	673	330	159	520	25	19
DLS-80	3" / DN80	550	710	330	159	550	25	50
DLS-100	4" / DN100	670	810	430	159	670	32	80
DLS-150	6" / DN150	800	950	480	275	800	32	150
DLS-200	8" / DN200	900	1050	560	325	900	40	320
DLS-250	10" / DN250	1200	1350	744	377	1200	50	490
DLS-300	12" / DN300	1250	1630	780	426	1250	65	710
DLS-350	14" / DN350	1300	1980	820	478	1300	65	970

Pressure and materials can be customised on request.

