

HAULM TOPPING

Potato haulm cutters

Haulm cutters top and chop the foliage before harvest and return it to the field. Three-point mounted, with cutters that move to suit different row spacings.

3WP-3000

Trailed Boom Sprayer



Specification	Unit	3WP-3000
Hitch type		Trailed
Dimensions, folded (L x W x H)	mm	6800x3000x3600
Weight	kg	2700
Tractor power required	hp	130-180
Working pressure	MPa	0.2-0.5
Tank capacity	L	3 000 main tank + 300 rinse tank
Agitation		Jet agitation
Tank rinse system		Fixed tank cleaning spray
Work rate	ha/h	≥5.33

4JM-180/200/300/360B/360D

Potato Haulm Cutter



Specification	Unit	4JM-180	4JM-200	4JM-300	4JM-360B	4JM-360D
Hitch type		Mounted	Mounted	Mounted	Mounted	Mounted
Dimensions (L x W x H)	mm	2390x2060x1200	2334x2552x1262	2390x3430x1200	2390x4030x1200	2390x4030x1200
Weight	kg	800	865	1060	1180	1188
Tractor power required	hp	60-100	80-125	100-180	100-180	100-180
Row spacing	mm	900	1000	750	900	900
Rows		2	2	4	4	4
Working width	mm	1800	2000	3000	3600	3600
Stubble height	mm	≤100	≤100	≤100	≤100	≤100
Work rate	ha/h	≥0.53	≥0.6	≥0.83	≥1	≥1
Working speed	km/h	3-7	3-7	3-7	3-7	3-7