

**5XT-40**
**Potato Soil Removal and Cleaning Machine**


| Specification          | Unit | 5XT-40                |
|------------------------|------|-----------------------|
| Dimensions (L × W × H) | mm   | 4280×2400×1800        |
| Weight                 | kg   | 1004                  |
| Capacity               | t/h  | 40                    |
| Belt drive             |      | Geared motor          |
| Drive                  |      | Motor                 |
| Total power            | kW   | 4.5                   |
| Power supply           |      | 380 V AC, 50 Hz       |
| Conveying width        | mm   | 800                   |
| Soil web pitch         | mm   | 45                    |
| Cleaning roller type   |      | Spiral spring rollers |
| Cleaning rollers       |      | 5                     |
| Min. intake height     | mm   | 1020                  |
| Soil discharge height  | mm   | 1600                  |
| Soil belt width        | mm   | 480                   |

**5SD-40/60/80**
**Potato Piler**


| Specification          | Unit  | 5SD-40          | 5SD-60          | 5SD-80                      |
|------------------------|-------|-----------------|-----------------|-----------------------------|
| Dimensions (L × W × H) | mm    | 9492×2440×1500  | 18600×2780×2990 | 10160×2982×2163 (retracted) |
| Weight                 | kg    | 3705            | 7280            | 5680                        |
| Capacity               | t/h   | 60              | 60              | 80                          |
| Telescopic extension   | mm    | 4950            | 5500            | 5800                        |
| Max. extended length   | mm    | 14440           | 24100           | 15240                       |
| Max. lift height       | mm    | 7300            | 7000            | 7300                        |
| Potato damage rate     |       | ≤1              | ≤1              | ≤1                          |
| Max. slewing radius    | mm    | 12720           | 16100           | 14550                       |
| Min. slewing radius    | mm    | 7712            | 10600           | 8750                        |
| Belt speed             | m/min | 50 max.         | 60.6 max.       | 78 max.                     |
| Belt width             | mm    | 650             | 790             | 800                         |
| Total power            | kW    | 8.4             | 18.65           | 11                          |
| Power supply           |       | 380 V AC, 50 Hz | 380 V AC, 50 Hz | 380 V AC, 50 Hz             |