

TWO MODELS

ZHS30F and ZHS35F rough-terrain forklifts

Four-wheel-drive diesel forklifts on big 20.5/70-16 tyres, with an enclosed cab, an automatic transmission and 250–300 mm of ground clearance. They lift pallets, bins and bales where a warehouse forklift cannot go: gravel yards, orchards, pack sheds and building sites.

Specification	ZHS30F · 3 t	ZHS35F · 3.5 t
LOAD AND SIZE		
Rated load	3 000 kg	3 500 kg
Standard lift height	3 m	3 m
Optional lift heights	4, 4.5, 5 or 6 m	4, 4.5, 5 or 6 m
Standard forks	1 220 × 140 × 40 mm	1 220 × 140 × 40 mm
Mast ground clearance	250–300 mm	250–300 mm
Max. climbing grade	30°	30°
Operating weight	4 000 kg	4 500 kg
Overall size L × W × H	3 850 × 1 850 × 2 600 mm	3 850 × 1 850 × 2 600 mm
ENGINE AND DRIVE		
Engine	Yunnei YN27, 4-cyl. diesel	Yunnei YN27GBZ, 4-cyl. diesel
Rated power	37 kW at 2 400 rpm	42 kW at 2 400 rpm
Transmission	Hydraulic torque converter, automatic	Hydraulic torque converter, automatic
Max. speed	30 km/h	30 km/h
Drive	4×4, Isuzu-50 axles	4×4, hub-reduction axles
TYRES, STEERING AND BRAKES		
Tyres	20.5/70-16, 280 kPa	20.5/70-16, 280 kPa
Steering	Hydraulic, 35°	Hydraulic, 35°
Min. turning radius	4 000 mm	4 000 mm
Service brake	Air-over-oil disc	Air-over-oil disc
Parking brake	Disc	Disc
CAPACITIES		
Fuel tank	60 L	60 L
Hydraulic tank	60 L	60 L