

FEATURES

Built for rough ground

Frame Structure - 1



- Thickened and Widened.
- More loading Capacity.

Plate Chain - 2



- Emergency Braking.
- Avoid accidents.

Tilt Oil Cylinder - 3



- Max Tilt Angle 30°.
- Up and down.

Double Pump - 4



- Enough flow.
- Powerful and stable.

Articulated Chasis - 5



- Small turning radius.
- Hydraulic steering.

Engine Hood - 6



- Efficiency.
- Easy-to-open engine hood.

Instrument Panel - 8



- Easy Operation.
- 4 Forward and 2 reverse Gear.

Seat - 9



- Pilot Control.
- Comfortable Seat.

WHAT YOU GET

- Thickened, widened mast frame for more lifting capacity
- Heavy lifting chain with emergency braking
- Tilt cylinders: 30° backward tilt, up and down
- Double hydraulic pump for strong, fast lifting
- Articulated chassis for a small turning circle, with hydraulic steering
- Engine hood that opens fully for easy servicing
- Simple instrument panel, with 4 forward and 2 reverse gears
- Comfortable suspension seat in an enclosed cab

MAST OPTIONS

Mast	Lift heights
Standard, 2-section	3 m
2-section	3.5, 4 or 4.5 m
3-section	4.5, 5 or 6 m

CONTAINER LOADING

Three units fit in a 40 ft container and one in a 20 ft container, which keeps shipping to Southern Africa affordable.

IN THE YARD

