

WEAR PARTS

Harrow and plough discs

Plain and notched discs in 30MnB5 boron steel: hard, tough and wear-resistant, heat-treated for long life. Diameters 280–960 mm and thicknesses 3–12 mm, with a choice of centre holes. Discs can also be made to your drawing or sample.



Square



Round



Hexagon, round corners



Rounded square



Clover leaf



Square/round



Composite square



Hexagon

Diameter (mm)	Diameter (in)	Concavity (mm)	Concavity (in)	Thickness (mm)	Thickness (in)
305	12	19	0.75	3	0.12
330	13	25	1	3	0.12
355	14	38	1.5	3	0.12
410	16	38/43/46/48/51	1.5/1.69/1.75/1.85/2	3/3.5/4	0.12/0.14/0.16
435	17	57	2.25	3/3.5/4	0.12/0.14/0.16
460	18	38/44/52/57/63	1.5/1.75/2/2.25/2.5	3/3.5/4	0.12/0.14/0.16
485	19	57	2.25	3.5/4	0.14/0.16
510	20	0/44/51/57/63/70	0/1.75/2.25/2.5/2.75	3.5/4.5	0.14/0.16/0.20
535	21	63/70	2.5/2.75	3.5/4.5	0.14/0.16/0.20
560	22	0/54/57/63/70/76/79/83/89	0/2.125/2.25/2.5/2.75/3/3.125/3.25/3.5	3.5/4.5/6	0.14/0.16/0.20/0.24
585	23	79/83/89	2.875/3.25/3.5	3.5/4.5/6	0.14/0.16/0.20/0.24
610	24	63/70/73/76/81/83/89/95/101/108	2.5/2.75/2.875/3/3.19/3.25/3.5/3.75/4/4.5	3.5/4.5/6	0.14/0.16/0.20/0.24
660	26	57/63/76/83/86/89/102/108/114	2.25/2.44/3/3.25/3.35/3.5/4/4.25/4.5	5/5.5/6/7/8	0.20/0.22/0.24/0.28/0.32
710	28	85/102/108/114/127/130	3.5/4/4.25/4.5/5/5.125	5/5.5/6/7/8	0.20/0.22/0.24/0.28/0.32
810	32	128/132	5.04/5.20	8/12	0.32/0.48
910	36	164	6.46	12	0.48

