

PERFORMANCE DATA • 380 V 50 HZ

8-pole motors • about 730 rpm

Low speed and high torque for large, slow machines.

Model	Frame	Power kW	Power hp	Speed rpm	Current A at 380 V	Efficiency %	Power factor
YE3-80M1-8	80M	0.18	0.24	700	0.8	56.0	0.61
YE3-80M2-8	80M	0.25	0.34	700	1.1	59.0	0.61
YE3-90S-8	90S	0.37	0.5	695	1.4	66.0	0.61
YE3-90L-8	90L	0.55	0.74	695	2.0	70.0	0.61
YE3-100L1-8	100L	0.75	1	705	2.3	73.5	0.67
YE3-100L2-8	100L	1.1	1.5	705	3.2	76.5	0.69
YE3-112M-8	112M	1.5	2	715	4.2	77.5	0.70
YE3-132S-8	132S	2.2	3	730	5.9	80.0	0.71
YE3-132M-8	132M	3	4	730	7.6	82.5	0.73
YE3-160M1-8	160M	4	5.4	725	9.8	85.0	0.73
YE3-160M2-8	160M	5.5	7.4	725	13.1	86.0	0.74
YE3-160L-8	160L	7.5	10	730	17.4	87.5	0.75
YE3-180L-8	180L	11	15	725	25.0	89.0	0.75
YE3-200L-8	200L	15	20	730	33.2	90.4	0.76
YE3-225S-8	225S	18.5	25	735	40.6	91.2	0.76
YE3-225M-8	225M	22	30	735	46.8	91.5	0.78
YE3-250M-8	250M	30	40	735	62.6	92.2	0.79
YE3-280S-8	280S	37	50	740	76.5	93.0	0.79
YE3-280M-8	280M	45	60	740	92.6	93.5	0.79
YE3-280M1-8	280M	55	74	740	110	93.8	0.81
YE3-315S-8	315S	55	74	740	110	93.8	0.81
YE3-315M-8	315M	75	101	740	150	94.0	0.81
YE3-315L1-8	315L	90	121	740	176	94.5	0.82
YE3-315L2-8	315L	110	148	740	215	94.8	0.82
YE3-355M1-8	355M	132	177	745	257	95.0	0.82
YE3-355M2-8	355M	160	215	745	312	95.0	0.82
YE3-355L1-8	355L	185	248	745	360	95.2	0.82
YE3-355L-8	355L	200	268	745	385	95.2	0.83
YE3-355-1-8	355	220	295	745	423	95.2	0.83
YE3-355-2-8	355	250	335	745	481	95.2	0.83