

Product technical specifications and specifications

Item		Item description
Input/output characteristic	Digital input channel	Channel 5 for universal digital input, max. frequency 1KHz, channel 1 can be used as pulse input channel, max. input 50KHz, expansion terminals can be realized
	Analog input channel	Channel 2 for analog input channel, AI1 is 0-10V input, AI2 can choose 4-20mA or 0-10V or 0-20mA input, expansion terminal can be realized
	Pulse output channel	0.1-20KHz pulse square signal output to achieve setting frequency, output frequency and other physical quantity output
	Analog output channel	Channel 1 for analog output channel, AO can choose 0-20mA or 0-10V to achieve setting frequency, output frequency and other physical quantity output, expansion terminal can be realized
	Monopulse control	Suitable for working site where need one button to control inverter start and stop, first press to start, then press to stop, and that cycle repeats. Its very simple and reliable
	Fixed length control	Realize fixed length control
	Timing control	Timing control function: setting time range 0.1Min - 6500.0Min
	Virtual terminal	Five group virtual input & output IO can realize simply logical control
Operating keypad	Keypad display	The parameters as setting frequency, output frequency, output voltage, output current can be displayed
	Button locked	Lock all or part of the buttons
Protection function		Motor power on short circuit test, input & output phase loss protection, over-current protection, over voltage protection, under voltage protection, over heat protection, overload protection, under load protection, short circuit protection to ground, terminal protection and no stop protection under power off, etc.
Environment	Application site	Indoor, not bare to sunlight, no dust, no corrosive gas, no flammable gas, no vapor, no water drop or salt etc.
	Altitude	Under 1000 meter (above 1000 meter require to reduce volume to use, output current reduce about 10% of rated current per 1000 meter high)
	Environment temperature	-10°C - +40°C (environment temperature between 40°C - 50°C, need to reduce volume or strengthen heat sink)
	Environment humidity	Smaller than 95%RH, no drop condenses
	Vibration	Smaller than 5.9M/S ² (0.6g)
	Storage temperature	-40°C ~ +70°C
Structure	Protection grade	185kW and below: IP20; 200kW and above: IP00
	Cooling mode	Forced air cooling
Installation mode		185kW and below: wall-mounted; 200kW and above: cabinet-type, supporting cabinet installation