

4UL-170D/170E

Combine Harvester With Bagging Function



Specification	Unit	4UL-170D	4UL-170E
Hitch type		Trailed	Trailed
Dimensions (L × W × H)	mm	9210×3400×3000	9627×3147×3031
Weight	kg	6500	5500
Tractor power required	hp	140–210	140–210
Working width	mm	1700	1800
Depth control		Depth limiting wheel	Depth limiting wheel
Digging depth	mm	150–300	150–300
Haulm removal	mm	Counter-rotating haulm rollers	Haulm separation web
Digging share		Fixed combined shovel	Fixed combined shovel
Cleaning & separation	/ Conveying	Conveying web + star-wheel separator	Vibrating screen
Conveyor		Grid chain	Grid chain
Work rate	ha/h	≥0.4	≥0.33

4UX-170A/180B/180E/200

Potato Harvester



Specification	Unit	4UX-170A	4UX-180B	4UX-180E	4UX-200
Hitch type		Mounted	Mounted	Mounted	Mounted
Dimensions (L × W × H)	mm	3875×2110×1255	3880×2215×1215	4350×2175×1300	3880×2568×1260
Weight	kg	1580	1630	1800	1867
Tractor power required	hp	120–160	120–160	≥118	140–200
Row spacing	mm	850–900	900–1000	900–1000	≥1100
Rows		2	2	2	2
Working width	mm	1700	1800	1800	2000
Digging depth	mm	150–300	150–300	150–300	150–300
Lifting rate (potatoes exposed)		≥96%	≥96%	≥96%	≥96%
Potato damage rate		≤1.5%	≤1.5%	≤1.5%	≤1.5%
Skin damage rate		≤2%	≤2%	≤2%	≤2%
Work rate	ha/h	≥0.46	≥0.53	≥0.53	0.6