

HANDLING

Handling & storage equipment

Trailers, receiving hoppers, cleaners, conveyors, pilers and bagging lines for everything that happens after harvest — soil removal, sorting, transport into store and out again.

4UZ-80/100

Sweet Potato Combine Harvester



Specification	Unit	4UZ-80	4UZ-100
Hitch type		Self-propelled	Self-propelled
Dimensions (L x W x H)	mm	4150×2050×2200	4200×2250×2200
Weight	kg	1500	1550
Working width	cm	80	100
Engine power	kW	25.8	25.8
Engine speed	rpm	2400	2400
Track gauge	mm	780	780
Track width	mm	230	230
Working speed	km/h	0.5–1.0	0.5–1.0
Work rate	ha/h	0.04–0.053	0.047–0.067

5SY-8/12

Potato Trailer



Specification	Unit	5SY-8	5SY-12
Hitch type		Trailed	Trailed
Dimensions (L x W x H)	mm	7440×2240×2270	9064×2671×2365
Weight	kg	2830	4090
Tractor power required	hp	90–160	90–160
Payload	t	8	12
Belt speed	m/s	0–1.6 (adjustable)	0–1.6 (adjustable)
Road speed	km/h	≤35	≤35
Work rate	t/h	35	50
Body volume	L	7000–10000	14900