

## STORAGE

# Storage & ventilation

Purpose-designed potato stores with ducted ventilation, climate control, humidification and impact-recording sensors, plus the loaders and bagging machines that feed them.

## 5SZ-40/60/60X

### Potato Scooper



| Specification          | Unit | 5SZ-40          | 5SZ-60          | 5SZ-60X         |
|------------------------|------|-----------------|-----------------|-----------------|
| Dimensions (L x W x H) | mm   | 8000×1250×1450  | 8845×2180×1550  | 8000×1250×1450  |
| Extended length        | mm   | 10800           | 11845           | 11000           |
| Max. slewing radius    | mm   | 10000           | 11300           | 10500           |
| Weight                 | kg   | 1878            | 1770            | 1420            |
| Discharge height       | mm   | 460–1366        | 1000–1300       | 1000–1300       |
| Slewing angle          |      | 130             | 130             | 130             |
| Capacity               | t/h  | 40              | 60              | 40              |
| Potato damage rate     | %    | ≤1 %            | ≤1 %            | ≤1 %            |
| Total power            | kW   | 6               | 8.1             | 7.4             |
| Power supply           |      | 380 V AC, 50 Hz | 380 V AC, 50 Hz | 380 V AC, 50 Hz |

## 5SZC-60

### Potato Loader



| Specification                            | Unit | 5SZC-60                 |
|------------------------------------------|------|-------------------------|
| Dimensions (L x W x H)                   | mm   | 5080×2450×3300          |
| Weight                                   | kg   | 3000                    |
| Capacity                                 | t/h  | 60                      |
| / Max inclination angle of the lower arm |      | 28.5                    |
| / Max inclination angle of the upper arm |      | 131                     |
| Max. belt speed                          | m/s  | 1.2                     |
| Belt width                               | mm   | 1038                    |
| Side guard width                         | mm   | 850                     |
| Controls                                 |      | Wireless remote control |
| Power supply                             |      | 380 V AC, 50 Hz         |
| Total power                              | kW   | 11                      |