

PRODUCT CATALOG · MACHINERY

Construction & garden machinery

Mini excavators, mini dumpers, mini and full-size skid steer loaders with their attachments, plus tree spades, ride-on and zero-turn mowers, and wood chippers — direct from the factory to your farm.



WHO WE ARE

Farm equipment, at the price it *actually* costs.

Built by farmers, for farmers. Andrivo sources farm infrastructure and equipment from international manufacturers, handles the entire import process, and delivers to your farm anywhere in Southern Africa.

Farmers usually pay for a chain of markups they never see — a factory, an export agent, an importer and a local distributor, each adding a margin nobody discloses. Andrivo removes that chain. Our only charge is a service fee on top of the true cost: 30%, or 25% with a referral code.

25%

fee with a referral code (30% without)

0

distributors in between

SADC

we deliver across Southern Africa

How every quote works

1**Factory direct**

We work directly with the manufacturer of every machine in this catalog — no middlemen.

2**Inspected before it ships**

Each order is checked against the factory spec sheet before it leaves the plant.

3**Shipping & customs handled**

Freight, duties, clearing and transport to your gate are all managed by us.

4**Parts & aftersales**

Spares in stock, and every machine logged to your farm under My Farm by Andrivo.

CONTENTS

Compact machines for every job on the farm

Compact construction machines for digging, loading and moving material, with a full range of attachments, and garden machinery for mowing, chipping and tree work. Tell us the job and we will match the machine.

Construction machinery	Garden machinery
Mini excavators04–08	Tree spades34–35
Mini excavator attachments09–10	Ride-on lawn mowers (42–62 in)36–39
Mini dumpers11	Zero-turn stand-up mowers40
Mini skid steer loaders12–17	Wood chippers41–42
Mini skid steer attachments18–19	Walk-behind mowers43–44
Skid steer loaders20–26	
Skid steer attachments27	
Excavator attachments28–33	

Getting a quote

Send us the machine and model, the attachments you need, and your delivery town. Engines, cabs, tracks or tyres and attachment packs can often be changed to suit your work.

Specifications are the manufacturer's and may change; we confirm the final spec on every quote.



MINI EXCAVATOR

Model: 10



CE / EPA / EURO5

Operation weight	1000KG
Engine	YIPU
Power	8kw
Bucket capacity	0.025CBM
Rotation speed	11r/min
Crawler grounding length	1200mm
Crawler width	180mm
Max digging height	2580mm
Max discharge height	1745mm
Max digging depth	1700mm
Max digging radius	3030mm
Mini turning radius	1290mm
Platform clearance to ground	370mm
Swing angle	360°
Climbing gradient	30°
Bulldozer Max. depth	170mm
Bulldozer Max raising height	240mm
Walking speed	2.5km/h
Bucket digging force	11.5kN
Hydraulic system press	16MPa
Overall dimension (L*W*H)	2870 *950 *2030mm
Overall dimension(With shed)	2870 *950 *2285mm





MINI EXCAVATOR

Model: 12

CE / EPA / EURO5

Operation weight	1200kg
Engine	B&S
Power	13.5HP
Bucket capacity	0.03CBM
Rotation speed	11r/min
Crawler grounding length	1200mm
Crawler width	180mm
Max digging height	2650mm
Max discharge height	1800mm
Max digging depth	1750mm
Max digging radius	3030mm

Mini turning radius	1290mm
Platform clearance to ground	370mm
Swing angle	360°
Climbing gradient	30°
Bulldozer Max. depth	170mm
Bulldozer Max raising height	240mm
Walking speed	2.5km/h
Bucket digging force	11.5KN
Hydraulic system press	16MPa
Overall dimension (L*W*H)	2870 *950 *2030mm
Overall dimension(With shed)	2870 *950 *2285mm



Construction & garden machinery

andrivo.sales@outlook.com - +27 79 519 8131

05



MINI EXCAVATOR

Model: 15



CE / EPA / EURO5

Operation weight	1500KG
Engine	KUBOTA
Power	10.2kw
Bucket capacity	0.04CBM
Rotation speed	9r/min
Crawler grounding length	1100mm
Crawler width	180mm
Max digging height	2800mm
Max discharge height	1800mm
Max digging depth	2100mm
Max digging radius	3160mm

Mini turning radius	1587mm
Platform clearance to ground	370mm
Swing angle	360°
Climbing gradient	30°
Bulldozer Max depth	190mm
Bulldozer Max raising height	260mm
Walking speed	0-3km/h
Bucket digging force	16.5KN
Hydraulic system press	16MPa
Bucket width	400mm
Overall dimension (L*W*H)	3250*1100*2300mm



Construction & garden machinery

andrivo.sales@outlook.com - +27 79 519 8131

06



MINI EXCAVATOR

Model: 20

CE / EPA / EURO5

Operation weight	2000KG
Engine	KUBOTA D1105
Power	14kw
Bucket capacity	0.06m³
Rotation speed	12r/min
Wheelbase	1230mm
Crawler width	230mm
Max digging height	3391mm
Max discharge height	2290mm
Max digging depth	2200mm
Max digging radius	3850mm

Mini turning radius	1700mm
Platform clearance to ground	210mm
Swing angle	360°
Climbing gradient	35°
Bulldozer Max depth	275mm
Bulldozer Max raising height	230mm
Walking speed	0-5KM/H
Bucket digging force	10KN
Hydraulic system press	18KN
Bucket width	450mm
Overall dimension (L*W*H)	3655*1050*2232mm



Construction & garden machinery

andrivo.sales@outlook.com · +27 79 519 8131

07



MINI EXCAVATOR

Model: 40



CE / EPA / EURO5

Operation weight	4000KG
Engine	KUBOTA D1703
Power	18.2kw
Bucket capacity	0.12m³
Rotation speed	12r/min
Wheelbase	1670mm
Crawler width	300mm
Max digging height	4800mm
Max discharge height	3410mm
Max digging depth	3260mm
Max digging radius	5480mm

Mini turning radius	2530mm
Platform clearance to ground	295mm
Swing angle	360°
Climbing gradient	35°
Bulldozer Max depth	385mm
Bulldozer Max raising height	365mm
Walking speed	0-10KM/H
Bucket digging force	18KN
Hydraulic system press	30KN
Bucket width	600mm
Overall dimension (L*W*H)	4915*1755*2525mm



Construction & garden machinery

andrivo.sales@outlook.com · +27 79 519 8131

08

MINI EXCAVATOR ACCESSORIES

Model: Universal

CE / EPA / EURO5



200mm Bucket



400mm Bucket



600mm Bucket



Tilt bucket



Sieve bucket



Mechanical Quick Hitch



Hydraulic Quick Hitch



Dig ditch buckets



Rotary bucket



Snow ploughs



Rotating grappler



Wood grabbers

MINI EXCAVATOR ACCESSORIES

Model: Universal

CE / EPA / EURO5



Ripper



Angled quick hitch



Shell buckets



Miller



Wood choppers



Drills



Plate compactors



Forklift



Auger



Rake



Breaker Hammer



Thumb Clamp



MINI DUMPER

Model: MD 300

CE / EPA / EURO5

Engine brand	LONCIN	Cooling system	Forced Air Cooling
Engine type	4-Stroke / Single cylinder	Front/Rear wheel	4.8/4.00-8
Fuel type	Gasoline	Bucket size	850*680*440mm
Engine power	6.5hp	Speed	0-5.0km/h
Displacement	196cc	Net weight	170kg
Tipping method	Manual	Gross weight	200kg
Transmission	3F+1R	Max loading capacity	300kg



MINI DUMPER

Model: MD 550

CE / EPA / EURO5

Engine brand	B&S	Min radius of turn	0.95m
Engine type	4-Stroke / Single cylinder	Track center distance	509mm
Fuel type	Gasoline	Speed	1.7/3.5 km/h
Engine power	6.5HP (4.8KW/3600)	Min ground clearance	85mm
Displacement	208cc	Climb grade	20°
Fuel tank capacity	3.1L	Hydraulic tank capacity	7L
Oil tank capacity	0.6L	Hydraulic oil grade	46#
Travel motor brand	Like Hydraulics	Cargo box volume	0.22 m³
Work pressure	20MPa	Bucket size	1040*730*590mm
Max torque	805Nm	Vehicle size	1735*844*1255mm



MINI SKID STEER LOADER

Model: W 360

CE / EPA / EURO5

Rated load	200KG	Fuel tank capacity	5L
Maximum operating capacity	300KG	Wheel size	18*8.5-8
Bucket capacity	0.12m³	Vehicle height	1300mm
Bucket width	1050mm	Length with standard bucket	2070mm
Engine	KOOP	Vehicle width (standard tire)	980mm
Rated power	7KW	Height at maximum extension	2400mm
Number of cylinders	1	Dumping height	1510mm
Operating weight	900KG	Discharge distance	250mm
Maximum breakout force	3.5KN	Wheelbase	750mm
Driving speed	0-6km/h	Ground clearance	130mm
		Other engines	RATO/BS&S



MINI SKID STEER LOADER

Model: T 360 

CE / EPA / EURO5

Rated load	200KG	Fuel tank capacity	5L
Maximum operating capacity	300KG	Track model	180*72*35
Bucket capacity	0.12m³	Vehicle height	1300mm
Bucket width	1050mm	Length with standard bucket	2070mm
Engine	KOOP	Vehicle width (standard tire)	980mm
Rated power	7KW	Height at maximum extension	2400mm
Number of cylinders	1	Dumping height	1510mm
Operating weight	900KG	Discharge distance	250mm
Maximum breakout force	3.5KN	Track length on ground	900mm
Driving speed	0-6km/h	Ground clearance	130mm
		Other engines	RATO/B&S



Construction & garden machinery

andrivo.sales@outlook.com · +27 79 519 8131

13



MINI SKID STEER LOADER

Model: W 460 

CE / EPA / EURO5

Rated load	300KG
Maximum operating capacity	400KG
Bucket capacity	0.12m³
Bucket width	1050mm
Engine	KOOP
Rated power	14KW
Number of cylinders	2
Operating weight	1200KG
Maximum breakout force	4.5KN
Driving speed	0-6km/h
Fuel tank capacity	10L

Wheel size	18*8.5-8
Vehicle height	1300mm
Length with standard bucket	2140mm
Vehicle width (standard tire)	1050mm
Height at maximum extension	2400mm
Dumping height	1510mm
Discharge distance	250mm
Wheelbase	800mm
Ground clearance	110mm
Other engines	RATO/B&S



MINI SKID STEER LOADER

Model: T 460

CE / EPA / EURO5

Rated load	300KG
Maximum operating capacity	400KG
Bucket capacity	0.12m ³
Bucket width	1050mm
Engine	KOOP
Rated power	14KW
Number of cylinders	2
Operating weight	1200KG
Maximum breakout force	4.5KN
Driving speed	0-6km/h
Fuel tank capacity	10L

Track model	180*72*35
Vehicle height	1300mm
Length with standard bucket	2140mm
Vehicle width (standard tire)	1050mm
Height at maximum extension	2400mm
Dumping height	1510mm
Discharge distance	250mm
Wheelbase	800mm
Ground clearance	110mm
Other engines	RATO/B&S



Construction & garden machinery

andrivo.sales@outlook.com · +27 79 519 8131

15



MINI SKID STEER LOADER

Model: W 490

CE / EPA / EURO5

Rated load	250KG
Maximum operating capacity	350KG
Bucket capacity	0.12m³
Bucket width	1200mm
Engine	RATO
Rated power	17KW
Number of cylinders	2
Operating weight	1200KG
Maximum breakout force	4.5KN
Driving speed	0-6km/h
Fuel tank capacity	10L

Wheel size	23"8.5-12
Vehicle height	1300mm
Length with standard bucket	2700mm
Vehicle width (standard tire)	1100mm
Height at maximum extension	2530mm
Dumping height	1400mm
Discharge distance	600mm
Wheelbase	940mm
Ground clearance	230mm
Other engines	KOOP/B&S



Construction & garden machinery

andrivo.sales@outlook.com · +27 79 519 8131

16



MINI SKID STEER LOADER

Model: T490 

CE / EPA / EURO5

Rated load	250KG
Maximum operating capacity	350KG
Bucket capacity	0.12m³
Bucket width	1200mm
Engine	RATO
Rated power	17KW
Number of cylinders	2
Operating weight	1200KG
Maximum breakout force	4.5KN
Driving speed	0-6km/h
Fuel tank capacity	10L

Track model	180*72*45
Vehicle height	1300mm
Length with standard bucket	2700mm
Vehicle width (standard tire)	1100mm
Height at maximum extension	2530mm
Dumping height	1400mm
Discharge distance	600mm
Wheelbase	940mm
Ground clearance	230mm
Other engines	KOOP/S&S



Construction & garden machinery

andrivo.sales@outlook.com · +27 79 519 8131

17

MINI SKID STEER LOADER ACCESSORIES

Model: Universal

CE / EPA / EURO5



Wood grabber



Pallet Fork



Digger



Snow Blower



Bucket



Trencher



Road Sweeper



Rotary Plow



Drilling Auger

MINI SKID STEER LOADER ACCESSORIES

Model: Universal

CE / EPA / EURO5



Lawn mower



Mixer



Hydraulic breaker



Dozer blade



Scarifiers



Angle Broom



Stump grinder



Pioneer



Rotary harrow



SKID STEER LOADER

Model: CS 40

CE / EPA / EURO5



Rated load	400KG
Bucket capacity	0.2m³
Engine	KUBOTA
Rated power	18.2KW
Tire model	6.50-10
Fuel tank capacity	28L
Rated flux	50L/min
Maximum travel speed	9km/h
Overall operating height	3400mm
Unloading angle	40°
Front turning radius	1660mm
Rear turning radius	1253mm
Track width	785mm
Width	920mm
Bucket width	1070mm
Without bucket length	2200mm
Overall length with bucket	2950mm
Height to top of cab	1813mm



Construction & garden machinery

andrivo.sales@outlook.com +27 79 519 8131



SKID STEER LOADER

Model: CS 70

CE / EPA / EURO5

Rated load	700KG	Unloading angle	40°
Bucket capacity	0.4m³	Front turning radius	1958mm
Engine	XINCHAI	Rear turning radius	1630mm
Rated power	37KW	Track width	1450mm
Tire model	10-16.5	Width	1720mm
Fuel tank capacity	70L	Bucket width	1740mm
Rated flux	62.5L/min	Without bucket length	2640mm
Maximum travel speed	12Km/h	Overall length with bucket	3420mm
Overall operating height	3980mm	Height to top of cab	2140mm



andrive Construction & garden machinery

andrivo.sales@outlook.com +27 79 519 8131

21



SKID STEER LOADER

Model: CS 85 

CE / EPA / EURO5

Rated load	850KG	Overall operating height	4295mm
Bucket capacity	0.4m³	Unloading angle	40°
Engine	Cummins	Front turning radius	1958mm
Rated power	55KW/75HP	Rear turning radius	1728mm
Weight	3200KG	Wheelbase	991mm
Tire model	12-16.5	Width	1880mm
Fuel tank capacity	80L	Bucket width	1880mm
Operating mode	Mechanical	Without bucket length	2750mm
Maximum travel speed	12km/h	Overall length with bucket	3490mm
		Height to top of cab	2160mm



Construction & garden machinery

andrivo.sales@outlook.com · +27 79 519 8131



SKID STEER LOADER

Model: CS 100

CE / EPA / EURO5

Rated load	1050KG	Overall operating height	4295mm
Bucket capacity	0.5m³	Unloading angle	40°
Engine	KUBOTA	Front turning radius	2115mm
Rated power	90HP/67.6KW	Rear turning radius	1100mm
Weight	3470KG	Wheelbase	1179mm
Tire model	12inch	Width	1817mm
Fuel tank capacity	88L	Bucket width	1880mm
Operating mode	Hydraulic	Without bucket length	2889mm
Maximum travel speed	12km/h	Overall length with bucket	3688mm
		Height to top of cab	2023mm



Construction & garden machinery

andrivo.sales@outlook.com · +27 79 519 8131

23



SKID STEER LOADER

Model: CS 150

CE / EPA / EURO5

Rated load	1250KG	Overall operating height	4295mm
Bucket capacity	0.5m³	Unloading angle	40°
Engine	KUBOTA	Front turning radius	2115mm
Rated power	90HP/67.6KW	Rear turning radius	1100mm
Weight	4200KG	Wheelbase	1179mm
Tire model	12inch	Width	1817mm
Fuel tank capacity	88L	Bucket width	1880mm
Operating mode	Hydraulic	Without bucket length	2889mm
Maximum travel speed	12km/h	Overall length with bucket	3688mm
		Height to top of cab	2023mm



SKID STEER LOADER

Model: CT 100

CE / EPA / EURO5

Self weight bucket (kg)	3800
Bucket capacity (m³)	0.5
High Flow Flux (L/min)	120
Rated power (Kw)	55
Operating load (kg)	1000
Tire (track) model	320*84
Fuel tank capacity (L)	90
Rated flux (L/min)	80
Max Speed (km/h)	12\18
Overall operating height (mm)	3480
Height to bucket hinge pin (mm)	2900
Height to top of cab (mm)	2150
Height to bottom of level bucket(mm)	2730
Without bucket length (mm)	2750
Overall length with bucket(mm)	3500

Dumping angle at maximum height(°)	40
Dumping height(mm)	2230
Dumping reach(mm)	715
Rollback o bucket on ground(°)	30
Rollback of bucket at full height(°)	104
Wheelbase(mm)	1500
Ground clearance(mm)	200
Angle of departure(°)	20
Front turning radius without bucket(mm)	1298
Front tuning radius(mm)	2010
Rear tuning radius(mm)	1714
Rear axle to bumper (mm)	890
Tread width (mm)	1462
Width (mm)	1782
Bucket width (mm)	1830



SKID STEER LOADER

Model: CT 120

CE / EPA / EURO5

Self weight bucket (kg)	4500	Dumping angle at maximum height(°)	40
Bucket capacity (m³)	0.55	Dumping height(mm)	2450
High Flow Flux (L/min)	140	Dumping reach(mm)	700
Rated power (kW)	74	Rollback o bucket on ground(°)	30
Operating load (kg)	1200	Rollback of bucket at full height(°)	104
Tire (track) model	320*84	Wheelbase(mm)	1500
Fuel tank capacity (L)	90	Ground clearance(mm)	200
Rated flux (L/min)	88	Angle of departure(°)	20
Max Speed (km/h)	12\18	Front turning radius without bucket(mm)	1365
Overall operating height (mm)	4800	Front tuning radius(mm)	2200
Height to bucket hinge pin (mm)	3150	Rear tuning radius(mm)	1742
Hheight to top of cab (mm)	2160	Rear axle to bumper (mm)	938
Height to bottom of level bucket(mm)	2983	Tread width (mm)	1654
Without bucket length (mm)	3000	Width (mm)	1994
Overall length with bucket(mm)	3700	Rearset width (mm)	2030

SKID STEER LOADER ACCESSORIES

Model: Universal ↕

CE / EPA / EURO5



Road boring machine ↕



Enclosed cleaner ↕



Snow plows ↕



Snow ploughs ↕



Digger ↕



Forks ↕



Pioneer ↕



Lawn mower ↕



Snow throwers ↕

EXCAVATOR ACCESSORY

Hydraulic Quick Hitch



Overall Length	534-545 mm
Overall Height	307mm
Overall Width	258-263mm
Pin to Pin Center Distance	230-270mm
Forearm Open Width	155-170mm
Retractable Distance of Oil Cylinder	205-275mm
Top to Bottom Pin Distance	195mm
Pin Diameter	45-50mm
Weight	50-60 kg
Working Pressure	40-380Kg/cm ²
Required Oil Flow	10-20L/min
Suitable Excavator	4-7Ton

EXCAVATOR ACCESSORY

Powerful crusher



Suitable Excavator	6-9 ton
Weight	730 kg
Driving Pressure	240bar
Driving Flow	150L/min
OpeningA	630mm
Cutting Depth B	420mm
Overall Length C	1720mm
Blade Length DI/D2 (D)	120mm
Shearing Force1	60ton
Crushing Force	40ton

EXCAVATOR ACCESSORY

Eagle Shear



Arm Installation	6-9 ton
Working Pressure	200bar
Working Flow	100lpm
Weight	580kg
Rotating Flow	30lpm
Rotating Pressure	100bar
Opening	300mm
Cutting Depth	310mm
Full Length	1790mm

EXCAVATOR ACCESSORY

Tilt rotator



Full Length	560 mm
Full width	540mm
Full height	920mm
Inclination	± 45° single cylinder
Weight	150 kg
Solenoid valve line	4
Torque	13.5K N.M
The right excavator	2-4T
Pin Diameter	35-45mm
Center Distance	230-320mm
Bucket Width	154-210mm

EXCAVATOR ACCESSORY

Concrete Crusher



Suitable Excavator	20-28 ton
Weight	1750kg
Opening	820mm
Blade Length	180mm
Height	1980mm
Width	1400mm
Crushing Force	100ton
Cutting Force	210ton
Driving Pressure	300bar
Driving Flow	200lpm

EXCAVATOR ACCESSORY

Car dismantling pliers



Suitable Excavator	20-30 ton
Weight	1600kg
Opening With Jaw	850mm
Overall Length	2530mm
Overall Width	2-230*2mm
Maximum Cuntting Force	120ton
Driving Pressure	320bar
Driving Flow	200lpm
Rotating Motor Pressure	100bar
Rotating Motor Flow	20-30lpm
Rotating Motor Frequency	10-12 r/min

EXCAVATOR ACCESSORY

Clamp Bucket 



Suitable Excavator	12-16 ton
Weight	820kg
Height	1750mm
Width	690mm
Opening	1550mm
Driving Pressure	250bar
Driving flow	160lpm
Tine width	560mm

EXCAVATOR ACCESSORY

A lotus-shaped grapple 



Suitable Excavator	9-16 ton
Weight	900kg
Height	1648mm
Width	1260mm
Opening	1600mm
Driving Pressure	250bar
Driving flow	160lpm
Capacity	0.6cm³

EXCAVATOR ACCESSORY

Ripper 



Suitable Excavator	18-26 ton
Pin to Pin Distance	465mm
Overall width	870mm
Overall Height	1300mm
Pin Diameter	70-80mm
Dipper Width	300-350mm
Plate Thickness	80mm
Weight	426kg

EXCAVATOR ACCESSORY

Sleeper Machine 



Suitable Excavator	6-9 ton
Weight	716kg
Height	1265mm
Width	1546mm
Opening	600mm
Driving PressureFlow	200bar
Driving Flow	150-200lpm



EXCAVATOR ACCESSORY

Hydraulic Pulverizer 

Suitable Excavator	20-28ton
Weight	1200kg
Opening	400mm
Length	1324mm
Width	730mm



EXCAVATOR ACCESSORY

Hydraulic Power Thumb 

Suitable Excavator	18-26 ton
Length	1000-2000mm
Width	600-130mm
Height	260-400mm
Working Pressure	280bar
Working Flow	100-140lpm



EXCAVATOR ACCESSORY

Clamshell Bucket 

Suitable Excavator	18-26 ton
Weight	2200kg
Opening	2200mm
Working Pressure	250bar
Set Up Pressure	300bar
Working Flow	220lpm



EXCAVATOR ACCESSORY

Hydraulic Steel/Rock/Log Grab 

Suitable Excavator	18-26 ton
Weight	1550kg
Opening	2000mm
Working Pressure	160-180bar
Set Up Pressure	200bar
Working Flow	100-140lpm

EXCAVATOR ACCESSORY

Hydraulic Breaker



Weight	1600kg
Ledgth	2695mm
Pressure	200-240bar
Flow	160-200lpm
Rate	400-700bpm
Hose	1inch
Chisel	135mm
Suit	19-26ton

EXCAVATOR ACCESSORY

Pile Hammer



Suitable Excavator	18-26 ton
Power of Impulse	15ton
Maximum Vibration	1800r/min
Working Flow	176lpm
Working Pressure	120-180bar
Weight	900kg
Bottom Measurement	1320*885 L*W/mm
Height	1060mm
Width	885mm

EXCAVATOR ACCESSORY

Bush cleaner



Excavator Weiht	10-15 ton
Rotor length	950mm
Rotational speed	1600 rpm
Number of blades	15
Cutting Diameter	300 mm
Hydraulic	24.5mpa
Oil Flow	150 l/min
Gross Weight	1000 kg

EXCAVATOR ACCESSORY

Hydraulic sawing machine



Opening size	1500 mm
Blade length	700mm
Cut the tree diameter	500mm
The root stubble is high	250 mm
The right excavator tonnage	6-16 tons
Weight	530 kg

EXCAVATOR ACCESSORY

Hydraulic Plate Compactor



Suitable Excavator	30-38 ton
Eccentric Moment	50Nm
Frequency	2800rpm
Centrifugal Force	480kN
Working Pressure	320 bar
Working Flow	210lpm
Turning	180 degree
Main Body Weight	2650kg
Extension Boom Weight	750kg
Total weight	3400kg

EXCAVATOR ACCESSORY

Excavator Mower



Working width	1.2 m (3'11")
Branch thickness	4cm (1.57")
Travel speeds up to	5-7 km/h (3.11 - 4.35 mph)
Required hydraulic connections	1 x Double Acting + 1 x Drain
Required oil flow	85 lpm @ 230 bar (22.5 gpm @ 3336 psi)
Required oil flow	85 lpm @ 315 bar (22.5 gpm @ 4569 psi)
Weight	320kg (705lb)

* This data is only for theoretical values and some models, and is for reference only
The specific situation is subject to the customer service



◀ Tree moving machine

Tree spade attachment & Host



Tree-spade attachment parameters

The data is for reference only.
Please refer to the actual product.

Project Model		C40-3	C50-4	C60-4	C70-4	C80-4
Number of blades		3	4	4	4	4
Weight (kg)		530	700	830	920	1050
Excavation volume(m³)		0.03	0.08	0.1	0.15	0.24
Tonnage of applicable excavator (tons)		5.5+	6+	6+	7+	7.5+
Size (mm)		1070*1020*1120	1100*1100*1295	1120*1160*1425	1150*1190*1510	900*800*1616
Opening width (mm)		580	620	660	680	570
Suitable for tree diameter		50-70	60-100	80-120	90-140	100-150
Compatible hosts (Bobcat brand)		S16	S16	S16	S18	S18
Dirt ball size (mm)	Upper surface diameter	430	550	650	750	850
	Lower surface diameter	240	280	320	380	450
	Height	380	450	500	500	550
Match the host model	CS400	✓	✗	✗	✗	✗
	CS450	✓	✓	✓	✓	✓
	CS500	✓	✓	✓	✓	✓
	CS550	✓	✓	✓	✓	✓

Excavator tree spade ▶

Tree spade attachment & Excavatore



Tree-spade attachment parameters

Tronador / Spade Machine
Proprietario / Customer service

Project \ Model		C80-6	C90-6	C100-6	C120-6	C140-6
Number of blades		6	6	6	6	6
Weight (kg)		1050	1080	1100	2000	2200
Excavation volume(m³)		0.26	0.28	0.32	0.6	0.9
Tonnage of applicable excavator (tons)		7.5+	9+	9.5+	20+	26+
Size (mm)		910*855*1590	1050*950*1660	1130*1050*1705	1340*1250*2110	1560*1480*2350
Opening width (mm)		400	450	515	700	780
Suitable for tree diameter		100-150	110-160	120-170	150-200	200-350
(Bobcat brand)		S18	S550	S770	S770	
Dirt ball size (mm)	Upper surface diameter	850	950	1050	1250	1450
	Lower surface diameter	430	460	500	760	850
	Height	550	570	600	765	870
Match the host model	CS400	×	×	×	×	×
	CS450	×	×	×	×	×
	CS500	✓	✓	✓	×	×
	CS550	✓	✓	✓	×	×



Ride-on lawn vehicles 42"

Hydro-Gear, 42" mowing width
Please contact us for more details

Engine model	25HP Kohler KT740 / 27HP Loncin LC2P82F 23HP Honda GXV690 / 25HP Kawasaki FR691V
Drive mode	Hydro-Gear hydraulically driven
Fuel tank capacity	10L
Engine brand	Loncin General Dynamics
Startup mode	Electric start
Emissions	725cc / 803cc / 688cc / 725cc
Forward speed	0-10km/h
Back speed	0-5km/h
Mowing width	106cm
Number of blades	2
Cutting height	25-90mm/12 levels of adjustment
Package size	2176*1188*1068mm (Iron frame packing)
Weight	275kg



Ride-on lawn vehicles 48"

TruGreen is a registered trademark of
Pascall Limited, a company registered in the UK

Motor	Loncin
Horsepower	27HP
Emissions	803 CC
Drive mode	Hydro-Gear ZT-2800
Fuel tank capacity	15 L
Startup mode	Electric start
Cutting width	122 cm
Number of blades	3
Cutting height	38-127 mm
Weight	307 kg
Package size	1900*1270*1900 mm



Ride-on lawn vehicles 50"

The data is for reference only.
Please refer to customer service.

Product model	EAZ50-EC
Engine model	ENCORE EFI
Drive mode	Hydro-Gear hydraulically driven
Fuel tank capacity	12L
Emissions	803cc
Startup mode	Electric start
Forward speed	0-12km/h
Back speed	0-6km/h
Mowing width	127cm
Number of blades	3
Cutting height	38-114 mm/ 7levels of adjustment
Package size	1902*1358*950 mm
Weight	332 kg



Ride-on lawn vehicles 62"

For more information, please contact our sales team.

Engine brand	Loncin
Horsepower	27HP
Emissions	803 CC
Drive mode	Hydro-Gear ZT-2800
Fuel tank capacity	25 L
Startup mode	Electric start
Cutting width	158 cm
Number of blades	3
Cutting height	38-127 mm
Weight	404 kg
Package size	2310*1840*1980 mm



Zero-turn stand-up lawn mower

Tractor & Garden Machinery
Representative Office

Product model	ZTS-TZ 24C32	ZTS-TZ 24C36	ZTS-TZ 24C42
Engine brand	24HP V-Twin	24HP V-Twin	24HP V-Twin
Emissions	764CC	764CC	764CC
Transmission	Hydro Gear EZT-2200	Hydro Gear EZT-2200	Hydro Gear EZT-2200
Mechanical chassis	Assembled	Assembled	Assembled
Cutting width	810mm	910mm	1050mm
Cutting Height (Range)	38-114mm	38-114mm	38-114mm
Blade combining	Electromagnetic clutch	Electromagnetic clutch	Electromagnetic clutch
Cutting Belt Type	Premium B-section	Premium B-section	Premium B-section
Startup mode	Electric start	Electric start	Electric start
Driving mode	Zero turns	Zero turns	Zero turns
Forward speed	7.7mph(12.4kph)	7.7mph(12.4kph)	7.7mph(12.4kph)
Reversing speed	3.4mph(5.5kph)	3.4mph(5.5kph)	3.4mph(5.5kph)
Front tire specifications	13x5.0-6	13x5.0-6	13x5.0-6
Rear tire specifications	18x9.5.0-8	18x9.5.0-8	18x9.5.0-8
Chronograph	Standard	Standard	Standard
Fuel capacity	10L	10L	20L
Number of blades	2	2	3
Headlights	LED lights are standard	LED lights are standard	LED lights are standard
Total weight	280kg	292kg	310kg
Machine size	1660*1050*1305mm	1600*950*1290mm	1900* 1300*940mm
Package weight	74KG	84KG	81KG
Engine model	Loncin764CC	Loncin764CC	Loncin764CC
Certificate	CE/EPA/EURO 5	CE/EPA/EURO 5	CE/EPA/EURO 5
40 high cube container loads	36 Pcs	39 Pcs	36 Pcs
20 high cube container loads	12 Pcs	12 Pcs	12 Pcs

**Wood Chipper
(Vertical)**

AYS 001



There are three models of vertical branch crusher: 6.5 horsepower, 13 horsepower and 15 horsepower
If you need other model parameters, please consult the sales staff

Wood chipper

The data is for reference only
 Please consult with the sales staff

Product model	AYS001
Cutting diameter	7.6 cm
Blade speed	2800 rpm
Engine model	4 stroke: 170F/P
Startup mode	Manual start
Emissions	212cc
Maximum output power	7HP
Power speed	3600 rpm
Number of blades	20
Fuel tank capacity	3.6L
Oil capacity	0.6L
Fuel type	Unleaded petrol
Tire type	Tubeless
Gas mileage	1.5 L/h
Gross/net weight	76/70kg
Package size	76*49*120cm

**Wood Chipper
(horizontal)
AYS 6300A**



The horizontal shredder has gasoline, diesel, electric and other power
It can be customized on demand, and the specific parameters can be consulted by the sales staff

Wood chipper

*No data is for reference only.
Please select the actual price.

Product model	AYS6300A
Cutting diameter	8.9 cm
Blade speed	2800rpm
Engine model	4 stroke: 188F/P
Startup mode	Manual start
Emissions	389 CC
Horsepower MAX	13HP
Power speed	3600 rpm
Number of blades	Moving knife *2+ piece fixed knife*1
Fuel tank capacity	6 L
Oil capacity	1.1L
Fuel type	Tubeless
Gas mileage	4 L/h
Gross/net weight	170/160kg
Package size	112*57*98 cm



Lawn mower (gasoline engine)

Trabalha com eficiência e segurança. É a solução para o seu negócio.

Machine model	AYJ005
Cutting width	60 cm
Cutting height	20-80 cm
Engine model	177F (OVH 4-stroke)
Emissions	270 C C
Maximum power	6kw/3600 rpm
Blade specifications	32
Travel speed	Forward:1.88-3.32km/h Back off:0.91km/h
Belt model	Drive system:A783*1 Middle:B1400*1 Blade:B929*1
Brake	Blade brakes
Gearbox	R.O.O.1
Fuel tank capacity	6L
Oil capacity	1.1L
Fuel type	Unleaded petrol
Startup mode	Manual start
Gas mileage	2.3L/h
Gross/net weight	140/125 kg
Package size	119*80*98 cm





Lawn mower (gasoline engine)

This illustration is for reference only.
 The actual appearance may vary.

Machine model	DL100A
Engine model	Briggs & Straggs 6.5 HP
Mowing wide	100 cm
Cutting height	0.88-6 cm
Hob speed	8-flute hob, 150 times/m
Lever	With anti-vibration device, adjustable
Configuration	Three-section rubber rollers, anti-aging plastic grass collection box
Machine weight	217Kg
Hob weight	45.5Kg
Size	160*122*105 cm