

YE3 SERIES

High-efficiency motors that cost less to run

YE3 motors meet the IE3 premium-efficiency level, so they use less electricity than older standard motors doing the same job. On a pump or fan that runs all day, the saving on your power bill adds up quickly. They are fully enclosed and fan-cooled, dust- and water-jet-protected, and built for continuous duty.

0.12–375 kW

power range

IE3

premium efficiency

IP55dust and water-jet
protected**380 V**three-phase, 50 Hz (60 Hz
on request)**CHOOSING A MOTOR****1. Power (kW)**

Match the power your pump, fan or machine needs. The machine's own nameplate or manual gives it. When in doubt, go one size up rather than down.

2. Speed

The number of poles sets the speed. 2-pole $\approx$ 2 900 rpm for most pumps and fans. 4-pole $\approx$ 1 450 rpm, the all-round choice. 6-, 8- and 10-pole run slower with more torque, for mills, mixers and conveyors.

3. Mounting

Foot-mounted (B3) bolts to a base. Flange-mounted (B5, B14) bolts to the machine. Foot-and-flange (B35, B34) does both. V1 hangs vertically, shaft down, on a flange.

4. Supply

These motors run on three-phase 380–400 V. For single-phase farms, ask us about a frequency inverter that runs a three-phase motor from a single-phase supply.

SPECIFICATIONS

Item	Standard
Frame sizes	63 to 355
Poles	2, 4, 6, 8 and 10
Voltage and frequency	380 V, 50 Hz (60 Hz available)
Efficiency class	IE3
Duty	S1, continuous
Enclosure and cooling	Totally enclosed, fan-cooled (IC411)
Protection	IP55
Insulation class	F
Terminal box	Right-hand side as standard