

CUMMINS



Advanced design and sophisticated manufacturing, adaptable to harsh working conditions, with strong capabilities for high-intensity and heavy-duty operations. Holset exhaust bypass valve has better power performance. The integrated design of cylinder blocks, cylinder heads, and other components allows for "one piece multi functionality", reducing the number of connecting parts by 40% compared to other similar engines, greatly reducing the failure rate.



Cummins series gas generator set

Genset's model	Rated Power (kW/KVA)	Standby Power (kW/KVA)	Rated Current (A)	Engine Model	Cylinder No.	Bore*Stroke (mm)	Gas consumption (m³/kW.h)		Dimension (L*W*H mm)	Weight (kg)
							Natural gas	Biogas		
KCC-30GF	30/37.5	33/41.25	54	4BT3.9-G1	4.L	102*120	0.33	0.55	1700*600*1400	800
KCC-40GF	40/50	44/55	72	4BT3.9-G2	4.L	102*120	0.33	0.55	1875*650*1400	850
KCC-50GF	50/62.5	55/68.75	90	4BTA3.9-G2	6.L	102*120	0.33	0.55	1900*700*1400	950
KCC-80GF	80/100	88/110	144	6BTA5.9-G2	6.L	102*120	0.33	0.55	2250*800*1500	1350
KCC-100GF	100/125	110/137.5	180	6BTA5.9-G2	6.L	102*120	0.33	0.55	2250*800*1500	1420
KCC-120GF	120/150	132/165	216	6BTA5.9-G12	6.L	102*120	0.33	0.55	2300*900*1550	1450
KCC-150GF	150/187.5	165/206.25	270	6CTA8.3-G2	6.L	114*135	0.33	0.55	2500*1000*1650	1800
KCC-200GF	200/250	220/275	360	6CTA8.9-G2	6.L	114*135	0.33	0.55	2700*1000*1700	2000
KCC-300GF	300/375	330/412.5	540	6ZTAA13-G3	6.L	130*163	0.33	0.55	3200*1250*1800	3000
KCC-400GF	400/500	440/550	720	KT38T	6.L	159*159	0.33	0.55	3700*1550*2050	3970
KCC-500GF	500/625	550/687.5	900	KTAA5.9-G6A	6.L	159*159	0.33	0.55	4000*1850*1950	4600
KCC-600GF	600/750	660/825	1080	KTA38-G2	12.V	159*159	0.33	0.55	4220*1850*2100	6200
KCC-800GF	800/1000	880/1100	1440	KTA38-G5	12.V	159*159	0.33	0.55	4220*1850*2450	7150
KCC-1100GF	1100/1375	1210/1512.5	1980	KTA50-G8	16.V	159*159	0.33	0.55	5250*2070*2600	11900
KCC-1200GF	1200/1500	1320/1650	2160	KTA50-GS8	16.V	159*159	0.33	0.55	6000*2400*2600	12000